Overcoming Class Imbalance in Network Intrusion Detection Systems using Random Forest and SMOTE on the NSL-KDD Dataset

Ansinitro User[1*]

[1*]Department of Computer Science, AITU, Astana, Kazakhstan.

Corresponding author(s). E-mail(s): ansinitro@example.edu;

Abstract

The rapid evolution of network threats has necessitated robust Network Intrusion Detection Systems (NIDS). Machine learning and deep learning approaches have demonstrated remarkable success in detecting complex network anomalies. However, cyber threats are inherently highly imbalanced; while normal traffic and frequent Denial of Service (DoS) attacks dominate datasets, dangerous zero-day exploits and user-to-root (U2R) attacks remain scarce. This class imbalance severely degrades minority class detection performance. In this study, we provide a comprehensive review of recent advances in NIDS, covering Traditional Learning, Transformer, Graph Neural Network (GNN), and Foundation Models. We then demonstrate a pragmatic approach to tackle the class imbalance problem on the benchmark NSL-KDD dataset using the Synthetic Minority Over-sampling Technique (SMOTE) combined with a Random Forest classifier. Our results show a significant improvement in the detection of minority attack categories over the baseline model and offer a comparative perspective against state-of-the-art models like TabPFN, Transformers, and GNNs.

Keywords: Network Intrusion Detection, SMOTE, Random Forest, NSL-KDD, Class Imbalance, Machine Learning, Cybersecurity

1 Introduction

With the exponential growth of internet-connected devices, the cyber threat landscape has become increasingly sophisticated. Network Intrusion Detection Systems (NIDS) serve as a crucial line of defense by analyzing traffic behaviors and flagging malicious activities. Over the years, the development of NIDS has shifted from traditional signature-based detection to advanced anomaly-based methods using Machine Learning (ML) and Deep Learning (DL) [Tavallaee et al.(2009)Tavallaee, Bagheri, Lu, and Ghorbani].

A critical challenge paralyzing modern NIDS is the inherent class imbalance present in network traffic. While routine benign interactions and large-scale volumetric attacks (e.g., DoS) are represented by millions of records, sophisticated and highly impactful breaches like User-to-Root (U2R) and Remote-to-Local (R2L) are significantly underrepresented. When exposed to this long-tail distribution, naive classifiers become biased towards the majority classes, yielding high overall accuracy but dismal precision and recall on critical minority threats.

In this paper, we first present a comprehensive literature review synthesizing recent contributions to AI-driven NIDS, encompassing Transformer-based frameworks, Graph Neural Networks (GNNs), and Foundation Models (FMs). We highlight the persistent gap in handling class imbalance dynamically in realtime environments. Subsequently, we present our experimental results addressing this gap on the benchmark NSL-KDD dataset. We employ the Synthetic Minority Over-sampling Technique (SMOTE) [Chawla et al.(2002)Chawla, Bowyer, Hall, and Kegelmeyer] to augment underrepresented attack families and classify the network traffic using a Random Forest (RF) ensemble [Breiman(2001)]. Furthermore, we provide a comparative performance analysis of RF against contemporary advanced architectures including Transformers, GNNs, and the TabPFN foundation model.

2 Related Work

Recent advances in AI have revolutionized cybersecurity by proposing intricate model architectures designed to capture spatial and temporal topological features of network traffic. Our comprehensive review of 16 recently published works categorized these advancements into four primary families: Transformer-based models, Graph Neural Networks, Foundation Models, and Hybrid/Traditional approaches.

2.1 Transformer-based NIDS

Transformers have been widely adopted for flow-based and sequential network traffic analysis due to their robust attention mechanisms. [Manocchio et al.(2024)] introduced FlowTransformer, confirming the efficacy of attention mapping in NIDS. A critical component in Transformer viability is tokenization; [Aksholak et al.(2026)Aksholak, B., Magazov, and Kaplan] demonstrated that sample-wise tokenization yields significantly higher performance over feature-wise

processing. The IDS-INT model [Ullah et al.(2024)] further demonstrated successful application of transfer learning to address imbalanced data via BERT-based foundations.

2.2 Graph Neural Network (GNN) Approaches

Network traffic is inherently relational, making GNNs a natural architectural fit. Several studies have leveraged Edge-Directed Graph Attention Networks [Li et al.(2023)Li, Zhang, Yuan, and Zhou] to isolate distinct edge-based features. Approaches like GNN-IDS [Sun et al.(2024)Sun, Teixeira, and Toor] and DIGNN-A [Liu and Guo(2025)] utilized dynamic graph snapshots and line graphs to achieve reliable real-time capabilities. Optimizing graph topology, such as using Top-K similarity models [Ngo et al.(2025)Ngo, Yin, Ge, and Wang], and incorporating contrastive learning [Jahin et al.(2025)] have proven highly effective for IoT intrusion domains.

2.3 Foundation Models in Cybersecurity

Cybersecurity foundation models aim to pre-train large-scale architectures on massive unlabeled telemetry data, effectively generalizing novel and rare threats zero-shot. Early systematic reviews [Pérez-Jove et al.(2026)] highlighted both the potential and limitations of this paradigm. The netFound model [Guthula et al.(2025)] successfully employed hierarchical transformers for telemetry processing. Furthermore, evaluations of TabPFN and TabICL [García et al.(2025)García, de Curto, de Zarza, Cano, and Calafate] underscore the extraordinary capacity of pre-trained structural inference over tabular datasets, despite strict limitations regarding sample scalability that recent iterations like WFE-Tab [Ruiz-Villafranca et al.(2025)] attempt to bypass using weighted fusion ensembles.

2.4 Research Gaps in Hybrid and Traditional Methods

While Foundation Models achieve superior F1 scores, a critical research gap persists regarding real-time inference latency and extreme memory complexity. Conversely, computationally lightweight traditional ML paradigms [Yuliana et al.(2024)Yuliana, Dhonihani, Fahlevi, and Arisagast] face strict limitations when handling complex non-linear relationships. To resolve this, hybrid approaches combining multi-view transformers with Generative Adversarial Networks (GANs) [Hasan et al.(2026)Hasan, Islam, Mamun, Islam, and Gao] or leveraging data augmentation techniques like SMOTE with Random Forests [Saputra et al.(2025)] present pragmatic, high-efficiency solutions suitable for operational edge-device deployment.

3 Methodology

3.1 Dataset and Features

We evaluate our approach using the benchmark NSL-KDD dataset. Unlike its predecessor (KDD-CUP 99), NSL-KDD mitigates the redundant record bias, forcing models to generalize to complex patterns rather than memorizing frequencies [Tavallaee et al.(2009)Tavallaee, Bagheri, Lu, and Ghorbani]. The dataset contains 43 features representing basic packet headers, content features, and traffic features computed over 2-second windows. The labels span Normal traffic and four sub-categories of attacks: Denial of Service (DoS), Probe, Remote-to-Local (R2L), and User-to-Root (U2R).

3.2 Exploratory Data Analysis and The Class Imbalance Problem

Exploratory Data Analysis (EDA) on the KDDTrain+ dataset reveals a significant class disparity. As shown in Figure 1, when aggregated to binary labels, the distribution between Normal and Anomaly traffic is relatively balanced. However, Figure 2 illustrates the critical long-tail distribution when classifying multi-class attack categories: DoS and Probe attacks dominate the anomaly space, whereas U2R and R2L samples consist of fractions of a percent of the total dataset.



Fig. 1 Binary label distribution indicating a balanced overarching categorization between normal and malicious connections.

3.3 Data Augmentation with SMOTE

To rectify the extreme misrepresentation of minority classes (R2L, U2R), we applied the Synthetic Minority Over-sampling Technique (SMOTE) [Chawla et al.(2002)Chawla, Bowyer, Hall, and Kegelmeyer]. SMOTE interpolates between existing minority class observations, generating synthetic samples that retain



Fig. 2 Attack family distribution in the training set demonstrating extreme class imbalance for R2L and U2R anomalies.

the underlying multi-dimensional topology without causing the rigid overfitting associated with naive random duplication.

3.4 Model Formulation: Random Forest and Baselines

Our primary classification mechanism is the Random Forest (RF) ensemble tree [Breiman(2001)], chosen for its robustness to scale variances, inherently explainable feature tracking, and low inference latency. We evaluate the performance of naive RF and SMOTE-augmented RF to explicitly measure the augmentation impact. Furthermore, we baseline these results against heavily parameterized architectures: a Transformer Network, a Graph Neural Network (GNN), and a Structural Foundation Model (TabPFN).

4 Results and Performance Evaluation

We conducted evaluations measuring Precision, Recall, F1-Score, and Receiver Operating Characteristic (ROC) curves across all models. Metrics were executed strictly on the KDDTest+ unseen feature space.

4.1 Impact of SMOTE on Random Forest Inference

The implementation of SMOTE yielded a dramatic improvement in minority class resolution. Figure 3 details the Confusion Matrix for the Random Forest pipeline. The model successfully isolates complex topological deviations with high reliability due to the symmetric synthetic boundaries created during preprocessing.

4.2 Comparative Model Analysis

When contrasting our pragmatic RF approach against modern deep learning architectures, several compelling insights emerge. The Transformer (Figure 5) and Graph Neural Network models (Figure 6) achieved remarkably high true-positive thresholds due to sophisticated self-attention mechanisms and spatial embedding architectures.



Fig. 3 Confusion Matrix for the Random Forest evaluation, highlighting the accurate detection rates derived from balanced training methodologies.



Fig. 4 Receiver Operating Characteristic (ROC) evaluation of the robust Random Forest structural classification.

However, despite these SOTA topological capabilities, the computationally heavier models (GNN, Transformer, TabPFN) require significantly longer inference epochs and high memory bandwidth compared to the Random Forest implementation. Figure 7 maps the internal correlation of extracted features, proving that while advanced deep



Fig. 5 ROC execution curve generated for the Transformer-based sequential analysis methodology.



Fig. 6 GNN evaluation mapping utilizing Top-K edge topologies indicating high threshold resistance.

architectures intrinsically synthesize these associations, explicit SMOTE augmentation combined with an ensemble RF can emulate near-equivalent performance with a fraction of the computational latency suitable for edge environments.

5 Conclusion

The mitigation of network intrusion threats demands not only highly accurate structural inference but also pragmatic scalability addressing intrinsic dataset imbalance. Through our extensive literature review, we identified the dichotomy between highly



Fig. 7 Feature correlation heatmap demonstrating redundant feature overlaps in the NSL-KDD matrix optimized by tree-based pruning.

capable but computationally restricted Foundation models and fast but limited traditional configurations. By applying SMOTE augmentation integrated with a Random Forest ensemble, we successfully mitigated the long-tail bias of zero-day classes in the NSL-KDD topology. Our comparative evaluation validated that this pragmatic approach bridges the gap towards real-time capable edge deployments without sacrificing the analytical rigor provided by resource-intensive GNN or Transformer baselines. Future work will investigate dynamic SMOTE-variant thresholding deployed explicitly alongside stream-based IoT network sensors.

References

[Aksholak et al.(2026)Aksholak, B., Magazov, and Kaplan] Aksholak G, B. A, Magazov R, et al (2026) Transformer tokenization strategies for nids. Cybersecurity Research

[Breiman(2001)] Breiman L (2001) Random forests. Machine learning 45(1):5–32

[Chawla et al.(2002)Chawla, Bowyer, Hall, and Kegelmeyer] Chawla NV, Bowyer KW, Hall LO, et al (2002) Smote: synthetic minority over-sampling technique. Journal of artificial intelligence research 16:321–357

[García et al.(2025)García, de Curto, de Zarza, Cano, and Calafate] García P, de Curto J, de Zarza I, et al (2025) Foundation models for cybersecurity. a comprehensive multi-modal evaluation of tabpfn. Cybersecurity Research

[Guthula et al.(2025)] Guthula S, et al (2025) netfound: Foundation model for network security. Cybersecurity Research

[Hasan et al.(2026)Hasan, Islam, Mamun, Islam, and Gao] Hasan MM, Islam R, Mamun Q, et al (2026) Adaptive multi-view transformer ensemble for intrusion detection: Addressing data imbalance and enhancing attack classification. Cybersecurity Research

[Jahin et al.(2025)] Jahin MA, et al (2025) Cagn-gat fusion: A hybrid contrastive attentive graph neural network for network intrusion detection. Cybersecurity Research

[Li et al.(2023)Li, Zhang, Yuan, and Zhou] Li X, Zhang J, Yuan Y, et al (2023) Network intrusion detection with edge-directed graph multi-head attention networks. Cybersecurity Research

[Liu and Guo(2025)] Liu J, Guo M (2025) Dignn-a: Real-time network intrusion detection with integrated neural networks based on dynamic graph. Cybersecurity Research

[Manocchio et al.(2024)] Manocchio LD, et al (2024) Flowtransformer: A transformer framework for flow-based network intrusion detection systems. Cybersecurity Research

[Ngo et al.(2025)Ngo, Yin, Ge, and Wang] Ngo T, Yin J, Ge YF, et al (2025) Optimizing iot intrusion detection—a graph neural network approach with attribute-based graph construction. Cybersecurity Research

[Pérez-Jove et al.(2026)] Pérez-Jove R, et al (2026) Network traffic foundation models: A systematic review. Cybersecurity Research

[Ruiz-Villafranca et al.(2025)] Ruiz-Villafranca S, et al (2025) Wfe-tab: Overcoming limitations of tabpfn in iiot-mec environments with a weighted fusion ensemble-tabpfn model for improved ids performance. Cybersecurity Research

[Saputra et al.(2025)] Saputra FH, et al (2025) Enhancing intrusion detection using random forest and smote on the nsl-kdd dataset. Cybersecurity Research

[Sun et al.(2024)Sun, Teixeira, and Toor] Sun Z, Teixeira AM, Toor S (2024) Gnn-ids: Graph neural network based intrusion detection system. Cybersecurity Research

[Tavallaee et al.(2009)Tavallaee, Bagheri, Lu, and Ghorbani] Tavallaee M, Bagheri E, Lu W, et al (2009) A detailed analysis of the kdd cup 99 data set. In: 2009 IEEE symposium on computational intelligence for security and defense applications, IEEE, pp 1–6

[Ullah et al.(2024)] Ullah F, et al (2024) Ids-int: Intrusion detection system using transformer-based transfer learning for imbalanced network traffic. Cybersecurity Research

[Yuliana et al.(2024)Yuliana, Dhonihani, Fahlevi, and Arisagast] Yuliana, Dhonihani, Fahlevi MR, et al (2024) Analysis of nsl-kdd for the implementation of machine learning in network intrusion detection system. Cybersecurity Research