Electroweak mass-interface qualification

Ordinary DP regression passes; the threshold failure remains open. The QP-mass source patch is unapplied. These controls establish neither independent physical accuracy nor performance acceptance.

Both studies use `e+ e- > t t~ a [virt=QED]` in the pinned `loop_qcd_qed_sm_Gmu` model, with TIRust backend 9, cache disabled and normal stability handling at `MLStabThres=1e-6`. Fresh CLI generation, generated-source correspondence and compilation are retained for the original integration and the mass prototype. The comparison concerns this one EW process.

Ordinary sample: 100 accepted DP points per arm

Observed per arm	Original	Mass candidate
Physical points	100	100
Accepted DP / QP points	100 / 0	100 / 0
Public accepted status	219	219
Returned coefficient / accuracy slots	800 / 200	800 / 200

All returned coefficient, accuracy, status, history and observed IEEE/software-state words agree exactly. The pair passes both the `3e-6` regression gate and `1e-8` target with zero pair difference. Its maximum reported accuracy estimate is `1.0098069303873654e-7`, below the checked threshold. These are agreement and estimator observations, not an independent finite-answer oracle. No accepted QP point or changed native QP-mass input is observed; unobserved internal QP attempts are not excluded.

Each worker retains 101 initialization calls, including one scientifically unqualified bootstrap. The remaining 100-point warmup and final sample each return 200 overall/sole-order rows; those duplicate rows are not additional physical points. Explicit `LoopPoleMode=0` evaluates full sums and restores stored filter state after each call. These records do **not** qualify persistent filter learning.

Threshold / soft-photon fixture: both arms refuse

Target and observation	Original	Mass candidate
Ordinary control	Accepted 219	Accepted 219
Saved threshold fixture	**Refused 420**	**Refused 420**
Reported threshold accuracy	1	1
QP software latch before → after	0 → 1	0 → 1

The ordinary control and complete 100-point initialization records agree exactly. At the threshold, four changed words in failed return buffers are retained only as diagnostics. They are **not accepted coefficients** and receive no numerical accuracy, improvement or degradation comparison. Caller momentum/scale words remain unchanged and observed IEEE vectors agree, but neither is a witness of repaired or native reducer inputs. The mass correction does not resolve this stress failure.

The earlier pre-READY refusal and corrected pole-policy readiness check are preserved. Five later policy snapshots per arm retain the source-derived full-sum bypass and stored initialization flags; those flags are not learned filters. Native QP inputs, independent physical truth, genuine >53-bit physical masses, broader stress/cache coverage and promotion remain unqualified. No timings are added; Hua-Sheng's precise local performance acceptance remains pending.

Evidence: ordinary index `48a8b22cdb65…`, threshold index `df6f4e453f57…`. Exact identities and pure reproduction: `ew-qualification-selection.json`, `derive_evidence.py`. Style follows preserved pyAmpliCol revision `7266c1600f6e…`.