

Chapters

Chapter	Page
1. Intro electroculture.	2.
2. The workings of the apparatus.	3.
3. Drawing 1.	5.
4. Drawing 2.	6.
5. Drawing 3.	7.
6. Conclusion so far.	9.
7. Afterword regarding the pseudoscientific side.	10.

Intro electroculture.

In short it is a way to grow plants with electricity.

If you look it up you can find conflicting information. Some say it works and swear by it while others condemn it and call it pseudoscience.

It is good to make a distinction on this topic.

On the one hand we have people who put spirals in the ground and pray to the sun God that the plants grow bigger and better.

On the other hand, we have the scientist who test and try out what works and what does not.

I will make it fairly simple; a plant does grow better with mild electricity. Too much burns the roots so that is the reason we don't put power cables in our gardens.

The interesting thing is that because it is not clear why and how it works and so people start to speculate, without a legitimate scientific backbone this field is forced to be taken up by hobbyists. There was recently research was conducted that tested out if electroculture works but they took the idea of only using spirals as I described earlier. A normal spiral of copper has no seebeck effect, no thermocouple, no thermic gradient and no thermic mass. And many other things like a Daniell-cell chemical reaction. The result that electroculture doesn't work is not a fault of the principles on its own but rather how people use it and what one measures.

The thing that interested me personally is that the original Christofleau device actually uses fairly basic principles, I will note them below. ([FR764497A] is a reference to the original patent of Justin Christofleau)

1. Thermoelectricity (Heat to Current)

- The Seebeck Effect: The generation of an electric micro-current caused by a temperature gradient (difference) between two dissimilar metal conductors [FR764497A].
- The Thermocouple: The physical junction where the copper (hot solar side) and zinc (cold shadow/wind side) meet to actively produce voltage [FR764497A].
- Thermal Mass: The use of heavy cast iron (the wings) to store heat energy during the day and slowly dissipate it, stabilizing current generation into the night.

2. Electrochemistry (Material Interaction)

- Galvanic Action (Daniell-Cell): The creation of a natural battery within the soil. When the copper and zinc components interface with moist earth, the ground acts as an electrolyte to close the electric circuit.
- Electrode Potential: The inherent chemical property where zinc naturally acts as an electron donor (Anode / negative pole at -0.76V) and copper acts as an electron receiver (Cathode / positive pole at +0.34V).

- **Galvanic Corrosion:** The science of metal degradation when dissimilar materials touch in wet environments, which dictates the uniform use of galvanized components for ground connections.

3. Field Theory & Electrotechnics (Atmospheric Capture)

- **Point Discharge (The Needle Effect):** The law of physics stating that electric charge concentrates on sharp points. The pointed top antennas compress the natural atmospheric potential gradient to harvest static electricity and air ions.
- **Dielectric Insulation:** The use of non-conductive mediums (such as your 1mm open air gap acting as a dielectric) to prevent the positive and negative current paths from short-circuiting along the longitudinal seams.
- **Terrestrial Magnetism:** Utilizing the Earth's magnetic field by aligning the heavy physical core and magnetic discs strictly along the North-South axis to guide charge migration via Lorentz forces.

The information I could find where old blueprints and replicas of the original. But how it exactly worked was though to find out. So how does it work then?

The workings of the apparatus.

To understand how the Christofleau device works, we must stop looking at it as a passive decoration and start seeing it for what it truly is: a **passive, atmospheric micro-power plant**. It does not generate electricity from nothing; instead, it acts as a bridge that connects, amplifies, and channels three naturally occurring energy sources directly into the root zone of the plants.

Here is the step-by-step synergy of how these physics principles work together in practice:

1. Creating the Electrical "Pump" (Harvesting Energy)

The earth and the atmosphere form a natural battery. The air carries a positive static charge (which increases by roughly 100 to 300 Volts per meter as you go higher), while the ground carries a negative charge. The Christofleau device taps into this difference to create a steady flow of energy.

- **The Atmospheric Top (Point Discharge):** The sharp needles at the very top utilize the "needle effect." Because electrical charges naturally concentrate on sharp points, these spikes compress the surrounding atmospheric electric field. They actively harvest static electricity and air ions from the wind and sky.
- **The Chemical Base (The Daniell-Cell):** While the top gathers static electricity, the core of the device utilizes the copper and zinc elements. When exposed to moisture in the air or the soil, these two dissimilar metals create a natural chemical battery. The zinc willingly gives up electrons (Anode), and the copper receives them (Cathode), generating a reliable base voltage.
- **The Thermal Motor (Seebeck Effect):** To keep this current moving even when the air is calm, the sun plays a vital role. The sun warms the exposed copper side of the device while the zinc

side remains cooler in the shadow or wind. This temperature difference triggers the Seebeck effect, acting as a thermal motor that pumps a continuous electrical micro-current through the system, stabilized into the night by the heavy thermal mass of the casing.

2. Guiding the Current (The Magnetic Highway)

Once the device has harvested atmospheric energy and generated chemical voltage, this charge needs to travel into the ground without resistance.

- **The Heavy Conductor:** This is why the device uses a massive, thick, tapered central rod rather than a thin wire. It provides a massive "highway" with near-zero electrical resistance, forcing the positive atmospheric charges straight downward.
- **North-South Magnetic Alignment:** By aligning the device strictly along the Earth's North-South magnetic axis, the electrical current flows perfectly parallel to the planet's natural magnetic field lines. This alignment eliminates magnetic drag (Lorentz forces), allowing the atmospheric energy to merge seamlessly with the natural telluric currents already flowing through the soil.

3. What Happens in the Soil? (The Biological Breakthrough)

When this constant, gentle micro-current (measured in micro-amperes, not the harsh voltage of a power cable) enters the soil via the ground wire, it fundamentally changes the environment around the plant roots:

- **Electro-Osmosis:** The gentle electrical field pulls water molecules and dissolved nutrients (like nitrogen, phosphorus, and potassium) more effectively through the soil toward the roots, accelerating the plant's natural capillary action.
- **Nutrient Ionization:** Plant nutrients in the soil are typically bound to clay and organic matter as ions (charged particles). The micro-current loosens these bonds, making minerals far more bio-available so the plant can absorb them with less effort.
- **Microbial Stimulation:** The weak electrical field stimulates the activity of beneficial soil bacteria and mycorrhizal fungi. This speeds up the decomposition of organic matter, converting it into usable plant food much faster than in standard soil.

Personally, I think the authentic Christofleau device is a masterpiece of early system engineering. It does not introduce artificial energy into the garden. Instead, it takes **solar heat (thermoelectricity)**, **material interaction (electrochemistry)**, and **atmospheric voltage (field theory)**, blends them together using **magnetic alignment**, and delivers a perfectly metered, life-stimulating micro-current exactly where the plant needs it most.


The biggest problem I have with this is that this is theory and that this topic is not broadly researched. There are more people preaching than scientific papers. So, what did I find?

Modern research heavily validates this distinction. A recent 2025 study published in **PLOS ONE** ("Passive electroculture using copper rods does not improve plant growth") proved that the hobbyist method of inserting basic copper spirals yields zero agricultural benefit. However, when we look at the core mechanisms of the Christofleau device, the science shifts. A 2024 paper in **Smart Agricultural Technology** ("Galvanic Janus paper") proved that passive copper-zinc galvanic coupling successfully generates micro-currents that significantly boost plant height and biomass. Furthermore,

systematic reviews in **Scientia Horticulturae** confirm that these low-level electric fields trigger critical biological mechanisms, such as enhancing cell membrane permeability and accelerating auxin hormone transport.

There where a couple of things that I did different than original. Firstly, was welding. Online and in the original I saw that that welding was used for most connections. I refrained from using welds which is noticeable. Besides that, with the Copper and Zink components that needs to be soldered is only soldered on 4 points instead of on a whole surface. (see drawings) finally I made it in such a way that montage should be easy enough.

Drawing 1.



This is the first part of assembly. It should be noted that the base is not standard size, so it needs to be made out of a solid, personally I would recommend drilling $\text{Ø}30$ or 35 , then turning it up to $\text{Ø}55$, the last you could mill since the depth is $74.8/2=37.4$ that should be manageable for most C.N.C. workplaces. This part is felt did need some clarification.


I hope the rest like the slots and the ISO tolerances are logical. For a slot the tolerance is 1.62 g6 on H7. This is because it does need to be precise but it shouldn't be too tight. It is different with a 5.11 H7 in the main base, the part that goes in there should have an as high as possible surface area. But on this drawing, it is simply screw in the bolts and lock it into place.

The wings have the function of shade to have different temperatures on different parts of the base. This will create slight differences that will activate the Seebeck effect between the integrated copper and zinc components.

Based on the theory by casting a permanent shadow on one side while the other side is exposed to direct sunlight, the metal wings prevent the entire base from reaching thermal equilibrium. This architectural layout creates a localized thermal gradient (temperature difference) right across the junction where the dissimilar metals meet. Because the electrical output of a thermocouple is

directly proportional to this temperature delta, the wings act as the passive mechanical driver that keeps the electron "pump" running continuously throughout the day (FR764497A).

Drawing 2.



Here we can see clearly the Copper and Zink parts. Together they form a Galvanic Cell. How that works is that when the Copper and Zink come into contact with water they will react to each other and initiate an electrochemical reaction due to their difference in electrode potential.

I have made some holes in the Zink part so that water can drain if it sips though. I would recommend hitting the hole once with a hammer so that that part lies slightly lower than the rest, this so that water does not stay in one point. That the copper part is not flat is meant for more surface and more difference in local temperature when the sun shines on it.

As we can see here, the central rod passes directly through the base and is securely locked into position by a pin, while the Galvanic Cell itself just rests within the base. This floating assembly allows for effortless installation and ensures that the different metals can expand or contract freely during temperature changes without putting mechanical stress on the core.

The function of this central rod is twofold: it serves as both the main structural spine and the primary electrical highway. It collects the high-voltage atmospheric charge from the top spikes, merges it with the micro-current generated by the Galvanic Cell, and channels this combined energy straight down into the earth with minimal resistance.

The primary role of the antenna spikes is to act as an atmospheric harvester via point discharge, drawing in air ions and static potential. To maximize the efficiency of this entire multi-layered energy

collector, the complete assembly must be strictly aligned along the Earth's North-South magnetic axis. This positioning ensures that the thermoelectric current flowing from the solar-heated copper side toward the shaded zinc side, combined with the downward charge traveling through the central rod, flows parallel to natural telluric currents. This intentional alignment minimizes magnetic drag, creating a harmonious and uninhibited flow of micro-current directly into the root zone.

While the qualitative physics behind the device are well-established, the quantitative outputs such as the exact voltage generated by the Seebeck effect or the current density of the galvanic cell cannot be accurately modelled in advance. They are highly dependent on real-world chaotic variables, including soil composition, changing humidity, fluctuating atmospheric potential, and micro-climatic wind cooling. Therefore, this open-hardware prototype is explicitly designed as a standardized empirical testing platform, built to gather the first precise, real-world data tracks of the Christofleau paradigm under modern measurement conditions.

Because this model is quite smaller than the original it will also behave differently because of that. The size does matter in this instance because smaller parts retain less heat and warm up faster than bigger parts. This means that sunlight will make the copper warm up faster too.

In more difficult wording; Because this model is significantly smaller than the original, its thermodynamic behaviour will shift due to a reduction in thermal inertia. In this context, size is a critical variable: smaller components possess less thermal mass, meaning they retain less heat but warm up at a much faster rate. On the one hand, this lower mass allows the copper component to respond almost instantly to morning sunlight, triggering a rapid onset of the Seebeck effect. On the other hand, a smaller thermal mass risks reaching thermal equilibrium more quickly, as heat conducts faster across reduced distances.

It should be noted that the exact height on the pole is also different than in the original because of this. How much is something that should be tested out since I have no forehand knowledge on what is the best distance, perhaps radiotechnology is the branch that holds the answer to this question.

When a device acts as an atmospheric harvester, its physical dimensions and height above the ground plane function much like a radio antenna. Because this prototype is scaled down, its electrical resonance and impedance relative to the atmospheric potential gradient will shift, meaning that principles of antenna tuning and wave propagation will be essential to discover the precise height required for maximum energy harvesting.

It should be noted that I used RC in measurements, this is because the relation with $\pi/6$ and could either be perceived as an aesthetic choice or in correlation to wavelengths and radiotechnology. Even though I left the antenna open to improvement the rest is calibrated to work with $\pi/6$ fractions. One could say intuition.


Conclusion so far.

With all this said, I will conclude this document. Given the widespread lack of mechanistic explanations regarding how electroculture actually operates, I hope this paper has made the core physics as clear and accessible as possible. To be clear: I do not expect this device to magically grow crops as tall as people, but neither do I expect zero biological response.

Mainstream science is often too quick to write off alternative hypotheses. While it is entirely understandable to dismiss charlatans and "spiral hippies," blindly ignoring the underlying principles is counterproductive—it only breeds more misinformation. Because there is next to no monetary gain for large corporations, a passively driven, open-hardware system is heavily suppressed by institutional inertia and stuck with the label of pseudoscience.

There is a profound irony in watching academia inadvertently create its own enemies. By refusing to take the raw mechanics seriously, they push the field into a space where unscientific speculation thrives. From an engineering perspective, it seems incredibly shortsighted to disregard photographic and historical proof from over a century ago based on the modern, oversimplified interpretations we see today.

Btw to give it a name I call it RCM, Revised Christofleau Machine.



An old Pear Tree laden with fruit. This tree is so old that before being rejuvenated by the Electroculture* process it barely carried a few leaves.

Afterword regarding the pseudoscientific side.

There is one thing though that kept bothering me.

When looking at gardens of the hobbyists and when asked, the strange thing seems that the plants do seem to either be healthier or yielding more than normally. when looking at the tests that science already did like the "Passive electroculture using copper rods does not improve plant growth" it could not be because of the spirals.

But I think I know what is going on so I write it down as a hypothesis.

In this document I heavily focus on and choose the side of science and the 4 earthly elements. Looking at what the physical world exclusively. To understand it easier I refer to Masaru Emoto the Japanese researcher and his work regarding the photography of water and the effect of emotions and words.

Now there is one critical note to make and that is that the experiments of Masaru Emoto when reproduced yielded no proof. This seems to me quite logical but for that I have to refer to the work of Cleve Backster. Even though when talking about plants or water is different since the one is an organism and the other just water. It seems that the intention of humans does have an effect on our environment.

What this hypothesis of mine means is that putting up a spiral to promote growth does help plants and the reason why testing it yields no results is because the mindset behind it.

A spiral in the garden is not magical battery but more plainly an extension or accelerator of human intentions. A bit like a double placebo effect. It works when people think it works and it does not when people do not think it works. In that regard a sceptical researcher set out to debunk will get exactly what they hope for as will one that wants to conclude that it does work. This would explain perfectly the discrepancy in research data and the schism in science and also explain why the effects differ so much per person and test.

I think this is a bit like "Tsukkomi" and "Boke" and that there also lies the problem. I specifically take these terms to elaborate the difference in humans and thus also scientists.

I place this part at the very end on purpose, this part is more like the Aether, not an earthly element and something unmeasurable. At least as far as I know we lack the instruments to correctly understand and define this element. So, this part should be taken with a grain of salt, I state that specifically for the Tsukkomi since this is a part more akin to the mindset of a Boke. Before when talking about the scientific side is what is proven but this is to be researched and looked into.

For this part I would recommend the book "the secret life of plants" as a reference.

Thank you for reading. Mad Hatter out.

=====

CERN OPEN HARDWARE LICENCE NOTICE (CERN-OHL-S v2)

=====

Project Name: RCM (Revised Christofleau Machine)

Document Type: CAD Source Files (.SLDPRT, .SLDASM), Production G-code, and Theoretical Empirical Framework.

Author/Licenser: Copyright © 2026 S. v Harten (MadHatter-Auditor). Some rights reserved.

This work is licensed under the strongly reciprocal open-source terms detailed below.

=====

This documentation describes open-source hardware, mechanical configurations, and conceptual matrices licensed under the CERN Open Hardware Licence Version 2 – Strongly Reciprocal (CERN-OHL-S v2). You may use, copy, modify, share, and distribute this source documentation and any resulting physical hardware under the terms and conditions of the CERN-OHL-S v2 license.

CRITICAL CONDITION: STRONGLY RECIPROCAL OBLIGATIONS

This is a strongly reciprocal (copyleft) hardware license. If you modify this source documentation, use these design files to manufacture physical devices, or derive works from the integrated conceptual systems specifically including the RCM Base-12 Material Resonance Matrix, the Calibrated $\pi/6$ Fractional Casing, and the Thermoelectric CAD Coil/Plate Structures, you MUST comply with the following terms:

1. LICENSE RECIPROCITY: You must license all modifications, derivative documentation, and resulting physical hardware designs under the exact same CERN-OHL-S v2 license terms.
 2. SOURCE DISTRIBUTION: You must make the complete source documentation of your modified design publicly available and easily accessible to anyone receiving the physical hardware.
 3. NOTICES & ATTRIBUTION: You must retain all original copyright notices, attribution to MadHatter-Auditor, and this license notice intact on all copies of the documentation and physical products.
-

VERIFICATION & REFERENCES

The complete legal text of the license can be verified and downloaded at:

Official Steward: <https://ohwr.org>

License Identifier: SPDX: CERN-OHL-S-2.0

Project Repository Reference: <https://github.com/MadHatter-Auditor/vortex-anapole-confinement>

=====

DISCLAIMER: THIS HARDWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE LICENSOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES.

=====