

# Information Science

## 2: Functions

Naonori Kakimura

垣村尚徳

kakimura@global.c.u-tokyo.ac.jp

# (Rev.) Goal of the Course

---

2

- Study basic concepts of information science
  - Introduction to computer science
    - Useful in various fields
  - More theoretical than previous course “information”
  
- Programming exercises using Ruby
  - easy-to-use language similar to Python or Perl
    - introduction to other advanced languages(C, Java)
    - Used in large-size system (Rakuten, Twitter)
  - We use “irb”: interactive Ruby
  - Made in Japan

- Lectures w./ simple demos + Exercises
- You need to do exercises on your own
  - A lot of exercises on ITC-LMS
  - Many online tutorials
    - Project Euler <https://projecteuler.net/>
- You can do **at your own pace**
  - It's impossible to keep pace with everyone
  - ▣ some of you cannot finish exercises during the session
    - → take it to home and try it yourselves

# Today's Purpose

---

- Getting used to Ruby(using irb) 2
  - Functions
  - Loading files
  - Local variables

## ➤ Functions

- Concept
- How to use in Ruby

## ➤ Loading a file in irb


## ➤ Local variables

# Difference btw Calc and Computers

## ➤ A computer has a memory

- Can calculate such as  $(10+2)*(100/40+31)$
- Can store a variable
- Can store a program (stored-program concept)
  - IF, WHILE, ..
- A program executes a sequence of commands
- **function**: a principal component of programs


Last week



# Function $f$ in Mathematics

7

- Given an input  $x$ , return value  $f(x)$ 
  - Like a black box



## ➤ Example

- $f(x) = x^2$ 
  - if  $x=2$ ,  $f$  returns  $f(2)=4$
  - if  $x=5$ ,  $f$  returns  $f(5)=25$


Rem. We do not need to see the inside when we write  $f$

We separate the outside from the inside to understand

(capsulation)

# Functions in Programs

- Give a name to **some action**, and do not see inside







# Functions in Programs

- We can group a sequence of commands

ABC




Composition of functions



# Functions in Programs

10


- ✓ A function receives a value (called an **argument/parameter**), and return a value (called the **returned value**)



✓ `sqrt(x);`

- • • Return the square root of x

Rem. Available even if you don't know how to compute  $\sqrt{x}$



Examples

`m = sqrt(16.0)`

parameter/argument


m will have the returned value 4.0

How can we make an original function in Ruby?

# Functions returning the max of two numbers 13

---


Suppose we want to make the function max



**Parameter/argument:** two numbers  
(allows **multiple** parameters)

**Returned value:** one number  
(returns only one type of value)

Suppose we want to make the function max



```
def max(x, y)
```

```
...      Description to obtain the max value
```

```
end
```

After the above description, we can call “max(5,7)”, which returns 7

## Ex. Function that returns the max of two

15

- Name · · · max ← determined as you like
- parameters · · · two numbers w/ any names
- returned value · · · a number(max of the two)

↓ Write it based on Ruby syntax

```
def max(x, y)
```


```
... We here write the details(later)
```

```
end
```

# Remark: Other Functions

16

- ✓ The argument/returned value of a function may be nothing






# Ex. Defining Functions --- computing BMI

17

## ➤ body-mass index


- a measure for human body shape
- $\text{Body mass [kg]} \div (\text{height [m]} * \text{height [m]})$
- ratio btw weight and height: implying fat or slim



Normal: 18.5--25

Overweight: 25--30

Obese: 30--



```
def bmi(height, weight)
...(expression to compute bmi)
end
```

# Defining Functions --- computing BMI

---

19

```
irb(main):003:0> def bmi(height , weight)
irb(main):004:1>   weight / (height/100.0) ** 2
irb(main):005:1> end
=> nil
```

height & weight: variables

# Defining Functions --- computing BMI

---

20

```
irb(main):003:0> def bmi(height , weight)
irb(main):004:1>   weight / (height/100.0) ** 2
irb(main):005:1> end
=> nil
```

height & weight: variables

```
irb(main):007:0> bmi(188.0, 104.0)
=> 29.4250792213671
```

```
irb(main):008:0> 1.1*bmi(174.0, 119.0 * 0.454)
=> 19.6289470207425
```

can calculate using the function bmi

Make the following functions

1. `feet_to_cm( $f$ ,  $i$ )` that converts  $f$  feet  $i$  inch to cm.  
Note that  $1 \text{ feet} = 12 \text{ inch} = 30.48 \text{ cm}$ .
2. `pound_to_kg( $p$ ,  $o$ )` that converts  $p$  pound  $o$  ounce to kg. Note that  $1 \text{ pound} = 16 \text{ ounce} = 0.4536 \text{ kg}$ .


# Exercises (Requiring Submission Later)

---

22

Make the following functions

3.  $\text{distance}(x, y, u, v)$  that computes the distance between two points  $(x, y)$  and  $(u, v)$  in plane.



# Remark on Exercises

---

- When you have made a program,
  - Confirm that it returns no error
  - Confirm that it works well for some input

# Answers of Exercises


---

24

```
def feet_to_cm(f, i)
    30.48*f + 30.48/12*I      # (f + i/12.0)*30.48
end

def pound_to_kg(p, o)
    0.4536*p + 0.4536/16*o
end                                # (p + o/16.0)*0.4536

def distance(x, y, u, v)
    sqrt((x-u)*(x-u) + (y-v)*(y-v))
end                                # same as sqrt((x-u)**2+(y-v)**2)
```



Don't forget  
Include(Math) before



## ➤ Functions

- Concept
- How to use in Ruby

## ➤ Loading a file in irb

- Make a directory
- Make a new file

## ➤ Local variables

- It is annoying to enter commands each time you run irb
  - We want to store programs in a file separated from Ruby

So far: Type command one-by-one

```
irb(main):003:0> def bmi(height , weight)
irb(main):004:1>   weight / (height/100.0) ** 2
irb(main):005:1> end
```

→ Prepare a file in another place, and load it in irb

```
irb(main):003:0> load("./bmi.rb")
```

```
# BMI of a person with height (cm) and weight (kg)
def bmi(height , weight )
  weight / ( height /100.0) ** 2
end
```

- This course will make a lot of Ruby files
  - Better to make a new directory(folder) in your Home directory, and to put Ruby files in it

Step 1: Exit “irb”,

Step 2: Prepare a new directory in Home

- ▣ By Finder: Right-click → New Folder
- ▣ By a terminal
  - > `mkdir MyRubySource` (you can change the name)

Step 3: Go to the directory with a terminal

- ▣ Ex: > `cd MyRubySource`

Step 4: Start “irb”

# Define/Read a Function from a File

28

- Download `bmi.rb` from ITC-LMS in the directory
  - it is prepared / You can make it by yourself

```
irb(main):001:0> bmi(188.0, 104.0)
```

```
NoMethodError: undefined method
```

Because we quit irb,  
all functions vanished

```
irb(main):001:0> load("./bmi.rb")
```

```
=> true
```

"./" means "current  
directory"

```
irb(main):002:0> bmi(188.0, 104.0)
```

```
=> 29.4250792213671
```

# Make/Edit a Ruby file using a Text Editor 29

---

- **Text editor**: software to edit a text file
  - a text file: a file consisting of only characters
  - Open/Edit a Ruby file

- **mi**: pre-installed text editor


- Click  on the Dock

- Cf. Other text editors

- **Emacs** ... Advanced, useful editor for programmers
- Notepad++, Memo pad, Sakura, etc ... for windows

# Window of mi

30



# Open bmi.rb with mi

31

Comments for human being:  
Sentences after # (until end of line ) are not read by Ruby

```
# BMI of a person with height (cm) and weight (kg)
def bmi(height , weight)
  weight / ( height /100.0) ** 2
end
```

Better to have an indent for visibility

bmi.rb

Same as the description of a function  
which you defined before in irb


1. Create `yardpound.rb` as in the next slides

- Containing `feet_to_cm(f, i)` and `pound_to_kg(p, o)`
  - we can store several functions in one file

We can define multiple functions in one file



- Try to change the line-break code
  - Code is different in environments



# Can Define Multiple Functions in One File <sup>34</sup>

```
def feet_to_cm(f, i)
  (f + i/12.0)*30.48
end

def pound_to_kg(p, o)
  (p + o/16.0)*0.4536
end
```

yardpound.rb

- Save a text file as a name with the postfix “.rb”
  - to recognize that it is a Ruby file
  - Just add “.rb” at the end of the file name

# Can Define Multiple Functions in One File <sup>35</sup>

```
def feet_to_cm(f, i)
  (f + i/12.0)*30.48
end

def pound_to_kg(p, o)
  (p + o/16.0)*0.4536
end
```

yardpound.rb

```
irb(main):003:0> load("./yardpound.rb")
```

```
=> true
```

```
irb(main):004:0> feet_to_cm(5, 11)
```

```
=> 180.34
```

2. Create distance.rb containing the function distance (which we made)

- Requiring submission later

3. Make a function bmi\_yp(f,i,p,o) that returns BMI when we are given height of f feet i inch and weight of p pound o ounce

- Using bmi.rb and yardpound.rb

# Read a Ruby file in another Ruby file

37

Can use a defined function in another one if it is loaded

```
load ("../bmi.rb")  
load ("../yardpound.rb")  
  
def bmi_yp(f,i,p,o)  
  bmi(feet_to_cm(f,i), pound_to_kg(p,o))  
end
```

bmi\_yp.rb

Do not forget to “load” necessary files  
to “include” Math if necessary

# Tips: A Function as a Constant

When you want to define an invariant value

Cf. A variable may be changed with some reason

```
# BMI of a person with height (cm) and weight (kg)
def bmi(height , weight )
  weight / ( height/100.0) ** 2
end
def k_height()          #Height of Mr. K
  188.0
end
def k_weight()          #Weight of Mr. K
  104.0
end
```

bmi.rb

# Tips: A Function as a constant

---

39

```
irb(main):005:0> load("./bmi.rb")
```

```
=> true
```

```
irb(main):006:0> k_weight()
```

```
=> 104.0
```

```
irb(main):007:0> bmi(k_height(), k_weight())
```

```
=> 29.4250792213671
```

## ➤ Functions

- Concept
- How to use in Ruby

## ➤ Loading a file in irb

## ➤ Local variables



# Local Variable: Variables in a Function

41


Ex. A function that computes the area of a triangle whose side have lengths  $a$ ,  $b$ , and  $c$ .

➤ Use Heron's formula

$$\text{Area} = \sqrt{s(s-a)(s-b)(s-c)}$$

where

$$s = \frac{a+b+c}{2}$$



Useful to use the variable  $s$  to express computation

# Local Variable

42

Ex. A function that computes the area of a triangle whose side have lengths  $a$ ,  $b$ , and  $c$ .

Parameters  $a, b, c$  are also local variables.  
→ We cannot invoke  $a, b, c$  outside

```
def heron(a,b,c)
  s = 0.5*(a+b+c)
  sqrt(s * (s-a) * (s-b) * (s-c))
end
```

$s$  is called *a local variable*

heron.rb

A local variable is valid only inside the function  
(See Exercises)

Increase readability of the expression

- The returned value of a function is the value computed at the end
  - To specify the returned value, write “return”


```
def heron(a,b,c)
    s = 0.5*(a+b+c)
    return sqrt(s * (s-a) * (s-b) * (s-c))
end
```

Returned value is basically  
one computed at the last line

- Make a file `heron.rb`, and confirm it works
  - Try `heron(3,4,5)`, `heron(3,4,7)`, `heron(3,4,8)`, etc.
    - consider why we have sometimes an error
  - Check Problem 2-8 (Problem 8 in Section 2)
  
- **Solve for submission**
  - 2-2 logarithm
  - 2-4 computing the area of an equilateral triangle
  
  - If you have time
    - 2-3 (a)(b) and 2-7

# Quizzes (**Deadline 10/19 23:59**)

45

- Copy&Paste programs which you have made during the session
    - distance.rb
    - heron.rb
    - solve 2-2, 2-4 etc.
  - Evaluate your understanding on a scale of 1 to 5
    - 5: I have understood all
    - 4: very well
    - 3: well
    - 2: a bit
    - 1: I could not understand anything
- GOOD
- 
- BAD
- Tell me if you have some specific comment

- Conditions, Iterations, and Arrays 1
  - Getting more functions...
- 10/10: public holidays