

DynamicNLPModels

David Cole, Sungho Shin, Francois Pacaud

August 16, 2022

Contents

Contents	ii
I Introduction	1
1 Introduction	2
2 What is DynamicNLPMODELS?	3
3 Bug reports and support	4
II Quick Start	5
III API Manual	6
4 API Manual	7

Part I

Introduction

Chapter 1

Introduction

Welcome to the documentation of [DynamicNLPModels.jl](#)

Warning

This documentation page is under construction.

Note

This documentation is also available in [PDF format](#).

Chapter 2

What is DynamicNLPModels?

Chapter 3

Bug reports and support

Please report issues and feature requests via the [Github issue tracker](#).

Part II

Quick Start

Part III

API Manual

Chapter 4

API Manual

[DynamicNLPModels.DenseLQDynamicBlocks](#) - Type.

Struct containing block matrices used for creating and resetting the `DenseLQDynamicModel`. A and B matrices are given in part by Jerez, Kerrigan, and Constantinides in section 4 of "A sparse and condensed QP formulation for predictive control of LTI systems" (doi:10.1016/j.automatica.2012.03.010). States are eliminated by the equation $x = Ax_0 + Bu + \hat{A}w$ where $x = [x_0^T, x_1^T, \dots, x_N^T]$ and $u = [u_0^T, u_1^T, \dots, u_{N-1}^T]$

-
- A : block A matrix given by Jerez et al. with $ns(N + 1)$ rows and ns columns
 - B : block B matrix given by Jerez et al. with $ns(N)$ rows and nu columns
 - Aw : length $ns(N + 1)$ vector corresponding to the linear term of the dynamic constraints
 - h : $nu(N) \times ns$ matrix for building the linear term of the objective function. Just needs to be

multiplied by s_0 .

- h_{01} : $ns \times ns$ matrix for building the constant term for the objective function. This can be found by

taking $s_0^T h_{01} s_0$

- h_{02} : similar to h_{01} , but one side is multiplied by Aw rather than by As_0 . This will just

be multiplied by s_0 once

- $h_constant$: linear term in the objective function that arises from Aw. Not a function of s_0
- $h_{0_constant}$: constant term in the objective function that arises from Aw. Not a function of s_0
- d : length $nc(N)$ term for the constraint bounds corresponding to E and F. Must be multiplied by s_0 and

subtracted from g_l and g_u . Equal to the blocks $(E + FK) A$ (see Jerez et al.)

- dw : length $nc(N)$ term for the constraint bounds that arises from w. Equal to the blocks $(E + FK) Aw$
- KA : size $nu(N) \times ns$ matrix. Needs to be multiplied by s_0 and subtracted from u_l and u_u to update

the algebraic constraints corresponding to the input bounds

- KAw: similar to KA, but it is multiplied by Aw rather than A

See also `reset_s0`!

[source](#)

`DynamicNLPModels.DenseLQDynamicModel` - Method.

`DenseLQDynamicModel(dnlp::LQDynamicData; implicit = false) -> DenseLQDynamicModel`
`DenseLQDynamicModel(s0, A, B, Q, R, N; implicit = false ...) -> DenseLQDynamicModel`
 A constructor for building a `DenseLQDynamicModel` <: `QuadraticModels.AbstractQuadraticModel`

Input data is for the problem of the form

$$\text{minimize } \frac{1}{2} \sum_{i=0}^{N-1} (s_i^T Q s_i + 2u_i^T S^T x_i + u_i^T R u_i) + \frac{1}{2} s_N^T Q f s_N \text{ subject to } s_{i+1} = A s_i + B u_i + w_i \text{ for } i = 0, 1, \dots, N-1$$

Data is converted to the form

$$\text{minimize } \frac{1}{2} u^T H u + h^T u + h_0 \text{ subject to } J z \leq g \leq u \leq u_u$$

Resulting H, J, h, and h0 matrices are stored within `QuadraticModels.QPData` as H, A, c, and c0 attributes respectively

If K is defined, then u variables are replaced by v variables. The bounds on u are transformed into algebraic constraints, and u can be queried by `get_u` and `get_s` within `DynamicNLPModels.jl`

Keyword argument `implicit = false` determines how the Jacobian is stored within the `QPData`. If `implicit = false`, the full, dense Jacobian matrix is stored. If `implicit = true`, only the first nu columns of the Jacobian are stored with the Linear Operator `LQJacobianOperator`.

[source](#)

`DynamicNLPModels.LQDynamicData` - Type.

`LQDynamicData{T,V,M,MK} <: AbstractLQDynData{T,V}`

A struct to represent the features of the optimization problem

$$\text{minimize } \frac{1}{2} \sum_{i=0}^{N-1} (s_i^T Q s_i + 2u_i^T S^T x_i + u_i^T R u_i) + \frac{1}{2} s_N^T Q f s_N \text{ subject to } s_{i+1} = A s_i + B u_i + w_i \text{ for } i = 0, 1, \dots, N-1$$

Attributes include:

- `s0`: initial state of system
- `A`: constraint matrix for system states
- `B`: constraint matrix for system inputs
- `Q`: objective function matrix for system states from 1:(N-1)
- `R`: objective function matrix for system inputs from 1:(N-1)

- N : number of time steps
- Qf: objective function matrix for system state at time N
- S : objective function matrix for system states and inputs
- ns: number of state variables
- nu: number of input variables
- E : constraint matrix for state variables
- F : constraint matrix for input variables
- K : feedback gain matrix
- 'w' : constant term for dynamic constraints
- sl: vector of lower bounds on state variables
- su: vector of upper bounds on state variables
- ul: vector of lower bounds on input variables
- uu: vector of upper bounds on input variables
- gl: vector of lower bounds on constraints
- gu: vector of upper bounds on constraints

see also `LQDynamicData(s0, A, B, Q, R, N; ...)`

[source](#)

`DynamicNLPModels.LQDynamicData` – Method.

`| LQDynamicData(s0, A, B, Q, R, N; ...) -> LQDynamicData{T, V, M, MK}`

A constructor for building an object of type `LQDynamicData` for the optimization problem

$$\text{minimize } \frac{1}{2} \sum_{i=0}^{N-1} (s_i^T Q s_i + 2u_i^T S^T x_i + u_i^T R u_i) + \frac{1}{2} s_N^T Q f s_N \text{ subject to } s_{i+1} = A s_i + B u_i + w_i \forall i = 0, 1, \dots, N-1, u_i =$$

-
- s0: initial state of system
 - A : constraint matrix for system states
 - B : constraint matrix for system inputs
 - Q : objective function matrix for system states from 1:(N-1)
 - R : objective function matrix for system inputs from 1:(N-1)
 - N : number of time steps

The following attributes of the `LQDynamicData` type are detected automatically from the length of `s0` and size of `R`

- ns: number of state variables
- nu: number of input variables

The following keyword arguments are also accepted

- $Q_f = Q$: objective function matrix for system state at time N ; dimensions must be $ns \times ns$
- $S = \text{nothing}$: objective function matrix for system state and inputs
- $E = \text{zeros}(\text{eltype}(Q), 0, ns)$: constraint matrix for state variables
- $F = \text{zeros}(\text{eltype}(Q), 0, nu)$: constraint matrix for input variables
- $K = \text{nothing}$: feedback gain matrix
- $w = \text{zeros}(\text{eltype}(Q), ns * N)$: constant term for dynamic constraints
- $sl = \text{fill}(-\text{Inf}, ns)$: vector of lower bounds on state variables
- $su = \text{fill}(\text{Inf}, ns)$: vector of upper bounds on state variables
- $ul = \text{fill}(-\text{Inf}, nu)$: vector of lower bounds on input variables
- $uu = \text{fill}(\text{Inf}, nu)$: vector of upper bounds on input variables
- $gl = \text{fill}(-\text{Inf}, \text{size}(E, 1))$: vector of lower bounds on constraints
- $gu = \text{fill}(\text{Inf}, \text{size}(E, 1))$: vector of upper bounds on constraints

[source](#)

[DynamicNLPModels.LQJacobianOperator](#) - Type.

`LQJacobianOperator{T, V, M}`

Struct for storing the implicit Jacobian matrix. All data for the Jacobian can be stored in the first nu columns of J . This struct contains the needed data and storage arrays for calculating Jx , $J^T x$, and $J^T \Sigma J$. Jx and $J^T x$ are performed through extensions to `LinearAlgebra.mul!()`.

Attributes

- `truncated_jac1`: Matrix of first nu columns of the Jacobian corresponding to $Ax + Bu$ constraints
- `truncated_jac2`: Matrix of first nu columns of the Jacobian corresponding to state variable bounds
- `truncated_jac3`: Matrix of first nu columns of the Jacobian corresponding to input variable bounds
- `N`: number of time steps
- `nu`: number of inputs
- `nc`: number of algebraic constraints of the form $gl \leq Es + Fu \leq gu$
- `nsc`: number of bounded state variables
- `nuc`: number of bounded input variables (if K is defined)
- `SJ1`: placeholder for storing data when calculating ΣJ
- `SJ2`: placeholder for storing data when calculating ΣJ
- `SJ3`: placeholder for storing data when calculating ΣJ
- `H_sub_block`: placeholder for storing data when adding $J^T \Sigma J$ to the Hessian

[source](#)

[DynamicNLPModels.SparseLQDynamicModel](#) - Method.

`SparseLQDynamicModel(dnlp::LQDynamicData) -> SparseLQDynamicModel` `SparseLQDynamicModel(s0, A, B, Q, R, N; ...)` -> `SparseLQDynamicModel` A constructor for building a `SparseLQDynamicModel` <: `QuadraticModels.AbstractQuadraticModel` Input data is for the problem of the form

$$\text{minimize } \frac{1}{2} \sum_{i=0}^{N-1} (s_i^T Q s_i + 2u_i^T S^T x_i + u_i^T R u_i) + \frac{1}{2} s_N^T Q f s_N \text{ subject to } s_{i+1} = A s_i + B u_i + w_i \text{ for } i = 0, 1, \dots, N-1$$

Data is converted to the form

$$\text{minimize } \frac{1}{2} z^T H z \text{ subject to } l \leq J z \leq u \text{ con } l \leq z \leq u$$

Resulting H and J matrices are stored as `QuadraticModels.QPData` within the `SparseLQDynamicModel` struct and variable and constraint limits are stored within `NLPModels.NLPModelMeta`

If K is defined, then u variables are replaced by v variables, and u can be queried by `get_u` and `get_s` within `DynamicNLPModels.jl`

[source](#)

`DynamicNLPModels._set_sparse_H!` - Method.

```
| _set_sparse_H!(H_colptr, H_rowval, H_nzval, Q, R, N; Qf = Q, S = zeros(T, size(Q, 1), size(R,
| ↪ 1))
```

set the data needed to build a `SparseArrays.SparseMatrixCSC` matrix. `Hcolptr`, `Hrowval`, and `Hnzval` are set so that they can be passed to `SparseMatrixCSC()` to obtain the H matrix such that $z^T H z = \sum_{i=1}^{N-1} s_i^T Q s_i + \sum_{i=1}^{N-1} u_i^T R u_i + s_N^T Q f s_N$.

[source](#)

`DynamicNLPModels._set_sparse_J!` - Method.

```
| _set_sparse_J!(J_colptr, J_rowval, J_nzval, A, B, E, F, K, bool_vec, N, nb)
| _set_sparse_J!(J_colptr, J_rowval, J_nzval, A, B, E, F, K, N)
```

set the data needed to build a `SparseArrays.SparseMatrixCSC` matrix. `Jcolptr`, `Jrowval`, and `Jnzval` are set so that they can be passed to `SparseMatrixCSC()` to obtain the Jacobian, J. The Jacobian contains the data for the following constraints:

$A s_i + B u_i = s_{i+1}$ $g_l \leq E s_i + F u_i \leq g_u$

If K is defined, then this matrix also contains the constraints $u_l \leq K x_i + v_i \leq u_u$

[source](#)

`DynamicNLPModels.add_jtsj!` - Method.

```
| add_jtsj!(H::M, Jac::LQJacobianOperator{T, V, M}, Σ::V, alpha::Number = 1, beta::Number = 1)
```

Generates $Jac' \Sigma Jac$ and adds it to the matrix H.

alpha and beta are scalar multipliers such $\beta H + \alpha Jac' \Sigma Jac$ is stored in H, overwriting the existing value of H

[source](#)

DynamicNLPModels.get_A - Method.

```
get_A(LQDynamicData)  
get_A(SparseLQDynamicModel)  
get_A(DenseLQDynamicModel)
```

Return the value A from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

DynamicNLPModels.get_B - Method.

```
get_B(LQDynamicData)  
get_B(SparseLQDynamicModel)  
get_B(DenseLQDynamicModel)
```

Return the value B from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

DynamicNLPModels.get_E - Method.

```
get_E(LQDynamicData)  
get_E(SparseLQDynamicModel)  
get_E(DenseLQDynamicModel)
```

Return the value E from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

DynamicNLPModels.get_F - Method.

```
get_F(LQDynamicData)  
get_F(SparseLQDynamicModel)  
get_F(DenseLQDynamicModel)
```

Return the value F from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

DynamicNLPModels.get_K - Method.

```
get_K(LQDynamicData)  
get_K(SparseLQDynamicModel)  
get_K(DenseLQDynamicModel)
```

Return the value K from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

DynamicNLPModels.get_N - Method.

```
get_N(LQDynamicData)  
get_N(SparseLQDynamicModel)  
get_N(DenseLQDynamicModel)
```

Return the value N from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

`DynamicNLPModels.get_Q` – Method.

```
| get_Q(LQDynamicData)  
| get_Q(SparseLQDynamicModel)  
| get_Q(DenseLQDynamicModel)
```

Return the value Q from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

`DynamicNLPModels.get_Qf` – Method.

```
| get_Qf(LQDynamicData)  
| get_Qf(SparseLQDynamicModel)  
| get_Qf(DenseLQDynamicModel)
```

Return the value Qf from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

`DynamicNLPModels.get_R` – Method.

```
| get_R(LQDynamicData)  
| get_R(SparseLQDynamicModel)  
| get_R(DenseLQDynamicModel)
```

Return the value R from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

`DynamicNLPModels.get_S` – Method.

```
| get_S(LQDynamicData)  
| get_S(SparseLQDynamicModel)  
| get_S(DenseLQDynamicModel)
```

Return the value S from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

`DynamicNLPModels.get_gl` – Method.

```
| get_gl(LQDynamicData)  
| get_gl(SparseLQDynamicModel)  
| get_gl(DenseLQDynamicModel)
```

Return the value gl from LQDynamicData or SparseLQDynamicModel.dynamicdata or DenseLQDynamicModel.dynamicdata

[source](#)

`DynamicNLPModels.get_gu` – Method.

```
get_gu(LQDynamicData)
get_gu(SparseLQDynamicModel)
get_gu(DenseLQDynamicModel)
```

Return the value `gu` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_jacobian` – Method.

```
get_jacobian(lqdm::DenseLQDynamicModel) -> LQJacobianOperator
get_jacobian(Jac::AdjointLinearOperator{T, LQJacobianOperator}) -> LQJacobianOperator
```

Gets the `LQJacobianOperator` from `DenseLQDynamicModel` (if the `QPdata` contains a `LQJacobianOperator`) or returns the `LQJacobianOperator` from the adjoint of the `LQJacobianOperator`

[source](#)

`DynamicNLPModels.get_ns` – Method.

```
get_ns(LQDynamicData)
get_ns(SparseLQDynamicModel)
get_ns(DenseLQDynamicModel)
```

Return the value `ns` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_nu` – Method.

```
get_nu(LQDynamicData)
get_nu(SparseLQDynamicModel)
get_nu(DenseLQDynamicModel)
```

Return the value `nu` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_s` – Method.

```
gets(solutionref, lqdm::SparseLQDynamicModel) -> s <: vector
gets(solutionref, lqdm::DenseLQDynamicModel) -> s <: vector
```

Query the solution `s` from the solver. If `lqdm <: SparseLQDynamicModel`, the solution is queried directly from `solution_ref.solution`. If `lqdm <: DenseLQDynamicModel`, then `solution_ref.solution` returns `u` (if `K = nothing`) or `v` (if `K <: AbstractMatrix`), and `s` is found from transforming `u` or `v` into `s` using `A`, `B`, and `K` matrices.

[source](#)

`DynamicNLPModels.get_s0` – Method.

```
get_s0(LQDynamicData)
get_s0(SparseLQDynamicModel)
get_s0(DenseLQDynamicModel)
```


Return the value `s0` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_sl` – Method.

```
| get_sl(LQDynamicData)
| get_sl(SparseLQDynamicModel)
| get_sl(DenseLQDynamicModel)
```

Return the value `sl` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_su` – Method.

```
| get_su(LQDynamicData)
| get_su(SparseLQDynamicModel)
| get_su(DenseLQDynamicModel)
```

Return the value `su` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_u` – Method.

```
getu(solutionref, lqdm::SparseLQDynamicModel) -> u <: vector
getu(solutionref, lqdm::DenseLQDynamicModel) -> u <: vector
```

Query the solution `u` from the solver. If `K = nothing`, the solution for `u` is queried from `solution_ref.solution`

If `K <: AbstractMatrix`, `solution_ref.solution` returns `v`, and `get_u` solves for `u` using the `K` matrix (and the `A` and `B` matrices if `lqdm <: DenseLQDynamicModel`)

[source](#)

`DynamicNLPModels.get_ul` – Method.

```
| get_ul(LQDynamicData)
| get_ul(SparseLQDynamicModel)
| get_ul(DenseLQDynamicModel)
```

Return the value `ul` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.get_uu` – Method.

```
| get_uu(LQDynamicData)
| get_uu(SparseLQDynamicModel)
| get_uu(DenseLQDynamicModel)
```

Return the value `uu` from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

DynamicNLPModels.get_w – Method.

```
get_w(LQDynamicData)
get_w(SparseLQDynamicModel)
get_w(DenseLQDynamicModel)
```

Return the value w from `LQDynamicData` or `SparseLQDynamicModel.dynamicdata` or `DenseLQDynamicModel.dynamicdata`

[source](#)

DynamicNLPModels.reset_s0! – Method.

```
reset_s0!(lqdm::SparseLQDynamicModel, s0)
reset_s0!(lqdm::DenseLQDynamicModel, s0)
```

Resets s_0 within `lqdm.dynamic_data`. For a `SparseLQDynamicModel`, this updates the variable bounds which fix the value of s_0 . For a `DenseLQDynamicModel`, also resets the constraint bounds on the Jacobian and resets the linear and constant terms within the objective function (i.e., `lqdm.data.c` and `lqdm.data.c0`). This provides a way to update the model after each sample period.

[source](#)

DynamicNLPModels.set_A! – Method.

```
set_A!(LQDynamicData, row, col, val)
set_A!(SparseLQDynamicModel, row, col, val)
set_A!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $A[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

DynamicNLPModels.set_B! – Method.

```
set_B!(LQDynamicData, row, col, val)
set_B!(SparseLQDynamicModel, row, col, val)
set_B!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $B[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

DynamicNLPModels.set_E! – Method.

```
set_E!(LQDynamicData, row, col, val)
set_E!(SparseLQDynamicModel, row, col, val)
set_E!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $E[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

DynamicNLPModels.set_F! – Method.

```
set_F!(LQDynamicData, row, col, val)
set_F!(SparseLQDynamicModel, row, col, val)
set_F!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $F[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_K!` – Method.

```
set_K!(LQDynamicData, row, col, val)
set_K!(SparseLQDynamicModel, row, col, val)
set_K!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $K[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_Q!` – Method.

```
set_Q!(LQDynamicData, row, col, val)
set_Q!(SparseLQDynamicModel, row, col, val)
set_Q!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $Q[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_Qf!` – Method.

```
set_Qf!(LQDynamicData, row, col, val)
set_Qf!(SparseLQDynamicModel, row, col, val)
set_Qf!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $Qf[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_R!` – Method.

```
set_R!(LQDynamicData, row, col, val)
set_R!(SparseLQDynamicModel, row, col, val)
set_R!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry $R[\text{row}, \text{col}]$ to val for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_S!` – Method.

```
set_S!(LQDynamicData, row, col, val)
set_S!(SparseLQDynamicModel, row, col, val)
set_S!(DenseLQDynamicModel, row, col, val)
```

Set the value of entry `S[row, col]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_gl!` – Method.

```
set_gl!(LQDynamicData, index, val)
set_gl!(SparseLQDynamicModel, index, val)
set_gl!(DenseLQDynamicModel, index, val)
```

Set the value of entry `gl[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_gu!` – Method.

```
set_gu!(LQDynamicData, index, val)
set_gu!(SparseLQDynamicModel, index, val)
set_gu!(DenseLQDynamicModel, index, val)
```

Set the value of entry `gu[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_s0!` – Method.

```
set_s0!(LQDynamicData, index, val)
set_s0!(SparseLQDynamicModel, index, val)
set_s0!(DenseLQDynamicModel, index, val)
```

Set the value of entry `s0[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_sl!` – Method.

```
set_sl!(LQDynamicData, index, val)
set_sl!(SparseLQDynamicModel, index, val)
set_sl!(DenseLQDynamicModel, index, val)
```

Set the value of entry `sl[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_su!` – Method.

```
set_su!(LQDynamicData, index, val)
set_su!(SparseLQDynamicModel, index, val)
set_su!(DenseLQDynamicModel, index, val)
```

Set the value of entry `su[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_ul!` – Method.

```
| set_ul!(LQDynamicData, index, val)  
| set_ul!(SparseLQDynamicModel, index, val)  
| set_ul!(DenseLQDynamicModel, index, val)
```

Set the value of entry `ul[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`DynamicNLPModels.set_uu!` – Method.

```
| set_uu!(LQDynamicData, index, val)  
| set_uu!(SparseLQDynamicModel, index, val)  
| set_uu!(DenseLQDynamicModel, index, val)
```

Set the value of entry `uu[index]` to `val` for `LQDynamicData`, `SparseLQDynamicModel.dynamicdata`, or `DenseLQDynamicModel.dynamicdata`

[source](#)

`LinearOperators.reset!` – Method.

```
| LinearOperators.reset!(Jac::LQJacobianOperator{T, V, M})
```

Resets the values of attributes `SJ1`, `SJ2`, and `SJ3` to zero

[source](#)