



Composition:

- Inner tube: special NBR rubber resistant to hydraulic oil.
- Reinforcement: two textile braids.
- Cover: black rubber resistant to oil, abrasion and weather.

Working temperature: From -40°C to +100°C

Part nº	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MB2304	1/4"	6,4	14,4	145	2.102,5	580	8.410	45	0,16
MB2305	5/16"	7.9	17,7	130	1.885	520	7.540	55	0.41
MB2310	5/8"	15.9	26,9	80	1.160	320	4.640	105	0.81
MB2312	3/4"	19	30	70	1.015	280	4.060	130	1.17
MBDD2304	1/4"	6,4	14,4	145	2.102,5	580	8.410	45	0,16
MBDD2305	5/16"	7,9	17,7	130	1.885	520	7.540	55	0,41
MBDD2306	3/8"	9,5	19,3	110	1.595	440	6.380	70	0,57
MBDD2308	1/2"	12,7	22,7	93	1.348,5	372	5.394	85	0,69
MBDD2310	5/8"	15,9	26,9	80	1.160	320	4.640	105	0,81
MBDD2312	3/4"	19,0	30	70	1.015	280	4.060	130	1,17
MBDD2316	1"	25,4	37,4	55	797,5	220	3.190	150	2,42