



Crimp Specification

Parflex Division

maandag, september 21, 2026

*All units in inches

Crimper: Hose Style: Coupling Style: Hose
Adjustable **563TJ** **43** Description

Wire Braided High Performance
Hose Tough Jacket
SAE 100R17

Size	Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-8	21MM ONLY	0.915	FULL		1-5/16	VFull
-10	26MM ONLY	1.050	FULL		1-9/16	VFull
-12	27MM / 29MM	1.255	FULL	-	1-1/2	VFull
-16	37MM / 39MM	1.565	FULL		1-3/4	VFull

Comments
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
PFD: Pertains to steel & stainless steel fittings. Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Do not use a ParKrimp Machine to crimp stainless steel 43 Series on a Parflex Hose
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.

VFull

