



Crimp Specification

Parflex Division

maandag, september 21, 2026

*All units in inches

Crimper: Hose Style: Coupling Style: Hose
Adjustable **563TJ** **55** Description

Wire Braided High Performance
Hose Tough Jacket
SAE 100R17

Size	Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-4	12mm / 13mm	0.530	1.076	-	1-3/16	VHY
-6	14mm / 16mm	0.675	1.116		1-5/16	VHY
-8	19mm / 20mm	0.805	1.246		1-9/16	VHY

Comments
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)
PFD: Pertains to steel & stainless steel fittings. Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.

VHY

