



Crimp Specification

Parflex Division

maandag, september 21, 2026

*All units in inches

Crimper: Hose Style: Coupling Style: Hose
Adjustable **563TJ** **56** Description

Wire Braided High Performance
Hose Tough Jacket
SAE 100R17

Size	Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-4	12mm / 13mm	0.530	FULL	-	15/16	VFull
-6	14mm / 16mm	0.675	FULL		1	VFull
-8	19mm / 20mm	0.805	FULL		1-1/8	VFull

Comments
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).

VFull

