



Crimp Specification

Parflex Division

maandag, september 21, 2026

*All units in millimeters

English ▼

Crimper:	Hose Style:	Coupling Style:	Hose	High pressure hose
Adjustable	580N	56	Description	SAE 100R8

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-8	20mm / 22mm	23.11	FULL	-	28	VFull
-10	23mm / 25mm	25.65	FULL	-	31	VFull
-12	27mm / 29mm	29.46	FULL	-	34	VFull
-16	32mm / 34mm	37.72	FULL	-	49	VFull

Comments
Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)

VFull

