



Crimp Specification

maandag, september 21, 2026

*All units in millimeters

English ▼

Crimper:	Hose Style:	Coupling Style:	Hose	ISO 3862 Type R13
Adjustable	R35TC	V4/V6	Description	Parker Specification

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-12	32mm	33,9	FULL	Min Die Lenght 70mm		VFull
-16	40mm	42,5	FULL	Min Die Lenght 85mm		VFull
-20	50mm	50,2	FULL	Min Die Lenght 100mm		VFull
-24	62mm	63,2	FULL	Min Die Lenght 110mm		VFull
-32	74mm	77,35	FULL	Min Die Lenght 118mm		VFull
-40	92mm	94	FULL	Die Set min Lenght 150mm		VFull
-48	96mm	99,6	FULL	Die Set min Lenght 118mm		VFull

Comments
Size -12 up to -20 Fitting V4 (external and internal skiving)
Minimum of 340 tons crimping force for size -32
Size -24 up to -48 Fitting V6 (external and internal skiving)
Crimp Diameter Tolerance is +/- 0.2mm
Minimum of 400 tons crimping force for size -40

Size	External Skive	External Tool	Internal Skive	Internal Tool
12	52		15	
16	65		17	
20	74		21,5	
24	65		22	
32	75		22	
40	99		30	
48	75		22	

VFull

