



Crimp Specification
Polyflex Europe Division

woensdag, september 9, 2026

**All units in millimeters*

English ▾

Crimper:
Adjustable

Hose Style:
1202H

Coupling Style:
55

Hose
Description

Polyflex Thermoplastic Hose

Size	End Fitting	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
-8		21,5 or 22 mm	21,9	32		41	VHY

Comments
PFDE: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety).
PFDE: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFDE: Pertains to steel & stainless steel fittings. Refer to Polyflex Catalog 4460 for hose assembly instructions.
PFDE: Crimp diameter is measured minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFDE: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0,15\text{mm}$ ($\pm 0.005"$). Crimp length tolerance is $\pm 1\text{mm}$ ($0.04"$).
PFDE: Crimp acceptance is based on the center measurement average with a maximum taper of $0,25\text{mm}$ ($0.010"$) between the top and bottom crimp averages.

VHY

