



Crimp Specification

donderdag, september 10, 2026

*All units in millimeters

English ▼

Crimper:	Hose Style:	Coupling Style:	Hose	
Adjustable	2030TB-V70CON	F6	Description	PTFE hose convoluted, conductive

Size	End Fitting	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing	PDF
Standard Straight Dies								
-4		min. 12mm	12,0	FULL	see pdf	23,0	VFull	View
-5		min. 14mm	14,8	FULL	see pdf	26,0	VFull	View
-6		min. 14mm	16,7	FULL	see pdf	25,0	VFull	View
-8		min. 17mm	18,9	FULL	see pdf	27,0	VFull	View
-10		min. 20mm	21,5	FULL	see pdf	31,0	VFull	View
-12		min. 24mm	25,3	FULL	see pdf	29,0	VFull	View
-16		min. 32mm	35,0	FULL	see pdf	30,0	VFull	View
-20		min. 40mm	41,9	FULL	see pdf	38,0	VFull	View

Comments
PFDE: Pertains to steel & stainless steel fittings. Refer to Polyflex Catalog 4460 for hose assembly instructions.
Crimp Diameter Tolerance is +/- 0.1mm (0.005)

