



Crimp Specification
Polyflex Europe Division

donderdag, september 10, 2026

**All units in millimeters*

English ▾

Crimper:	Hose Style:	Coupling Style:	Hose	Polyflex Thermoplastic Hose Wire reinforced
Adjustable	2040N (V00)	56	Description	

Size	End Fitting	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies							
-3		min. 12mm	11,8	FULL		16	VFull
-4		min. 12mm	13,8	FULL		24	VFull
-5		min. 14mm	15,8	FULL		1	VFull
-6		min. 17mm	17,4	FULL		1	VFull
-8		min. 20mm	21,6	FULL		1-1/8	VFull
-10		min. 24mm	25,1	FULL		31	VFull
-12		min. 28mm	28,2	FULL		34	VFull
-16		min. 34mm	35,2	FULL		49	VFull

Comments
PFDE: Crimp acceptance is based on the center measurement average with a maximum taper of 0,25mm (0.010") between the top and bottom crimp averages.
PFDE: Crimp diameter tolerance on all Crimpers is $\pm 0,25\text{mm}$ ($\pm 0.010"$).
PFDE: Pertains to steel & stainless steel fittings. Refer to Polyflex Catalog 4460 for hose assembly instructions.
PFDE: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety).
PFDE: Crimp diameter is measured minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFDE: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.

VFull

