

[Home](#)

[Print](#)



Crimp Specification

Hose Products Division

donderdag, september 10, 2026

\*All units in millimeters

English ▾

| Crimper:<br>Adjustable | Hose Style:<br>424 | Coupling Style:<br>43                      | Hose<br>Description | For Phosphate Ester Fluids |                |                   |         |
|------------------------|--------------------|--------------------------------------------|---------------------|----------------------------|----------------|-------------------|---------|
| Size                   | End Fitting        | Crimper Die                                | Crimp Diameter      | Crimp Length               | Approx Setting | Hose<br>Insertion | Drawing |
| Standard Straight Dies |                    |                                            |                     |                            |                |                   |         |
| -16                    |                    | 38 - 40mm Diameter.<br>70mm Minimum Length | 40.65               | FULL                       |                | 44                | VFull   |
| -20                    |                    | 48 - 50mm Diameter.<br>90mm Minimum Length | 50.30               | FULL                       |                | 48                | VFull   |
| -24                    |                    | 54 - 58mm Diameter.<br>90mm Minimum Length | 58.40               | FULL                       |                | 37                | VFull   |
| -32                    |                    | 66 - 69mm Diameter.<br>90mm Minimum Length | 69.70               | FULL                       |                | 46                | VFull   |

| Comments                                                                                                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special assembly instructions: Do not allow tube to contact any petroleum base fluids. Use liquid soap as hose lubricant.                                                    |
| DIE SIZES LISTED ARE THE MINIMUM CLOSED DIAMETER ALLOWED. DIE LENGTH MUST BE ADEQUATE TO ACHIEVE FULL CRIMP LENGTH AS SHOWN IN ONE STRIKE, MULTIPLE STRIKES ARE NOT ALLOWED. |
| Crimp Diameter Tolerance is +/- 0.010" (0.25mm)                                                                                                                              |

