



Crimp Specification
Hose Products Division

donderdag, september 10, 2026
**All units in inches*

Crimper:	Hose Style:	Coupling Style:	Hose	GlobalCore Hydraulic Hose 28 MPa/4000 psi Constant Working Pressure
Adjustable	487/487ST/TC/CP 43		Description	

Size	End Fitting	Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies							
-4		15-17mm Diameter. 50mm Minimum Length	0.655	FULL		0.81	VFull
-6		20 - 21mm Diameter. 65mm Minimum Length	0.835	FULL		1.13	VFull
-8		22 - 24mm Diameter. 65mm Minimum Length	0.955	FULL		1.31	VFull
-10		26 - 27mm Diameter. 65mm Minimum Length	1.070	FULL		1.56	VFull
-12		28 - 31mm Diameter. 70mm Minimum Length	1.255	FULL		1.50	VFull
-16		38 - 41mm Diameter. 70mm Minimum Length	1.640	FULL		1.75	VFull

Comments
Crimp Diameter Tolerance is +/- 0.010" (0.25mm)
DIE SIZES LISTED ARE THE MINIMUM CLOSED DIAMETER ALLOWED. DIE LENGTH MUST BE ADEQUATE TO ACHIEVE FULL CRIMP LENGTH AS SHOWN IN ONE STRIKE, MULTIPLE STRIKES ARE NOT ALLOWED.

