



Crimp Specification
Hose Products Division

donderdag, september 10, 2026

**All units in millimeters*

English ▼

Crimper:	Hose Style:	Coupling Style:	Hose	GlobalCore Hydraulic Hose 28 MPa/4000 psi Constant Working Pressure
Adjustable	487/487ST/TC/CP 77		Description	

Size	End Fitting	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies							
-20		49 - 50mm Diameter. 84mm Minimum Length	50.30	FULL		63.8	V77
-24		57 - 59mm Diameter. 90mm Minimum Length	59.20	FULL		67.7	V77
-32		69 - 72mm Diameter. 100mm Minimum Length	73.05	FULL		77.5	V77

Comments
Do not use any lubricant to assemble spiral hose and fittings.
Minimum of 380 tons crimping force required for size -32 stainless steel fittings.
DIE SIZES LISTED ARE THE MINIMUM CLOSED DIAMETER ALLOWED. DIE LENGTH MUST BE ADEQUATE TO ACHIEVE FULL CRIMP LENGTH AS SHOWN IN ONE STRIKE, MULTIPLE STRIKES ARE NOT ALLOWED.
Crimp Diameter Tolerance is +/- 0.010" (0.25mm)
Minimum of 300 tons crimping force required for size -32 steel fittings.

