



Crimp Specification
Parflex Division

donderdag, september 10, 2026

*All units in millimeters

English ▼

Adjustable Hose Style: Coupling Style: Hose
 528N **56**

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-3	10mm / 12mm	12.45	FULL	-	16	VFull
-4	12mm / 14mm	14.48	FULL	-	24	VFull
-5	12mm / 14mm	16.00	FULL	-	26	VFull
-6	14mm / 16mm	17.40	FULL	-	25	VFull
-8	20mm / 21mm	21.59	FULL	-	28	VFull
-10	20mm / 22mm	24.38	35.46	-	31	VHY

Comments
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)
Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).

