



Crimp Specification

Parflex Division

donderdag, september 10, 2026

*All units in millimeters

English ▼

Crimper: **Adjustable** Hose Style: **53DM** Coupling Style: **56** Hose Description: **Meets or exceeds SAE 100R18**

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-4	12mm / 13mm	13.97	FULL	-	24	VFull
-5	13mm/14mm	16.00	FULL		26	VFull
-6	16mm / 17mm	17.91	FULL	-	25	VFull
-8	20mm / 22mm	22.10	FULL	-	28	VFull
-10	20mm/22mm	26.54	FULL		43	VFull

Comments
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)

VFull

