



Crimp Specification
Parflex Division

donderdag, september 10, 2026

**All units in millimeters*

English ▼

Crimper:	Hose Style:	Coupling Style:	Hose	
Adjustable	575X	CG	Description	Low expansion hose

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-3	10mm / 12mm	12.45	21.18	-	23	VHY
-4	12mm / 14mm	14.48	27.33	-	30	VHY
-6	14mm / 16mm	17.40	28.35	-	33	VHY
-12	27mm / 29mm	30.73	53.34	-	56	VHY
-16	37mm / 39mm	41.02	55.12	-	70	VHY

Comments
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Pertains to steel & stainless steel fittings. Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)

VHY

