



Crimp Specification
 Parflex Division

woensdag, september 9, 2026

*All units in millimeters

English

Crimper:	Hose Style:	Coupling Style:	Hose	Wire Braided High Performance Hose
Adjustable	590	58	Description	

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-10	20mm / 22mm	25.65	35.46	-	43	VHY
-12	27mm / 29mm	29.46	35.46		44	VHY
-16	32mm / 34mm	37.08	48.16	-	58	VHY

Comments
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of $0.010"$ (0.25 mm) between the top and bottom crimp averages.
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Pertains to steel & stainless steel fittings. Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)

VHY

