



Crimp Specification

Parflex Division

woensdag, september 9, 2026

*All units in millimeters

English ▼

Crimper:	Hose Style:	Coupling Style:	Hose	Wire Braided High Performance Hose Tough Jacket
Adjustable	590TJ	48	Description	

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies						
-12	27MM / 29MM	30.5 / 30.8	FULL	-	25	VFull
-16	36MM / 38MM	38.3 / 38.6	FULL		32	VFull

Comments
PFD: Pertains to steel & stainless steel fittings. Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)
PFD: Crimp diameter tolerance on all Adjustable Crimpers is $\pm 0.005"$ ($\pm 0.13\text{mm}$). Crimp length tolerance is $\pm 0.030"$ ($\pm 0.76\text{mm}$).
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.

VFull

