



Crimp Specification
Hose Products Division

Wednesday, September 9, 2026

**All units in millimeters*

English ▾

Crimper:
Adjustable

Hose Style:
721TC

Coupling Style:
71

Hose
Description

SAE 100R12
N 856 Type R12

Size	End Fitting	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies							
-6		22 - 24mm Diameter. 40mm Minimum Length	24.40	FULL		27	VFull
-8		27 - 28mm Diameter. 45mm Minimum Length	28.20	FULL		32	VFull
-10		28 - 31mm Diameter. 50mm Minimum Length	31.25	FULL		33	VFull
-12		32 - 34mm Diameter. 50mm Minimum Length	34.65	FULL		37	VFull
-16		38 - 43mm Diameter. 64mm Minimum Length	43.30	FULL		44	VFull
-20		49 - 51mm Diameter. 64mm Minimum Length	51.70	FULL		46	VFull
-24		54 - 58mm Diameter. 80mm Minimum Length	58.40	FULL		59	VFull
-32		66 - 70mm Diameter. 90mm Minimum Length	70.75	FULL		62	VFull

Comments
Do not use any lubricant to assemble spiral hose and fittings.
DIE SIZES LISTED ARE THE MINIMUM CLOSED DIAMETER ALLOWED. DIE LENGTH MUST BE ADEQUATE TO ACHIEVE FULL CRIMP LENGTH AS SHOWN IN ONE STRIKE, MULTIPLE STRIKES ARE NOT ALLOWED.
Crimp Diameter Tolerance is +/- 0.010" (0.25mm)

