

[Home](#)

[Print](#)



Crimper:
Adjustable

Hose Style:
787/787ST/TC/CP 77

Coupling Style:
Hose

Hose
Description

GlobalCore Hydraulic Hose
35 MPa/5000 psi Constant
Working Pressure

Size	End Fitting	Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing
Standard Straight Dies							
-8		22 - 23mm Diameter. 45mm Minimum Length	0.940	FULL		1.36	V77
-10		26 - 27mm Diameter. 50mm Minimum Length	1.067	FULL		1.53	V77
-12		30 - 31mm Diameter. 60mm Minimum Length	1.255	FULL		1.78	V77
-16		38 - 39mm Diameter. 70mm Minimum Length	1.551	FULL		2.13	V77
-20		49 - 50mm Diameter. 84mm Minimum Length	1.980	FULL		2.51	V77
-24		57 - 59mm Diameter. 90mm Minimum Length	2.330	FULL		2.67	V77
-32		69 - 72mm Diameter. 100mm Minimum Length	2.875	FULL		3.05	V77

Comments
Crimp Diameter Tolerance is +/- 0.010" (0.25mm)
Do not use any lubricant to assemble spiral hose and fittings.

