



Crimp Specification

Parflex Division

Wednesday, September 9, 2026

*All units in millimeters

English ▼

Crimper: Hose Style: Coupling Style: Hose
Adjustable **919** **91N** Description

SAE 100R14, TYPE A PTFE
hose with Stainless Braid
Natural FDA compliant tube

Size	Crimper Die	Crimp Diameter	Crimp Length	Approx Setting	Hose Insertion	Drawing	PDF
-4	See attachment for profile	8.76			12.7	91N-ADJ	View
-5	See attachment for profile	10.03			14.3	91N-ADJ	View
-6	See attachment for profile	12.19			15.9	91N-ADJ	View
-8	See attachment for profile	14.61			17.5	91N-ADJ	View
-10	See attachment for profile	17.15			17.5	91N-ADJ	View
-12	See attachment for profile	20.32			19.1	91N-ADJ	View
-16	See attachment for profile	26.80			23.8	91N-ADJ	View

Comments
PFD: Crimp diameter is measured at a minimum of three places, 45 degrees apart, at the top, then middle and bottom of the crimp.
PFD: Crimp acceptance is based on the middle measurement average with a maximum taper of 0.010" (0.25 mm) between the top and bottom crimp averages.
Crimp Diameter Tolerance is +/- 0.010" (0.25mm)
PFD: Align measurement caliper or micrometer on the center of crimp impressions avoiding the crimp ribs.
PFD: Pertains to steel & stainless steel fittings. Refer to Parflex Catalog 4660 for hose assembly instructions. (www.parker.com/parflex).
PFD: Reference Parker Fluid Connector Group (FCG) Safety Bulletin 4400-B.1 (www.parker.com/safety)

91N-ADJ

