

INTERPUMP TREEATHLON

THEOT3K



APPLICATIONS :



APPLICABLE SPECIFICATIONS

IMM SPECS

Compact hose. NO-SKIVE construction. NBR tube compound compatible with several fluids. Approved up to 500.000 impulse cycles. Tested at 120% Max WP.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 3 high tensile steel wire braids.

Coverage: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluids: Mineral and biological oils, glycol-water based, water, lubricants.

working temperature: from -40 to +100° C petroleum based fluids (Intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THEOT3K-06	3/8"	9.5	06	18.8	500	7250	2000	29000	110	4.331	0.584	0.392	0022-06
THEOT3K-08	1/2"	12.7	08	22.4	475	6888	1900	27550	140	5.512	0.833	0.560	0022-08
THEOT3K-10	5/8"	16	10	25.8	420	6090	1680	24360	200	7.874	0.967	0.650	0022-10
THEOT3K-12	3/4"	19	12	29.6	380	5510	1520	22040	240	9.449	1.189	0.799	0022-12
THEOT3K-16	1"	25.4	16	38.0	315	4568	1260	18270	300	11.811	1.737	1.167	0022-16

Available with MSHA and Mega cover. In case of order use code THEMT3K and THEVT3K.

Marking: -