

NAME

gma-mapper-protocol – GMA client/server protocol specification

EXPERIMENTAL

This document includes experimental changes to the protocol which have not yet been officially released.

DESCRIPTION

The `mapper(6)` program displays a battle grid map for the players to see their tactical positions with respect to their opponents and features of their environment (e.g., dungeon rooms). To take advantage of its full multi-user capabilities, multiple `mapper` clients may be connected to the `GMA server(6)`. The following document is the definitive specification describing the protocol used to communicate all messages between these programs (as well as others which interact with the `GMA server`, such as `gma-console(6)`).

When a client is connected to a `GMA server`, they exchange commands to indicate changes to the map display or other game state information. To help keep communications simple and to help clients recover from malformed or missing data, each command is a newline-terminated line of text as described in detail below. If the `mapper` sends one of these commands to the service, it is indicating that the local user made those changes and requests that other connected map clients update themselves accordingly. If the `mapper` receives the command from the service, it should comply to make the corresponding change to itself.

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in RFC 2119.

The software implementing this protocol **MUST** allow Unicode text encoded as UTF-8 everywhere (of which 7-bit ASCII is a subset).

Each command (sent or received) consists of a command word followed by a JSON object holding the parameters appropriate to that command. (See the description of the `//` command for an exception to this rule.)

The JSON object **MAY** be omitted (particularly if the command in question has no parameters). Any expected parameter fields which do not appear in the JSON object are automatically assumed to have an appropriate “zero” value (i.e., empty string, zero numeric value, empty list, boolean false, etc.). Any fields sent which were not expected by the receiver are silently ignored.

JSON field names are matched case-sensitively. A client **MAY** match names regardless of case but **MUST** emit them as documented here.

Field values are strings unless otherwise noted.

Unless otherwise noted, there is no response expected from these commands. Even where a response is expected, it will be asynchronously sent. In any case the client **SHOULD NOT** wait for a server response before considering its request to be completed. As a special case, a client **MAY** be implemented to wait synchronously for a server response during the authentication negotiation stage.

This describes protocol version 422. These notes are intended to be detailed enough to implement a client from and should be considered the definitive standard reference to the protocol.

In the protocol command descriptions, **BOLD** text indicates literal text to be sent as-is, *Italics* indicate a parameter whose value should appear in place of the name shown, and [square brackets] surround optional items which may be omitted.

The normal course of actions at the start of the conversation is for the server to immediately send an initial greeting beginning with a `PROTOCOL` command followed by comments, `AC`, `DSM`, `UPDATES`, and/or `WORLD` commands, then send an `OK` command to indicate to the client its protocol version and to issue an authentication challenge (if configured to authenticate). It is **RECOMMENDED** that the initial greeting be limited only to comments, waiting until after authentication to send anything more specific about your game.

After the `OK` command, the client responds with an `AUTH` command if it is required to authenticate. The

server will respond with GRANTED or DENIED and then MAY issue more of the initial greeting commands listed above.

Finally, the server will issue a READY command to the client and begin normal interaction with the client.

The server MUST NOT send the AC, GRANTED, OK, READY, UPDATES, or WORLD commands after the initial READY is sent. Clients MUST NOT send the AUTH command after receiving the server's READY signal. (Note that prior to protocol 414, servers were not allowed to send DENIED to clients after the READY message. Now they can send a DENIED message at any time to indicate that they wish to terminate the client's session immediately.)

Command Summary

The messages sent by clients and servers is summarized in the following table and then explained in detail in the following paragraphs. In the table, Message is the standard message name recommended for identifier names in source code, Command is the string actually sent over the network, C↔S indicates whether the message is only sent from client to server, only from server to client, or if it could be sent in either direction. Priv indicates if the command may only be sent by a client authenticated as the GM. Note that Reply indicates the command which SHOULD (eventually) arrive in response, but no guarantee is made as to if or when that happens since all communications are asynchronous.

| Message | Command | C↔S | Reply | Priv | Payload | Description |
|---------------------|---------|-----|-----------------|-------|---------|---|
| Accept | ACCEPT | C→S | — | no | JSON | Subscribe to a set of messages |
| AddAudio | AA | C↔S | — | no | JSON | Add audio to client's known set |
| AddCharacter | AC | C←S | — | N/A | JSON | Add primary PC to party |
| AddDicePresets | DD+ | C→S | DD= | no | JSON | Add presets to user's set |
| AddImage | AI | C↔S | — | no | JSON | Add image to client's known set |
| AddObjAttributes | OA+ | C↔S | — | no | JSON | Add values to an attribute |
| AdjustView | AV | C↔S | — | no | JSON | Scroll clients' views |
| Allow | ALLOW | C→S | — | no | JSON | Indicate supported features |
| Auth | AUTH | C→S | GRANTED | no | JSON | Authenticate to server |
| Challenge | OK | C←S | AUTH | N/A | JSON | Ask client to authenticate |
| CharacterName | AKA | C↔S | — | no | JSON | Declare character name for a player |
| ChatMessage | TO | C↔S | — | no | JSON | Send chat message |
| Clear | CLR | C↔S | — | no | JSON | Remove objects from client |
| ClearChat | CC | C↔S | — | no | JSON | Clear the chat history |
| ClearFrom | CLR@ | C↔S | — | no | JSON | Remove elements from a map file |
| CombatMode | CO | C↔S | — | yes | JSON | Turn on/off combat mode |
| Comment | // | C↔S | — | no | any | Human-readable comment |
| DefineDicePresets | DD | C→S | DD= | maybe | JSON | Store new presets for user |
| DefineDiceDelegates | DDD | C→S | DD= | maybe | JSON | Assign die-roll delegates |
| Denied | DENIED | C←S | — | N/A | JSON | Server denies access |
| Echo | ECHO | C↔S | ECHO | no | JSON | Send data for server to echo back to client |
| Failed | FAILED | C↔S | — | yes | JSON | Request failed or denied by GM |
| FilterAudio | AA/ | C→S | — | yes | JSON | Filter saved audio definitions |
| FilterCoreData | CORE/ | C→S | — | yes | JSON | Filter availability of the game database |
| FilterDicePresets | DD/ | C→S | DD= | maybe | JSON | Remove some presets for user |
| FilterImages | AI/ | C→S | — | yes | JSON | Filter saved image definitions |
| Granted | GRANTED | C←S | — | N/A | JSON | Server grants access |
| HitPontAcknowledge | HPACK | C↔S | — | yes | JSON | Acknowledge hit point update request |
| HitPointRequest | HPREQ | C↔S | FAILED HPACK | no | JSON | Request change in hit points |
| LoadArcObject | LS-ARC | C↔S | — | no | JSON | Add an arc to the map |
| LoadCircleObject | LS-CIRC | C↔S | — | no | JSON | Add an ellipse to the map |
| LoadFrom | L | C↔S | — | no | JSON | Load elements from file |
| LoadLineObject | LS-LINE | C↔S | — | no | JSON | Add a line to the map |
| LoadPolygonObject | LS-POLY | C↔S | — | no | JSON | Add a polygon to the map |

| | | | | | | |
|------------------------------|-----------|-----|-------------------|-------|------|---|
| LoadRectangleObject | LS-RECT | C↔S | — | no | JSON | Add a rectangle to the map |
| LoadSpellArea-OfEffectObject | LS-SAOE | C↔S | — | no | JSON | Add an area of effect to the map |
| LoadTextObject | LS-TEXT | C↔S | — | no | JSON | Add some text to the map |
| LoadTileObject | LS-TILE | C↔S | — | no | JSON | Add a graphic tile to the map |
| Marco | MARCO | C←S | POLO | N/A | none | Check if client is alive |
| Mark | MARK | C↔S | — | no | JSON | Visually mark a spot |
| PlaceSomeone | PS | C↔S | — | no | JSON | Place creature token |
| Polo | POLO | C→S | — | no | none | Acknowledge server's ping |
| Priv | PRIV | C←S | — | N/A | JSON | Privileged command denied |
| Protocol | PROTOCOL | C←S | — | N/A | int | Signal protocol version in use |
| QueryAudio | AA? | C↔S | AA | no | JSON | Ask for definition of audio |
| QueryCoreData | CORE | C→S | CORE= | no | JSON | Query the core game database |
| QueryCoreIndex | COREIDX | C→S | COREIDX= | no | JSON | Query the core database index |
| QueryDicePresets | DR | C→S | DD= | maybe | JSON | Request user's presets |
| QueryImage | AI? | C↔S | AI | no | JSON | Ask for definition of image |
| QueryPeers | /CONN | C→S | CONN | no | none | Request list of peer clients |
| Ready | READY | C←S | — | N/A | none | Server sign-on complete |
| Redirect | REDIRECT | C←S | — | N/A | JSON | Instruct client to use a different server |
| RemoveObjAttributes | OA- | C↔S | — | no | JSON | Remove values from an attribute |
| RollDice | D | C→S | ROLL | no | JSON | Initiate a die roll |
| RollResult | ROLL | C←S | — | N/A | JSON | Result of a die roll |
| Sync | SYNC | C→S | any | no | none | Request replay of commands |
| SyncChat | SYNC-CHAT | C→S | CC ROLL TO | no | JSON | Request replay of messages |
| TimerAcknowledge | TMACK | C↔S | — FAILED | yes | JSON | Acknowledge timer request |
| TimerRequest | TMRQ | C↔S | TMACK PROGRESS | no | JSON | Request a new timer |
| Toolbar | TB | C↔S | — | yes | JSON | Turn on/off client toolbar |
| UpdateClock | CS | C↔S | — | yes | JSON | Change the current time of day |
| UpdateCoreData | CORE= | C←S | — | N/A | JSON | Update a core data item |
| UpdateCoreIndex | COREIDX= | C←S | — | N/A | JSON | Update core data index |
| UpdateDicePresets | DD= | C←S | — | N/A | JSON | Receive user's presets |
| UpdateInitiative | IL | C↔S | — | yes | JSON | Update the initiative list |
| UpdateObjAttributes | OA | C↔S | — | no | JSON | Update object attributes |
| UpdatePeerList | CONN | C←S | — | N/A | JSON | Notify of all connected peers |
| UpdateProgress | PROGRESS | C↔S | — | no | JSON | Indicate progress on task |
| UpdateStatusMarker | DSM | C↔S | — | yes | JSON | Define creature status marker |
| UpdateTurn | I | C↔S | — | yes | JSON | Indicate turn in combat |
| UpdateVersions | UPDATES | C←S | — | N/A | JSON | Advertise software updates |
| World | WORLD | C←S | — | N/A | JSON | Campaign world info |

Command Details

The client/server messages and their parameters are detailed below, ordered by the server command string sent or received.

// This is a server comment. The entire command SHOULD be ignored by all clients. This is used to inject informative context and messages into the client/server conversation which may be of interest for debugging or interactive use.

The mapper client will interpret a server comment beginning with the text "notice:" which is received during the initial connection negotiation (i.e., before the READY message is given by the server) as a notice that the end user should see. The text following the word "notice:" is posted in an alert box. Clients MUST recognize the string in all lower-case if

they choose to implement this feature; they MAY also recognize it regardless of case.

This is one of two exceptions to the rule that a command contains a JSON parameter object. In this case, the entire line should be ignored by the client and not interpreted further. This allows, for example, comments to be sent at the start of the server's signon message to provide a human-readable declaration as to the allowed usage of the server.

PROTOCOL v

This command (which—if used at all—MUST be the first command sent by the server to the client) gives an up-front indication to the client as to what protocol version is expected by the server. Older versions of the server waited until the OK command to notify the client, but as of protocol version 400 this is now too late for the client to correctly process the commands that may be sent before the OK. This, along with the // server comment command, are the only two commands which do *not* have a JSON data payload attached to them. The protocol version number is simply sent as an ASCII string of digits separated from the PROTOCOL command word by a space. The reason for this is that this data format is valid in all protocol versions, including those before version 400, so it can be used to unambiguously identify the server's protocol to all possible clients.

Servers which implement protocol versions 400 and later MUST send this message at the start of their conversations. Servers which implement older protocol versions SHOULD send it.

AA Add an audio clip to the map. The payload is a JSON object with the following fields:

Format

The audio format in which the sound clip is encoded. Currently the only format supported is “wav” but others may be supported in the future.

Name The name of the audio clip as known within the mapper.

File The filename or server ID by which the audio clip can be retrieved.

IsLocalFile (bool)

If true, then File gives a local file pathname for the audio clip; otherwise it gives the server-specific ID which the client will use to retrieve the file from the server.

The mapper VTT client caches and manages audio files in a manner analogous to the way it handles image files (see the description of the AI server message below).

AA? Request for the named audio clip. Clients may send this if they need an audio clip of the given *name* (as described above for the AA command) but no such sound is defined yet in the client. This queries the server or connected peers to see if any of them know of the needed file. The client should continue to process tasks without waiting for a response (which is never guaranteed). If another peer knows of the requested file, it should respond with an “AA” command. The payload is a JSON object with the following fields:

Name The audio clip name as known to the mapper.

AA/ Filters (removes) all the saved audio clip definitions held in the server's database whose names match a regular expression. The payload is a JSON object with the following fields:

Filter

The regular expression used to select which audio clip names will be removed.

KeepMatching (bool)

If true, only those sounds whose names match the Filter expression will be kept; the others will be removed. Otherwise, the opposite is done: those whose names match Filter will be removed.

| | |
|--------|---|
| AC | Add a character to the pop-up menu for map clients. This makes it easy to place important character tokens on the map and ensures that such tokens are given consistent <i>id</i> values rather than generating random ones. Clients MUST NOT send this command to each other; it is intended for the server to send to the clients. The payload includes the same fields as the PS command. |
| ACCEPT | <p>A client sends this message to the server to indicate that from this point forward (until another ACCEPT command), only the commands listed should be sent to it by the server. The payload is a JSON object with this parameter:</p> <p><i>Messages (list)</i></p> <p>A list of command names the client wishes to receive. This is a list of command names as they appear in this specification (e.g., ["AI", "CO", "TO"]). If it contains the special value "*" or is empty, this means to accept all messages. Note that the server may still decide to send messages such as comments or the MARCO command (or others) at its discretion despite this request from the client.</p> |
| AI | <p>Add an image to the map. (Supersedes the function of the AI, AI:, AI., and AI@ commands as of protocol version 400.) The payload is a JSON object with the following fields:</p> <p><i>Animation (object)</i></p> <p>If this value is given and non-null, this image is to be animated from individual frames. If the client is capable of animating multi-frame files, the base filename can be used directly. Servers offering this file SHOULD provide the multi-frame animated image file in a variety of formats, and SHOULD provide single-frame files in all formats in which they provide static images.</p> <p>Individual frame files are named by prefixing the base filename with ":<i>n</i>:" where <i>n</i> is the frame number, starting with 0. The Animation object has the following fields:</p> <p><i>Frames (int)</i></p> <p>The number of frames in the animation.</p> <p><i>FrameSpeed (int)</i></p> <p>The number of milliseconds to delay between frames.</p> <p><i>Loops (int)</i></p> <p>If present and non-zero, the animation will play this many times before stopping. Otherwise, the animation plays forever.</p> <p><i>Name</i> The name of the image as known within the mapper.</p> <p><i>Sizes (list of objects)</i></p> <p>A list of sizes available for this object. This will be <i>merged</i> with any previously defined sizes for the same image name. Each element of this list is an object with the following fields:</p> <p><i>File</i> The filename or server ID by which the image can be retrieved.</p> <p><i>ImageData (base64-encoded bytes)</i></p> <p>If non-empty or not null, this provides the raw image data. This is DEPRECATED but still supported. Instead, images SHOULD be loaded to the game server and their ServerID used by clients.</p> <p><i>IsLocalFile (bool)</i></p> <p>If true, then File gives a local file pathname for the image; otherwise it gives the server-specific ID which the client will use to retrieve the file from the server.</p> <p><i>Zoom (float)</i></p> <p>The magnification level this bitmap represents for the given image. Typically images are provided for zoom levels of 0.25, 0.5, 1, 2, and 4.</p> |

This does not *draw* the image on the map; it merely defines it so the client knows what to draw when an image of the given `Name` at the specified `Zoom` factor is called for.

Note on clients retrieving images by server ID when `IsLocalFile` is `false` and `File` contains a server-side ID: as currently implemented, the `mapper` client checks to see if it has a cached version of the file. If so, and that file is newer than 2 days, it is used without further checks. If the cached file is older, the server is queried to see if it has a newer version of the file; if so, that is retrieved and cached; otherwise, the existing cache is updated to note that it was the known latest version as of that moment. If no usable cache file is available, the file with the given id is obtained from the server. For example, if the image id were “`abcdefg`”, the URL of the file to be retrieved would be `base/a/ab/abcdefg.gif` or `base/a/ab/abcdefg.png` where `base` is the base URL as specified to the `--curl-url-base=base` option (or `curl-url-base=base` configuration file line).

Servers SHOULD be set up to provide alternative file formats so that, for example, with ID `abcdefg` files such as `a/ab/abcdefg.jpg` (JPEG format) or `a/ab/abcdefg.png` (PNG format) may be retrieved for clients which use those other formats. Currently, `mapper.tcl` uses GIF or PNG format files.

AI? Request for the named image. Clients may send this if they need an image of the given `name` and `zoom` (as described above for the **AI** command) but no such image is defined yet in the client. This queries the server or connected peers to see if any of them know of the needed image. The client should continue to process tasks without waiting for a response (which is never guaranteed). If another peer knows of the requested image, it should respond with an “AI” command. The payload is a JSON object with the following fields:

Name The image name as known to the mapper.

Sizes (*list of objects*)

The list of sizes for which the image data are requested. Each element of the list is an object with the following field:

Zoom (*float*)

The requested magnification factor for the image.

AI/ Filters (removes) all the saved image definitions held in the server’s database whose names match a regular expression. The payload is a JSON object with the following fields:

Filter

The regular expression used to select which image names will be removed.

KeepMatching (*bool*)

If true, only those images whose names match the `Filter` expression will be kept; the others will be removed. Otherwise, the opposite is done: images whose names match `Filter` will be removed.

AKA Declare that the logged-in user is controlling one or more characters on the VTT map. Normally, the mapper tool will assume that users are controlling creatures whose names (as known on the map) match the players’ login usernames. If that is not the case for any given player, this command may be sent by that player’s client to indicate what creature token(s) they are controlling, so the other map clients (and any other interested programs) can know who is who on the battlefield. The JSON payload has the following fields:

Names (*list of strings*)

The names of the creatures this player is controlling.

NotPlaying (*bool*)

If true, this user (all clients logged in with the same username) is not playing any characters and should not be included in any UI dialogs or other features which select or list active characters.

| | |
|-------|---|
| | <p>User The login name for the user's session. This field is not normally supplied as part of the request by the player's client. It will be filled in by the server when relaying the AKA message to all peer clients, using the requester's logged in user name in this field.</p> |
| ALLOW | <p>The client MAY send this command to the server after logging in. This tells the server that the client supports one or more optional features. The JSON payload has the following field:</p> <p>Features (<i>list of strings</i>)</p> <p>This is a list of feature names which the client wishes to enable. Every time an ALLOW command is given, it resets the entire set of features, rather than adding to them. Currently, the following one features are recognized:</p> <p>DICE-COLOR-BOXES</p> <p>The client supports formatting controls in the die-roll title string sent to the server in the D command and received from the server via the ROLL command. Specifically, the title may consist of multiple sub-titles separated by U+2016 characters (). Each of these may also have a suffix consisting of the U+2261 (≡) character followed by a color name or #rrggb color code, indicating the foreground color for that part of the title. A second such suffix may be added to indicate the background color. If this feature is not enabled, these formatting codes are stripped out by the server before sending die roll results to a client which isn't prepared to interpret them.</p> <p>DICE-COLOR-LABELS</p> <p>The client supports formatting controls in die-roll label fields in the roll details in a format as described above for sub-titles. This allows custom colors to be used for special die-roll modifiers that need to stand out visually from all the rest.</p> <p>GMA-MARKUP</p> <p>The client is capable of interpreting GMA markup formatting codes received in chat messages.</p> |
| AUTH | <p>If the server included a challenge string (see the OK command below), then it requires a password before the client is allowed to join the server. This is intended to prevent accidental connections by clients to the wrong servers, and to filter out nuisance connections from spammers or other random connections, so it is a fairly simple authentication mechanism using a password shared by all clients in a play group. The payload is a JSON object with the following parameters:</p> <p>Client</p> <p>This describes the client program. By convention, this value SHOULD include the version number (e.g., "mapper 4.0.1").</p> <p>Platform</p> <p>This describes the platform on which the client is running. It SHOULD have the format "OS version machine" (e.g., "FreeBSD 14.3-RELEASE amd64").</p> <p>Response (<i>base64-encoded bytes</i>)</p> <p>The client's response to the server's challenge.</p> <p>User If provided, the User field gives the local username of the player who is running the client. This name will be displayed for purposes such as chat-window conversations and dice rolling. If not provided, "anonymous" will be used, unless the authentication is successful for the GM role, in which case "GM" will be used regardless of any value sent by the client for the User field.</p> <p>Calculation of the Response field is as follows.</p> <p>Given:</p> |

C is the server's challenge as a binary string of bytes (after decoding from the base-64 string actually sent by the server),

i is the number of rounds of hash function to apply,

$H(x)$ is the binary SHA-256 hash digest of *x*,

P is the password needed to connect to the server, and the notation

$x||y$ means to concatenate strings *x* and *y*,

To calculate the `Response` string, the client must do the following:

- (1) If no value for *i* was provided by the server, obtain *i* by extracting the first two bytes from *C* as an unsigned, big-endian, 16-bit integer value.
- (2) Calculate $D=H(C||P)$.
- (3) Repeat *i* times: Calculate $D'=H(P||D)$; then let $D=D'$

The binary value of *D* is then encoded using base-64 and sent as the `Response` value.

Starting with protocol version 332, the server is guaranteed to respond to the `AUTH` command with either a `DENIED` or `GRANTED` message (q.v.). The client MAY wait for this response before proceeding with its other operations, so that it knows for sure how the authentication went.

AV

Adjust the map's viewport by making the grid square identified by the `Grid` parameter visible at the top-left of the display. If this field is not present or is empty, then clients MAY fall back to the older behavior of adjusting the view by setting the horizontal scrollbar to `XView` as a fraction of its full distance, where 0.0 is all the way to the left and 1.0 is all the way to the right; the vertical scrollbar is similarly set based on `YView` where 0.0 is all the way to the top and 1.0 is all the way to the bottom. The payload is a JSON object with the following fields:

`Grid` The name of the grid square which should be in the upper-left of the display. This uses the same naming convention as the grid is labelled on the display (e.g., the far upper-left grid square of the entire map is `A0`).

`XView` (*float*)

The fraction of full distance the *x*-axis scrollbar should be moved to.

`YView` (*float*)

As `XView`, but for the *y* axis.

CC

Clear the chat history. The payload is a JSON object with the following fields:

`RequestedBy`

The name of the user who initiated this operation, if known. Clients SHOULD NOT set this field; it is set by the server when sending this message to clients.

`DoSilently` (*bool*)

If true, the client MAY clear its chat history without notifying the user; otherwise it SHOULD indicate the action to the user.

`Target` (*int*)

If 0 or missing, clear all messages in the history. Otherwise, if positive, clear all messages with `MessageID` less than the `target` value. If negative, clear all but the most recent $-target$ messages (e.g., a `target` of -50 clears all but the most recent 50 messages).

`MessageID` (*int*)

This message counts the same as a chat message and is included in the history itself. Thus, the server sets this field to a unique identifier for this message. Clients SHOULD NOT set this field.

| | |
|------|---|
| CLR | <p>Remove object with a given internal ID from the map. The payload is a JSON object with the following field:</p> <p>ObjID This may be the object ID for the specific object to remove, or “*” to mean all objects should be removed; “E*” to mean all map elements should be removed; “M*” to mean all monster tokens should be removed; “P*” to mean all player tokens should be removed; or the form “[<i>imagename</i>=]<i>name</i>”) may be used, which removes a creature token whose display name matches the <i>name</i> value.</p> |
| CLR@ | <p>This command tells the client to “unload” the contents of a map file. In other words, all the elements listed in that file are removed from the map canvas rather than being added to it. The payload is a JSON object with the following fields:</p> <p>File The pathname or server ID which specifies the map file in question.</p> <p>IsLocalFile (<i>bool</i>) If true, File refers to a local file the client can read directly. Otherwise it is a server ID which can be used to fetch the file from its cache or from the server.</p> |
| CO | <p>Sets the combat mode state in the client. The payload is a JSON object with the following attribute:</p> <p>Enabled (<i>bool</i>) If true, the client should be in combat (initiative) mode, otherwise it should not.</p> |
| CONN | <p>Update the list of connected peer clients to those described in the JSON payload, which contains the following field. Clients MUST NOT send this command. This supersedes the CONN, CONN:, and CONN. commands from protocol versions prior to 400.</p> <p>PeerList (<i>list of objects</i>) A list of objects, each describing a single connected client, with the following fields:</p> <p>Addr The IP address and port the peer connected from.</p> <p>User The username as provided during authentication.</p> <p>Client The name of the client program in use.</p> <p>LastPolo (<i>float</i>) The number of seconds since the server last heard a POLO command from the peer.</p> <p>IsAuthenticated (<i>bool</i>) If true, the client successfully negotiated the server’s authentication process.</p> <p>AKA (<i>list of strings</i>) The list of creature names, if any, that the player is controlling instead of a creature matching the User field value.</p> <p>NotPlaying (<i>bool</i>) If true, this user is not playing any characters at all. In this case the AKA value should be empty and MUST be ignored at any rate.</p> <p>IsMe (<i>bool</i>) If true, this object describes the client which received this command.</p> |
| CORE | <p>Query the server’s core SRD database. The server SHOULD respond with a CORE= message containing the requested item or indicating that no such item was found. The payload is a JSON object with the following attributes:</p> |

| | |
|---|--|
| Type | The type of object being requested. Currently the supported types include <code>bestiary</code> , <code>class</code> , <code>feat</code> , <code>language</code> , <code>skill</code> , <code>spell</code> , and <code>weapon</code> . |
| Code | The GMA unique code that identifies the entry. May be blank since only one of <code>Code</code> and <code>Name</code> is necessary. |
| Name | The common name of the entry. May be blank since only one of <code>Code</code> and <code>Name</code> is necessary. |
| RequestID | If you place an arbitrary string value in this field, it will be sent back to you in the corresponding <code>CORE=</code> response message. |
| CORE= | This message from the server provides core SRD data for an item that the client might want to know about. Typically, this is in response to a <code>CORE</code> message from the client requesting this information. Clients MUST gracefully deal with the receipt of a <code>CORE=</code> message they didn't need or are no longer interested in, as well as the case where they requested core data but received no corresponding response. The payload is a JSON object containing the requested data, with the following attributes: |
| NoSuchEntry | (<i>bool</i>) If true, the requested entry was not found in the database. Otherwise (including the case where this attribute is missing) the remaining attributes contain the requested information. |
| IsHidden | (<i>bool</i>) If true, the requested entry is hidden from player view by the GM. No <code>Data</code> field will be given. |
| IsLocal | (<i>bool</i>) If present and true, this entry was a local addition to the database. Otherwise it was imported from publicly-available SRD data for the game system. |
| Code | The GMA code for the requested item. |
| Name | The GMA name for the requested item. |
| Type | The type of core data item being provided, as per the <code>Type</code> field of the <code>CORE</code> message (q.v.). |
| RequestID | If present and non-empty, this is the <code>RequestID</code> value provided by the client when making the request that resulted in this reply. |
| Data | This value is a JSON-encoded object containing the specific data relating to the item in question. Its format depends on the item <code>Type</code> . |
| The <code>Data</code> payload for each type is described in the following sections. N.B. The descriptions that follow of the various <code>Data</code> objects are speculative at this point and entirely subject to change. | |
| Data fields for <code>bestiary</code> type items: | |
| ImageTag | If the GM maintains a library of creature token images for their local <code>bestiary</code> , and one is defined for this creature, then this field will contain the image tag name for this creature's token. |
| Species | The name of the species of the creature. |
| CR | The challenge rating of the creature. Fractions may appear as, e.g., $1/2$. |

XP (*int*)
 XP reward for defeating the creature.

Class The class and levels if applicable.

Alignment (*object*)
 The alignment for the creature, as an object with the following fields:

 Alignments (*list*)
 A list of alignment codes (CG, LN, etc.) which this creature may be.

 Special
 Any special comment about alignment.

Source
 The reference to the source this item originally came from.

Size (*object*)
 The creature's size, as an object with the following fields:

 Code The size code as documented in the GMA encounter and familiar data.

 SpaceText
 Any comment about the creature's threatened space.

 ReachText
 Any comment about the creature's reach distance.

Type Creature type.

Subtypes (*list*)
 List of applicable subtypes.

Initiative (*object*)
 The creature's initiative modifier, as an object with the following fields:

 Mod (*int*)
 The total initiative modifier value.

 Special
 Any special information related to initiative.

Senses
 A description of the creature's senses.

Aura A description of the creature's aura effect.

HP (*object*)
 The creature's hit points as an object with the following fields:

 Typical (*int*)
 Typical hit point total.

 Current (*int*)
 The creature's current hit point total.

 Special
 Any special comments about the creature's health.

 HitDice
 The hit dice die-roll specification.

Save (*object*)
 The creature's saving throws, as an object with these fields:

Fort *(object)*
 The Fortitude saving throw, as an object with these fields:

Mod *(int)*
 The total saving throw modifier value.

Special
 Any special commentary about this saving throw.

NoSavingThrow *(bool)*
 If true, the creature has no such saving throw at all and the other fields should be ignored.

Ref1 *(object)*
 The creature's Reflex saving throw, in the same format as the Fortitude saving throw.

Will *(object)*
 The creature's Will saving throw, in the same format as the Fortitude saving throw.

Special
 Any special comments about the creature's saving throws.

DefensiveAbilities
 A description of the creature's defensive abilities.

DR *(object)*
 The creature's damage reduction, as an object with the following fields:

DR *(int)*
 The number of hit points resisted.

Bypass
 Description of what will bypass the DR.

Immunities
 A description of the things the creature is immune from.

Resists
 A description of the resistances the creature has.

Speed *(object)*
 The creature's movement speed, as an object with the following fields:

Code The encoded list of speeds.

Special
 Additional commentary about movement speed.

SpecialAttacks
 A description of the various special attacks the creature may make.

Abilities *(object)*
 The creature's ability scores, as an object with the following fields:

Str *(object)*
 The Strength score, as an object with the following fields:

Base *(int)*
 The raw ability score value.

Special
 Any special notes about this ability score.

| | | |
|--------------|----------|--|
| NullScore | (bool) | If true, the creature does not have this ability score at all, and the other fields should be ignored. |
| Dex | (object) | The Dexterity score, as an object in the same format as Strength. |
| Con | (object) | The Constitution score, as an object in the same format as Strength. |
| Int | (object) | The Intelligence score, as an object in the same format as Strength. |
| Wis | (object) | The Wisdom score, as an object in the same format as Strength. |
| Cha | (object) | The Charisma score, as an object in the same format as Strength. |
| Combat | (object) | The combat statistics for the creature, as an object with the following fields: |
| BAB | (int) | The base attack bonus. |
| CMB | (int) | The combat maneuver bonus. |
| CMD | (int) | The combat maneuver defense value. |
| CMBSpecial | | Any special notes on the CMB. |
| CMDSpecial | | Any special notes on the CMD. |
| SQ | | A description of the creature's special qualities. |
| Environment | | A description of the environment where this creature commonly appears. |
| Organization | | A description of the groups in which this creature is usually found. |
| Treasure | | The treasure type and amount usually found with this creature. |
| Appearance | | A short description of the creature's physical appearance. |
| IsTemplate | (bool) | If true, this is a template from which other creatures can be built. |
| Strategy | (object) | The creature's strategy in an encounter, as an object with these fields: |
| BeforeCombat | | How the creature will prepare for the encounter. |
| DuringCombat | | How the creature will manage its encounter with the players. |

Morale
 How resolute the creature is in the face of deadly combat.

IsCharacter *(bool)*
 If true, this is a creature that may be a character.

IsCompanion *(bool)*
 If true, this creature may be a companion.

IsUnique *(bool)*
 If true, there is only one of this creature in existence.

AgeCategory
 The age category for the creature.

Gender
 The creature's gender

Bloodline
 The creature's bloodline.

Patron
 The creature's patron deity.

AlternateNameForm

DontUseRacialHD *(bool)*
 If true, don't use racial hit dice when creating a character with levels.

VariantParent

Mythic *(object)*

- IsMythic *(bool)*
- MR *(int)*
- MT *(int)*

OffenseNote

StatisticsNote

Gear *(object)*

- Combat
- Other

Schools *(object)*

- Focused
- Prohibited
- Opposition

ClassArchetypes

BaseStatistics

RacialMods

Mystery

Notes

Domains *(list)*

AC *(object)*

- Components *(object)*
- Adjustments *(object)*
- AttackModes *(list of objects)*
 - Tier *(int)*
 - BaseWeaponID
 - Multiple *(int)*
 - Name
 - Attack
 - Damage
 - Critical *(object)*
 - CantCritical *(bool)*
 - Threat *(int)*
 - Multiplier *(int)*
 - Ranged *(object)*
 - IsRanged *(bool)*
 - Increment *(int)*
 - MaxIncrements *(int)*
 - IsReach *(bool)*
 - Special
 - Mode
- Languages *(list of objects)*
 - Name
 - IsMute *(bool)*
 - Special
- Feats *(list of objects)*
 - Code
 - Parameters
 - IsBonus *(bool)*
- Skills *(list of objects)*
 - Code
 - Modifier *(int)*
 - Notes
- Spells *(list of objects)*
 - ClassName
 - CL *(int)*
 - Concentration *(int)*
 - NoConcentration *(bool)*
 - PlusDomain *(int)*

Description

Special

Spells (*list of objects*)

Name

AlternateName

Frequency

Special

Slots (*list of objects*)

IsCast (*bool*)

IsDomain (*bool*)

MetaMagic (*list*)

Data fields for class type items:

Spells (*object*)

Describes the spell-casting capability of the class, with the following fields:

Type The magic type (arcane, etc.)

Ability

The name of the ability score relevant to spells.

HasBonusSpells (*bool*)

True if the class allows bonus spells (e.g., clerics' domain spells)

IsSpontaneousCaster (*bool*)

True if the class casts spells without needing to prepare them in advance.

CastPerDay (*list*)

A list of the number of spells which may be cast per day. Each element is an object which has the following values:

ClassLevel (*int*)

The class level for which this applies.

SpellLevel (*int*)

The level of spell for which this applies.

IsProhibited (*bool*)

If true, this level of spell is not possible at this class level.

IsUnlimitedUse (*bool*)

If true, this level of spell can be used an unlimited number of times per day at this class level.

Number (*int*)

The number of spells granted at this spell and class level.

PreparedPerDay (*object*)

The number of spells which may be prepared per day by class level and spell level. Each element has the same values as for the CastPerDay attribute above.

SpellsKnown (object)

The number of spells which may be known by class level and spell level. Each element has the same values as for the `CastPerDay` attribute above.

Data fields for feat type items:

Parameters

Describes the parameters allowed for the feat, if any.

Description

The text description of the feat.

Prerequisites

The text description of the prerequisites for the feat.

Benefit

Description of the benefit granted by taking this feat.

Normal

Description of the situation if the feat is not taken.

Special

Any special notes or circumstances.

Source

The reference to the source book or other place where this feat originally came from.

*Race**Note**Goal**CompletionBenefit**SuggestedTraits**Types (list)*

A list of feat types to which this belongs.

FlagNames (list)

A list of flags which apply to this feat.

MetaMagic (object)

If this is a metamagic feat, the following fields will appear in the `MetaMagic` attribute:

IsMetaMagicFeat (bool)

If true, this is a metamagic feat and the other fields here will apply.

*Adjective**LevelCost (int)*

The number of levels this feat costs (i.e., the number of spell slots higher than normal this spell will use).

IsLevelCostVariable (bool)

If true, the spell level cost is not fixed.

Symbol

The symbol to use on GMA character record sheets and encounter run sheets for spells which were prepared with this feat.

Data fields for language type items:

There is no additional data. The language name appears in the Name field.

Data fields for skill type items:

ClassSkillFor (*list*)

A list of the class codes for which classes this skill is a class skill.

Ability

Relevant ability score name.

HasArmorPenalty (*bool*)

If true, this skill is subject to an armor check penalty.

TrainingRequired (*bool*)

If true, the character must be trained to use this skill.

Source

The reference to the original source for this skill.

Description

The abbreviated text description of the skill.

FullText

The full text description of the skill.

ParentSkill

The name of the parent skill if applicable.

IsVirtual (*bool*)

If true, this skill cannot be taken; one of its children must be taken specifically.

IsBackground (*bool*)

If true, this is a background skill.

Data fields for spell type items:

School

Descriptors (*list*)

Components (*object*)

Components (*list*)

Material

Focus

HasCostlyComponents (*bool*)

MaterialCosts (*int*)

Casting (*object*)

Time

Special

Range (*object*)

Range

Distance (*int*)

DistancePerLevel (*int*)

DistanceSpecial

```

    Effect (object)
        Area
        Effect
        Targets
    Duration (object)
        Duration
        Special
        Concentration (bool)
        PerLevel (bool)
    SR (object)
        SR
        Special
        Object (bool)
        Harmless (bool)
    Save (object)
        SavingThrow
        Effect
        Special
        Object (bool)
        Harmless (bool)
    IsDismissible (bool)
    IsDischarge (bool)
    IsShapeable (bool)
    ClassLevels (list of objects)
        Class
        Level (int)
    Deity
    Domain
    Description
    Source
    Bloodline
    Patron
Data fields for weapon type items:
    Cost (int)
        The cost in copper pieces for a standard weapon of this type.
    Damage (object)
        The damage done by this weapon. The value is an object where the keys
        are size category codes and the values are the damage done by a weapon
        of that size category.

```

Critical (*object*)

The critical hit stats for the weapon. This is an object with the following fields.

CantCritical (*bool*)

If true, this weapon cannot score a critical hit at all. The other fields should be ignored.

Multiplier (*int*)

The number of extra dice to add when a critical hit is scored.

Threat (*int*)

The minimum die value to threaten a critical hit (e.g., 19 means to threaten on a natural 19–20).

Ranged (*object*)

For ranged weapons, the fields in this attribute describe those parameters.

Increment (*int*)

The range increment for the weapon.

MaxIncrements (*int*)

The maximum number of increments before the target is out of range.

IsRanged (*bool*)

If true, this is a ranged weapon and the other fields are meaningful.

Weight (*int*)

The weight in grams of the weapon.

DamageType (*list*)

The type of damage done. This is a list of strings, with each indicating a damage type such as B for bludgeoning, P for piercing, and S for slashing.

Qualities (*list*)

A list of weapon qualities. The codes in the list may include: 1 (one-handed), 2 (two-handed), b (brace), D (disarm), d (double), E (Elven), f (fragile), G (Gnome), g (grapple), H (Halfling), L (light), M (monk), m (martial), O (Orc), R (ranged), r (reach), S (non-lethal), s (simple), t (trip), U (unarmed), W (Dwarven), X (exotic), x (deadly), and Z (masterwork).

CORE/

Filter the core database items which are visible to the players. The payload is a JSON object with the following fields:

Filter

This is a regular expression matching the `Code` value of all the entries to be affected by this command.

Type The type of core data entry to target.

IsHidden (*bool*)

If true, set the entries matching the `Filter` expression so they are hidden from the players. Otherwise, make them visible.

InvertSelection (*bool*)

If true, all entries which do *not* match `Filter` are affected.

- COREIDX** Query the core database to retrieve a list of entries. This gives the information by which the actual data behind these entries may be retrieved using the **CORE** message. The payload includes the following fields:
- Type** The type of entry to index, as per the **CORE** message.
 - CodeRegex**
If present and non-empty, limit the responses to those whose **Code** field matches this regular expression.
 - NameRegex**
If present and non-empty, limit the responses to those whose **Name** field matches this regular expression.
 - Since** (*RFC 3339-formatted datetime string*)
If present and non-empty, limit the responses to those which were modified since the given date and time.
 - RequestID**
If a string value is provided here, it will be repeated in the server's response message.
- COREIDX=** The server response to a **COREIDX** message. Since the number of entries in the database may be quite large, the server will send a number of these reply messages, one per item from the database. It includes the following fields:
- RequestID**
The **RequestID** sent to the server in the **COREIDX** request that initiated this update, if any.
 - Type** The database item type
 - IsDone** (*bool*)
If true, this is the final response in this set.
 - N** (*int*) The number of response this is, starting with 1.
 - Of** (*int*)
The total number of responses that will be given.
 - Name** The item's name.
 - Code** The item's code.
- CS** Update the client's clock. The JSON payload includes the following fields:
- Absolute** (*int64*)
The absolute time on the GMA world clock (in tenths of seconds since the epoch).
 - Relative** (*int64*)
The elapsed time on the GMA world clock (in tenths of seconds since the GM set a reference point, e.g., the start of combat).
 - Running** (*bool*)
If true, the local client should continue advancing the clock in real-time locally after updating the time to the new absolute time. Otherwise, cancel real-time updates if they were running, leaving the clock at the given absolute time. The local real-time updating events should only be performed when not in combat mode.
- D** Roll dice using the server's built-in die rolling facility. The JSON payload contains the following fields:
- Recipients** (*list of strings*)
The names of the people who should receive the results of the die roll. For global or GM results, this should be `null`.

RequestID

If you put a string value in this field, it will be sent back in any **ROLL** response messages the server sends to you in response to this request. This allows a client to associate responses to the requests that generated them. You may leave this blank or omit it if you don't care to match requests with responses.

ToAll (*bool*)

If true, this is a global die-roll, and the result should be sent to all clients.

ToGM (*bool*)

If true, this die-roll will be sent "blind" to the GM only. Not even the requester will see the result of the roll, only the GM will.

RollSpec

The die-roll specification, like "d20+12" or "6d6 fire". If this field is empty, the previous die-roll from this client is repeated, or "1d20" if there was no previous one.

Targets (*list of strings*)

The names of the creatures to whom this die roll is being specifically targeted. If the die-roll spec contains a `|target` option, that will override any value passed here and will be reflected in the **Targets** field of the results sent back from the server.

Type The type of die roll. Normally this is left out or blank, but it may be a string that describes the specific purpose for this roll. While any string value may be given (which allows client-specific usage of this field since the string will be sent back with the die-roll results), the following are defined with specific purposes:

attack

The die roll is assumed to be a combat attack roll checked against the known AC of the target creature. This will cause the results to include a success or failure indicator. If there is no known AC for the creature, this has no effect. This will also force the same behavior as putting the "`|c`" option in the **RollSpec** string.

attack-ff

As **attack**, but checks against the flat-footed AC. This is automatically assumed if the **Type** is **attack** and the creature is known to be flat-footed.

attack-touch

As **attack**, but checks against the touch AC.

attack-cmd

As **attack**, but checks against the CMD value.

damage

Doesn't affect the process of rolling the dice, but the **gma** program will deduct the result value from the target creature's hit point total upon receipt of the results.

Certain die-roll spec options may automatically imply the type value. In which case, the die-roll options take precedence and will be reflected in the results returned from the server.

DD

Define (store) Die-Roll Presets. Clients send this command to the server to request it to store a set of die-roll presets for it to retrieve for use in subsequent sessions. The JSON payload is identical to the one sent by the server in the **DD=** command, except that it does not contain **DelegateFor** or **Delegates** fields.

The server **SHOULD** respond by issuing a **DD=** command to all peer clients logged in with

the same username as the affected user as well as any authorized delegates.

DD+ Add to Die-Roll Presets. Clients send this command to the server to add an additional set of die-roll presets to the collection it was already holding for that user. The JSON payload is identical to the one sent for the **DD** command. The server **SHOULD** respond by issuing a **DD=** command to all peer clients logged in with the same username as the requesting client and all authorized delegates.

DD/ Filter die-roll presets. This removes a set of die-roll presets from the server's storage for the user. The server **SHOULD** respond by issuing a **DD=** command to all peer clients logged in with the same username as the affected user and all authorized delegates. The JSON payload includes the following fields:

Filter

The value is a regular expression. The server will delete all die-roll presets whose **Name** attribute matches this regular expression.

Global (*bool*)

If present and true, this operation filters items out of the system-wide global set of presets instead of a user's set. This makes this a privileged command.

For

The name of the user whose presets are being filtered. This is optional; if omitted, the presets of the user making this request are affected. Only the GM and authorized delegates may filter other users' presets.

DD= This command defines the list of die-roll presets the client should know. This replaces any previous set of presets the client was using. Clients **MUST NOT** send this command. This supersedes the commands **DD=**, **DD :**, and **DD .** in protocol versions prior to 400. The JSON payload includes the following fields:

For

The username of the player for whom these presets were stored. The default, if no name is given or if it is empty, is the currently logged-in user.

Global (*bool*)

If present and true, these presets are the system-wide set that apply to all users rather than those of the target user. For the **DD** command, this means the operation is redefining the entire set of system-wide presets. For **DD+**, the operation is adding to the system-wide presets without changing the other existing ones.

Note that when any of these commands are sent with this parameter set to true, they become privileged commands.

In the **DD=** response from the server, the presence of this parameter with a true value indicates that this contains only the system-wide presets. In this case, clients **MUST NOT** conclude that the absence of the user's personal presets in the payload means it can delete its copy of the user's presets. Without the **Global** parameter, this message contains all presets the client should know about, including the user's set plus the system-wide globals.

DelegateFor (*list of strings*)

The list of all the other users for whom the target user is a delegate.

Delegates (*list of strings*)

The list of delegates who also have visibility and control for the owner's presets. If empty or missing, there are no delegates.

Presets (*list of objects*)

Each element in this list describes a single preset. It has the following fields:

Global (*bool*)

If this parameter is present and true, it indicates that this preset was defined at a system-wide level and may not be changed or deleted by the user. The client **MUST** track it separately and **MUST NOT** confuse it with

a non-global preset with the same name. This parameter is only set by the server. Clients MAY NOT set this when defining or modifying presets and sending them to the server.

We RECOMMEND clients use a notation to make system-wide and per-user preset names distinct to the user. For example, the GMA Mapper uses single prefix characters on names for variables and tables as in `$foo` and `#bar`, but double prefix characters for system-wide names, as in `$$foo` and `##bar`.

Name The name by which this preset is identified to the user. This MUST be unique for that user. The client SHOULD sort the preset list by the Name field before displaying. If a vertical bar (“|”) appears in the Name, all text up to and including the bar SHOULD be suppressed from display. The formatting of the Name field is not mandated by this specification. However, the following standard interpretation for data to the left of the vertical bar (if any) is RECOMMENDED for clients using this feature:

1. Regular die-roll presets with a preferred display ordering SHOULD have a three-digit decimal zero-padded sequence number to the left of the bar, e.g., “000|attack”, “001|damage”, “002|fort save”, etc. The numbers need not be strictly consecutive. Clients SHOULD use dictionary sorting for preset items so that the numeric sort-order sequence value is correctly arranged regardless of number of characters; however the recommendation here is also to pad them with zeroes to three digits for the benefit of clients which cannot or will not do so. Clients MAY include optional *flags* and *client_data* fields delimited semicolons following the sequence value (e.g., “042;b|example”). This contains a number of single-character flags. The following flag is currently recognized:

b Send the die roll blindly to the GM only.

This means the full definition of the simple preset name is:

sequence[; flags[; client_data]] | name

2. Stored variables MAY be stored as a die-roll preset with a Name field in the format

“\$sequence; var; flags[; client] | displayname”.

where *§* is Unicode character U+00A7 (section symbol), *sequence* is a three-digit decimal zero-padded display sequence number as described above, *var* is the name of the variable by which the contents of this preset may be inserted into another die-roll specification, *flags* are a set of zero or more single-letter flags affecting how the client should use this value, and *client* is an optional field with client-specific data not otherwise defined here. If the *client* field is not given, the semicolon immediately before it may be omitted as well. For example:

“\$042;CL;e|caster level”

The *flags* are up to the client to interpret, but we RECOMMEND the flag “e” to mean the value should be enabled (or “on”) by default and “g” to mean the die-roll expression to the left of it should be grouped together in parentheses.

If the *var* value is empty (e.g., “\$000;;e|inspiration”), clients SHOULD interpret this to mean that the preset’s value should not be assigned to a variable name, but should be appended to any die-roll specification made while it is enabled.

3. It is RECOMMENDED that clients allow for grouping of related presets and/or modifiers by appending one or more group names to the end of the numeric sort order digits. Each such name is separated from the digits and each other with a right-pointing triangle Unicode U+25B6 (represented here as the “>” character). For example, 012|attack is an ungrouped attack roll, 013>monster|attack is an attack roll belonging to the “monster” group, 030>monster>save|Fortitde is a Fortitude saving throw belonging to the “save” subgroup of the “monster” group, and §042>monster;;|mod is a modifier in the “monster” group. Clients SHOULD allow users to collapse all of the die rolls with the same group name(s) appearing consecutively in the die-roll preset list.
4. Stored tables MAY be stored as a die-roll preset with a Name field in the format

#sequence; flags[; client] | tblname

and the DieRollSpec field in the format

; dieexpr; n0; t0; ...; nN-1; tN-1; *; tN;

The field delimiter (“;” in this example) is arbitrary but must be consistent; it is whatever character appears as the first character in DieRollSpec (to allow for punctuation marks such as semicolons to appear in the table text as needed). The semicolon delimiters in the Name field are always semicolons. This declares a lookup table named *tblname* (which MUST be unique within the preset list). The set of *flags* is up to the client to manage. Currently the defined flags are:

- b The die rolls should be send blindly to the GM only.
- m the table’s text may include GMA markup formatting codes

The *dieexpr* gives a standard die-roll expression which the client should send to the server whenever a roll on this table is requested. Following this are a set of cases represented by numeric values *n* in increasing order along with corresponding text strings *t* which may contain GMA markup formatting codes if the *m* flag is present. The last case, which is taken if the result of the die roll exceeded any of the values of *n* found up to that point, is represented by “*”.

When the user wishes to invoke a random roll using the lookup table, the client will send a die-roll request to the server with *dieexpr* (along with, perhaps, additional modifiers and options) to get a random result back, which is then compared to the values in the lookup table until a value is found that is greater than or equal to the result, or the final “*” value is reached, whereupon the corresponding text string is displayed by the client to the user in some appropriate fashion. Clients SHOULD transmit this result to other clients via a TO message.

5. Clients MAY encode arbitrary dictionaries of complex data into presets by encoding the Name field as

©[sequence[; client_data]] | name

where *sequence* is an optional sequence and/or group hierarchy as described above, and *client_data* is an arbitrary string to be interpreted by other programs consuming this preset data as they choose. In this case, the DieRollSpec field MUST be a properly-formed JSON

object string with no newline characters that encodes the data being stored in this preset. The “©” character is the Unicode codepoint U+00A9.

6. Clients MUST gracefully handle the existence of data formats not listed above without losing or corrupting any presets or metadata.

Notably, the `gma(6)` program itself automates the creation and destruction of ephemeral presets for combatants on an encounter-by-encounter basis. The names for these presets include an additional component, *area*, which identifies the dungeon location or encounter identifier. To accomplish this, GMA prepends the string `$[area]` to the *client_data* field for any of the complex types which support that. Otherwise it prepends that string to the *sequence* value.

Description

A text description of the purpose of the preset.

DieRollSpec

The die-roll specification to send to the server when rolling this preset.

DDD Define Die-roll Delegate. Clients send this command to the server to indicate that other user(s) are allowed to retrieve and store their die-roll presets. The server SHOULD immediately send `DD=` commands to the requesting user and all delegates. From this point on, any updates to the requesting user’s presets will result in `DD=` commands sent to all delegates as well. The JSON payload includes:

For The user for whom these delegates are being defined. If empty or missing, the default is to define them for the requesting user. Only the GM may set delegates for someone else.

Delegates (list of strings)

The list of usernames who are allowed to access the requesting user’s die-roll presets. This replaces the previous set of delegates. If the list is empty (or the `Delegates` field missing), then all delegates are removed.

DENIED Access to the server is denied. The server will send this to a client; clients MAY NOT send it. When a client receives this message, it MUST not continue to communicate with the server. In fact, the server SHOULD terminate the network connection after sending the `DENIED` message. The JSON payload sent with this command includes the field:

Reason

Text description of why the access was refused.

DR Retrieve the authenticated user’s die roll presets. This SHOULD result in the server sending the `DD=` command back to the requesting client. The JSON payload may contain the following field:

Global (bool)

If present and true, this requests a list of only the global, system-wide set of presets rather than all of the presets the client should know about.

For The name of the user whose presets are being requested. Only the GM or an authorized delegate may request other users’ presets. If this field is empty or missing, the requesting user’s presets are requested.

DSM Defines (or re-defines) a condition status marker which the client SHOULD use to mark creature tokens when the creature has the associated condition in effect. The JSON payload includes the following fields:

Condition

The name of the condition being described. If there was already a marker defined for that condition, it is replaced with the new definition. If either `Shape` or

`Color` is the empty string or null, then the condition is effectively removed from the list of conditions known to the mapper. Creature conditions are in effect if their name appears in the list value for that creature's `StatusList` attribute. The mapper comes with the following conditions pre-defined: ability damage, ability drained, bleed, blinded, confused, cowering, dazed, dazzled, dead, deafened, disabled, dying, energy drained, entangled, exhausted, fascinated, fatigued, flatfooted, frightened, grappled, helpless, incorporeal, invisible, nauseated, panicked, paralyzed, petrified, pinned, poisoned, prone, shaken, sickened, stable, staggered, stunned, and unconscious.

`Shape` The shape of the marker to be placed if the creature has this condition. The mapper will attempt to arrange multiple markers with the same shape such that they are all visible at the same time. This value may be one of the following:

| | |
|----|---|
| v | A small downward-pointing triangle against the middle of the left edge of the token. (This is a lower-case "v".) |
| v | A small downward-pointing triangle against the middle of the right edge of the token. (This is a lower-case "v".) |
| o | A small circle against the middle of the left edge of the token. (This is a lower-case "o".) |
| o | A small circle against the middle of the right edge of the token. (This is a lower-case "o".) |
| <> | A small diamond against the middle of the left edge of the token. |
| <> | A small diamond against the middle of the right edge of the token. |
| / | A slash (upper right to lower left) through the entire token. |
| \ | A back-slash (upper left to lower right) through the entire token. |
| // | A double slash (upper right to lower left) through the entire token. |
| \\ | A double back-slash (upper left to lower right) through the entire token. |
| - | A single horizontal line drawn through the center of the entire token. |
| = | A double horizontal line drawn through the center of the entire token. |
| | A single vertical line drawn through the center of the entire token. |
| | A double vertical line drawn through the center of the entire token. |
| + | A cross drawn through the entire token. |
| # | A hash-mark drawn through the entire token. |
| V | A large downward triangle drawn around the entire token. (This is an upper-case letter "V".) |
| ^ | A large upward triangle drawn around the entire token. |
| <> | A large diamond drawn around the entire token. |
| O | A large circle drawn around the entire token. (This is an upper-case letter "O".) |

`Color` The color to draw the marker in any of the forms documented above, or the special value "*", which means to draw the marker in the same color as the creature's threatened area.

If `color` begins with "--" (e.g., "--red"), then the marker is drawn with dashed lines instead of solid ones. If it begins with ". ." (e.g., ". .blue"), then the effect

is the same, but the dashes are shorter.

Transparent (*bool*)

If true, the creature token should be displayed in a semi-transparent form whenever it has this condition (added in protocol 404).

Description

A description of the effects on the character of having that condition applied. This is intended to be shown to players (for example, if they hover their mouse over an affected creature token).

ECHO

Ask that the server send this message back to you. This may be used for synchronization since it indicates to the client when the server got to this request amongst the others it received. The following fields may be populated:

s An arbitrary string value.

i (*int*) An arbitrary integer value.

b (*bool*) An arbitrary boolean value.

o (*object*) An arbitrary set of key/value pairs, with each value having any type.

The server will also populate the following additional fields in its reply, which a client can use to calculate the round-trip time for the request and identify how much of that was internal to the server and how much was network latency.

ReceivedTime (*RFC 3339-formatted datetime string*)

The time when the server received the packet from the client.

SentTime (*RFC 3339-formatted datetime string*)

The time when the server sent the response packet to the client.

FAILED

Gives notice that a client request was not accepted. This may be issued by the server for reasons such as an error in the request itself that the server is able to detect before processing it further, or it may originate from a GM client in response to a player request such as TMRQ where the request contains an error or the GM decides to decline the request. If this message is sent by a client, it **MUST** be a privileged client, and will be relayed to the indicated requesting client. The JSON payload includes the following fields:

IsError (*bool*)

If true, this notice indicates that the request failed because it contains an error that prevents it from being carried out.

IsDiscretionary (*bool*)

If true, this notice is the result of a decision by the GM to decline the player's request.

Command

The original command being referenced.

Reason

Freeform text describing why the request failed or was declined. This should be all that needs to be shown to the end user to explain the issue.

RequestID

The unique identifier sent along with the original request.

RequestedBy

The user name of the original requester.

RequestingClient

The client ID of the original requester. When the FAILED message is sent by a GM client, the server will relay it to this client session.

| | |
|---------|---|
| GRANTED | <p>Access to the server is granted. The server will send this to a client; no client should send it. The JSON payload contains the field:</p> <p>User The user name for this client. This is the name provided by the client, “anonymous” if the client didn’t give one, or “GM” if the client authenticated as the GM.</p> |
| HPACK | <p>Acknowledge a hit point change request made via a previous HPREQ message. The JSON payload for this message has the following fields:</p> <p>RequestID The ID of the original request, as sent by the client when making it.</p> <p>RequestingClient The client connection ID as it appeared in the original request.</p> <p>RequestedBy The user name of the original requester. If the server is unable to locate the original requesting client connection as specified by the RequestingClient field, it MAY send HPACK messages to clients logged in by the user named in this field instead.</p> |
| HPREQ | <p>Request an update to a target creature’s hit points. This request will be sent to the GM for approval. If the GM approves, the creature’s hit points will be amended in the system and will be reflected as appropriate in the tracking information sent by the server. The client SHOULD also receive a corresponding HPACK message acknowledging this request. Clients MUST cope with the possibility of not receiving those acknowledgement messages or there being long delays between the request and acknowledgement. If the GM declines to accept the request, or if the request contains an error, a FAILED message SHOULD be sent back to the requesting client with the same RequestID value as the original request. The JSON payload for this message includes the following fields:</p> <p>Targets (<i>list of strings</i>) The names of the creatures as they appear on the map. This should hold a single value when requesting an update to a character’s hit point total, but may, for example, be useful to specify multiple characters at once for communal spells granting many people at once a block of temporary hit points.</p> <p>Description Text description of what this request is for, where it came from, etc.</p> <p>RequestedBy The user name of the user who initiated this request. Clients NEED NOT supply this field; it will be supplied by the server as it relays the request on to the GM.</p> <p>RequestingClient The client connection ID of the user who initiated this request. Clients MUST NOT supply this field; it will be supplied by the server as it relays the request on to the GM. The meaning of this value is opaque and is only used by the server.</p> <p>RequestID A unique identifier for this request. Replies sent back to the requesting client in regard to this request will reference this same ID. A UUID string is suggested for this value.</p> <p>Health (<i>object</i>) The health object values you wish to set. If this is null, no changes are requested. Otherwise, the only values which will be considered for this request are:</p> <p>MaxHP (<i>int</i>) The creature’s maximum number of hit points.</p> |

LethalDamage (*int*)
The amount of lethal damage sustained.

NonLethalDamage (*int*)
The amount of non-lethal damage sustained.

AC (*int*)
Current armor class

FlatFootedAC (*int*)
Current flat-footed armor class

TouchAC (*int*)
Current touch armor class.

CMD (*int*)
Current combat maneuver defense.

TmpHP (*object*)
A request to add temporary hit points to the creature. If `null`, no temporary hit points are being requested. Otherwise, the following fields are expected:

TmpHP (*int*)
The number of temporary hit points to add to the creature's temporary hit point pool.

TmpDamage (*int*)
The number of temporary hit points already removed due to damage (usually this will be zero, but just in case this request needs to account for something that's already happened, this may be noted here).

Expires (*duration*)
The time remaining until the temporary hit points expire, in the same format as for the Expires field in the TMREQ message (q.v.).

I Update the time clock for initiative-based actions. If the mapper is in combat mode, the clock display is updated accordingly. The JSON object payload includes the following fields:

ActorID
The object identifier of the creature whose turn it is. This may be the unique object ID code, the creature name as documented in the AC command, the special string “*Monsters*” which indicates that all creatures with monster-type tokens have initiative, or may be of the form “/regex”, which matches all creatures whose names match the regular expression *regex*.

Hours (*int*)
The number of hours elapsed since the start of combat.

Minutes (*int*)
The number of minutes elapsed since the start of this hour of combat.

Seconds (*int*)
The number of seconds elapsed since the start of this minute of combat.

Rounds (*int*)
The number of rounds elapsed since the start of combat.

Count (*int*)
The number of initiative slots elapsed since the start of the round.

II Update the initiative list. The JSON payload includes the following field:

InitiativeList (list of objects)

The current initiative list is given as a list of initiative slots, each of which is an object with the following fields:

Slot (int)

The slot number. As currently implemented this is a number in the range [0,59] which gives the “count” (1/10th second) in the round where this creature may act.

CurrentHP (int)

The creature’s current hit point total. **This field is deprecated.** Clients **MUST** use the OA command to change a creature’s health attribute when hit points change instead of sending the current hit points here. A future version will remove support for this field.

Name The creature’s name as displayed on the map.

IsHolding (bool)

If true, the creature is holding their action.

HasReadiedAction (bool)

If true, the creature is holding a readied action.

IsFlatFooted (bool)

If true, the creature is flat-footed.

L Loads map elements into the map client, either replacing or adding to the current contents of the map. Supersedes the function of commands L, M, M?, and M@ in protocol versions prior to 400. The payload is a JSON object with the following fields:

File The local pathname or server ID identifying the map file to be loaded.

IsLocalFile (bool)

If true, **File** refers to a local filename; otherwise it is a server ID.

CacheOnly (bool)

If true, the server is only advising the client that it would be good to have a cached copy of the file on hand for later. The client **MUST NOT** actually load the file’s contents to the displayed map at this time.

Merge (bool)

If true, the map elements in **File** are merged with the map’s current contents. Otherwise the map’s current elements are replaced by the new ones in **File**.

LS-type This set of commands load a single map element into the map. As opposed to the **L** command which directs the client to read a file to get one or more objects, this just sends an object directly to it. This may be used, for example, when one client draws an element interactively and wants the other clients to display it as well.

These supersede the function of the commands **LS**, **LS:**, and **LS.** in protocol versions prior to 400.

All of the following **LS-type** commands include as many of the following parameters as are applicable to them, in addition to type-specific parameters:

ID The unique object identifier. This is a string containing upper- or lower-case letters, digits, underscores and octothorpes. By convention, we create these as hexadecimal UUID values, but they may be any arbitrary string, including human-readable IDs such as “PC1”, etc.

X (float)

The *x* coordinate of the “reference point” of the element, in standard map pixel units.

Y (float)

The y coordinate of the “reference point” of the element, in standard map pixel units.

Points (list of coordinate objects)

If an object needs more than a single coordinate pair to specify their location, (e.g., the diagonally opposite corner of a rectangle) the subsequent points are listed in this parameter. Each element in the list is an object with the fields:

X (float)

The x coordinate in standard map pixel units.

Y (float)

The y coordinate in standard map pixel units.

Z (int) The z “coordinate” of the element is its vertical stacking order on the displayed map canvas. Higher numbers are drawn after lower numbers. If two objects have the same z value and physically overlap, the result is not defined.

Line The color used to draw the shape’s outline, as a standard color name or RGB string such as “#336699”.

Fill As with the **Line** field, specifies a color to fill the interior of the element. If omitted or empty, the object will not be filled. Note that line objects are *filled* with the **Fill** color. They don’t have an outline so don’t use the **Line** value.

Stipple

If nonempty, the value is the name of a bitmap image which is assumed to be known to the client. The shape will be filled in with the **Fill** color using this bitmap to form a stipple pattern in that color. If the **Stipple** bitmap is empty or unknown to the client, a solid color fill is used instead. If the **Fill** field is empty, then **Stipple** is ignored. Clients **SHOULD** by default understand stipple bitmap names “gray12”, “gray25”, “gray50”, and “gray75”.

Width (int)

The width in pixel units of the element’s outline.

Layer The map layer this element belongs to. Currently not implemented.

Level The dungeon level where this element appears. Currently not implemented.

Group The object group to which this element belongs. Currently not implemented.

Dash (int)

The outline of the element is to be drawn with the specified dash pattern:

- 0 Solid (the default)
- 1 Long dashes
- 2 Medium dashes
- 3 Short dashes
- 4 Long-Short pattern
- 5 Long-Long-Short pattern

Hidden (bool)

If true, this element **MUST NOT** be displayed on-screen. Currently not implemented by the mapper client.

Locked (bool)

If true, this element **MUST NOT** be edited further by clients.

Each of the following commands which begin with **LS-** defines a different kind of map element.

LS-ARC

Draws an arc on the canvas. The arc is drawn around the circumference of the ellipse inscribed in the rectangle defined by the reference point and the first point in the `Points` attribute (as opposite corners of a rectangle). The payload is a JSON object with these parameters in addition to those common to all map elements:

`ArcMode (int)`

Specifies how to draw the arc on-screen.

- 0 Pie slice (default); connects the arc endpoints to the center of the circle.
- 1 Arc; does not connect the endpoints to anything else.
- 2 Chord; connects the endpoints to each other via a straight line segment.

`Start (float)`

The number of degrees around the circle to begin drawing the arc.

`Extent (float)`

The number of degrees around the circle to end drawing the arc.

LS-CIRC

Draws an ellipse on the map canvas. The payload is a JSON object as described for all map elements above. The ellipse is defined as described for the LS-ARC command, but the entire circumference is drawn.

LS-LINE

Draws a straight line segment from the reference point to the each point in the `Points` attribute (if more than one point is in `Points` the result will be multiple connected line segments). The JSON payload has the following attribute in addition to the common ones described above:

`Arrow (int)`

The style of arrows to draw on the ends of the line:

- 0 No arrows
- 1 Arrow on the first point (the reference)
- 2 Arrow on the last point
- 3 Arrows on both first and last points

LS-POLY

Draws a polygon on the map canvas. The vertices of the polygon start at the reference point and continue through every point in the `Points` attribute, and finally connecting back to the reference point again. The JSON payload contains the following fields in addition to the common ones described above:

`Spline (int)`

The factor to use when smoothing the sides of the polygon between its points. 0 means not to smooth at all, resulting in a shape with straight edges between the vertices. Otherwise, larger values provide more smoothing.

`Join (int)`

The join style for the edges of the polygon:

- 0 Beveled corners
- 1 Mitered corners

2 Rounded corners

LS-RECT

Draws a rectangle defined by the reference point and the first point in the *points* attribute (as opposite corners of the rectangle).

LS-SAOE

Draws the zone of a spell's area of effect on the canvas. The JSON payload contains the following field in addition to those described above:

AoEShape (int)

The shape of the area of effect:

- 0 Cone: a 90° pieslice defined as described for a pieslice arc element.
- 1 Radius: an ellipse defined as described for a circle element.
- 2 Ray: a rectangle defined as described for rectangle elements.

LS-TEXT

Places some text on the canvas. The JSON payload includes the following fields in addition to those common to all elements:

Text The text to be displayed.

Font (object)

The typeface to use for the text. This is an object with the following fields:

Family

The name of the font family as recognized by Tk.

Size (float)

The font size as recognized by Tk. The client MAY truncate this to an integer if it can't handle fractional point sizes.

Weight (int)

The type wight to use. This may be 0 for normal or 1 for bold-face.

Slant (int)

The type slant to use. This may be 0 for Roman (normal) or 1 for Italic (slanted).

Anchor (int)

Where the reference point is considered to be relative to the text:

- 0 Center
- 1 North
- 2 South
- 3 East
- 4 West
- 5 Northeast
- 6 Northwest
- 7 Southwest
- 8 Southeast

LS-TILE

Draws an image tile on the canvas. The JSON payload has the following fields in addition to those common to all map elements:

Image The image name as known to the mapper.

BBHeight (*float*)

The bounding-box height for the region bordering the image.

BBWidth (*float*)

The bounding-box width for the region bordering the image.

MARCO Status check. If received, reply with a **POLO** command. Clients **MUST NOT** send this command.

N.B. It is important that your client not ignore these occasional ping messages. For example, if your client is too slow receiving messages such that the server needs to expend extra work to queue them up for you, it will be willing to do so if you have been at least responding to **MARCO** messages. If you haven't, the server will suspect your client has locked up or is not going to be able to catch up with the data being sent to it, and may decide to terminate the client's connection.

MARK Make a brief animated marker at the specified coordinates to draw attention to that space. The JSON payload contains the following fields:

X (*float*)

The *x* coordinate of the marker.

Y (*float*)

The *y* coordinate of the marker.

OA Updates attributes of a specified map object. Any attributes not listed in the command **MUST** remain as-is. The JSON payload includes the following fields:

ObjID The unique object identifier for the object to be modified. Alternatively, it may be in the form *@name* where *name* is the creature's name in any of the forms allowed for the **AC** command.

NewAttrs (*object*)

The set of new attributes and their values, expressed as an object with field names matching the object attributes to be changed and their associated values being the new values for those attributes.

Example: `OA {"ObjID": "a984a3", "NewAttrs": {"X": 12, "Y": 44.5}}`

Note that there was an implicit assumption in the past that the **Name** attribute of a creature would not change and it could be used as an immutable identifier within a map client for a creature token. However, this is not the case and in fact GMA now includes explicit features to change this very attribute. Clients must be prepared to deal with the consequences of a change to any attribute, including **Name**. The **mapper** client itself does this correctly starting with version 3.39.

OA+ Adds one or more values to a single attribute of an object known to the mapper. The payload is a JSON object with the following fields:

ObjID The unique object identifier, specified as for the **OA** command.

AttrName

The name of the attribute to be modified. This **MUST** be an attribute whose value is a list of strings. (E.g., the **StatusList** attribute of creature objects.)

Values (*list of strings*)

A list of string values to be added to those already in the named attribute.

OA- Removes one or more values from a single attribute of an object known to the mapper. The payload is a JSON object with the following fields:

- ObjID** The unique object identifier, specified as for the `OA` command.
- AttrName**
The name of the attribute to be modified. This **MUST** be an attribute whose value is a list of strings. (E.g., the `StatusList` attribute of creature objects.)
- Values** (*list of strings*)
A list of string values to be removed from those already in the named attribute. It is not an error if the value wasn't there to begin with.
- OK** The server sends this to the client when it is ready for the client to start sending commands to it. The accompanying JSON payload includes the following fields:
- Protocol** (*int*)
The protocol version used by the server. Map clients which do not support that protocol **SHOULD** warn their users and **SHOULD** disconnect since they can't guarantee they can actually communicate with the server.
- Challenge** (*base64-encoded bytes*)
If present, the `Challenge` value is a base-64-encoded authentication challenge. A client must successfully respond with a valid `AUTH` command before any of its commands to the server will be accepted. The server will also refuse to send the client any map updates until it has successfully authenticated.
- Iterations** (*int*)
The number of rounds of hashing to apply to generate the challenge response. This value **SHOULD** be in the range [64,4095].
- ServerStarted** (*RFC 3339-formatted datetime string*)
The absolute wall-clock time that the server was started.
- ServerActive** (*RFC 3339-formatted datetime string*)
The absolute wall-clock time of the server's last `MARCO` ping signal. If this was long ago (more than a minute or two with out-of-the-box server configuration), it is an indicator that the server's main event loop is deadlocked.
- ServerTime** (*RFC 3339-formatted datetime string*)
The current wall-clock time on the server. This provides an accurate point of reference to determine how long ago the other server time values occurred.
- ServerVersion**
The server's version number. (Added in protocol 405.)
- PRIV** Notice from the server that a command sent by the client is denied due to insufficient privilege. Clients **MUST NOT** send this command. The JSON payload includes the following fields:
- Command**
The command the client was attempting.
- Reason**
The reason that command was denied.
- POLO** No-op. Clients **MUST** ignore if received. Clients **SHOULD** send this in response to a `MARCO` command from the server.
- PROGRESS**
The server sends this to the client to indicate progress of a long-running operation such as downloading files. (Formerly this was sent as a comment prior to protocol

version 400.) The payload is a JSON object with the following fields:

`OperationID`

A unique identifier for the operation we're reporting progress for.

`Targets` (*list*)

If this progress bar is associated with a specific character or characters, they are listed by name here.

`IsTimer` (*bool*)

If true, this is showing the status of a running timer instead of an operation in progress.

`Title` The description of the operation in progress. This is suitable for display to the user.

`Value` (*int*)

The current value of the progress meter. Units are arbitrary. The value may fluctuate up or down over the course of the updates that are received. It may also go negative. It is up to the client to display negative values appropriately based on the type of progress meter or other context. For example, timers generated by GMA will run negative for a number of updates to show that the timer has expired before sending a final update with `IsDone` `true` to indicate that the timer should be removed from view.

`MaxValue` (*int*)

The maximum value expected for the progress meter when it is finished. If this is 0, we don't yet know what the maximum will be, which **SHOULD** cause the client to use a progress meter style that indicates that it is not possible to estimate remaining time to completion. Also note that this value **MAY** change over the course of the progress report if the server becomes aware that it has a better maximum value available to it at that point.

`IsDone` (*bool*)

A boolean indication that the operation is completed. The client **SHOULD** remove the progress meter from display when the operation is completed.

Clients **SHOULD NOT** send these; they are for the server to notify the client about progress. If a client does send progress update messages to other peers, it should be clear that what is being tracked is a process that the other clients are interested in.

As a special case, the server may send this message with `OperationID=*` and `IsDone=true`. This is a signal to clients that all timers should be cancelled and dismissed from view. If a subsequent `PROGRESS` message is sent with the `OperationID` of a timer that was dismissed in this way, clients should treat it like a new timer being created at that point.

PS Place a creature token on the map. This may be used to define a new creature object if no object with the given *ID* already exists, or replaces an existing token with the (possibly different) parameters given. The JSON payload includes the following fields:

`ID`

The internal ID by which this creature is to be known. This must be unique. The client which creates the character token locally should create a unique ID, which is then broadcast via this command to the other clients, which use the same ID.

`Name`

The name as displayed on the map. Must be unique among all creatures currently displayed.

Health (*object*)

If not null, this gives the current health status of the creature. It is an object with the following fields:

MaxHP (*int*)

The creature's maximum number of hit points.

TmpHP (*int*)

The creature's temporary hit points, in addition to their maximum.

TmpDamage (*int*)

The number of hit points worth of damage suffered against the temporary hit point total.

LethalDamage (*int*)

The amount of lethal damage sustained.

NonLethalDamage (*int*)

The amount of non-lethal damage sustained.

Con (*int*)

The grace amount of hit points the creature may sustain over their maximum before they are considered dead.

IsFlatFooted (*bool*)

If true, the creature is flat-footed.

IsStable (*bool*)

If true, the creature has been stabilized to prevent death while critically wounded. Creatures which are in non-critical states of health don't have this attribute set even though technically (in a sense) they are "stable".

Condition

A custom condition status to display on the map, if you wish to override the map's calculation.

HPBlur (*int*)

If 0, the creature's health is displayed accurately. Otherwise, this gives the percentage by which to "blur" the hit points as seen by the players. For example, if **HPBlur** is 10, then hit points are displayed only in 10% increments.

AC (*int*)

The creature's current full armor class.

FlatFootedAC (*int*)

The creature's current flat-footed armor class. If this is not specified or is 0, it will be assumed to be the same value as **AC**, but that will not be reflected in this data structure, simply how consumers of the data are free to interpret it.

TouchAC (*int*)

The creature's current touch armor class.

CMD (*int*)

The creature's current combat maneuver defense.

Hidden (*bool*)

If true, this creature token is hidden from player view, although the GM can still see it. Added in protocol 404.

Gx (float)

The grid *x* coordinate for the creature's reference point. Note that this is in grids, not pixel units.

Gy (float)

The grid *y* coordinate for the creature's reference point. Note that this is in grids, not pixel units.

PolyGM (bool)

If true, only the GM may access the polymorph capabilities of this creature. Map clients not logged in as GM MUST not display any information indicating that there are different skins available, nor allow the user to select among them.

Skin (int)

If 0, show the default appearance on the creature's token. Otherwise, show one of the alternative images defined for that creature.

SkinSize (list of strings)

This gives a list of values to use for the *Size* attribute corresponding to the *Skin* number. For example, if there are 3 skins defined for a shape-changing creature, and the first two are medium-size but the third is large, then *SkinSize* would have a value like ["M:base", "M:disguise", "L:giant"].

Elev (int)

The creature's elevation in feet relative to the "floor" level.

Color The color code used to draw the creature's threat zone.

Note A note to attach to the creature token to indicate special conditions or status.

Size The tactical size category of the creature. This has the general form

category[*natural*][*->extended*][*=space*][:[*]*comment*]

where *category* is a single-letter category code, *natural* is a custom natural reach distance in feet (if different than the standard for that size category), *extended* is a custom extended reach distance in feet (if different than the standard for that size category), and *space* is a custom creature space diameter in feet (if different than the standard for that size category). (Changed in protocol 406.)

This is now DEPRECATED. If present and the *SkinSize* field is also present, then the value of *Size* MUST equal the value of the first element of *SkinSize*. The preferred usage going forward is to not set the *Size* field at all, and just use *SkinSize* alone. If there is only one skin for the creature, this value will have only a single value.

DispSize

If non-empty, this indicates that the creature is temporarily resized to the given size category and should be displayed as such. The value is otherwise identical to *Size*. (Added in 406.)

StatusList (list of strings)

A list of condition codes which apply to the character. These are defined by the DSM command (q.v.).

AoE (object)

If not null, a spell area of effect should be drawn around the creature. The value is an object with these fields:

Radius (*float*)

The distance in standard map pixel units away from the creature's center to the perimeter of the area of effect.

Color The color with which to draw the spell area.

MoveMode (*int*)

The mode of locomotion currently employed by the creature:

- 0 Land (walking)
- 1 Burrowing
- 2 Climbing
- 3 Flying
- 4 Swimming

Reach (*int*)

Indicates if the creature is wielding a reach weapon and thus has an expanded threat zone. If 0, the threat zone is normal for the creature. If 1, it cannot attack adjacent foes but has a wider threat space. If 2, it has both threat zones active at the same time.

Killed (*bool*)

If true, the creature is dead.

Dim (*bool*)

If true, the creature does not have initiative now, and their token should be de-emphasized compared to the one with initiative.

CreatureType (*int*)

The specific type of creature. This may be 0 if the type is unknown, 1 for monsters, or 2 for players. Clients **MUST NOT** set this field to a value other than 1 or 2.

CustomReach (*object*)

Specify a custom reach distance for this creature, if different than the standard for a creature of its size category. This contains the following fields:

Enabled (*bool*)

If true, there is a custom reach distance as described in the other fields. if false, the other fields should be ignored.

Natural (*int*)

The number of feet from the perimeter of the creature token to which the creature's natural reach extends.

Extended (*int*)

As Natural but indicates the distance for reach weapons.

Targets (*list of strings*)

The list of designated combat targets. If non-empty, the first creature named in this attribute is the target of attack die rolls and all creatures named are the targets of any damage die rolls made by this creature.

(Added in protocol 406.)

READY The server sends this to the client to indicate that all preliminary data has been sent, authentication (if applicable) has been successful, and the client may proceed to carry out normal operations now.

REDIRECT

Instructs the client to use a different server for this session. This is used when the GM wants to use an alternate server temporarily without requiring the players to

reconfigure all their clients. The server **SHOULD** send this during the initial stage of client interaction to avoid authenticating to a server you won't be using and then authenticating to the other one, but **MAY** be sent at any point. The client **SHOULD** disconnect immediately upon receiving this command, so the rest of the server negotiation may not even happen at all. The JSON payload includes the following values:

Host The host name or IP address of the server to connect to for this session.

Port (*int*)

The TCP port number on which to connect to the server.

Reason

The reason for the redirection to a new server.

This command **SHOULD** appear before any commands which would alter the client's internal state such as **DSM** or **AC**, because we cannot guarantee that the client will undo those settings before connecting to the new server which will send its own set of those commands. Ideally, when redirecting clients to a different server, **REDIRECT** should be the first item in the server's init file.

ROLL Reports the results of a die roll initiated by the **D** command. Clients **MUST NOT** send this command. The JSON payload includes the following fields:

Sender

The name of the user who rolled the dice.

Origin (*bool*)

If present and true upon receipt of this message from the server, this indicates that the client receiving it was the same client who originated the die roll request whose result is being reported here, as opposed to a client who is merely being given a copy of the results of another client's die roll.

Replay (*bool*)

If present and true upon receipt of this message from the server, this indicates that this message is being "replayed" (e.g., as a result of a **SYNC-CHAT** request from the client) and this is not the original sending of the message. As such, the client **SHOULD NOT** make active responses to it such as performing lookup table reports on it.

Recipients (*list of strings*)

The names of the people the message was explicitly addressed to. For global messages, this should be `null`.

Targets (*list of strings*)

The names of the creatures this roll was targeted at. This is simply whatever list was sent in the **D** command's **Targets** field, if any.

Type The type of thing the result applies to. This is simply whatever string was sent in the **D** command's **Type** field, if any.

MessageID (*int*)

The unique number assigned by the server for this chat message. (Die roll results are essentially a kind of chat message.)

MoreResults (*bool*)

If true, there will be more **ROLL** messages yet to come which are part of the result set for the same die roll request.

RequestID

The **RequestID** string passed by the client when requesting this die roll, or the empty string if they didn't.

Sent (*RFC 3339-formatted datetime string*)

The date and time the message was sent. Clients **SHOULD NOT** set a nonempty value for this field. It will be filled in by the server when sending messages to clients. If this field is missing or empty when received from the server, it means the date was not available to report for that message. Note that the special value “0001-01-01T00:00:00Z” is the “zero” value for dates and indicates that the date is not known (as is the case if this field is omitted entirely or is the empty string).

ToAll (*bool*)

If true, this is a global message sent to all clients. The contents of the `Recipients` field are ignored; it should be omitted or set to `null`.

ToGM (*bool*)

If true, this message will be sent only to the GM. The contents of the `Recipients` field are ignored; it should be omitted or set to `null`.

Title The title describing the purpose of the die-roll as set by the user, if any. The title string may include special formatting codes which will be used by clients supporting the `DICE-COLOR-BOXES` optional feature (see the `ALLOW` command for details). Clients which did not request this feature will not see the special formatting codes in the title string.

Result (*object*)

The result of the die roll. This is an object with the following fields:

Result (*int*)

The final numerical result of the die-roll.

InvalidRequest (*bool*)

If true, the die roll never happened because the request could not be understood. In this case, the details about the request and reason for failure are in the `Details` array. The `Result` integer field should be disregarded since there was no result generated.

ResultSuppressed (*bool*)

If true, this result message describes a die roll request without disclosing the results of the roll. This is used, for example, when sending a die roll for the GM to see privately (not even showing the requester the result). In this case, the value of the `Result` field should be ignored.

Details (*list of objects*)

The details behind how that result was generated are given as a list of objects with the following fields:

Type A text label describing what the value means in the context of the die-roll result.

Value The value for this part of the result (as a string).

SOUND Play a sound clip. Clients **SHOULD** allow users to locally disable playing of sounds as a user preference. The payload is a JSON object with the following fields:

Name The name of the sound to play. This is the name that was defined by a previous `AA` command (q.v.). This may be “*” to refer to all sounds (e.g., to stop all playing sounds).

Loop (*bool*)

If true, continue playing the sound in a repeating loop until stopped.

Stop (bool)

If true, stop playing the named sound.

Addr (list of strings)

If non-empty, this is a list of client addresses (in the form reported by the `Addr` field in the `CONN` server message). This requests that only the clients listed play (or stop playing) the specified sound.

SYNC This command **MUST** be ignored if received by a client. A client sends this to the server to request a replay of map commands which would be necessary to catch it up to the state the other maps are currently in. A server may be configured to perform a sync operation upon client connection (after, if required, authentication) without the client explicitly sending a `SYNC` command to it.

SYNC-CHAT

This command **MUST** be ignored if received by a client. Supersedes the `SYNC` command with `CHAT` argument in protocol versions prior to 400. A client sends this to the server to request a replay of chat messages (including die-roll result notices) according to the JSON payload, which may include this field:

Target (int)

If missing or 0, all chat messages in the server's history are sent to the client. Otherwise, if `Target` is positive, all messages with `messageIDs` greater than `Target`. If `Target` is negative, its absolute value gives the number of recent messages to send to the client (e.g., if `Target` is -50, then the most recent 50 messages are re-sent to the client).

TB Controls the display of the toolbar in the mapper client. The JSON payload is an object with the following field:

Enabled (bool)

If true, the client **SHOULD** display its toolbar. If false, the client **SHOULD NOT** display it. The client may override this request based on the user's preferences.

TMACK Acknowledges a timer request. If a client receives this, it means the GM has accepted their timer request into the set of tracked timers, and subsequent `PROGRESS` messages **MAY** appear as that timer's value is updated over time. The JSON payload for this message includes the following fields:

`RequestID`

The ID of the original request, as sent by the client when making it.

`RequestingClient`

The client connection ID as it appeared in the original request.

`RequestedBy`

The user name of the original requester. If the server is unable to locate the original requesting client connection as specified by the `RequestingClient` field, it **MAY** send `TMACK` messages to clients logged in by the user named in this field instead.

TMRQ Request a new timer. This sends a request to the GM's GMA client. If the GM approves, the timer will be added to the collection of timers being tracked for the game. This **MAY** result in subsequent `PROGRESS` messages being received by clients as the timer's value is updated over time. If no GMA process hears the message, nothing may happen. Clients which receive this message **MUST** ignore it. If the GM declines to accept the incoming timer request, or if the request contains an error, a `FAILED` message **SHOULD** be sent back to the requesting client with the same `RequestID` value as the original request. If the GM accepts the timer into

the tracking system, their client SHOULD send a TMACK message with matching RequestID field to the original requester to notify them of that fact. Clients MUST cope with the possibility of not receiving those acknowledgement messages or there being long delays between the request and acknowledgement.

The JSON payload for this message includes the following fields:

Description

A one-line text description giving the purpose of the timer.

Expires

The time at which the timer should expire. This may be given as an absolute or relative time. If the string begins with an @ character, it will be an absolute timer and the field MUST have the form

@[[year-]month-]date] hour : minute[: second[. tenths]]

where the *year*, *month*, *date*, *hour*, *minute*, and *second* values are numeric and conform to the campaign world calendar currently in play, and *tenths* is a single digit representing tenths of seconds. For example, “@15:32” represents a timer which expires at 32 minutes past 3 P.M., and “@10-15 12:00:05” expires at five seconds past noon on the fifteenth day of the tenth month of the current year. Text names or abbreviations may be used for *name* if defined for the calendar in effect at the time, so on the Golarion calendar that last example could also have been “@LAM-15 12:00:05” since the tenth month is Lamashan.

Otherwise, the value indicates a relative amount of time from the time and date on the clock at the moment the timer is accepted into the system by the GM. This expiration MAY begin with a + or – sign. Following this is a number and a unit name, such as “5 rounds” or “3 hours”, or an expression in the form

[[days:]hours:]minutes:seconds[.tenths]

so “3 hours”, “+3 hours”, “3:00”, and “+3:00” all set a timer for three hours into the future, while “-2 rounds” sets one that expires two rounds in the past (which may not be as useless as it sounds depending on the circumstances in the game, but probably is).

Targets (*list of strings*)

If this is empty, the timer is assumed to apply to everyone. Otherwise, it applies to the individuals named in the list. If these are the names of players, they should match their login names exactly.

ShowToAll (*bool*)

If true, the timer should be visible to the players. Otherwise, only the GM sees it on their time tracker.

IsRunning (*bool*)

If true, the timer should start running immediately. Otherwise, the GM will need to manually start it at a future point in time.

RequestedBy

The user name of the user who initiated this request. Clients NEED NOT supply this field; it will be supplied by the server as it relays the request on to the GM.

RequestingClient

The client connection ID of the user who initiated this request. Clients MUST NOT supply this field; it will be supplied by the server as it relays the request on to the GM. The meaning of this value is opaque and is only

used by the server.

RequestID

A unique identifier for this request. Replies sent back to the requesting client in regard to this request will reference this same ID. A UUID string is suggested for this value.

TO Send chat message to a set of recipients. The payload is a JSON object with the following fields:

Sender

The name of the user sending the message. Clients SHOULD NOT set this field; it is set by the server when sending these messages to peers.

Origin (*bool*)

If present and true upon receipt from the server, this means that the client receiving this message was the same client who sent the original message, instead of merely receiving a copy of the message sent by a peer client. Clients MUST NOT set this field.

Replay (*bool*)

If present and true upon receipt of this message from the server, this indicates that this message is being “replayed” (e.g., as a result of a SYNC-CHAT request from the client) and this is not the original sending of the message.

Recipients (*list of strings*)

The names of the people the message was explicitly addressed to. For global messages, this should be null.

MessageID (*int*)

The unique number assigned by the server for this chat message. Clients SHOULD NOT set this field.

Sent (*RFC 3339-formatted datetime string*)

The date and time the message was sent. Clients SHOULD NOT set a nonempty value for this field. It will be filled in by the server when sending messages to clients. If this field is missing or empty when received from the server, it means the date was not available to report for that message. Note that the special value “0001-01-01T00:00:00Z” is the “zero” value for dates and indicates that the date is not known (as is the case if this field is omitted entirely or is the empty string).

ToAll (*bool*)

If true, this is a global message sent to all clients. The contents of the Recipients field are ignored; it should be omitted or set to null.

ToGM (*bool*)

If true, this message will be sent only to the GM. The contents of the Recipients field are ignored; it should be omitted or set to null.

Markup (*bool*)

If true, the text of this message may contain GMA markup formatting codes which the client SHOULD either filter out or interpret appropriately for display to the user. If a client did not indicate to the server that it was capable of understanding these codes via the ALLOW command (q.v.), then the server will filter out these codes before sending the message to that client.

Text The text of the message to be sent.

Pin (*bool*)

If present and true, this message should be pinned in the recipients’ chat windows as a persistent message until dismissed by the recipient.

- /CONN This command causes the server to send a summary of the connections it is currently serving. These are sent back to the client via the CONN command documented above.
- UPDATES This provides the latest available versions of various programs. A client MAY alert the user or initiate an automatic upgrade if it recognizes that it or one of its dependencies is out of date. Clients MUST NOT send this command. (Formerly this was sent as a comment prior to protocol version 400.) The payload contains the following field:

Packages (*list of objects*)

Each element in this list is a JSON object with the following fields:

Name The name of the software package, such as “mapper”, “go-gma”, or “core”.

MinimumVersion

If a server wishes to limit clients from this package to only those with a minimum version number (as self-reported by the client in its AUTH message), then a MinimumVersion and VersionPattern field MUST be added to that package’s information here. The MinimumVersion field is a string with the minimum client version allowed to be used, as a semantic version string such as “1.2”, “1.7.3”, “1.6-alpha.1”, etc. This will be matched against the value captured from the client’s version number via the VersionPattern field. *This field should be used only in server init files. Clients SHOULD NOT use this field, nor expect it to be sent by the server.*

VersionPattern

This gives a regular expression which is matched against the Client field sent by the client as part of its AUTH message when signing on to the server. This expression MUST contain a single capturing group which yields the client’s version number to be compared against the MinimumVersion field described above. *This field should be used only in server init files. Clients SHOULD NOT use this field, nor expect it to be sent by the server.*

Instances (*list of objects*)

A list of all available instances of the named package. Each is a JSON object with the following fields:

OS The name of the operating system platform for which this instance of the package is available (e.g., “freebsd”, “linux”, “darwin”, “windows”, etc.). If this is empty, then this instance is platform-independent.

Arch The name of the hardware architecture for which this instance of the package is compiled (e.g., “amd64”, etc.) If this is empty, then this instance is architecture-independent.

Version

The semantic version number that users should be using. This is set by the GM (or designated server administrator—henceforth we will simply use the term “GM” for this role) for their game. It may not necessarily be the latest version available generally. The version string MAY omit the third version number (e.g., “4.2” instead of the more standards-compliant “4.2.0”).

Token The download token used for obtaining a copy of the package. This is entirely under the GM’s control and refers to a file the GM placed on their game server for their players to access. The *token* value is the non-static part of the download URL from their

game server.

WORLD This command provides various campaign-world information useful for the client to know. Clients **MUST NOT** send this command. The payload includes the following parameters:

Calendar

The name of the calendar system in play, as known to the GMA game clock. (Formerly this was sent as a comment in the form `// CALENDAR // system` prior to protocol version 400.)

Declares which calendaring system the various dates and times are based upon.

ClientSettings (*object*)

Any of the following settings will override the client's own settings. Clients **SHOULD** notify users that this has happened. This allows the GM to make global changes to things like where images are stored without requiring players to adjust all their settings.

MkdirPath

The path to the `mkdir` program on the server (used for GM uploads of mapper content to the server).

ImageBaseURL

The base URL from which the client will retrieve map and image files.

ModuleCode

The current module's ID code.

SCPDestination

The directory where GM uploads of mapper content should be sent to.

ServerHostname

The hostname (and optionally username in the form *name@host*) for the GM to upload mapper content to the server.

Example: `WORLD {"Calendar": "golarion"}`

SEE ALSO

`mapper(5)`, `gma(6)`, and `server(6)`.

AUTHORS

Steve Willoughby / `steve@madscience.zone`; John Mechalas (elevation and movement modes).

HISTORY

This document defines map protocol version 422, which adds the explicit `NotPlaying` flags to indicate if a user should not be considered as controlling any characters.

Historically, protocol version 421 adds client platform identification and sound support.

Version 420 introduced targets to die rolls and armor class as a tracked creature health item. It also introduces the `AKA` command.

Version 419 added support for pinned chat messages.

Version 418 added support for temporary hit point tracking and user requests for hit point changes.

Version 417 introduced support for system-wide die-roll presets, table definitions and markup formatting in chat messages. It also added the `Origin` and `Replay` fields to the `ROLL` and `TO` messages.

Version 416 added the `FAILED`, `TMRQ`, and `TMACK` messages.

Version 415 added the `Iterations` parameter to the `OK` message.

Version 414 changed the definition of the `DENIED` message to allow it to be sent at any time during the conversation.

Protocol 413 added speculative definitions for the `CORE`, `CORE/`, and `CORE=` commands, and extensions

to the `PROGRESS` command.

Protocol 412 added support for sharing die-roll presets.

Protocol 411 added timestamps to chat messages and die-roll results.

Protocol 410 added the `REDIRECT` command and the `ClientSettings` field of the `WORLD` command.

Protocol version 409 added the `Stipple` pattern fill attribute.

Protocol version 408 introduced the `PolyGM` creature attribute.

Protocol version 407 added the image animation features.

Protocol version 406 dropped the `Area` attribute from creatures and added the `CustomReach` attribute and the expanded syntax for the `Size` attribute, as well as the new `DispSize` attribute.

Protocol version 405 introduced the `ServerVersion` field to the server's greeting.

Protocol 404 introduced the `Hidden` attribute for creature tokens, the transparent image type, and the `Transparent` attribute for status markers.

Protocol version 403 introduced the `AI/` server message and additional fields to the `OK` message.

Protocol version 402 improved the `ROLL` server message by adding support for blind rolls to the GM.

Protocol version 401 introduced the `Grid` parameter to the `AV` command.

Protocol version 400 changed the server communication protocol to use JSON instead of TCL lists. It also introduced the `PROGRESS`, `PROTOCOL`, `READY`, `UPDATES`, and `WORLD` commands.

As of the beta-3 release, the `RequestID` and `MoreResults` fields were added to die roll requests and results messages.

Version 332 added the `GRANTED` server response, guaranteeing that `AUTH` will be followed by a response in any case.

Version 331 changed the way persistent chat messages are managed, altering the `ROLL`, `TO`, `SYNC`, and `CC` commands.

Version 329 added the `CC` command and the extended form of `SYNC`.

Previously, version 328 introduced the `ACCEPT` command.

Version 327 added the `DENIED` and `PRIV` response commands.

Version 326 added support for chat channels and die rolling, and changed the response from the `/CONN` command to be a structured sequence of data records rather than sending the reply in comments.

Protocol 325 added connection debugging support by changing the `AUTH` command and adding `/CONN`.

The version 324 protocol added the `DSM`, `OA+`, and `OA-` protocol commands. This version of the protocol also assumes mapper file format 15 is being used.

Previously, protocol version 323 added support for server-side persistent state and the introduction of the `SYNC` protocol command.

Protocol version 322 added comments to version 321.

Protocol version 321 added authentication support to the capabilities of protocol 320.

Map protocol version 320 has the same commands as 319, but the `HEALTH` attribute of creatures changed from map version 12 to 13, so we are advancing the protocol version at the same time since maps released for protocol 319 were expecting the older map format.

Map protocol version 319 differs from version 318 (the first explicitly numbered version) by the addition of the `CLR@`, `M?`, and `M@` commands.

COPYRIGHT

Part of the GMA software suite, copyright © 1992–2025 by Steven L. Willoughby, Aloha, Oregon, USA.
All Rights Reserved. Distributed under BSD-3-Clause License.