

**Readerboard
User's Guide
WORKING
DRAFT**

The information in this document, and the hardware and software it describes, are hobbyist works created as an educational exercise and as a matter of personal interest for recreational purposes.

It is not to be considered an industrial-grade or retail-worthy product. It is assumed that the user has the necessary understanding and skill to use it appropriately. The author makes NO representation as to suitability or fitness for any purpose whatsoever, and disclaims any and all liability or warranty to the full extent permitted by applicable law. It is explicitly not designed for use where the safety of persons, animals, property, or anything of real value depends on the correct operation of the software.

As an educational exercise, it is assumed that the user has the necessary skill to appropriately set up, build, and use this project. Do not proceed to use, whether exactly as provided in the repository or with modifications of your own, unless you know exactly what you're doing and have verified that your actions and the product materials are suitable for your purpose and function as expected.

For readerboard hardware (PCB) version 3.2.2, schematic version 3.2.3, and firmware version 0.0.0.

Copyright © 2023, 2024 by Steven L. Willoughby (aka MadScienceZone), Aloha, Oregon, USA. All Rights Reserved. This document is released under the terms and conditions of the Creative Commons “Attribution-NoDerivs 3.0 Unported” license. In summary, you are free to use, reproduce, and redistribute this document provided you give full attribution to its author and do not alter it or create derivative works from it. See

<http://creativecommons.org/licenses/bynd/3.0/>

for the full set of licensing terms.



CONTENTS

| | |
|--|-----|
| Contents | iii |
| List of Figures | v |
| List of Tables | v |
| 1 Hardware | 1 |
| Version 1.0 | 1 |
| Version 2.0 | 1 |
| Version 2.1 | 2 |
| Version 3.2 | 2 |
| Firmware Implications | 2 |
| Construction | 2 |
| 2 Protocol Description | 7 |
| Web Service API | 7 |
| USB vs. RS-485 | 8 |
| Command Summary | 10 |
| *—Strobe Lights in Sequence | 11 |
| <—Scroll Text Across Display | 12 |
| ==Set Operational Parameters | 13 |
| ?—Query Discrete LED Status | 13 |
| @—Set Column Cursor Position | 15 |
| A—Select Font | 15 |
| C—Clear Matrix Display | 17 |
| F—Flash Lights in Sequence | 17 |
| H—Draw Bar Graph Data Point | 18 |
| I—Draw Bitmap Image | 19 |
| K—Set Current Color | 20 |
| L—Light Multiple LEDs | 20 |
| Q—Query Readerboard Status | 21 |
| S—Light Single LED | 22 |
| T—Display Text | 23 |
| X—Turn off Discrete LEDs | 23 |

| | |
|---|-----------|
| 3 Server-Only Commands | 25 |
| post—Post a Message to the Displays | 25 |
| unpost—Remove a Posted Message | 26 |
| update—Update Dynamic Content | 26 |
| 4 Pinouts | 29 |
| Connectors for Version 3.2 Boards | 29 |
| Connectors for Legacy Boards | 30 |
| 5 Font Glyphs | 33 |
| Font #0 standard.font | 33 |
| Font #1 standard_variable.font | 42 |
| Font #2 symbol.font | 51 |
| Default Glyph | 57 |
| Font Definition Files | 57 |
| 6 Preparing and Updating Firmware Images | 61 |
| 7 Schematics and Diagrams | 65 |

LIST OF FIGURES

| | |
|---------------------------------|---|
| 1.1 Bill of Materials | 3 |
|---------------------------------|---|

LIST OF TABLES

| | |
|---|----|
| 2.1 Examples of RS-485 Escape Bytes. | 11 |
| 2.2 Summary of All Commands | 12 |
| 2.3 Control Codes in String Values | 13 |
| 2.4 Baud Rate Codes | 14 |
| 2.5 ASCII Encoded Integer Values (0–63) | 15 |
| 2.6 Font Codes | 16 |
| 2.7 Font Table for Fonts #0 and #1 | 16 |
| 2.8 Font Table for Font #2 | 17 |
| 2.9 Discrete LED Codes and Colors | 18 |
| 2.10 Transition Effect Codes | 20 |
| 2.11 Color codes for $\langle rgb \rangle$ parameters | 21 |
| 3.1 Special Codes in Post Messages | 26 |
| 6.1 Firmware Configuration Values | 63 |

C H A P T E R

1

HARDWARE

People who are really serious
about software should make
their own hardware.

—Alan Kay

AS A HOBBY PROJECT, the design of the hardware and software for the readerboard project “grew in the telling” as new ideas sprang to mind. As of this writing, there are three different models of hardware prototypes which were designed and created.

Version 1.0

The initial prototype (PCB 1.0.1) was a fairly large board, approximately $20\frac{5}{8} \times 6\frac{5}{8}$ “ with an LED pitch of $\frac{1}{8}$ “.

It requires an Arduino Mega 2560 or Arduino Due to drive it. A custom-made shield board attaches to the Arduino, which provides connectors for power and ribbon cables to drive the display (one to control the matrix, the other for the 8 status LEDs which appear in a horizontal row along the bottom right of the matrix).

Version 2.0

This version is based on the 1.0 design, but shrunk to a board size of about $18\frac{3}{16} \times 5\frac{3}{16}$ “ with an LED pitch of $\frac{1}{4}$ “. It also replaces the obsolete TPIC6B595 with the newer STPIC6D595 chip. It also relocates the ribbon cable which

connects the Arduino controller to the LED matrix, moves the eight status LEDs to a vertical column to the right of the matrix, and switches to resistor arrays for the matrix current limiting resistors, instead of the individual discrete resistors used on the 1.0.1 board.

Version 2.1

Version 2.1 is a significant change to the 2.0 board in terms of how it interfaces with the Arduino, although it has the same size and physical layout as the 2.0 board.

This one eliminates the need for the ribbon cables and shield board. Instead, the Arduino controller mounts directly to the back of the display board. This means that the lower portion of the left edge of the enclosure has all of the external connections in one place, including power, RS-485 in and out, and the USB connector(s) on the Arduino itself.

Version 3.2

The current version of the hardware expands on the version 2.1 design by replacing the single-color LEDs with RGB LEDs arranged into 24 logical rows—each of the eight physical rows is logically a row of red, green, and blue LED elements.

As of this writing, the current revision of this board is schematic version 3.2.3 and PCB version 3.2.2.

Firmware Implications

The boards for versions 1.0 and 2.0 were compatible and used the same Arduino shield. Thus, they use the same firmware images. The 2.1 board, however, which integrates the Arduino directly instead of using a separate shield with ribbon cables, assigns signals to different I/O pins, and as such needs a different firmware image.

Both images are generated from the same source files, with compile-time switches to make one or the other.

Version 3.2 expands the number of logical rows due to the RGB implementation, which requires corresponding changes to the firmware and protocol to support the new color data.

At this point in development it is unclear whether we'll continue making the different versions available using compile-time switches or if we'll just support this version going forward.

Construction

Once you have created a printed circuit board (PCB) from the fabrication files included with the readerboard Git repository and obtained the parts

| Part No. | Qty | Mouser | Description |
|-----------------|------------|----------------------|--|
| | 1 | | Printed circuit board rev 3.2.2 |
| | 1 | | Arduino Due or Mega 2560 |
| C0–9,11,12 | 12 | 810-FA18X7R1H10400 | 0.1 μ F capacitor |
| C10 | 1 | 667-ECA-1HM100I | 10 μ F electrolytic capacitor |
| D0–511 | 512 | | LED, 5mm, RGB, common cathode |
| D512 | 1 | | LED, 5mm, green |
| D513–14 | 2 | | LED, 5mm, yellow |
| D515–16 | 2 | | LED, 5mm, red |
| D517–18 | 2 | | LED, 5mm, blue |
| D519 | 1 | | LED, 5mm, white |
| J0 | 1 | | Arduino stacking pin set |
| J1 | 1 | | 8-position Euro-style terminal block |
| J2 | 1 | | 2-position jumper header |
| P0 | 1 | | 2-position jumper shunt |
| Q0–23 | 24 | 942-IRF9530NPBF | IRF9530 p-channel MOSFET |
| R0–7,35–50 | 24 | 604-MFR-24FRF521K | 1K resistor |
| R8–23 | 16 | | 4 \times 360 Ω resistor array, isolated |
| R24,29–31 | 4 | 603-MFR-25FTE52-300R | 300 Ω resistor |
| R25–28 | 4 | | 360 Ω resistor |
| R32–34 | 3 | 603-MFR-25FRF5210K | 10K resistor |
| Rterm | 1 | | 120 Ω resistor |
| U0,12,13 | 3 | 595-CD74HCT238PWR | CD74HCT238PWR non-inverting 3-to-8 decoder |
| U1,2,14,15 | 4 | | ULN2803CDWR octal NPN Darlington array |
| U3–10 | 8 | | STPIC6D595MTR power 8-bit shift register |
| U11 | 1 | | THVD1439 half-duplex RS-485 driver/receiver |
| | 24 | | TO-220 heat sinks for Q0–23 |
| | 1 | | 9V 2A DC power supply |

Figure 1.1: Bill of Materials

as listed in Figure 1.1, carefully solder the components in place.

Warning! Danger! Only perform the assembly operation if you are qualified to do so. Soldering electronic components may be hazardous due to the high temperatures, sharp objects, electrical voltages, potentially toxic materials, and other dangers. This requires skill and expertise as well as personal protection equipment to perform safely. Please also observe all precautions to avoid damaging the electronic components themselves from harm due to heat or static electricity discharge.

Suggested Order

For best results, solder components in a way that allows best access to the solder points without some parts getting in the way of connecting subsequent ones. For example:

1. Solder all the surface mount chips first: U0–U15.
 - U0, U12, U13: CD74HCT238PWR
 - U1, U2, U14, U15: ULN2803CDWR (ULN2803A SOP-18 packages may be used if aligned to the top 18 pads, leaving the bottom two empty, if they have otherwise identical pinouts and characteristics)
 - U3–U10: STPIC6D595MTR
 - U11: THVD1439DR (Note that this chip is oriented 180° from the other chips on the board, with pin 1 to the lower right.)
2. Solder the discrete resistors: R0–R7, R24–R50. See below first to ensure the correct values are used for R24–R31.
 - R0–R7, R35–50: 1K
 - R24, R29–R31: 300Ω
 - R25–R28: 360Ω
 - R32–R34: 10K
3. Solder the $0.1\mu\text{F}$ capacitors: C0–C9, C11–C12.
4. Solder the resistor arrays: R8–R23.
5. Solder the RGB LEDs D0–D511. Ensure that the common cathode goes to pin 2 so that pins 1, 3, and 4 are respectively the red, green, and blue anodes.
6. Solder the single-color LEDs D512–D519 in the colors of your choice, being mindful of the polarity. The anode has a square pin on the PCB. Our recommendation:
 - D512 (bottom): green (with $R24=300\Omega$)¹
 - D513: yellow (with $R25=360\Omega$)
 - D514: yellow (with $R26=360\Omega$)
 - D515: red (with $R27=360\Omega$)
 - D516: red (with $R28=360\Omega$)
 - D517: blue (with $R29=300\Omega$)

¹Resistor values based on typical LED voltage and current ratings. Check to see what is appropriate for your components.

- D518: blue (with $R_{30}=300\Omega$)
 - D519 (top): white (with $R_{31}=300\Omega$)
7. Solder the $10\mu F$ capacitor C10, being mindful of the correct polarity.
 8. Solder the Arduino bus stacking pins (six sets— 1×10 -pin, 5×8 -pin—all labeled collectively at J0). Ensure the pins extend down and out the back of the board.
 9. Solder the 2-pin header J2.
 10. Solder the terminal block J1.

Option: Using Single-Color LEDs

If you don't need RGB LEDs for your application, the same PCB may be used with single-color 5mm LEDs instead. Simply solder them onto the board so that their cathode is on pin 2 and the anode is on pin 4 of the LED footprint. This means the LEDs will electrically all be connected to the blue circuit.

Since they won't be used, omit parts U0, U2, U12, U14, C0, C11, Q0–Q15, R0–R7, and R35–R42.

Either tell the readerboard to light up all of its content in the blue color (since that's what will be driving your LEDs regardless of their actual color), or make a firmware change so that the readerboard disregards any color specification except black, lighting up the single-color LEDs for all other colors.

C H A P T E R



PROTOCOL DESCRIPTION

I don't stand on protocol. Just call me
your Excellency.

—Henry Kissinger

THE CONTROL PROTOCOL used to display information on the readerboard sign is very simple. Commands are expressed largely in plain ASCII characters and are executed immediately as they are received.¹

In addition to plain, printable 7-bit ASCII characters, a few control codes are recognized as described below. String data may include any 8-bit value except as otherwise indicated.

Web Service API

The organization of the rest of this chapter is oriented toward a description of the protocol used to control the hardware directly over a USB or RS-485 connection. However, you can set up a central server which is connected to all the readerboard signs and busylight indicators in a small area (via USB or RS-485). This allows clients to send commands to the server over the network for control of the readerboards.

The protocol between clients and servers uses messages which are simple HTTP requests posted to the server's listening port URL. If the server were configured to run on example.org on port 43210, then all client requests to that server would begin with

`http://example.org:43210/readerboard/v1/<message>?a=<targets>`

¹Technically, they may even be executed *while* they are being received.

Message Data Fields

As a general rule, if a message expects a field that is not provided, a suitable “zero” value will be assumed for that field. Any extra fields sent that were not expected are silently ignored.

Boolean fields may have values `true` or `false`; if they are presented without a value, they are considered to be `true`, and if completely missing they are assumed to be `false`. Thus,

```
.../readerboard/v1/⟨message⟩?a=⟨targets⟩&status=true  
is equivalent to  
.../readerboard/v1/⟨message⟩?a=⟨targets⟩&status=false  
and  
.../readerboard/v1/⟨message⟩?a=⟨targets⟩&status=false  
is equivalent to  
.../readerboard/v1/⟨message⟩?a=⟨targets⟩
```

Message Target Addresses

Every message also has a field called “`a`” which is a comma-separated list of target readerboards to which the message applies.

So, for example, the message containing `a=2` would cause the server to transmit the corresponding command to the readerboard with address 2 directly connected to it via USB, or would transmit to the RS-485 network the command starting with the hex byte 92.

If multiple devices are targeted, say with a message containing the field `a=2,5,37` with address 15 (*e.g.*, F_{16}) configured as the global address ad_G , it will transmit to the RS-485 network a command starting with the hex byte sequence BF 03 02 05 25.

USB vs. RS-485

The protocol used to send commands to the readerboard is different depending on whether the host is sending directly to a single readerboard over a USB cable, or to (possibly) multiple readerboards over an RS-485 bus network.

USB

A readerboard connected via USB accepts the commands just as documented below, with the addition that each such command is terminated by a $\sim D$ byte (hex value 04_{16}).

| | | | |
|---------------------------|----------|----------|-----|
| 0 | \cdots | $n - 1$ | n |
| $\langle command \rangle$ | | $\sim D$ | |

If there is an error parsing or executing a command, the readerboard will ignore all subsequent input until a ^D is received, whereupon it will expect to see the start of another command. Thus, ^D may not appear in any transmitted data except to terminate commands.

Commands which contain arbitrary-size data fields, such as text strings or lists of LEDs to light in sequence, end such fields with a terminator byte. In most cases this may be either a dollar-sign (“\$”) character or the escape control character (hex byte $1B_{16}$), indicated in the protocol diagram above simply as “\$”. In cases where a dollar-sign could be part of the data, then only an escape character may be used to terminate the field, in which case the protocol description will show the terminator as “ESC”.

RS-485

Commands sent over RS-485 are intended to target one or more of a set of connected readerboards over a network which may also contain other Lumos-protocol-compatible devices, so they adhere to a protocol that is also compatible with those devices.

Each command begins with one of the following binary headers, depending on the set of target readerboard signs which should obey the command.

Single Target or All Readerboards

To send a command to a single sign, begin with a single byte encoded as:

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|----------------------|---|---|---|
| 1 | 0 | 0 | 1 | $\langle ad \rangle$ | | | |

where $\langle ad \rangle$ is the sign’s address on the bus, which must be a value in the range 0–15. This byte is followed by any command as described below. If the global address ad_G is given as the $\langle ad \rangle$ value, then all readerboards which have that set as their global address will obey the command.

Multiple Targets

Alternatively, a command may be targeted to multiple signs by starting the command with a multi-byte code:

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | | | | |
|---|---|----------------------------|---|------------------------|---|---|---|--|--|--|--|
| 1 | 0 | 1 | 1 | $\langle ad_G \rangle$ | | | | | | | |
| 0 | 0 | $\langle n \rangle$ | | | | | | | | | |
| 0 | 0 | $\langle ad_0 \rangle$ | | | | | | | | | |
| ⋮ | | | | | | | | | | | |
| 0 | 0 | $\langle ad_{n-1} \rangle$ | | | | | | | | | |

where $\langle ad_G \rangle$ is the “global” device address which signals readerboards generally (see the = command below). This will send to the $\langle n \rangle$ devices addressed as $\langle ad_0 \rangle$ through $\langle ad_{n-1} \rangle$.

Note that device addresses are constrained to the range 0–15 if they are to be addressed in the command start byte. However, using the multiple target header, device addresses in the range 0–63 may be used.

All Off

As a special case, the single byte

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|----------------------|
| 1 | 0 | 0 | 0 | 0 | 0 | 0 | $\langle ad \rangle$ |

will cause the readerboard addressed as $\langle ad \rangle$ to turn off all LEDs. If $\langle ad \rangle$ is the ad_G address, then all readerboards will turn off all LEDs.

No other command bytes need to follow; this byte is sufficient to turn off the sign(s).

The corresponding HTTP message is `/readerboard/v1/alloff?a= $\langle ad \rangle$`

Subsequent Command Bytes

All subsequent bytes which follow the above binary headers *must* have their MSB cleared to 0.

To cover cases where a value sent as part of a command must have the MSB set, we use the following escape codes:

- A hex byte $7E_{16}$ causes the next byte received to have its MSB set upon receipt.
- A hex byte $7F_{16}$ causes the next byte to be accepted without any further interpretation.

Thus, the byte $C4_{16}$ is sent as the two-byte sequence $7E\ 44$, while a literal $7E$ is sent as $7F\ 7E$ and a literal $7F$ as $7F\ 7F$.

If there is an error parsing or executing a command, the readerboard will ignore all subsequent input until a byte arrives with its MSB set to 1, whereupon it will expect to see the start of another command.

A few illustrative examples are shown in Table 2.1.

Command Summary

The eight discrete LEDs are intended for a simple display of status information in a manner analogous to the Busylight project by the same author.² To support this usage, the F, S, X, *, and ? commands are recognized in a manner compatible with how Busylight uses those same commands.

²See github.com/MadScienceZone/busylight.

| Input Sequence | Resulting Byte |
|-----------------------|-----------------------|
| 00 | 00 |
| 7D | 7D |
| 7F 7E | 7E |
| 7F 7F | 7F |
| 7E 00 | 80 |
| 7E 01 | 81 |
| 7E 7D | FD |
| 7E 7E | FE |
| 7E 7F | FF |

Table 2.1: Examples of RS-485 Escape Bytes.

These are categorized as “Busylight compatibility commands.” Unlike all other commands listed here, these are recognized regardless of case. Since the readerboard has a power supply capable of illuminating all of the status LEDs at once,³ a new command L is added which allows any arbitrary pattern of steady LEDs to be turned on.

The remaining commands are used for management of the matrix display. All commands are summarized in Table 2.2.

Although the rev 2 hardware supports the ability to enable the RS-485 transmitter and send data back onto the network, this is not currently implemented by the firmware, and the intent is to have all devices listen passively to RS-485 traffic at all times.

*—**Strobe Lights in Sequence**

| 0 | 1 | 2 | 3 | ... | n | $n + 1$ |
|---|-------------------------|-------------------------|-------------------------|-----|-----------------------------|---------|
| * | $\langle led_0 \rangle$ | $\langle led_1 \rangle$ | $\langle led_2 \rangle$ | ... | $\langle led_{n-1} \rangle$ | \$ |

/readerboard/v1/strobe?a= $\langle ad \rangle$ &l= $\langle led_0 \rangle\langle led_1 \rangle\dots\langle led_{n-1} \rangle$

Each $\langle led \rangle$ value is an ASCII character corresponding to a discrete LED as shown in Table 2.9. An $\langle led \rangle$ value of “_” means there is no LED illuminated at that point in the sequence.

This command functions identically to the F command (see below), except that the lights are “strobed” (flashed very briefly with a pause between each light in the sequence).

³The Busylight cannot, since it is powered from the host computer’s USB port.

| Message | Cmd | Description | Notes |
|---------|-----|-----------------------------------|-------------|
| strobe | * | Strobe LEDs in Sequence | [1] |
| | ? | Query discrete LED status | [1] [2] [4] |
| flash | F | Flash LEDs in Sequence | [1] |
| light | L | Light one or more LEDs steady | [3] |
| light | S | Light one LED steady | [1] |
| off | X | All LEDs off | [1] |
| | ^D | Abort/terminate command | |
| scroll | < | Scroll text across display | |
| | = | Set operational parameters | [4] |
| move | @ | Move current column cursor | |
| font | A | Select character font | |
| clear | C | Clear matrix display | |
| graph | H | Add histogram/bargraph data point | |
| bitmap | I | Draw bitmap graphic image | |
| color | K | Set current color | |
| | Q | Query matrix display status | [2] [4] |
| text | T | Display text on display | |

[1] Busylight compatible command

[2] Sends response (USB only)

[3] Busylight extension (not in original Busylight)

[4] USB only

Table 2.2: Summary of All Commands

← Scroll Text Across Display

| 0 | 1 | 2 | ... | $n+1$ | $n+2$ |
|---|------------------------|---|-----|--------------------------|-------|
| < | $\langle loop \rangle$ | | | $\langle string \rangle$ | ESC |

/readerboard/v1/scroll?a= $\langle ad \rangle$ &loop= $\langle bool \rangle$ &t= $\langle string \rangle$

Displays the text $\langle string \rangle$ by scrolling it across the display from right to left. If $\langle loop \rangle$ is “.”, the text is only scrolled once; if it is “L” then it repeatedly scrolls across the screen in an endless loop.

The text is rendered in the current font and may contain any 8-bit bytes except as otherwise noted (but avoiding ASCII control codes is wise to be safe from conflict with future control codes which may be added to the protocol). The string is terminated by an escape character (hex byte 1B), indicated in the protocol description as ESC.

The string may include control codes as listed in Table 2.3.

| Code | Hex | Description |
|--------------------------------|----------------------------|---|
| $\sim C \langle pos \rangle$ | 03 $\langle pos \rangle$ | Move current column cursor to $\langle pos \rangle$ |
| $\sim D$ | 04 | Never allowed in strings (command terminator) |
| $\sim F \langle digit \rangle$ | 06 $\langle digit \rangle$ | Switch current font |
| $\sim H \langle pos \rangle$ | 08 $\langle pos \rangle$ | Move cursor left $\langle pos \rangle$ columns |
| $\sim K \langle rgb \rangle$ | 0B $\langle rgb \rangle$ | Change color to $\langle rgb \rangle$ |
| $\sim L \langle pos \rangle$ | 0C $\langle pos \rangle$ | Move cursor right $\langle pos \rangle$ columns |
| $\sim [$ | 1B | Never allowed in strings (string terminator) |

Table 2.3: Control Codes in String Values

=—Set Operational Parameters

| 0 | 1 | 2 | 3 | 4 |
|---|----------------------|------------------------|------------------------|------------------------|
| = | $\langle ad \rangle$ | $\langle uspd \rangle$ | $\langle rspd \rangle$ | $\langle ad_G \rangle$ |

This command sets a few operational parameters for the sign. Once set, these will be persistent across power cycles and reboots.

If the $\langle ad \rangle$ parameter is “_” then the RS-485 interface is disabled entirely. Otherwise it is a value from 0–15 encoded as described in Table 2.5. This enables the RS-485 interface and assigns this sign’s address to $\langle ad \rangle$.

The baud rate for the USB and RS-485 interfaces is set by the $\langle uspd \rangle$ and $\langle rspd \rangle$ values respectively. Each is encoded as per Table 2.4.

The $\langle ad_G \rangle$ value is an address in the range 0–15 which is not assigned to any other device on the RS-485 network. This is used to signal that all readerboards should pay attention to the start of the command because it might target them either as part of a list of specific readerboards or because the command is intended for all readerboards at once. This is encoded in the same way as $\langle ad \rangle$. If you only have one readerboard or do not wish to assign a global address, just set $\langle ad_G \rangle$ to the same value as $\langle ad \rangle$.

This command may only be sent over the USB port.

By default, an unconfigured readerboard is set to 9,600 baud with the RS-485 port disabled.

?—Query Discrete LED Status

| |
|---|
| 0 |
| ? |

This command causes the sign to send a status report back to the host to indicate what the discrete LEDs are currently showing. This response has the form:

| Code | Speed |
|------|-----------------|
| 0 | 300 |
| 1 | 600 |
| 2 | 1,200 |
| 3 | 2,400 |
| 4 | 4,800 |
| 5 | 9,600 (default) |
| 6 | 14,400 |
| 7 | 19,200 |
| 8 | 28,800 |
| 9 | 31,250 |
| A | 38,400 |
| B | 57,600 |
| C | 115,200 |

Table 2.4: Baud Rate Codes

| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|----|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-----|-----------------------------|----------------------------|
| L | $\langle led_0 \rangle$ | $\langle led_1 \rangle$ | $\langle led_2 \rangle$ | $\langle led_3 \rangle$ | $\langle led_4 \rangle$ | $\langle led_5 \rangle$ | ... | $\langle led_{n-1} \rangle$ | |
| \$ | F | | | | | | | | flasher status (see below) |
| \$ | S | | | | | | | | strober status (see below) |
| \$ | \n | | | | | | | | |

Each $\langle led_x \rangle$ value is a single character which is “_” if the corresponding LED is off, or the LED’s color code or position number if it is on. One such value is sent for each LED installed in the sign (typically eight for reader-boards), followed by a “\$” to mark the end of the list.

The flasher and strober status values are variable-width fields which indicate the state of the flasher (see F command) and strober (see * command) functions. In each case, if there is no defined sequence, the status field will be:

| 0 | 1 |
|-----------------------|---|
| $\langle run \rangle$ | - |

Otherwise, the state of the flasher or strober unit is indicated by:

| 0 | 1 | 2 | 3 | 4 | ... | $n + 3$ |
|-----------------------|-----------------------|---|-------------------------|-------------------------|-----|-----------------------------|
| $\langle run \rangle$ | $\langle pos \rangle$ | 0 | $\langle led_0 \rangle$ | $\langle led_1 \rangle$ | ... | $\langle led_{n-1} \rangle$ |

| Value | Code | Value | Code |
|-------|------|-------|------|
| 0–9 | 0–9 | 17–42 | A–Z |
| 10 | : | 43 | [|
| 11 | ; | 44 | \ |
| 12 | < | 45 |] |
| 13 | = | 46 | ^ |
| 14 | > | 47 | _ |
| 15 | ? | 48 | ' |
| 16 | @ | 49–63 | a–o |

(Each code is the numeric value plus 48.)

Table 2.5: ASCII Encoded Integer Values (0–63)

In either case, $\langle run \rangle$ is the ASCII character “S” if the unit is stopped or “R” if it is currently running. If there is a defined sequence, $\langle pos \rangle$ indicates the 0-origin position within the sequence of the light currently being flashed or strobed, encoded as described in Table 2.5. The $\langle led_x \rangle$ values are as allowed for the F or * command that set the sequence. (Regardless of the actual F or * command parameters, the report will show symbolic color codes where possible, or numeric position codes otherwise.)

The status message sent to the host is terminated by a newline character (hex byte 0A), indicated in the protocol description above as “\n”.

This command may only be sent on the USB port.

©—Set Column Cursor Position

| | |
|---|-----------------------|
| 0 | 1 |
| @ | $\langle pos \rangle$ |

/readerboard/v1/move?a= $\langle ad \rangle$ &pos= $\langle pos \rangle$

Sets the column cursor position to the value indicated by $\langle pos \rangle$. See Table 2.5.

A—Select Font

| | |
|---|-------------------------|
| 0 | 1 |
| A | $\langle digit \rangle$ |

/readerboard/v1/font?a= $\langle ad \rangle$ &idx= $\langle digit \rangle$

Sets the font to use for rendering text with the < and T commands. The font codes for $\langle digit \rangle$ are listed in Table 2.6. The full text fonts support the printable ASCII characters plus a majority of the Unicode glyphs with codepoints less than 256. See Tables 2.7–2.8 for a complete font glyph listing with codepoint assignments.

| Code | Font Description | | | | | | | |
|------|--|--|--|--|--|--|--|--|
| 0 | Fixed-width 5×7 matrix plus descenders in 8th row | | | | | | | |
| 1 | Variable-width version of font 0 | | | | | | | |
| 2 | Bold alphanumerics and special symbols | | | | | | | |

Table 2.6: Font Codes

| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
|-----|------|----|---|-------|------|-----|------|-----|----|
| 00x | | | | move | end | | font | | |
| 01x | back | | | color | forw | | | | 0x |
| 02x | | | | | | | | | |
| 03x | | | | esc | | | | | 1x |
| 04x | | ! | " | # | \$ | % | & | , | |
| 05x | (|) | * | + | , | - | . | / | 2x |
| 06x | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
| 07x | 8 | 9 | : | ; | < | = | > | ? | 3x |
| 10x | @ | A | B | C | D | E | F | G | |
| 11x | H | I | J | K | L | M | N | O | 4x |
| 12x | P | Q | R | S | T | U | V | W | |
| 13x | X | Y | Z | [| \ |] | ^ | _ | 5x |
| 14x | ' | a | b | c | d | e | f | g | |
| 15x | h | i | j | k | l | m | n | o | 6x |
| 16x | p | q | r | s | t | u | v | w | |
| 17x | x | y | z | { | | } | ~ | /// | 7x |
| 20x | " | " | ' | , | † | ‡ | ... | ' | |
| 21x | " | !! | - | ← | → | ↑ | ↓ | ≠ | 8x |
| 22x | ≤ | ≥ | ≈ | Γ | Δ | Ξ | Π | Σ | |
| 23x | Ω | π | ρ | σ | — | %o | | | 9x |
| 24x | í | ¢ | £ | ¤ | ¥ | ! | § | | |
| 25x | © | ª | « | ¬ | - | ® | | | Ax |
| 26x | ° | ± | ² | ³ | μ | ¶ | • | | |
| 27x | ¹ | º | » | 1/4 | 1/2 | 3/4 | ¸ | | Bx |
| 30x | À | Á | Â | Ã | Ä | Å | Æ | Ç | |
| 31x | È | É | Ê | Ë | Ì | Í | Î | Ï | Cx |
| 32x | Ð | Ñ | Ò | Ó | Ô | Õ | Ö | × | |
| 33x | Ø | Ù | Ú | Û | Ü | Ý | Þ | ß | Dx |
| 34x | à | á | â | ã | ä | å | æ | ¢ | |
| 35x | è | é | ê | ë | ì | í | î | ï | Ex |
| 36x | ð | ñ | ò | ó | ô | õ | ö | ÷ | |
| 37x | ø | ù | ú | û | ü | ý | þ | ÿ | Fx |
| | 8 | 9 | A | B | C | D | E | F | |

Table 2.7: Font Table for Fonts #0 and #1

| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
|-----|------|-----|-----|-------|------|--------|--------|------|----|
| 00x | | | | move | end | | font | | |
| 01x | back | | | color | forw | | | | 0x |
| 02x | | | | | | | | | |
| 03x | | | | esc | | | | | 1x |
| 04x | | ! | □ | ■ | | | | | |
| 05x | | | | , | | . | thin . | | 2x |
| 06x | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | |
| 07x | 8 | 9 | | | | | | | 3x |
| 10x | © | A | B | C | D | E | F | G | |
| 11x | H | I | J | K | L | M | N | O | 4x |
| 12x | P | Q | R | S | T | U | V | W | |
| 13x | X | Y | Z | | | | | | 5x |
| 14x | ® | ◀ | ▶ | ↑ | ↓ | ↖ | ↗ | ↘ | |
| 15x | ↙ | ← | → | ↑ | ↓ | ■■ | ■■■ | | 6x |
| 16x | ✓ | ✓ | ∞ | OE | œ | € | ⋮⋮ | ⋮⋮ | |
| 17x | ✗ | ◀ | ▶ | ▲ | ▼ | ↑↓ | ♦ | ◊ | |
| 20x | λ | Θ | Φ | Ψ | ♂ | ♀ | zero | zero | |
| 21x | ± | 干 | ⊕ | ⊙ | ≡ | clover | notes | | |
| 22x | AM | PM | °F | °C | | | | | |
| 23x | NM | WC | 1Q | WG | FM | WG | 3Q | WC | |
| 24x | | TS1 | TS2 | TS3 | TS4 | TS5 | TS6 | TS7 | |
| 25x | TS8 | | | | | | | | Ax |
| | 8 | 9 | A | B | C | D | E | F | |

TS⟨n⟩ = Thin space of ⟨n⟩ pixels

Table 2.8: Font Table for Font #2

C—Clear Matrix Display

| |
|---|
| 0 |
| C |

/readerboard/v1/clear?a=⟨ad⟩

Clears the matrix display so that no LEDs are illuminated. Does not affect the discrete LEDs.

F—Flash Lights in Sequence

| 0 | 1 | 2 | 3 | ... | n | n + 1 |
|---|---------------------|---------------------|---------------------|-----|-----------------------|-------|
| F | ⟨led ₀ ⟩ | ⟨led ₁ ⟩ | ⟨led ₂ ⟩ | ... | ⟨led _{n-1} ⟩ | \$ |

/readerboard/v1/flash?a=⟨ad⟩&l=⟨led₀⟩⟨led₁⟩⟨led₂⟩...⟨led_{n-1}⟩

| Code* | Light | Color |
|-------|--------------------------------|--|
| W | L ₀ | white |
| B | L ₁ | blue |
| b | L ₂ | blue |
| R | L ₃ | red |
| r | L ₄ | red |
| Y | L ₅ | yellow |
| y | L ₆ | yellow |
| G | L ₇ | green |
| - | — | (no LED/off) |
| 0–9 | L ₀ –L ₉ | LED installed at physical position 0–9 |

*If a sign is built with different colors in these positions, the letter codes for those LEDs will match the custom color arrangement for that sign.

(Custom firmware modification required.)

Table 2.9: Discrete LED Codes and Colors

Each $\langle led \rangle$ value is an ASCII character corresponding to a discrete LED as shown in Table 2.9. Note that the assignment of colors to these LEDs is dependent on your particular hardware being assembled that way. As an open source project, of course, you (or whomever assembled the unit) may choose any color scheme you like when building the board.

An $\langle led \rangle$ value of “_” means there is to be no LED illuminated at the corresponding position in the sequence.

Up to 64 $\langle led \rangle$ codes may be listed. The sign will cycle through the sequence, lighting each specified LED briefly before moving on to the next one. The sequence is repeated forever in a loop until an L, S or X command is received.

If only one $\langle led \rangle$ is specified, that light will be flashed on and off. Setting an empty sequence (no codes at all) stops the flasher’s operation.

The sequence is terminated by either a dollar-sign (“\$”) character or the escape control character (hex byte 1B), indicated in the protocol diagram above simply as “\$”.

This command may be given in upper- or lower-case (“f” or “F”).

H—Draw Bar Graph Data Point

| | | | |
|------------------------------------|---------------------|---------------------|---------------------|
| 0 | 1 | | |
| H | ⟨n⟩ | | |
| /readerboard/v1/graph?a=⟨ad⟩&v=⟨n⟩ | | | |
| 0 | 1 | 2 | 3 |
| H | K | ⟨rgb ₀ ⟩ | ⟨rgb ₁ ⟩ |
| ⟨rgb ₆ ⟩ | ⟨rgb ₇ ⟩ | ⟨rgb ₂ ⟩ | ⟨rgb ₃ ⟩ |
| ⟨rgb ₄ ⟩ | ⟨rgb ₅ ⟩ | ⟨rgb ₆ ⟩ | ⟨rgb ₇ ⟩ |

```
/readerboard/v1/graph?a=<ad>&v=<n>&colors=<rgb0><rgb1><rgb2><rgb3>
<rgb4><rgb5><rgb6><rgb7>
```

This command is used to draw a bar-graph element. Repeating this command causes a scrolling data display which shows a set of data samples over some period of time.

In the simplest form, it takes a single byte parameter. The value $\langle n \rangle$ is an ASCII digit character in the range “0”–“8”, and is drawn in the far-right column of the matrix display, as a column of $\langle n \rangle$ lights stacked up from the bottom row (a value of 0 results in no lights, up to 8 which is a full column of eight lights; a value of 9 is treated as if it were 8). All existing matrix data are scrolled left one column.

In the second form, it takes eight $\langle rgb \rangle$ values (q.v.) which give the color to light up each row in the bar-graph column.

In HTTP, the value of $\langle n \rangle$ is sent as an integer value.

I—Draw Bitmap Image

| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | ... |
|------------------------------------|-------------------------|-----------------------|------------------------------------|--------------------------------|------------------------------------|----|---|---|-----|
| I | $\langle merge \rangle$ | $\langle pos \rangle$ | $\langle trans \rangle$ | $\langle R\ coldata_0 \rangle$ | $\langle R\ coldata_1 \rangle$ | | | | |
| $\langle R\ coldata_{n-1} \rangle$ | \$ | | $\langle G\ coldata \rangle \dots$ | \$ | $\langle B\ coldata \rangle \dots$ | \$ | | | |

```
/readerboard/v1(bitmap?a=<ad>&merge=<bool>&pos=<pos>
&trans=<trans>&image=<R\ coldata>...$<G\ coldata>...$<B\ coldata>...)
```

Draws an arbitrary bitmap image onto the matrix display starting at column $\langle pos \rangle$, encoded as per Table 2.5. A $\langle pos \rangle$ value of “~” represents the current column cursor position.

Each column data, from left to right, are given by $\langle coldata \rangle$ values, each of which is a two-digit ASCII hexadecimal value with the least-significant bit representing the top row of the matrix.

The column data values are terminated by either a dollar-sign (“\$”) character or the escape control character (hex byte 1B), indicated in the protocol diagram above simply as “\$”.

The first set of column data provide the bits for the red color plane. After the terminating byte, two more sets of column data are sent, each with identical format to the first, to provide the bits for the green and blue color planes, respectively.

The column cursor is moved to be after the end of the image.

If $\langle merge \rangle$ is the character “.” then each column’s contents is cleared before setting the pixels as per the $\langle coldata \rangle$ value. If $\langle merge \rangle$ is “M” the bits set in $\langle coldata \rangle$ are added to the lit pixels already in the column.

The $\langle trans \rangle$ value indicates the transition effect to use when adding the image to the display. See Table 2.10.

| Code | Transition |
|------|--|
| . | No transition |
| > | Scroll in from left |
| < | Scroll in from right |
| ~ | Scroll up from bottom |
| v | Scroll down from top |
| L | wipe left |
| R | wipe right |
| U | wipe up |
| D | wipe down |
| | wipe left and right from middle column |
| - | wipe up and down from middle row |
| ? | choose a random transition |


Table 2.10: Transition Effect Codes

K—Set Current Color

/readerboard/v1/color?a= $\langle ad \rangle$ &color= $\langle rgb \rangle$

This command sets the color which all future commands will use by default (although some of them allow for the specification of colors directly on an *ad hoc* basis, which does not affect the current default color).

The $\langle rgb \rangle$ value is a value encoded as defined in Table 2.11. Note that anything drawn in black simply turns off the corresponding pixels.

L—Light Multiple LEDs

/readerboard/v1/light?a= $\langle ad \rangle$ &l= $\langle led_0 \rangle \langle led_1 \rangle \langle led_2 \rangle \dots \langle led_{n-1} \rangle$

This command is identical to the S command (see below), except that multiple discrete LEDs can be specified, all of which are illuminated simultaneously. See Table 2.9. Note that if a strobe sequence is running (via a previous * command), it remains running.

The list of $\langle led \rangle$ values is terminated by either a dollar sign (\$) character or an escape byte (hex value 1B), represented in the protocol diagram as “\$”.

| Code | Color |
|------|------------------|
| 0 | black (off) |
| 1 | red |
| 2 | green |
| 3 | yellow |
| 4 | blue |
| 5 | magenta |
| 6 | cyan |
| 7 | white |
| 9 | flashing red |
| : | flashing green |
| ; | flashing yellow |
| < | flashing blue |
| = | flashing magenta |
| > | flashing cyan |
| ? | flashing white |

Table 2.11: Color codes for $\langle rgb \rangle$ parameters**Q—Query Readerboard Status**

| |
|---|
| 0 |
| Q |

This command causes the sign to send a status report back to the host to indicate the general status of the device except for the discrete LED display which may be queried using the ? command. The response has the form:

| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-----------------------------|-------------------------|-------------------------------|-------------------------------|------------------------|----------------------------------|--------------------------|----|---|
| Q | $\langle model \rangle$ | = | $\langle ad \rangle$ | $\langle uspd \rangle$ | $\langle rspd \rangle$ | $\langle ad_G \rangle$ | \$ | V |
| $\langle hwversion \rangle$ | \$ | R | $\langle romversion \rangle$ | \$ | S | $\langle serial \rangle$ | | |
| \$ | M | $\langle R coldata_0 \rangle$ | $\langle R coldata_1 \rangle$ | ... | $\langle R coldata_{63} \rangle$ | | | |
| \$ | | $\langle G coldata_0 \rangle$ | $\langle G coldata_1 \rangle$ | ... | $\langle G coldata_{63} \rangle$ | \$ | | |
| | | $\langle B coldata_0 \rangle$ | $\langle B coldata_1 \rangle$ | ... | $\langle B coldata_{63} \rangle$ | \n | | |

The $\langle model \rangle$ field may be “L” for the legacy hardware the author still has lying around (but this shouldn’t be something anyone else would need to see), “M” for the current 64×8 matrix display hardware, or “C” for 64×8 RGB color display boards.

$\langle hwversion \rangle$ and $\langle romversion \rangle$ indicate the versions, respectively, of the hardware the firmware was compiled to drive, and of the firmware itself. Each of these fields are variable-width and conform to the semantic version standard 2.0.0.⁴ Each is terminated by a dollar-sign (\$) character (and thus those strings may not contain dollar signs).

The $\langle serial \rangle$ field is a variable-width alphanumeric string which was set when the firmware was compiled. It should be a unique serial number for the device (although that depends on some effort on the part of the person compiling the firmware to insert that serial number each time). Serial numbers 0–299 are reserved for the original author’s use. This string is also terminated with a dollar sign.

The $\langle coldata \rangle$ bytes are sent just as with the I command, as hexadecimal values indicating the LEDs lit on the matrix display, with $\langle coldata_0 \rangle$ being the leftmost column of the display and $\langle coldata_{63} \rangle$ being the rightmost. In each column, the least significant bit indicates the LED on the top row.

The $\langle ad \rangle$, $\langle uspd \rangle$, and $\langle rspd \rangle$ values are as last set by the = command (or the factory defaults if they were never changed).


The status message sent to the host is terminated by a newline character (hex byte 0A), indicated in the protocol description above as “\n”.

Busylight Device Query Response

If a dedicated (non-readerboard) busylight device is sent the Q command, it responds with the following information.

| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-----------------------------|----|---|------------------------------|------------------------|------------------------|--------------------------|----|---|
| Q | B | = | $\langle ad \rangle$ | $\langle uspd \rangle$ | $\langle rspd \rangle$ | $\langle ad_G \rangle$ | \$ | V |
| $\langle hwversion \rangle$ | \$ | R | $\langle romversion \rangle$ | \$ | S | $\langle serial \rangle$ | | |
| \$ | \n | | | | | | | |

S—Light Single LED



Stops the flasher (canceling any previous F command) and turns off all discrete LEDs. The single LED indicated by $\langle led \rangle$ is turned on. See Table 2.9. Note that if a strobe sequence is running (via a previous * command), it remains running.

This command may be given in upper- or lower-case (“s” or “S”).

⁴See semver.org.

T—Display Text

| 0 | 1 | 2 | 3 | 4 | ... | $n+4$ |
|---|-------------------------|-------------------------|-------------------------|--------------------------|-----|-------|
| T | $\langle merge \rangle$ | $\langle align \rangle$ | $\langle trans \rangle$ | $\langle string \rangle$ | | ESC |
| /readerboard/v1/text?a= $\langle ad \rangle$ &merge= $\langle bool \rangle$ &align= $\langle align \rangle$ &trans= $\langle trans \rangle$ &t= $\langle string \rangle$ | | | | | | |

Displays the text $\langle string \rangle$ at the current cursor position. The cursor position is then moved past the text to be ready for the next string to be printed.

The $\langle align \rangle$ code indicates how the text is aligned on the display (TBD).

The $\langle trans \rangle$ code specifies the transition effect to be used to add this string to the display as shown in Table 2.10.

The text is rendered in the current font and may contain any 8-bit bytes except as otherwise noted (but avoiding ASCII control codes is wise to be safe from conflict with future control codes which may be added to the protocol). The string is terminated by an escape character (hex byte 1B), indicated in the protocol description as ESC. (Since a dollar sign may appear in $\langle string \rangle$, the terminator must be an escape character for this command.)

The string may include control codes as listed in Table 2.3.

X—Turn off Discrete LEDs

| | |
|---|---|
| 0 | |
| | X |
| /readerboard/v1/off?a= $\langle ad \rangle$ | |

Turns off the flasher, strober, and all discrete LEDs.

This command may be given in upper- or lower-case (“x” or “X”).

C H A P T E R



SERVER-ONLY COMMANDS

The enjoyment of one's tools is
an essential ingredient of
successful work.

—Donald E. Knuth

FOR THE MOST PART the server exists as a way to host readerboards and busylights from a central machine while allowing users on other networked machines to post messages to them. One shortcoming of this approach is that although *access* to the devices is made widely available, *coordination* between the users wishing to place content on display is not provided. Each update totally changes the state of the target devices.

This chapter describes server-side coordination between users in a network environment by providing a set of commands which clients can post to the server to request information to be displayed for them alongside other content other users have posted. It also provides some services to keep boards updated with information known to the server which the devices don't themselves track, such as time of day.

post—Post a Message to the Displays

```
/readerboard/v1/post?a=<ad>&t=<text>&id=<id>&trans=<trans>  
&until=<datetime>&hold=<duration>&color=<rgb>&repeat=<schedule>
```

Adds a text message to the display list. The message may include the special tokens listed in Table 3.1. The server will maintain the list of posted images and will update the devices as needed to display dynamic content.

| Code | Description |
|------------|--|
| {big} | Display letters and numbers in large font |
| {date} | Date as “⟨dd⟩-⟨mmm⟩-⟨yyyy⟩” |
| {normal} | Stop displaying numbers in large font |
| {mdy} | Date as “⟨mm⟩/⟨dd⟩/⟨yyyy⟩” |
| {pom} | Phase of the moon (as a symbol) |
| {time12} | Time as “⟨hh⟩:⟨mm⟩ AM/PM” on 12-hour clock |
| {time24} | Time as “⟨hh⟩:⟨mm⟩” on 24-hour clock |
| {ymd} | Date as “⟨yyyy⟩-⟨mm⟩-⟨dd⟩” |
| {\$⟨name⟩} | User variable ⟨name⟩ |
| { | Literal “{” |
| } | Literal “}” |

Table 3.1: Special Codes in Post Messages

If any lower-level display matrix commands are received that directly manipulate the matrix, the display of posted messages is suspended in favor of the directly set content. When a clear command is received, then display of the posted message list will resume.

The ⟨id⟩ value must be unique but the server doesn’t assign these in order to keep the API simple. Thus, it is recommended that you assign these as UUIDs or other scheme to keep them from colliding.

If trans is given, this message will be introduced using the specified transition effect.

If until is given, the message will automatically unpost when the specified date and time is reached.

If hold is given, the message will remain on-screen for the specified time duration before moving on to the next posted message.

If color is given, the current color will be changed to the specified value before writing the message; otherwise (or additionally) color codes may be added in-line in the message text.

If repeat is given, ⟨schedule⟩ specifies (in a way yet to be determined) a repeating display schedule for this message (e.g., display this every hour on the hour).

unpost—Remove a Posted Message

```
/readerboard/v1/unpost?a=⟨ad⟩&id=⟨id⟩
```

Remove the message with the given ⟨id⟩ from the display list.

update—Update Dynamic Content

```
/readerboard/v1/update?⟨name0⟩=⟨value0⟩&⟨name1⟩=⟨value1⟩…
```

For each $\langle name \rangle$ and $\langle value \rangle$ pair, define or update the corresponding user variable (usable in posted messages as $\{\$\langle name \rangle\}$). The updated value will be displayed from this point until it is updated again.

C H A P T E R



PINOUTS

No cord or cable can draw so
forcibly, or bind so fast, as love
can do with a single thread.

—Robert Burton

THIS CHAPTER DESCRIBES each connector used by the readerboard devices and what signals are present on which pins. Note that this begins with the current hardware revision, which is most likely the only part you need to know about. Following that are the connector descriptions for older, legacy versions of the hardware. Be careful to know which version you need to refer to.

Connectors for Version 3.2 Boards

Arduino Bus Connectors [J0]

Two parallel rows of stacking pins, for a total of 50 pins, extend out of the back of the readerboard PCB. An Arduino Mega 2560 or Due microcontroller board is connected to these pins.

The USB connector on the Arduino board may be used to directly connect the readerboard to a PC for initial configuration and/or to use it as a directly-connected singleton device. (If there are multiple devices in use, it may be preferable to switch to the RS-485 network after initial configuration of the device.)

Power / RS-485 (8-pin terminal) [J1]

The single external connector on version 2.1.0 boards is an 8-pin screw terminal block. This accepts a +9 V DC power input and ground on pins 3 and 4 respectively, which powers the entire board and the attached Arduino controller. If RS-485 communications will be used, the incoming signal is received on pins 1, 2, and 5 while the outgoing signal is on pins 6, 7, and 8. (In actuality, the “input” and “output” sense is arbitrary and either set of A and B signals may be used as input or output.)

If this device is the last in the RS-485 network chain, insert a 120Ω resistor between the A and B terminals that would have been used as the output if there had been another device connected there. This properly terminates the RS-485 network at that point.

| | | | |
|---|---------------|---|----------------|
| 1 | A (Data in +) | 5 | GND |
| 2 | B (Data in -) | 6 | GND |
| 3 | +9 V DC in | 7 | A (Data out +) |
| 4 | GND | 8 | B (Data out -) |

Connectors for Legacy Boards


Connectors for Version 2.1 Boards

Power / RS-485 (8-pin terminal) [J0]

This is wired the same as J1 on the revision 3.2 boards.


Earlier Boards

Matrix Control (24-pin ribbon cable) [J1]



For readerboards before version 2.1.0, this 24-position ribbon cable carries signals to directly drive the 64×8 LED matrix. The other end of this cable mates with J0 on the shield board. The pinout of its IDC header is:

| | | | | | | | |
|---|-------|----|--------------|----|---------|----|-----|
| 1 | D6 | 7 | RCLK | 13 | +5 V DC | 19 | Gnd |
| 2 | D5 | 8 | D2 | 14 | +5 V DC | 20 | Gnd |
| 3 | D7 | 9 | \bar{G} | 15 | +5 V DC | 21 | R2 |
| 4 | D4 | 10 | D1 | 16 | +5 V DC | 22 | REN |
| 5 | SRCLK | 11 | <u>SRCLR</u> | 17 | Gnd | 23 | R1 |
| 6 | D3 | 12 | D0 | 18 | Gnd | 24 | R0 |

Discrete LEDs (10-pin ribbon cable) [J2]

For readerboards before version 2.1.0, this 10-position ribbon cable carries signals to directly drive the 64×8 LED matrix. The other end of the cable mates with J1 on the shield board. The pinout of its IDC header is:

| | | | |
|---|-----|----|----|
| 1 | GND | 6 | L6 |
| 2 | GND | 7 | L2 |
| 3 | L0 | 8 | L5 |
| 4 | L7 | 9 | L3 |
| 5 | L1 | 10 | L4 |

Board Power (3-pin screw terminal) [J0]

This 3-position screw terminal block provides power to the readerboard. Note that the +5 V supply is also connected to pins 13–16, and Ground to pins 17–20 of J1, the only power required here is the +9 V input that drives the LEDs themselves.

| | |
|---|------------|
| 1 | +5 V DC in |
| 2 | GND |
| 3 | +9 V DC in |

Shield Power (5-pin screw terminal) [Shield J2]

This 5-position screw terminal block accepts incoming +9 V DC power and ground on pins 4 and 3 respectively. It then provides +5 V DC, +9 V DC, and ground outputs on pins 1, 2, and 5 respectively to supply power to the main display board.

| | |
|---|-------------|
| 1 | +5 V DC out |
| 2 | GND |
| 3 | GND |
| 4 | +9 V DC in |
| 5 | +9 V DC out |

Shield RS-485 (6-pin screw terminal) [Shield J4]

This 6-position screw terminal block accepts incoming RS-485 signals A, B, and ground on pins 2, 1, and 3 respectively, and outputs the network signals A, B, and ground on pins 6, 5, and 4 respectively, to go on to the next device in the chain. If this is the last device, then nothing should be

connected to pins 5 and 6. Instead, install jumper J5 which connects a 120Ω resistor across those terminals to terminate the network at that point.


- 1 B (Data In -)
- 2 A (Data In +)
- 3 GND
- 4 GND
- 5 B (Data Out -)
- 6 A (Data Out +)


C H A P T E R









FONT GLYPHS


Font #0 standard.font














































































































**Font #1 standard_variable.font**











































Font #2 symbol.font









101 NW arrow




102 NE arrow




103 SE arrow




104 SW arrow




105 W arrow




106 E arrow




107 N arrow




108 S arrow




109 checkerboard




110 solid block




112 check




113 radical




114 infinity




115 oe




116 oe




117 Euro








118 three dots up




119 three dots down




120 large cross







141 clover




142 notes




144 AM




145 PM




146 degrees F




147 degrees C




152 new moon




153 waxing crescent




154 first quarter




155 waxing gibbous




156 full moon




157 waning gibbous




158 third quarter



159 waning crescent




160 (unicode space)




161



162



Default Glyph



Font Definition Files

In the firmware/readerboard directory there are a set of files with .font suffixes, which define the fonts that the readerboard can employ when writing text to the matrix. If you edit these files, or add more fonts, make the appropriate adjustments to the Makefile and run make in that directory to regenerate the glyph images on the preceding pages of this document, and the source files where the glyphs are actually stored in the device firmware. Then recompile the firmware image and flash it onto the hardware devices.

Each file defines up to 256 glyphs with codepoint values 0–255. The firmware will not allow some codepoints to be printed (see above, Tables 2.3, 2.7, and 2.8 on pp. 13–17), so to avoid reserved codes we recommend using codepoints ≥ 32 .

Any line which begins (possibly after leading whitespace) with a semi-colon ';' is a comment and is ignored completely.

Each glyph definition begins with a line enclosed in square brackets, in the form

[*codepoint* *description*]

Where *codepoint* is either the codepoint expressed as a decimal integer (e.g., “42”) or a dollar sign followed by the codepoint as a hex integer (e.g., “\$2B”), and *description* is an arbitrary text description of the character being defined.

For example:

```
[$25 percent]
@@..@|
@@..@|
...@..|
..@..|
.@...|
@..@|
@..@|
```



```
[$2E period]
..||||
..||||
..||||
..||||
..||||
..||||
@@|||||
@@|||||
```

As a special case, a glyph introduced with the heading

[default]

is defined to be the default glyph to be used if the user tries to print a glyph that is not defined in the font. Only one default glyph may be defined in the entire set of fonts.

The non-blank lines which follow the bracketed header line define the bitmap for the glyph. In this definition, positions which are off are noted with ‘.’ or ‘|’, while positions where the LED is on are noted with ‘@’.

Any completely blank columns to the right of all lit pixels should be represented by ‘|’ rather than ‘..’. This will make note of the drawn width of the character but the columns to the right which consist of ‘|’ characters are not actually stored in the firmware bitmap image, thus conserving ROM space.

If fewer than eight rows are specified, it is assumed that the rows that are present start at the top of the display, and the remaining unspecified rows are all off.

Character Aliases

If a character glyph is to be identical to another glyph, there is no point in storing two or more identical bitmaps in the ROM. In such a case, rather than presenting the duplicate bitmap, the character definition is simply

```
-><codepoint>
      or
-><codepoint>, <font index>
```

In the first case, the glyph for the indicated codepoint will be reused for this character, such as the case in Font #0 where the prime character (hex \$87) looks identical to the single-quote character (hex \$27). Only the single-quote glyph is actually specified in standard.font, so the prime character is defined only as

```
[$87 prime]
->$27
```

In the second case, the glyph to be duplicated comes from a different font file entirely. For example, many characters in Font #1 (standard_variable.font) have the same glyphs as Font #0, such as:

```
[$23 pound sign]
->$23,0
```


C H A P T E R



PREPARING AND UPDATING FIRMWARE IMAGES

The firmware that runs on the readerboard hardware (or, more precisely, the Arduino single-board computer attached to the circuit board) is located in the `firmware/readerboard` directory of the readerboard project repository.

After updating the code from the repository if necessary, perform the following steps to configure and prepare the firmware image:

Step 1: Configuration. Edit the first few lines of `readerboard.h`:

```
#define BANNER_HARDWARE_VERS "HW 3.2.3"
#define BANNER_FIRMWARE_VERS "FW 0.0.0"
#define BANNER_SERIAL_NUMBER "S/N XXXXXX"
#define SERIAL_VERSION_STAMP "V3.2.3$R0.0.0$XXXXXX"
//                                \___/ \___/ \___/
//                                |     |     |
//                                Hardware version |     |
//                                Firmware version |     |
//                                Serial number
```

The `BANNER_FIRMWARE_VERS` value should match the version of the firmware source code you are compiling.

Set the `BANNER_SERIAL_NUMBER` value to the serial number for your specific device. Serial numbers under 300 are reserved for the project author's use. If building your own device, assign a serial number that makes sense

to you. It will help you manage your collection of devices best if you give them unique serial numbers since those can be queried by software.

Set the SERIAL_VERSION_STAMP value to match the previous three values while still preserving the format “V...\$R...\$S...\$”. This string will be sent verbatim as part of the device’s response to being queried for its configuration and status.

An example of a properly configured file looks like this:

```
#define BANNER_HARDWARE_VERS "HW 3.2.3"
#define BANNER_FIRMWARE_VERS "FW 1.2.0"
#define BANNER_SERIAL_NUMBER "S/N R1024"
#define SERIAL_VERSION_STAMP "V3.2.3$R1.2.0$SR1024$"
//                                     \___/ \___/ \___/
//                                     |     |     |
//                                     Hardware version |     |
//                                     Firmware version |     |
//                                     Serial number
```

Step 2: Set Hardware Model. A little further down readerboard.h, there is a pair of lines like:

```
#define HW_MODEL (MODEL_3xx_RGB)
#define HW_MC (HW_MC_DUE)
```

This should come already set up for the latest hardware model (in this example, the revision 3 RGB models which incorporate the Arduino directly onto the main circuit board). If your hardware uses a different design, such as one of the older legacy boards, HW_MODEL needs to be changed to another hardware name, provided that name is actually supported (and supported correctly) in the rest of the firmware.

The supported values for these two configuration settings are listed in Table 6.1.

Step 3: Make. Run the `make` program. This will build the font tables from the various `*.font` files into the firmware code so the target device will be able to generate characters from those fonts.

Customizing and extending the fonts is described in Chapter 5.

Step 4: Compile. Using your Arduino compiler tools, compile the `readerboard.ino` file and upload it to your readerboard hardware. This step assumes you have set up your own Arduino development environment and is beyond the scope of this document to help you with.

| Values for HW_MODEL (Readerboard Hardware Model): | |
|--|---|
| MODEL_3xx_RGB | PCB revision 3.0 and later with RGB LEDs installed. |
| MODEL_3xx_MONOCHROME | PCB revision 3.0 and later with single-color LEDs installed with their anodes soldered into pin 4 (the blue circuit). |
| Values for HW_MC (Microcontroller Installed): | |
| HW_MC_MEGA_2560 | Arduino Mega 2560. |
| HW_MC_DUE | Arduino Due. |

Table 6.1: Firmware Configuration Values

C H A P T E R



S C H E M A T I C S A N D D I A G R A M S

The following page includes the schematics for the current 3.2.1 version of the readerboard PCB and the board assembly diagram, showing where the components are placed.

