1 Welfare Pride Intranet: Standalone Deployment Guide

Audience: Welfare Pride system administrators and deployment operators
Applies to: Docker containers, Linux VPS deployments, and Azure-ready MySQL TLS configuration
Repository context: `project-context/` and `session-worklogs/` are committed at the repository root.

> **Security first:** Do not publish the portal until HTTPS, a persistent database, a protected environment file, and a deployment administrator are in place. The fresh-install `admin` / `admin` account is intentionally temporary. Its first sign-in is restricted to password replacement and multi-factor authentication (MFA) enrollment; it cannot access portal content or administration until both steps are complete.

1.1 1. Deployment model

The Welfare Pride intranet is a standalone Node.js application. WordPress may provide a public-site link to the intranet, but WordPress shared hosting does not host its server-side application runtime. Deploy the intranet on a protected subdomain such as `intranet.example.org`.

Component	Docker deployment	Native Linux VPS deployment
Application	`app` container built from `deploy/hostinger/Dockerfile`	Node.js service managed by `systemd`
Database	MySQL 8.4 container and named volume	Dedicated MySQL 8 server or managed MySQL service
HTTPS	Caddy container and automatically managed certificates	Caddy or Nginx reverse proxy in front of the service
Scheduled work	Isolated scheduler container calling the authenticated dispatch route	Root or service-user cron entry calling the authenticated dispatch route
Upload persistence	Named Docker volume or configured object storage	Protected local path or configured object storage

1.2 2. First-login lifecycle

The installer writes `BOOTSTRAP_DEFAULT_ADMIN=true` for a fresh Docker or native deployment. On the application's first start, and only if the database has no local credential, the service creates one temporary local administrator.

Step	Required action
1	Browse to `https://intranet.example.org` and sign in using **username:** `admin` and **password:** `admin`.

Step	Required action
2	Set a new unique password. The portal enforces a minimum of 12 characters including uppercase, lowercase, number, and symbol.
3	Enroll a TOTP authenticator application by scanning the on-screen QR code, then confirm its six-digit code.
4	Store the recovery codes offline. Each recovery code is accepted once.
5	Set `BOOTSTRAP_DEFAULT_ADMIN=false` in `.env`, then restart the application. This is defense in depth; an existing local credential already prevents re-creation.
6	Open **Integration Settings → Local access** to manage MFA policy for later local accounts and configure optional Microsoft Entra OIDC, OAuth, or SAML sign-in.

1.3 3. Required configuration

Copy `deploy/hostinger/environment.template` to `.env` only on the server. Set its permissions to owner read/write only.

```
cp deploy/hostinger/environment.template .env
chmod 600 .env
```

Variable	Requirement
`DATABASE_URL`	MySQL connection string. Use a dedicated, least-privilege application database account.
`JWT_SECRET`	New high-entropy secret, unique to this production deployment.
`CRON_SECRET`	Different high-entropy secret used only by the scheduled dispatcher.
`BOOTSTRAP_DEFAULT_ADMIN`	`true` only for the initial bootstrap. Change to `false` after the first secure login.
`STORAGE_DRIVER`	`local` for persistent local volume/storage, or configure the S3-compatible variables for object storage.

Variable	Requirement
`DATABASE_SSL`	Set `true` for Azure Database for MySQL or another provider requiring TLS.
`DATABASE_SSL_REJECT_UNAUTHORIZED`	Keep `true` in production unless a database provider has documented an explicit certificate-chain exception.
`AI_BASE_URL`, `AI_MODEL`, `AI_API_KEY`	Optional server-only OpenAI provider configuration. Never expose the API key to the browser.

Generate secrets locally on the target host:

```
openssl rand -hex 32
```

1.4 4. Docker installation

Use this route when the target server supports Docker Engine and Docker Compose v2. The stack includes application, MySQL, scheduler, and Caddy services.

```
git clone https://github.com/<your-organization>/welfare-pride-intranet.git
welfare-pride-intranet
cd welfare-pride-intranet
chmod +x deploy/install.sh
sudo ./deploy/install.sh --mode docker --domain intranet.example.org
```

Confirm service health:

```
cd deploy/hostinger
docker compose --env-file ../../.env ps
docker compose --env-file ../../.env logs --tail=100 app
curl --fail --silent https://intranet.example.org/api/healthz
```

The installer creates `.env` only when one does not already exist. It does not overwrite an existing environment file. Docker volumes retain MySQL data, uploads, and Caddy certificate state across container restarts.

1.5 5. Native Linux VPS installation

Use this route for Ubuntu or another supported Linux VPS that has Node.js 22, Corepack, a reachable MySQL server, and a reverse proxy. Run the command as root only when you want the installer to create and start the `systemd` service.

```
git clone https://github.com/<your-organization>/welfare-pride-intranet.git
welfare-pride-intranet
cd welfare-pride-intranet
```

```
sudo ./deploy/install.sh \
  --mode native \
  --service-user welfarepride \
  --database-url 'mysql://welfare_pride:REPLACE@127.0.0.1:3306/welfare_pride'
```

Before running the installer, create the non-login service account and grant it ownership of the checked-out application directory and upload path:

```
sudo useradd --system --create-home --shell /usr/sbin/nologin welfarepride
sudo chown -R welfarepride:welfarepride /srv/welfare-pride-intranet
```

Inspect the service after installation:

```
sudo systemctl status welfare-pride-intranet
sudo journalctl -u welfare-pride-intranet -n 100 --no-pager
curl --fail --silent http://127.0.0.1:3000/api/healthz
```

Place Caddy or Nginx in front of port `3000`, terminate TLS there, and set the public domain. Do not expose port `3000` directly to the Internet.

1.6 6. Azure-ready MySQL TLS configuration

For Azure Database for MySQL Flexible Server, create a dedicated production database and set the application to use verified TLS.

```
DATABASE_URL=mysql://welfare_pride:REPLACE@your-server.mysql.database.azure.com:
3306/welfare_pride
DATABASE_SSL=true
DATABASE_SSL_REJECT_UNAUTHORIZED=true
```

The application and migration runner use the same TLS configuration. Keep certificate verification enabled for production connections.

1.7 7. Scheduled backup dispatch

The scheduler calls the protected dispatch route every minute and performs only due backup work. For a native VPS, create a root-owned cron entry or equivalent timer:

```
* * * * * curl --fail --silent --show-error --max-time 55 -X POST -H
"Authorization: Bearer YOUR_CRON_SECRET" https://intranet.example.org/api/cron/
dispatch >/dev/null 2>&1
```

Store the secret in a root-readable file or secret manager rather than writing it directly into shared shell history.

1.8 8. Operations and updates

Pull updates only after reviewing the release notes and backing up the database. The project context and sanitized worklogs are Git-versioned in `project-context/` and `session-worklogs/`.

```
git pull --ff-only
corepack pnpm install --frozen-lockfile
corepack pnpm run build
corepack pnpm run db:migrate
sudo systemctl restart welfare-pride-intranet
```

For Docker, use:

```
cd deploy/hostinger
docker compose --env-file ../../.env up -d --build
```

Back up the MySQL database, persistent upload storage, `.env` file held outside source control, and the repository itself. Do not commit database dumps, private documents, credentials, raw session records, or browser logs.

1.9 9. Release acceptance checks

Check	Expected result
Health endpoint	`GET /api/healthz` returns HTTP 200 and `{ "ok": true }`.
Bootstrap control	`admin` / `admin` works only on a fresh database when `BOOTSTRAP_DEFAULT_ADMIN=true`.
Credential rotation	First login cannot access protected routes until a new strong password is saved.
MFA	First login requires TOTP enrollment; later local sign-in requires TOTP or a one-time recovery code.
Admin policy	**Integration Settings → Local access** lists local accounts and allows MFA requirement policy changes.
Data persistence	Application restarts preserve MySQL data and uploads.
Secrets	`.env` is not committed, returned through the browser, or stored in project context/worklogs.
Source independence	A source scan finds no managed-platform runtime URL, package, or injected configuration dependency.

1.10 10. Support files

File or folder	Purpose
`deploy/install.sh`	Single installer entry point for Docker, native Linux, and managed Node modes.
`deploy/hostinger/environment.template`	Production environment-variable contract.
`docs/credential-rotation-notice.md`	Secret rotation and source-package hygiene requirements.
`project-context/`	Rebuild-ready product and architecture context.
`session-worklogs/`	Sanitized, versioned implementation decision summaries.
`docs/welfare-pride-recreation-master-prompt.md`	Reusable reconstruction prompt and feature inventory.

1.11 References