

BACHELOR THESIS

Olivier Amacker

ATTENTION REQUIRED — review before submission

- The thesis reference (`thesis-id`) has not been updated.
- The signature image (`signature`) is missing.
- The title is too long and wraps onto too many lines.

Numerical Stability of Functional MRI Connectivity Biomarkers



Informatique et Systèmes de communication (ISC)

Thesis reference ISC-ID-26-1

Hes·SO

University of Applied Sciences and Arts Western Switzerland

Faculty of Engineering and Architecture

Haute École d'Ingénierie de Sion

Olivier Amacker

Numerical Stability of Functional MRI Connectivity Biomarkers

Thesis submitted to the Bachelor degree programme
Informatique et Systèmes de communication (ISC) – Data engineering major
Haute École d'Ingénierie de Sion

Supervisor: **PROF. DR OSCAR ESTEBAN**

Co-supervisor: **DR OKITO YAMASHITA**

Expert: **DR AYUMU YAMASHITA**

Submitted on August 05, 2026. Revision 0.0.1

PROJECT REPOSITORY

> Go to **github**



Table of Contents

0.1 – The content of a thesis	11
0.2 – Academic titles	12
0.3 – Compiling the thesis	12
1 – Introduction	13
2 – State of the Art	15
3 – Development and Methodology	17
3.1 – Code availability	17
3.2 – Reproduction of Alizadeh et al., 2026	18
3.3 – Edge-wise FC Matrix Stability Analysis	20
3.4 – PCA-based Feature Extraction Stability	20
4 – Results and Discussion	21
5 – Conclusion	23
Bibliography	24
Appendix	27



Abstract

TODO Remove

- The context and motivation for the research.
- The main objective or research question.
- A brief description of the methodology or approach used.
- The key results or findings.
- The main conclusion or implications of the work.

The abstract should be self-contained, clear, and usually does not exceed 250–300 words. It allows readers to quickly understand the purpose and outcomes of the thesis without reading the full document.

The abstract **must** be written in both French and English.

TODO Double check

As [Functional Magnetic Resonance Imaging \(fMRI\)](#) pipelines become more computationally heavy, requiring high-dimensional computations, it is crucial to assess how small numerical variability introduced by several different factors like the running [Operating System \(OS\)](#), parallelization strategies, and hardware architecture affects the results of these pipelines.

Building upon the paper “Numerical Variability of [Magnetic Resonance Imaging \(MRI\)](#) Graph Measures”^[1], this work goes a step further than looking at different [MRI](#) graph measures by also looking at [Major Depressive Disorder \(MDD\)](#) biomarkers, specifically the [Principal Component Analysis \(PCA\)](#) based biomarkers proposed by the paper “Extraction of robust functional connectivity patterns across psychiatric disorders using principal component analysis-based feature selection”^[2] by perturbing several steps of the pipeline. It also assesses the impact of numerically perturbed fMRIPrep preprocessing on FC Functional Connectivity (FC) matrices using the Numerical Population Variability Ratio (NPVR) metric.

To reproduce the results of the original study^[1], the results were obtained by running the fMRIPrep^[3] (25.2.5) preprocessing pipeline through a [custom Docker container](#) with floating-point arithmetic perturbations introduced by the [Verificarlo](#)^[4] and [Fuzzy](#)^[5] libraries. After preprocessing, [FC](#) matrices were obtained using Nilearn^[6] (0.13.1). Different absolute thresholds were applied to the [FC](#) matrices, and graph metrics were computed using NetworkX^[7] (3.6.1).

For the assessment of the [PCA](#) feature selection, two steps of the pipeline were perturbed: the correlation coefficient computation using a [specific Fuzzy Docker image](#), and the principal component analysis by forcing it to use 32-bit floating-point inputs rather than 64-bit.

The results given by the original work reproduction closely matched the original ones, except for a specific graph where the Y-axis values were hardcoded inside the original code. The [PCA](#) feature extraction appeared to be very stable under the introduced numerical perturbations, simulating [OS](#) level numerical variability. Giving the exact same results.

These findings suggest that the PCA features extraction is not only stable across different imaging sites and datasets, but also robust to numerical variability.

Keywords

medical data science, fMRI, fMRIPrep, numerical stability, benchmark, PCA, neuroimaging



Résumé

TODO Double check

Alors que les pipelines de [Imagerie par Résonance Magnétique Fonctionnelle \(IRMf\)](#) deviennent de plus en plus lourdes computationnellement, nécessitant des calculs en haute dimension, il est crucial d'évaluer comment de petites variations numériques introduites par plusieurs facteurs tels que le [Système d'Exploitation \(SE\)](#) utilisé, les stratégies de parallélisation et l'architecture matérielle affectent les résultats de ces dernières.

S'appuyant sur le papier « Numerical Variability of [IRMf](#) Graph Measures » ^[1], ce travail va plus loin que l'examen de différentes mesures de graphes d'[Imagerie par Résonance Magnétique \(IRM\)](#) en examinant également les biomarqueurs du Trouble Dépressif Majeur (TDM), notamment les biomarqueurs basés sur l'[Analyse en Composantes Principales \(ACP\)](#) proposés par le papier "Extraction of robust functional connectivity patterns across psychiatric disorders using principal component analysis-based feature selection" ^[2], en perturbant plusieurs étapes du pipeline. Il évalue également l'impact du prétraitement fMRIPrep numériquement perturbé sur les matrices de Connectivité Fonctionnelle (CF) en utilisant la métrique Numerical Population Variability Ratio (NPVR).

Pour reproduire les résultats de l'étude originale ^[1], les résultats ont été obtenus en exécutant le pipeline de prétraitement fMRIPrep ^[3] (25.2.5) dans un [conteneur Docker personnalisé](#) avec des perturbations arithmétiques en virgule flottante introduites par les bibliothèques [Verificarlo](#) ^[4] et [Fuzzy](#) ^[5]. Après prétraitement, les matrices de [CF](#) ont été obtenues à l'aide de Nilearn ^[6] (0.13.1). Différents seuils absolus ont été appliqués aux matrices de [CF](#), et les métriques de graphes ont été calculées à l'aide de NetworkX ^[7] (3.6.1).

Pour l'évaluation de la sélection de caractéristiques par [ACP](#), deux étapes du pipeline ont été perturbées : le calcul des coefficients de corrélation à l'aide d'une [image Docker Fuzzy spécifique](#), et l'analyse en composantes principales en la forçant à utiliser des entrées en virgule flottante 32 bits plutôt que 64 bits.

Les résultats de la reproduction de l'étude originale correspondent étroitement aux résultats originaux, à l'exception d'un graphe spécifique dont les valeurs de l'axe Y étaient codées en dur dans le code original. L'extraction de caractéristiques par [ACP](#) s'est avérée très stable sous les perturbations numériques introduites, simulant la variabilité numérique au niveau du [SE](#), tout en produisant des résultats strictement identiques.

Ces résultats suggèrent que l'extraction de caractéristiques par [ACP](#) est non seulement stable entre différents sites d'imagerie et jeux de données, mais également robuste face à la variabilité numérique.

Mots-clés

medical data science, fMRI, fMRIPrep, numerical stability, benchmark, PCA, neuroimaging

Acknowledgements

I want to thank the following people and institution which played a huge role in making this bachelor thesis possible:

- Prof. Dr Oscar Esteban, for giving me the opportunity to conduct this Bachelor Thesis abroad, as well as for his guidance and supervision.
- Dr Okito Yamashita and Dr Ayumu Yamashita, for their dedication and continuous feedback throughout this project.
- Dr Yohan Chatelain for his help on the Fuzzy perturbations
- The Advanced Telecommunications Research Institute International (ATR), for providing the necessary resources and environment to carry out this work.
- My family and friends back home, for their emotional support and encouragement during this journey.

TODO Remove

Writing a report is an exercise that involves both **content** and **form**. In this document, we aim to simplify the formatting aspect without making any assumptions about the content, specifically in the context of the ISC degree programme¹.

0.1 – The content of a thesis

The general structure of a bachelor thesis typically includes the following sections:

1. **Abstract:** A concise summary of the thesis, including the research question, methodology, results, and conclusions.
2. **Résumé:** A summary of the thesis in French.
3. **Acknowledgements:** [Optional] A section to thank those who supported your work.
4. **Table of Contents:** An organized list of chapters and sections.
5. **Introduction:** Presents the background/context, motivation, objectives, and scope and plan of the thesis.
6. **State of the Art / Literature Review:** Reviews existing research and situates the thesis within the academic context, if relevant to your work.
7. **Development and Methodology:** Describes the methods, materials, and procedures used in the research/thesis.
8. **Results:** Presents the findings of the research, often with tables, figures, and analysis.
9. **Discussion:** Interprets the results, discusses implications, and relates findings to the research question.
10. **Conclusion:** Summarizes the main findings and contributions, and suggests future work.
11. **References / Bibliography:** Lists all sources cited in the thesis.
12. **Appendices:** (Optional) Contains supplementary material such as raw data, code, or additional explanations.

¹ Here is how to add a footnote <https://isc.hevs.ch>

This structure may vary depending on the field of study, but these elements are commonly found in most bachelor theses. They are recommended for the *ISC Bachelor thesis* and should be adapted to the specific requirements of your thesis (e.g., if you have a state of the art section or not).

You can also change the order or the names of the sections, for instance, if you want to put the state of the art before the introduction, or if you want to add a section on methodology before the results.

0.2 – Academic titles

Please note that the academic titles of your supervisors and experts are important.

They should be included on the cover page, and you should use the correct title when addressing them in the acknowledgements section. For instance, a professor should be addressed as “Prof. [Name]”, while a doctor should be addressed as “Dr [Name]” (**without a colon!**). A professor who is also a doctor should be addressed as “Prof. Dr [Name]”.

If you are unsure about the title of your supervisor, co-supervisor, or expert, you can ask them directly or check their profile on the university website.

0.3 – Compiling the thesis

If you compile your thesis using the `typst` command line tool, or by using the `typst` extension in Visual Studio Code, please note that you must install the fonts used in this template. You can do so by running the following command in your terminal:


```
./fonts/install_fonts.sh
```

Chapter 1

Introduction

Functional Magnetic Resonance Imaging (fMRI) has revolutionized neuroscience by enabling non-invasive observation of brain activity through blood oxygenation level-dependent signals. A key application is the analysis of Functional Connectivity (FC), which examines temporal correlations between spatially distinct brain regions to construct connectivity matrices. These matrices serve as the foundation for deriving graph-theoretical metrics and biomarkers used in clinical research, particularly for conditions such as **Major Depressive Disorder (MDD)**.

As **fMRI** pipelines become increasingly computationally intensive, involving high-dimensional matrix operations and complex preprocessing steps, the question of numerical reliability becomes crucial. Small numerical perturbations introduced by factors such as **Operating System (OS)** differences (as you can see on Figure 1), hardware architecture, and parallelization strategies can propagate through the pipeline, potentially affecting downstream results.



```
madeinshinea ~ 13:02
) cat math_test.c
#include <stdio.h>
#include <math.h>

int main() {
    double sum = 0.0;
    // A loop that accumulates complex math operations
    for (int i = 1; i <= 100000; i++) {
        sum += sin((double)i) * exp(cos((double)i / 10.0));
    }
    printf("Sum: %.18f\n", sum);
    return 0;
}

madeinshinea ~ 13:02
) distrobox enter ubuntu -- bash -c "ldd ./math_test && ./math_test"
linux-vdso.so.1 (0x00007d73b0821000)
libm.so.6 => /usr/lib/x86_64-linux-gnu/libm.so.6 (0x00007d73b06f0000)
libc.so.6 => /usr/lib/x86_64-linux-gnu/libc.so.6 (0x00007d73b04cf000)
/lib64/ld-linux-x86-64.so.2 (0x00007d73b0823000)
Sum: 2.872518434089170736

madeinshinea ~ 13:02
) distrobox enter alpine -- bash -c "ldd ./math_test && ./math_test"
/lib64/ld-linux-x86-64.so.2 (0x79be9332d000)
libm.so.6 => /lib64/ld-linux-x86-64.so.2 (0x79be9332d000)
libc.so.6 => /lib64/ld-linux-x86-64.so.2 (0x79be9332d000)
Sum: 2.872518434089184947
```

Figure 1 - Example of the same program giving different results depending on the OS

In the context of multi-site studies and clinical applications, where reproducibility is essential, understanding and quantifying this numerical variability is critical. Unstable biomarkers could lead to unreliable clinical decisions or failed replication across research sites. However, systematic assessment of numerical stability in [fMRI](#) pipelines remains limited, particularly for advanced feature extraction methods.

The goal of this bachelor thesis, conducted in collaboration with the [Advanced Telecommunications Research Institute International \(ATR\)](#), is to investigate the numerical stability of [fMRI](#) connectivity biomarkers. This work was divided into three complementary parts.

First, the objective was to reproduce the results of Alizadeh et al., 2026^[1], which examined how numerical variability affects the sample size required for statistical significance and the stability of [FC](#) matrix graph metrics using the Numerical Population Variability Ratio (NPVR) metric.

Second, the focus shifted to the numerical stability of the [FC](#) matrices themselves, rather than their derived graph metrics, providing edge-wise stability analysis.

Finally, the numerical stability of a feature extraction method based on [Principal Component Analysis \(PCA\)](#) was assessed, building on the work of Yamashita et al., 2026^[2]. This method extracts [FC](#) biomarkers robust to different sites and datasets. The stability assessment involved perturbing the correlation coefficient computation (`np.corrcoef`) and forcing the [PCA](#) to use 32-bit floating-point inputs rather than 64-bit.

Chapter 2

State of the Art

In recent years, different tools have been created to help the assessment of numerical variability. Notably [Verificarlo](#) Denis et al., 2018 ^[4] which is a tool used to compile programs with [LLVM](#) level arithmetic perturbations and [Fuzzy](#) ^[5] which consists of already perturbed [Docker containers](#) for certain [Python](#) libraries like [Numpy](#) or [Scipy](#), and more recently [Fuzzy PyTorch](#) Gonzalez-Pepe et al., 2026 ^[8] which extends this approach to deep learning workflows.

These tools rely on Monte Carlo Arithmetic (MCA) Parker et al., 1997 ^[9], a technique that introduces controlled random perturbations to floating-point operations during program execution. By repeatedly running the same pipeline with [MCA](#) instrumentation, researchers can quantify how numerical variability propagates through computational workflows.

Using these tools, the impact of numerical variability has been investigated across several neuroimaging domains such as functional, structural and diffusion imaging. As introduced in Section 1, Alizadeh et al., 2026 ^[1] evaluated the numerical variability of different graph measures derived from the [FC](#) matrices resulting from the widely used [fMRIPrep](#) Esteban et al., 2019 ^[3] preprocessing pipeline. Using the [NPVR](#) metric, they obtained values ranging from 0.1 to 0.2 for most graph metrics. These results were found to vary across brain regions, [FC](#) thresholds and confound regression strategies.

In structural imaging pipelines, Mirhakimi et al., 2025 ^[10] investigated numerical uncertainty in linear registration algorithms, demonstrating that small floating-point variations can lead to measurable differences in image alignment. Similarly, Chatelain et al., 2026 ^[11] quantified the impact of numerical variability on structural Magnetic Resonance Imaging (MRI) measures in Parkinson's disease, finding that numerical variation reached nearly one-third of population variability in multiple cortical and subcortical regions.

In diffusion imaging pipelines, Kiar et al., 2021 ^[12] showed that numerical uncertainty in analytical workflows leads to impactful variability in brain network measurements, revealing that different computational environments can produce substantially different connectivity results.

Interestingly, numerical variability has also been used as a resource rather than a limitation. Gonzalez-Pepe et al., 2026^[8] established that controlled numerical perturbations can serve as an effective data augmentation strategy for deep learning models, artificially expanding training datasets and improving model generalization.

However, these stability conclusions cannot be generalized across pipelines due to heterogeneous methodologies and implementations. While graph-theoretical metrics have been studied by Alizadeh et al., 2026^[1], edge-wise FC matrix stability remains unexplored. Additionally, the PCA-based feature extraction proposed by Yamashita et al., 2026^[2] has shown robustness across different sites and datasets, making its numerical stability verification crucial. This thesis addresses these gaps through edge-wise FC analysis and PCA-based extraction evaluation.

Chapter 3

Development and Methodology

This section describes the development process and methodology underlying this thesis. Beyond the thesis-specific code, this work included contributions to external repositories via pull requests, including fixes to the [ISC-HEI Typst thesis template](#), enhancements to [Yamashita et al.'s PCA-based feature extraction package](#), and a correction to the NPVR simulation in [Alizadeh et al.'s repository](#).

3.1 – Code availability

The code developed during this bachelor thesis is publicly available on [GitHub](#). The repository is organized using [git submodules](#) to separate concerns: the `bachelor-thesis-report` submodule contains this [Typst](#) report, while the `bachelor-thesis-project` submodule contains all analysis code, including preprocessing pipelines, analysis notebooks, and job submission scripts for the [ATR High Performance Computing \(HPC\)](#) cluster.

An interactive project website is available at olivier.amacker.dev/bachelor-thesis, providing browsable access to the four analysis notebooks developed with [Marimo](#) and their respective outputs, a daily journal documenting the project's progress, and the different presentations delivered during the thesis.

The development environment is managed via [Nix](#) and [uv](#), ensuring its reproducibility. The fuzzy fMRIPrep [Docker](#) container, built on [Verificarlo](#) and the Fuzzy libmath library, is published on [DockerHub](#) for reproducibility.

3.2 – Reproduction of Alizadeh et al., 2026

This section details the reproduction of the two distinct analyses presented in Alizadeh et al., 2026^[1]. The original code can be found [on GitHub](#), and before starting the reproduction, a comprehensive summary of the paper was created to ensure a thorough understanding of the methodology, preprocessing pipeline, and graph metrics which is accessible [here](#). The first analysis involved implementing NPVR calculation on simulated data to assess how NPVR variation influences the sample size required for Cohen's d coefficient. The second analysis used perturbed fMRIPrep outputs to evaluate NPVR variation across different graph metrics, thresholds, and brain regions.

3.2.1 – NPVR Simulation

An interactive notebook for this simulation can be accessed [online](#), as it doesn't rely on any external data.

The simulation begins by generating two synthetic populations using normal distributions with the same means but different standard deviations: $\sigma = 0.1$ for the low variability group and $\sigma = 0.4$ for the high variability group. For each population, the NPVR is calculated using the formula $NPVR = \frac{\sigma_{num}}{\sigma_{pop}}$, where σ_{num} represents the numerical variability and σ_{pop} the population variability. The populations are then visualized in the $\sigma_{num} / \sigma_{pop}$ space to assess their relative positions on NPVR contour lines. Finally, the relationship between NPVR, sample size, and Cohen's d variations is visualized to assess how numerical noise propagates into statistical inference.

During this reproduction, the original source code was reviewed and an error was identified. The NPVR values in the final visualization were hardcoded to 0.287 and 0.496 rather than computed from the generated distributions. This bug was fixed through a [pull request](#) that was merged into the original repository.

3.2.2 – Graph Metrics Stability Assessment

The notebook code developed for this step and its outputs are available as a [static HTML page](#).

This reproduction step involved several changes to the original procedure. First, a custom [Docker container](#) was created to perturb the latest version of fMRIPrep (25.2.5) instead of using the existing Fuzzy container, which used an older fMRIPrep version (23.2.1). Second, the [fMRI](#) data used for this section was provided by the [ATR](#) and originates from a multi-site dataset Koike et al., 2021^[13], rather than the [publicly available PPMI dataset](#) that was originally used. Third, when extracting the [FC](#) matrices, the original paper used six confound regressors corresponding to the main motion parameters (translations and rotations). However, as the data used in this work appeared to be noisier, nine additional confounds were included following the recommendation of Dr. Yamashita: global signal, CSF, white matter, and six aCompCor components (a_comp_cor_00 through a_comp_cor_05). Fourth, due to computational constraints, small-worldness was excluded from the analysis. Finally, how the NPVR is calculated based on the outputs of the different fMRIPrep runs was modified. In the original paper, they had the same number of runs per subject and the NPVR was calculated as follows:

$$\sigma_{\text{num}}^2 = \frac{1}{m} \sum_{j=1}^m \left[\frac{1}{n-1} \sum_{i=1}^n (x_{i,j} - x_{\cdot,j})^2 \right]$$

$$\sigma_{\text{pop}}^2 = \frac{1}{n} \sum_{i=1}^n \left[\frac{1}{m-1} \sum_{j=1}^m (x_{i,j} - x_{i,\cdot})^2 \right]$$

$$\text{NPVR} = \frac{\sigma_{\text{num}}}{\sigma_{\text{pop}}}$$

where n is the number of MCA repetitions, m is the number of subjects, and $x_{i,j}$ is the metric value for subject j in MCA run i .

Initially, some preprocessing runs failed, resulting in varying numbers of MCA runs per subject. However, after rerunning the failed subjects, the final dataset contained 5 subjects with 5 fuzzy fMRIPrep runs each. Although the final dataset was balanced, the pooled approach was retained to handle potential missing data robustly. The pooled numerical variance accounts for the varying number of runs per subject:

$$\sigma_{\text{num pooled}}^2(r) = \frac{1}{\sum_{j=1}^m (n_j - 1)} \sum_{j=1}^m (n_j - 1) \left[\frac{1}{n_j - 1} \sum_{i \in \Omega_j} (x_{i,j}(r) - x_{\cdot,j}(r))^2 \right]$$

Similarly, the pooled population variance accounts for the varying number of subjects per run:

$$\sigma_{\text{pop pooled}}^2(r) = \frac{1}{\sum_{i=1}^n (m_i - 1)} \sum_{i=1}^n (m_i - 1) \left[\frac{1}{m_i - 1} \sum_{j \in \Omega_i} (x_{i,j}(r) - x_{i,\cdot}(r))^2 \right]$$

The pooled **NPVR** for each region r is then:

$$\text{NPVR}_{\text{pooled}(r)} = \frac{\sigma_{\text{num pooled}(r)}}{\sigma_{\text{pop pooled}(r)}}$$

where n_j is the number of runs for subject j , m_i is the number of subjects in MCA run i , and Ω_j and Ω_i denote the sets of valid indices for subject j and run i , respectively.

This approach ensures that all available data contributes to the variability estimates, even if some runs are missing.

The remaining analysis followed the same procedure as the original study. After fMRIPrep preprocessing, the Schaefer 2018 parcellation ^[14] with 100 cortical regions and 7 functional networks was used to extract regional time series using Nilearn's NiftiLabelsMasker. Spatial smoothing of 6mm Full Width at Half Maximum (FWHM), temporal standardization, and detrending were applied during masking. The FC matrices were computed as Pearson correlation matrices using Nilearn's ConnectivityMeasure, with both with-confound and without-confound versions generated. The matrices were thresholded using absolute correlation values at six thresholds: 0.05, 0.1, 0.2, 0.3, 0.4, and 0.5, retaining both strongly positive and strongly negative correlations. For each threshold, four local graph metrics were computed using NetworkX: degree centrality, clustering coefficient, betweenness centrality, and eigenvector centrality. Additionally, one global metric was calculated: average shortest path length. The NPVR was then computed for each metric and threshold, and plotted across brain regions by projecting regional values onto the Schaefer 2018 atlas to assess spatial variability in numerical stability. Additionally, the NPVR was computed on the difference between with-confound and without-confound matrices to assess the impact of confound regression, following the approach of the original study.

3.3 – Edge-wise FC Matrix Stability Analysis

3.4 – PCA-based Feature Extraction Stability

3.4.1 – Reproduction on SRPB and BMB Datasets

3.4.2 – FC Matrix Extraction Perturbation

3.4.3 – PCA Dimensionality Reduction Perturbation

Chapter 4

Results and Discussion

Chapter 5

Conclusion

Bibliography

- [1] M. Alizadeh, Y. Chatelain, G. Kiar, and T. Glatard, “Numerical Variability of functional MRI Graph Measures,” *bioRxiv*, 2026, doi: [10.64898/2025.12.22.695524](https://doi.org/10.64898/2025.12.22.695524).
- [2] A. Yamashita *et al.*, “Extraction of robust functional connectivity patterns across psychiatric disorders using principal component analysis-based feature selection,” *Imaging Neuroscience*, vol. 4, p. IMAG.a.1121, 2026, doi: [10.1162/IMAG.a.1121](https://doi.org/10.1162/IMAG.a.1121).
- [3] O. Esteban *et al.*, “fMRIPrep: a robust preprocessing pipeline for functional MRI,” *Nature Methods*, vol. 16, p. , 2019, doi: [10.1038/s41592-018-0235-4](https://doi.org/10.1038/s41592-018-0235-4).
- [4] C. Denis, P. D. O. Castro, and E. Petit, “Verificarlo: checking floating point accuracy through Monte Carlo Arithmetic.” [Online]. Available: <https://arxiv.org/abs/1509.01347>
- [5] G. Kiar *et al.*, “verificarlo/fuzzy: Fuzzy v3.5.1.” [Online]. Available: <https://doi.org/10.5281/zenodo.20906259>
- [6] N. contributors, “nilearn.” [Online]. Available: <https://github.com/nilearn/nilearn>
- [7] A. A. Hagberg, D. A. Schult, and P. J. Swart, “Exploring Network Structure, Dynamics, and Function using NetworkX,” in *Proceedings of the 7th Python in Science Conference*, G. Varoquaux, T. Vaught, and J. Millman, Eds., Pasadena, CA USA, 2008, pp. 11–15.
- [8] I. Gonzalez-Pepe, H. Akhaddar, T. Glatard, and Y. Chatelain, “Fuzzy PyTorch: Rapid Numerical Variability Evaluation for Deep Learning Models.” [Online]. Available: <https://arxiv.org/abs/2605.25991>
- [9] D. S. Parker and D. Langley, “Monte Carlo Arithmetic: exploiting randomness in floating-point arithmetic,” 1997. [Online]. Available: <https://api.semanticscholar.org/CorpusID:2321215>
- [10] N. Mirhakimi, Y. Chatelain, T. Glatard, and J.-B. Poline, “Numerical Uncertainty in Linear Registration: An Experimental Study.” [Online]. Available: <https://arxiv.org/abs/2508.00781>
- [11] Y. Chatelain, A. Sokołowski, M. Sharp, J.-B. Poline, and T. Glatard, “The practical impact of numerical variability on structural MRI measures of Parkinson’s disease,” *bioRxiv*, 2026, doi: [10.64898/2026.01.09.698203](https://doi.org/10.64898/2026.01.09.698203).
- [12] G. Kiar *et al.*, “Numerical uncertainty in analytical pipelines lead to impactful variability in brain networks,” *PLOS ONE*, vol. 16, p. e250755, 2021, doi: [10.1371/journal.pone.0250755](https://doi.org/10.1371/journal.pone.0250755).
- [13] S. Koike *et al.*, “Brain/MINDS beyond human brain MRI project: A protocol for multi-level harmonization across brain disorders throughout the lifespan,” *NeuroImage: Clinical*, vol. 30, p. 102600, 2021, doi: <https://doi.org/10.1016/j.nicl.2021.102600>.
- [14] A. Schaefer *et al.*, “Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic Functional Connectivity MRI,” *Cerebral Cortex*, vol. 28, no. 9, pp. 3095–3114, 2018, doi: [10.1093/cercor/bhx179](https://doi.org/10.1093/cercor/bhx179).
- [15] Wellcome Centre for Human Neuroimaging, “Understanding MRI: What is functional MRI (fMRI)?” [Online]. Available: <https://www.youtube.com/watch?v=4UOeBM5BwdY>
- [16] Zachary Cortez, “fMRI Explained (Functional Magnetic Resonance Imaging).” [Online]. Available: <https://www.youtube.com/watch?v=IGwChiQJHk>
- [17] La Science En Schémas, “IMAGERIE MÉDICALE #7 : L'IRM (Imagerie par résonance magnétique).” [Online]. Available: https://www.youtube.com/watch?v=q_H5GRC48KU
- [18] Olivier Amacker, “Semester project.” [Online]. Available: <https://github.com/MadeInShineA/303.1-semester-project>

- [19] T. Glatard, “Fuzzy fMRIPrep.” [Online]. Available: <https://github.com/glatard/fuzzy-fmriprep>
- [20] Verificarlo, “Fuzzy.” [Online]. Available: <https://github.com/verificarlo/fuzzy>
- [21] Enthought, “Fuzzy environments for the perturbation evaluation and appl of num uncertainty via Mo | SciPy 2021.” [Online]. Available: <https://www.youtube.com/watch?v=3zgS8nYaKJ0>
- [22] Verificarlo, “Verificarlo.” [Online]. Available: <https://github.com/verificarlo/verificarlo>
- [23] N. Terzimehić, B. Bühler, and E. Kasneci, “Conversational AI as a catalyst for informal learning: An empirical large-scale study on LLM use in everyday learning,” *Computers and Education: Artificial Intelligence*, p. 100634, 2026, doi: <https://doi.org/10.1016/j.caeai.2026.100634>.
- [24] N. Kosmyna *et al.*, “Your Brain on ChatGPT: Accumulation of Cognitive Debt when Using an AI Assistant for Essay Writing Task.” [Online]. Available: <https://arxiv.org/abs/2506.08872>
- [25] K. Moon, A. E. Green, and K. Kushlev, “Homogenizing effect of large language models (LLMs) on creative diversity: An empirical comparison of human and ChatGPT writing,” *Computers in Human Behavior: Artificial Humans*, vol. 6, p. 100207, 2025, doi: <https://doi.org/10.1016/j.chbah.2025.100207>.
- [26] J. Becker, N. Rush, E. Barnes, and D. Rein, “Measuring the Impact of Early-2025 AI on Experienced Open-Source Developer Productivity.” [Online]. Available: <https://arxiv.org/abs/2507.09089>
- [27] A. Alansari and H. Luqman, “Large Language Models Hallucination: A Comprehensive Survey.” [Online]. Available: <https://arxiv.org/abs/2510.06265>

Appendix

Table of Acronyms

ACP :	Analyse en Composantes Principales
ATR :	Advanced Telecommunications Research Institute International
CF :	Connectivité Fonctionnelle
FC :	Functional Connectivity
FWHM :	Full Width at Half Maximum
HPC :	High Performance Computing
IRM :	Imagerie par Résonance Magnétique
IRMf :	Imagerie par Résonance Magnétique Fonctionnelle
MCA :	Monte Carlo Arithmetic
MDD :	Major Depressive Disorder
MRI :	Magnetic Resonance Imaging
NPVR :	Numerical Population Variability Ratio
OS :	Operating System
PCA :	Principal Component Analysis
PR :	Pull Request
SE :	Système d'Exploitation
TDM :	Trouble Dépressif Majeur
fMRI :	Functional Magnetic Resonance Imaging

List of Figures

Figure 1 Example of the same program giving different results depending on the OS 13

Code Appendix

```

1 class Cons[+A](hd: A, tl: ⇒ MyStream[A]) extends MyStream[A] {
2   override def isEmpty: Boolean = false
3   override val head: A = hd
4   override lazy val tail: MyStream[A] = tl
5   override def #::[B >: A](elem: B): MyStream[B] =
6     new Cons[B](elem, this)
7
8   override def ++[B >: A](anotherStream: ⇒ MyStream[B]): MyStream[B] =
9     new Cons[B](head, tail ++ anotherStream)
10
11  override def foreach(f: A ⇒ Unit): Unit = {
12    f(head)
13    tail.foreach(f)
14  }
15 }

```

Listing 1 - Code included from the file example.scala

```

1 def mergeSort(arr):
2   if len(arr) ≤ 1:
3     return arr
4
5   mid = len(arr) // 2
6   leftHalf = arr[:mid]
7   rightHalf = arr[mid:]
8
9   sortedLeft = mergeSort(leftHalf)
10  sortedRight = mergeSort(rightHalf)
11
12  return merge(sortedLeft, sortedRight)
13
14 def merge(left, right):
15   result = []
16   i = j = 0
17
18   while i < len(left) and j < len(right):
19     if left[i] < right[j]:
20       result.append(left[i])
21       i += 1
22     else:
23       result.append(right[j])
24       j += 1
25
26   result.extend(left[i:])
27   result.extend(right[j:])
28
29   return result
30
31 mylist = [3, 7, 6, -10, 15, 23.5, 55, -13]
32 mysortedlist = mergeSort(mylist)
33 print("Sorted array:", mysortedlist)

```

Listing 2 - Second code included from the file example.scala

```

1 class Cons[+A](hd: A, tl: ⇒ MyStream[A]) extends MyStream[A] {
2   override def isEmpty: Boolean = false
3   override val head: A = hd
4   override lazy val tail: MyStream[A] = tl

```



```
5  override def #::[B >: A](elem: B): MyStream[B] =  
6      new Cons[B](elem, this)  
7  
8  override def ++[B >: A](anotherStream: ⇒ MyStream[B]): MyStream[B] =  
9      new Cons[B](head, tail ++ anotherStream)  
10  
11  override def foreach(f: A ⇒ Unit): Unit = {  
12      f(head)  
13      tail.foreach(f)  
14  }  
15 }
```

Listing 3 - Second code included from the file example.scala

Typeset with Typst

ISC-HEI template by P.-A. Mudry · v0.8.0

Informatique et systèmes de communication — Sion, HES-SO Valais

No LaTeX was harmed in the making of this document.