

BACHELOR THESIS

Olivier Amacker

ATTENTION REQUIRED — review before submission

- The thesis reference (`thesis-id`) has not been updated.
- The signature image (`signature`) is missing.
- The title is too long and wraps onto too many lines.

Numerical Stability of Functional MRI Connectivity Biomarkers



Informatique et Systèmes de communication (ISC)

Thesis reference ISC-ID-26-1

Hes·SO

University of Applied Sciences and Arts Western Switzerland

Faculty of Engineering and Architecture

Haute École d'Ingénierie de Sion

Olivier Amacker

Numerical Stability of Functional MRI Connectivity Biomarkers

Thesis submitted to the Bachelor degree programme
Informatique et Systèmes de communication (ISC) – Data engineering major
Haute École d'Ingénierie de Sion

Supervisor: **PROF. DR OSCAR ESTEBAN**

Co-supervisor: **DR OKITO YAMASHITA**

Expert: **DR AYUMU YAMASHITA**

Submitted on July 27, 2026. Revision 0.0.1

PROJECT REPOSITORY

> Go to **github**



Table of Contents

1 – Writing a thesis	13
1.1 – The content of a thesis	13
1.2 – Academic titles	14
1.3 – Compiling the thesis	14
2 – Introduction	15
3 – Development and Methodology 1	17
4 – Development and Methodology 2	19
5 – Development and Methodology 3	21
6 – Development and Methodology 4	23
7 – Development and Methodology 5	25
8 – Development and Methodology 6	27
9 – Development and Methodology 7	29
10 – Results and Discussion	31
11 – Conclusion	33
Bibliography	34
Appendix	37



Abstract

- The context and motivation for the research.
- The main objective or research question.
- A brief description of the methodology or approach used.
- The key results or findings.
- The main conclusion or implications of the work.

The abstract should be self-contained, clear, and usually does not exceed 250–300 words. It allows readers to quickly understand the purpose and outcomes of the thesis without reading the full document.

The abstract **must** be written in both French and English.

TODO Double check

As [functional Magnetic Resonance Imaging](#) (fMRI) pipelines become more computationally heavy, requiring high-dimensional computations, it is crucial to assess how small numerical variability introduced by several different factors like the running [Operating System](#) (OS), parallelization strategies, and hardware architecture affects the results of these pipelines.

Building upon the paper “Numerical Variability of [fMRI](#) Graph Measures” ^[1], this work goes a step further than looking at different [Magnetic Resonance Imaging](#) (MRI) graph measures by also looking at [Major Depressive Disorder](#) (MDD) biomarkers, specifically the [Principal Component analysis](#) (PCA) based biomarkers proposed by the paper “Extraction of robust functional connectivity patterns across psychiatric disorders using principal component analysis-based feature selection” ^[2] by perturbing several steps of the pipeline. It also assesses the impact of numerically perturbed fMRIPrep preprocessing on FC Functional Connectivity (FC) matrices using the Numerical Population Variability Ratio (NPVR) metric.

To reproduce the results of the original study ^[1], the results were obtained by running the fMRIPrep ^[3] (25.2.5) preprocessing pipeline through a [custom Docker container](#) with floating-point arithmetic perturbations introduced by the Verificarlo ^[4] and Fuzzy ^[5] libraries. After preprocessing, FC matrices were obtained using Nilearn ^[6] (0.13.1). Different absolute thresholds were applied to the FC matrices, and graph metrics were computed using NetworkX ^[7] (3.6.1).

For the assessment of the [PCA](#) feature selection, two steps of the pipeline were perturbed using a [specific Fuzzy Docker image](#), the correlation coefficient computation and principal component analysis.

The results given by the original work reproduction closely matched the original ones, except for a specific graph where the Y-axis values were hardcoded inside the original code. The [PCA](#) feature extraction appeared to be very stable under the introduced numerical perturbations, simulating [OS](#) level numerical variability. Giving the exact same results.

These findings suggest that the PCA features extraction is not only stable across different imaging sites and datasets, but also robust to numerical variability.

Keywords

medical data science, fMRI, fMRIPrep, numerical stability, benchmark, PCA, neuro imaging



Résumé

TODO Double check

Alors que les pipelines d'[imagerie par résonance magnétique fonctionnelle](#) (IRMf) deviennent de plus en plus lourdes computationnellement, nécessitant des calculs en haute dimension, il est crucial d'évaluer comment de petites variations numériques introduites par plusieurs facteurs tels que le [Système d'Exploitation](#) (SE) utilisé, les stratégies de parallélisation et l'architecture matérielle affectent les résultats de ces dernières.

S'appuyant sur le papier « Numerical Variability of [IRMf](#) Graph Measures » ^[1], ce travail va plus loin que l'examen de différentes mesures de graphes d'[Imagerie par Résonance Magnétique](#) (IRM) en examinant également les biomarqueurs du Trouble Dépressif Majeur (TDM), notamment les biomarqueurs basés sur l'[Analyse en Composantes Principales](#) (ACP) proposés par le papier "Extraction of robust functional connectivity patterns across psychiatric disorders using principal component analysis-based feature selection" ^[2], en perturbant plusieurs étapes du pipeline. Il évalue également l'impact du prétraitement fMRIPrep numériquement perturbé sur les matrices de Connectivité Fonctionnelle (CF) en utilisant la métrique Numerical Population Variability Ratio (NPVR).

Pour reproduire les résultats de l'étude originale ^[1], les résultats ont été obtenus en exécutant le pipeline de prétraitement fMRIPrep ^[3] (25.2.5) dans un [conteneur Docker personnalisé](#) avec des perturbations arithmétiques en virgule flottante introduites par les bibliothèques Verificarlo ^[4] et Fuzzy ^[5]. Après prétraitement, les matrices de [CF](#) ont été obtenues à l'aide de Nilearn ^[6] (0.13.1). Différents seuils absolus ont été appliqués aux matrices de [CF](#), et les métriques de graphes ont été calculées à l'aide de NetworkX ^[7] (3.6.1).

Pour l'évaluation de la sélection de caractéristiques par [ACP](#), deux étapes du pipeline ont été perturbées à l'aide d'une [image Docker Fuzzy spécifique](#) le calcul des coefficients de corrélation et l'analyse en composantes principales.

Les résultats de la reproduction de l'étude originale correspondent étroitement aux résultats originaux, à l'exception d'un graphe spécifique dont les valeurs de l'axe Y étaient codées en dur dans le code original. L'extraction de caractéristiques par [ACP](#) s'est avérée très stable sous les perturbations numériques introduites, simulant la variabilité numérique au niveau du [SE](#), tout en produisant des résultats strictement identiques.

Ces résultats suggèrent que l'extraction de caractéristiques par [ACP](#) est non seulement stable entre différents sites d'imagerie et jeux de données, mais également robuste face à la variabilité numérique.

Mots-clés

medical data science, fMRI, fMRIPrep, numerical stability, benchmark, PCA, neuro imaging

Acknowledgements

I want to thank the following people and institution which played a huge role in making this Bachelor Thesis possible:

- Prof. Dr Oscar Esteban, for giving me the opportunity to conduct this Bachelor Thesis abroad, as well as for his guidance and supervision.
- Dr Okito Yamashita and Dr Ayumu Yamashita, for their dedication and continuous feedback throughout this project.
- Dr Yohan Chatelain for his help on the Fuzzy perturbations
- The [Advanced Telecommunications Research Institute International](#) (ATR), for providing the necessary resources and environment to carry out this work.
- My family and friends back home, for their emotional support and encouragement during this journey.

Chapter 1

Writing a thesis



Writing a report is an exercise that involves both **content** and **form**. In this document, we aim to simplify the formatting aspect without making any assumptions about the content, specifically in the context of the ISC degree programme¹.

1.1 – The content of a thesis

The general structure of a bachelor thesis typically includes the following sections:

1. **Abstract:** A concise summary of the thesis, including the research question, methodology, results, and conclusions.
2. **Résumé:** A summary of the thesis in French.
3. **Acknowledgements:** [Optional] A section to thank those who supported your work.
4. **Table of Contents:** An organized list of chapters and sections.
5. **Introduction:** Presents the background/context, motivation, objectives, and scope and plan of the thesis.
6. **State of the Art / Literature Review:** Reviews existing research and situates the thesis within the academic context, if relevant to your work.
7. **Development and Methodology:** Describes the methods, materials, and procedures used in the research/thesis.
8. **Results:** Presents the findings of the research, often with tables, figures, and analysis.
9. **Discussion:** Interprets the results, discusses implications, and relates findings to the research question.
10. **Conclusion:** Summarizes the main findings and contributions, and suggests future work.
11. **References / Bibliography:** Lists all sources cited in the thesis.
12. **Appendices:** (Optional) Contains supplementary material such as raw data, code, or additional explanations.

This structure may vary depending on the field of study, but these elements are commonly found in most bachelor theses. They are recommended for the *ISC Bachelor thesis* and should be adapted to the specific requirements of your thesis (e.g., if you have a state of the art section or not).

You can also change the order or the names of the sections, for instance, if you want to put the state of the art before the introduction, or if you want to add a section on methodology before the results.

¹ Here is how to add a footnote <https://isc.hevs.ch>

1.2 – Academic titles

Please note that the academic titles of your supervisors and experts are important.

They should be included on the cover page, and you should use the correct title when addressing them in the acknowledgements section. For instance, a professor should be addressed as “Prof. [Name]”, while a doctor should be addressed as “Dr [Name]” (**without a colon!**). A professor who is also a doctor should be addressed as “Prof. Dr [Name]”.

If you are unsure about the title of your supervisor, co-supervisor, or expert, you can ask them directly or check their profile on the university website.

1.3 – Compiling the thesis

If you compile your thesis using the `typst` command line tool, or by using the `typst` extension in Visual Studio Code, please note that you must install the fonts used in this template. You can do so by running the following command in your terminal:

```
./fonts/install_fonts.sh
```

Chapter 2

Introduction

Have fun **TODO** writing your thesis! and good luck with it !



Figure 1 - Grace Hopper

Chapter 3

Development and Methodology 1

Chapter 4

Development and Methodology 2

Chapter 5

Development and Methodology 3

Chapter 6

Development and Methodology 4

Chapter 7

Development and Methodology 5

Chapter 8

Development and Methodology 6

Chapter 9

Development and Methodology 7

Chapter 10

Results and Discussion

Chapter 11

Conclusion

Bibliography

- [1] M. Alizadeh, Y. Chatelain, G. Kiar, and T. Glatard, “Numerical Variability of functional MRI Graph Measures,” *bioRxiv*, 2026, doi: [10.64898/2025.12.22.695524](https://doi.org/10.64898/2025.12.22.695524).
- [2] A. Yamashita *et al.*, “Extraction of robust functional connectivity patterns across psychiatric disorders using principal component analysis-based feature selection,” *Imaging Neuroscience*, vol. 4, p. IMAG.a.1121, 2026, doi: [10.1162/IMAG.a.1121](https://doi.org/10.1162/IMAG.a.1121).
- [3] O. Esteban *et al.*, “fMRIPrep: a robust preprocessing pipeline for functional MRI,” *Nature Methods*, vol. 16, p. , 2019, doi: [10.1038/s41592-018-0235-4](https://doi.org/10.1038/s41592-018-0235-4).
- [4] Verificarlo, “Verificarlo.” [Online]. Available: <https://github.com/verificarlo/verificarlo>
- [5] Verificarlo, “Fuzzy.” [Online]. Available: <https://github.com/verificarlo/fuzzy>
- [6] N. contributors, “nilearn.” [Online]. Available: <https://github.com/nilearn/nilearn>
- [7] A. A. Hagberg, D. A. Schult, and P. J. Swart, “Exploring Network Structure, Dynamics, and Function using NetworkX,” in *Proceedings of the 7th Python in Science Conference*, G. Varoquaux, T. Vaught, and J. Millman, Eds., Pasadena, CA USA, 2008, pp. 11–15.
- [8] Wellcome Centre for Human Neuroimaging, “Understanding MRI: What is functional MRI (fMRI)?” [Online]. Available: <https://www.youtube.com/watch?v=4UOeBM5BwdY>
- [9] Zachary Cortex, “fMRI Explained (Functional Magnetic Resonance Imaging).” [Online]. Available: <https://www.youtube.com/watch?v=IGwChiQJJHk>
- [10] La Science En Schémas, “IMAGERIE MÉDICALE #7 : L'IRM (Imagerie par résonance magnétique).” [Online]. Available: https://www.youtube.com/watch?v=q_H5GRC48KU
- [11] Olivier Amacker, “Semester project.” [Online]. Available: <https://github.com/MadeInShineA/303.1-semester-project>
- [12] Y. Chatelain, A. Sokołowski, M. Sharp, J.-B. Poline, and T. Glatard, “The practical impact of numerical variability on structural MRI measures of Parkinson’s disease,” *bioRxiv*, 2026, doi: [10.64898/2026.01.09.698203](https://doi.org/10.64898/2026.01.09.698203).
- [13] T. Glatard, “Fuzzy fMRIPrep.” [Online]. Available: <https://github.com/glatard/fuzzy-fmriprep>
- [14] Enthought, “Fuzzy environments for the perturbation evaluation and appl of num uncertainty via Mo | SciPy 2021.” [Online]. Available: <https://www.youtube.com/watch?v=3zgS8nYaKJ0>
- [15] C. Denis, P. D. O. Castro, and E. Petit, “Verificarlo: checking floating point accuracy through Monte Carlo Arithmetic.” [Online]. Available: <https://arxiv.org/abs/1509.01347>
- [16] S. Koike *et al.*, “Brain/MINDS beyond human brain MRI project: A protocol for multi-level harmonization across brain disorders throughout the lifespan,” *NeuroImage: Clinical*, vol. 30, p. 102600, 2021, doi: <https://doi.org/10.1016/j.nicl.2021.102600>.
- [17] N. Terzimehić, B. Bühler, and E. Kasneci, “Conversational AI as a catalyst for informal learning: An empirical large-scale study on LLM use in everyday learning,” *Computers and Education: Artificial Intelligence*, p. 100634, 2026, doi: <https://doi.org/10.1016/j.caeai.2026.100634>.
- [18] N. Kosmyna *et al.*, “Your Brain on ChatGPT: Accumulation of Cognitive Debt when Using an AI Assistant for Essay Writing Task.” [Online]. Available: <https://arxiv.org/abs/2506.08872>

- [19] K. Moon, A. E. Green, and K. Kushlev, “Homogenizing effect of large language models (LLMs) on creative diversity: An empirical comparison of human and ChatGPT writing,” *Computers in Human Behavior: Artificial Humans*, vol. 6, p. 100207, 2025, doi: <https://doi.org/10.1016/j.chbah.2025.100207>.
- [20] J. Becker, N. Rush, E. Barnes, and D. Rein, “Measuring the Impact of Early-2025 AI on Experienced Open-Source Developer Productivity.” [Online]. Available: <https://arxiv.org/abs/2507.09089>
- [21] A. Alansari and H. Luqman, “Large Language Models Hallucination: A Comprehensive Survey.” [Online]. Available: <https://arxiv.org/abs/2510.06265>

Appendix

Table of Acronyms

ACP :	Analyse en Composantes Principales
ATR :	Advanced Telecommunications Research Institute International
CF :	Connectivité Fonctionnelle
FC :	Functional Connectivity
IRM :	Imagerie par Résonance Magnétique
IRMf :	imagerie par résonance magnétique fonctionnelle
MDD :	Major Depressive Disorder
MRI :	Magnetic Resonance Imaging
NPVR :	Numerical Population Variability Ratio
OS :	Operating System
PCA :	Principal Component analysis
PR :	Pull Request
SE :	Système d'Exploitation
TDM :	Trouble Dépressif Majeur
fMRI :	functional Magnetic Resonance Imaging

List of Figures

Figure 1 Grace Hopper	15
-----------------------------	----

Code Appendix

```

1 class Cons[+A](hd: A, tl: ⇒ MyStream[A]) extends MyStream[A] {
2   override def isEmpty: Boolean = false
3   override val head: A = hd
4   override lazy val tail: MyStream[A] = tl
5   override def #::[B >: A](elem: B): MyStream[B] =
6     new Cons[B](elem, this)
7
8   override def ++[B >: A](anotherStream: ⇒ MyStream[B]): MyStream[B] =
9     new Cons[B](head, tail ++ anotherStream)
10
11  override def foreach(f: A ⇒ Unit): Unit = {
12    f(head)
13    tail.foreach(f)
14  }
15 }

```

Listing 1 - Code included from the file example.scala

```

1 def mergeSort(arr):
2   if len(arr) ≤ 1:
3     return arr
4
5   mid = len(arr) // 2
6   leftHalf = arr[:mid]
7   rightHalf = arr[mid:]
8
9   sortedLeft = mergeSort(leftHalf)
10  sortedRight = mergeSort(rightHalf)
11
12  return merge(sortedLeft, sortedRight)
13
14 def merge(left, right):
15   result = []
16   i = j = 0
17
18   while i < len(left) and j < len(right):
19     if left[i] < right[j]:
20       result.append(left[i])
21       i += 1
22     else:
23       result.append(right[j])
24       j += 1
25
26   result.extend(left[i:])
27   result.extend(right[j:])
28
29   return result
30
31 mylist = [3, 7, 6, -10, 15, 23.5, 55, -13]
32 mysortedlist = mergeSort(mylist)
33 print("Sorted array:", mysortedlist)

```

Listing 2 - Second code included from the file example.scala

```

1 class Cons[+A](hd: A, tl: ⇒ MyStream[A]) extends MyStream[A] {
2   override def isEmpty: Boolean = false
3   override val head: A = hd
4   override lazy val tail: MyStream[A] = tl

```

```
5  override def #::[B >: A](elem: B): MyStream[B] =  
6      new Cons[B](elem, this)  
7  
8  override def ++[B >: A](anotherStream: ⇒ MyStream[B]): MyStream[B] =  
9      new Cons[B](head, tail ++ anotherStream)  
10  
11  override def foreach(f: A ⇒ Unit): Unit = {  
12      f(head)  
13      tail.foreach(f)  
14  }  
15 }
```

Listing 3 - Second code included from the file example.scala

Typeset with Typst

ISC-HEI template by P.-A. Mudry · v0.8.0

Informatique et systèmes de communication — Sion, HES-SO Valais

No LaTeX was harmed in the making of this document.