Madek

http://madek.zhdk.ch

Database: Entities and Relations

Version 2025-08 uvb

The naming of the entities follows largely Ruby on Rails conventions.

Relations to creator/updater user are omitted for readability.

Admin

User

Vocabulary-UserPermission

Vocabulary-ApiClientPermission

Vocabulary-GroupPermission

Vocabulary
public permissions

IoInterface

IoMapping

RDF-Class

RoleList

MetaKey

ContextKey

Person

Role

Keyword

Section

Context

PreviousID

PreviousID

ApiClient

Group (STI)
InstitutionalGroup

MD::Keyword

MD::Person

MetaDatum (STI table)

MD::Keywords

MD::Text

MD::People

MD::JSON

MD::MediaEntry

MD::TextDate

PreviousID

favorite -media_ entries / -collections

EditSession

XmpSidecar

MediaEntry- / Collection- / UserPermission

MediaEntry- / Collection- / ApiClientPermission

MediaEntry- / Collection- / GroupPermission

Lists of contexts for ordering purpose. No fkeys, pot. dead and broken refs.

section index

responsible

MediaEntry
public permissions

Collection
public permissions

AppSettings

responsible

Preview

MediaFile

UsageTerms

ZencoderJob

CollectionMediaEntryArc

CollectionCollectionArc

belongs to — has one

belongs to, not NULL — has many

exactly one out of many "belongs to" is present

conditional not NULL with custom constraint(s)

hbtm w. join table — cascade on delete is default

foreign keys are (almost) always set, custom checks and constraints via deferred triggers are used

likely to be removed

Table1 / Table2 /…