

OK. You've written a bot. It sort of seems to work. Now, before releasing it, you should polish it. There are a bunch of tools to do this.

Verification (:verify)

When I write a topic, before every rejoinder and every responder, I put a sample input comment. This has #! as a prefix. E.g.,

topic: ~mytopic (keyword)

t: This is my topic.

#! who cares

a: (who) I care.

#! do you love me

?: (do you love) Yes.

#! I hate food

*s: (I * ~hate * food) Too bad.*

This serves two functions. First, it makes it easy to read a topic-- you don't have to interpret pattern code to see what is intended. Second, it allows the system to verify your code in various ways. It is the “unit test” of a rule. If you've annotated your topics in this way, you can issue :verify commands.

Typically I start with proving the patterns work everywhere.

:verify pattern

Then I confirm keywords to access topics are OK.

:verify keyword

Then I verify rules don't block each other in a topic.

:verify blocking

Thereafter I can just do :verify to cover all of those. Then I do more exotic checks:

:verify sampletopic or :verify sample

will tell me if a sample would end up answered by some other topic. If I don't like the answer, then I need to fix that other topic's rule. Sampletopic just tells you if the rule was hijacked by a different topic. Sample tells you even if some other rule in the same topic hijacked you.

And I might do

:verify gambit

to see if the bot can answer questions it poses the user in gambits.

You can also verify individual topics in various ways. Here are more samples:

:verify – all topics, all ways but samples and gambits

:verify ~topicname - named topic, all ways but samples and gambits
:verify ~to* - all topics whose names start with ~to
:verify keyword - all topics doing keyword verification
:verify ~topic pattern - named topic, doing pattern verification
:verify blocking - all topics doing blocking verification
:verify sample - all topics doing sample verification
:verify gambit - all topics doing gambit verification
:verify all - all topics doing all verifications

Passing verification means that each topic is plausibly scripted. To be clear how valuable :verify is, consider this example. We authored a demo bot for a company and they added a bunch of code themselves. It was a 5500 rule bot. When I got around to verifying it, the results were: 57 keyword complaints, 92 pattern complaints, 45 blocking complaints, and (after fixing all those other complaints) 250 sampletopic complaints.

The :verify command takes the topic name first (and optional) and then a series of keywords about what to do.

:verify keyword

For responders, does the sample input have any keywords from the topic. If not, there may be an issue. Maybe the sample input has some obvious topic-related word in it, which should be added to the keywords list. Maybe it's a responder you only want matching if the user is in the current topic. E.g.,

#! Do you like swirl?

?: (swirl) I love raspberry swirl

can match inside an ice cream topic but you don't want it to react to *Does her dress swirl?*.

Or maybe the sample input has no keywords but you do want it findable from outside (E.g., an idiom), so you have to make it happen. When a responder fails this test, you have to either add a keyword to the topic, revise the sample input, add an idiom entry to send you to this topic, or tell the system to ignore keyword testing on that input.

You can suppress keyword testing by augmenting the comment on the sample input with !K or marking the topic as a whole TOPIC_NOKEYWORDS
 #!!K this is input that does not get keyword tested.

:verify pattern

For responders and rejoinders, the system takes the sample input and tests to see if the pattern of the following rule actually would match the given input. Failing to match means the rule is either not written correctly for what you want it to do or you wrote a bad sample input and need to change it. This test SHOULD NOT fail when you are done. Either your sample is bad, your pattern is bad, or ChatScript is bad.

Rules that need variables set certain ways can do variable assigns (\$) or _ at the end of

the comment. You can also have more than one verification input line before a rule.

```
#! I am male $gender = male  
#! I hate males $gender = male  
s: ($gender=male I * male) You are not my type
```

If you want to suppress testing, add !P to the comment.

```
#!!P This doesn't get pattern testing.
```

If the pattern absolutely SHOULD fail the test, use F. As in #!F or #!!FB.

If you want to suppress pattern and keyword testing, just use K and P in either order:

```
#!!KP this gets neither testing.
```

You can also test that the input does not match the pattern by using #!!R instead of #!, though unless you were writing engine diagnostic tests this would be worthless to you.

:verify blocking

Even if you can get into the topic from the outside and the pattern matches, perhaps some earlier rule in the topic can match and take control instead. This is called blocking. One normally tries to place more specific responders and rejoinders before more general ones.

The below illustrates blocking for *are your parents alive?* The sentence will match the first rule before it ever reaches the second one.

```
#! do you love your parents  
?: (<< you parent >>) I love my parents *** this rule triggers by mistake  
#! are your parents alive  
?: (<< you parent alive >>) They are still living
```

The above can be fixed by reordering, but sometimes the fix is to clarify the pattern of the earlier rule.

```
#! do you love your parents  
?: ( ![alive living dead] << you parent >>) I love my parents  
#! are your parents alive  
?: (<< you parent alive >>) They are still living
```

Sometimes you intend blocking to happen and you just tell the system not to worry about it using !B. Or you can have the entire topic ignored by the topic control

```
TOPIC NOBLOCKING.  
#! do you enjoy salmon?  
?: (<< you ~like salmon >>) I love salmon  
#!!B do you relish salmon?  
?: (<< you ~like salmon >>) I already told you I did.
```

The blocking test presumes you are within the topic and says nothing about whether the rule could be reached if you were outside the topic. That's the job of the keyword test.

And it only looks at you sample input. Interpreting your pattern can be way too difficult.

If `:trace` has been set non-zero, then tracing will be turned off during verification, but any rules that fail pattern verification will be immediately be rerun with tracing on so you can see why it failed.

:verify gambit

One principle we follow in designing our bots is that if a user is asked a question in a gambit, the bot had better be able to answer that same question if asked of it. The gambit verification will read all your gambits and if it asks a question, will ask that question of your bot. To pass, the answer must come from that topic or leave the bot with that topic as the current topic.

You can stop a topic doing this by adding the flag `TOPIC_NOGAMBITS`. There is no way to suppress an individual gambit, though clearly there are some questions that are almost rhetorical and won't require your bot answer them. E.g., *Did you know that hawks fly faster than a model airplane?*

:verify sampletopic & :verify sample

Once you've cleaned up all the other verifications, you get to sample verification.

It takes sample inputs of your responders and sees if the chatbot would end up at the corresponding rule if the user issued it from scratch. This means it would have to find the right topic and find the right rule. If it finds the right topic, it will usually pass if you have managed most of the blocking issues.

I start with `:verify sampletopic`, which only shows inputs that fail to reach the topic they came from. This is generally more serious. It may be perfectly acceptable that the input gets trapped in another topic. This sample result is merely advisory. But maybe the rule that trapped it should be moved into the tested topic. Or maybe its just fine. But if the output you got doesn't work for the input, you can go to the rule for the output you got and alter the pattern in some way that excludes it reacting inappropriately to the input.

Once that is cleaned up, `:verify sample` will include rules that fail to get back to the correct rule of the topic. Usually, if you've fixed blocking, this won't be a problem.

Changing tokenization

`:verify` normally works on the current `$cs_token` value. But in my bots, I might process inputs using two different values, one initially and one later. You can optionally specify what tokenization to be using by naming a user variable first.

:verify \$mytokencontrol ~mytopic pattern

Spelling

To insure the outputs don't have spelling errors, I do a :build like this:
 :build harry outputspell
and then fix any spelling complaints that should be fixed.

Sizing

We generally adhere to a tweet limit (140 characters) and run :abstract 140 to warn us of lines that are longer.

:topicinfo ~topic how

This displays all sorts of information about a topic including its keywords, how they overlap with other topics, what rules exist and whether they are erased or not. You either name the topic or you can just use ~, which means the current rejoinder topic (if there is one). You can also wildcard the name like ~co* to see all topics that start with ~co.

If how is omitted, you get everything. You can restrict things with a collection of how keywords. These include “keys”, to display the keywords, “overlap” to display the overlap with other topics' keywords, “gambits”, “rejoinders”, “responders” or “all” to limit rules to some of those, “used” and “available” to see only those rules meeting that criteria.

Of particular importance in finalization is the key overlap map. Keyword overlap is particularly interesting. As you assign keywords to topics, at times you will probably get excessive. Some topics will share keywords with other topics. For some things, this is reasonable. “quark” is a fine keyword for a topic on cheese and one on astronomy. But odds are “family” is not a great keyword for a topic on money. Often an extraneous keyword won't really matter, but if the system is looking for a topic to gambit based on “family”, you really don't want it distracted by a faulty reference to money. That is, you want to know what keywords are shared across topics and then you can decide if that's appropriate. Sometimes you are told a word but don't see it in the topic keywords. Use :up on that word to see how it intersects.

I use :topicinfo keys to generate a map across all topics. I then read the first column list of keywords for each topic to see if they obviously should be in that topic or if they don't really strongly imply that topic. If not, I try to remove them from it. Sometimes when I look at the list of topics that a key overlaps with, I find multiple topics with similar ideas. Like a topic called ~cars and one called ~automobiles. Often they are candidates for merging the topics.

:describe and :list

If you have used :describe to document all of your permanent variables (see advanced CS, :build), then :list can be used to show undocumented and potentially erroneously spelled permanent variables

`:list $ ^ ~ _ @`

will list the documented kinds of items (you name which ones you want, could be just \$) and for variables it will list be documented and undocumented.

:abstract

There are several useful :abstract calls to do during finalization.

:abstract 100 If you want to adjust output of yours that would be too long for something like a phone screen, you can ask :abstract to show you all rules whose output would

likely exceed some limit (here 100). Without a topic name it does the entire system. With a topic name e.g., `:abstract 100 ~topicname`, it is restricted to that topic. You can also use a wildcard like `~top*` to do all topics with `~top` at the start of the name. You can also provide a list of topics, like `:abstract ~topic1 ~topic2`.

:abstract censor ~mywords will note all output which contains any words in mywords. Of course regular uses may also appear. The censor command looks for any words referred to by the concept given.

:abstract spell will examine the outputs of all topics (or topic given) to find words whose spelling might be faulty. It's not a guarantee it is, but it can warn you about potential mistakes.

And `:abstract` is handy just to print out a human-readable copy of your bot, without all the ChatScript scripting mess. As part of that, you can add header comments that will appear in the abstract. These are done as:

```
#!/x whatever
I often subset gambits and responders in a topic by section, e.g.,
#!/x*** FAMILY COMPOSITION
...
#!/x*** FAMILY RELATIONSHIPS
...
```

:abstract story will display just topics and their gambits (+ rejoinders of them).

:abstract responder will display topics and their responders (+ rejoinders of them).

:permanentvariables

This gives you a list of all permanent variables found in your source. Not only is documenting them a good idea, but you might want to confirm they are all legit (correctly spelled) and reinitialized as appropriate.

Regression

Having built a functioning chatbot with lots of topics, I like to insure I don't damage old material in the future, so I create a regression test.

There are two ways to make a regression test (and you can have multiple tests). One is to create a source file with a bunch of questions. To be safe from most randomization effects, you should designate the user and `:reset` the bot. After doing a bunch of stuff you can do `:reset` again, so additional inputs are immune from effects of the prior stuff.

You can see an example of my std Rose regression file in

REGRESS/chatbotquestions/loebner.txt

It starts out like this:

```
:user test
:reset
# 2001 Chatterbox challenge
How is it going?
How old are you?
Are you male or female?
What is your favorite color?
Are you a bot?
What is the date?
...
:reset
```

and then has more questions and more :resets. Eventually it has a :quit before a bunch of stuff I'm not wanting tested at present.

The alternative way is to start a fresh conversation as a user and assuming it makes no mistakes then stop.

Now you can make a regression file by typing :regress init test (or whatever user name you used from either mechanism). CS reads your log file and converts it into

```
TMP/regress.txt
```

or you can do

```
:regress init user outputname
```

to name where it goes.

The user can be a full file name or just the name of a user whose log is in the USERS directory. The output name should be wherever you want to put the resulting regression file. If omitted it defaults to TMP/regress.txt .

Thereafter, all you have to do (not from a server version) is

```
:regress outputname
```

And the system will retest your conversation. I usually transfer the file over to a regression directory and rename it in there.

Regression will note any differences. Inconsequential differences it will merely tally at the end, more interesting differences which may or may not be correct show the alternative outputs and info, and differences CS thinks are major are flagged. If you use

```
:regress terse outputname
```

then the system will only note what it thinks are fatal differences.

If there are differences, maybe they are correct (you edited your code). But CS can detect where you merely edited the output, or a pattern, or a label, or added or subtracted rules nearby. So it is likely to tell you what you need to know.

The system will ask if you want to update your regression file, and if you answer "yes", it will rewrite the regression file with the updated test results. Do this if it detects minor differences so it can help stay on track in the future. Do this if the major differences are

in fact OK. Otherwise decline and go fix your code somewhere.