CSS Assignment Solutions

Flexbox, CSS Grid, Transforms and Animations - Questions 1 to 10

Contents

Question 1: Portfolio Page Using Flexbox
Question 2: 4-Column Product Gallery Using CSS Grid
Question 3: Three-Section Homepage Using Flexbox
Question 4: Dashboard Layout Using CSS Grid
Question 5: Pricing Section Using Flexbox
Question 6: Responsive Blog Layout Using CSS Grid
Question 7: CSS Loading Animation Using Only div Elements
Question 8: Photo Gallery Using Grid With Hover Zoom
Question 9: Card Flip Animation Using CSS 3D Transforms
Question 10: Responsive Layout Combining Flexbox and Grid

Each solution is a complete, single-file HTML page. Copy the code into an .html file and open it in a browser. Image URLs use picsum.photos placeholders and need an internet connection (replace them with your own images if you like).

Question 1: Portfolio Page Using Flexbox

Task: Header (name left, nav right), main with About Me + image side by side, centered footer, stack below 700px.

Key points

- Header uses display:flex with justify-content:space-between so the name sits left and links sit right.
- Main uses display:flex; align-items and justify-content center both sections vertically and horizontally.
- The media query switches flex-direction to column below 700px so everything stacks.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Portfolio</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body {
    font-family: Arial, sans-serif;
    min-height: 100vh;
    display: flex;
    flex-direction: column;
  }
  header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    padding: 20px 40px;
    background: #2c3e50;
    color: #fff;
  }
  header nav a {
    color: #fff;
    text-decoration: none;
    margin-left: 20px;
  }
  header nav a:hover { text-decoration: underline; }

  main {
    flex: 1;
    display: flex;
    justify-content: center;   /* horizontal centering */
    align-items: center;       /* vertical centering   */
    gap: 40px;
    padding: 40px;
  }
  .about, .image-section {
    flex: 1;
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    text-align: center;
  }
  .image-section img {
    max-width: 100%;
    border-radius: 12px;
  }
  footer {
    text-align: center;
    padding: 15px;
    background: #ecf0f1;
  }

  @media (max-width: 700px) {
    header, main { flex-direction: column; gap: 15px; }
    header nav a { margin: 0 10px; }
  }
</style>
</head>
<body>
```

```
  <header>
    <h2>Madhav Tiwari</h2>
    <nav>
      <a href="#">Home</a>
      <a href="#">About</a>
      <a href="#">Projects</a>
      <a href="#">Contact</a>
    </nav>
  </header>

  <main>
    <section class="about">
      <h2>About Me</h2>
      <p>I am a Computer Science student who enjoys building web
         applications and learning new technologies.</p>
    </section>
    <section class="image-section">
      <img src="https://picsum.photos/400/300" alt="Profile image">
    </section>
  </main>

  <footer>&copy; 2026 Madhav Tiwari. All rights reserved.</footer>
</body>
</html>
```

Question 2: 4-Column Product Gallery Using CSS Grid

Task: 8 product cards, 4 columns on desktop, 2 on tablet, 1 on mobile, hover scale, equal heights.

Key points

- grid-template-columns: repeat(4, 1fr) creates four equal columns; media queries reduce it to 2 and then 1.
- Grid items stretch by default, and grid-auto-rows: 1fr keeps every row the same height.
- Hover uses transform: scale(1.05) with transition: 0.3s for a smooth zoom.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Product Gallery</title>
<style>
  * { box-sizing: border-box; }
  body { font-family: Arial, sans-serif; margin: 0; padding: 30px; background: #f4f6f8; }
  h1 { text-align: center; }

  .gallery {
    display: grid;
    grid-template-columns: repeat(4, 1fr);   /* desktop */
    grid-auto-rows: 1fr;                     /* equal row heights */
    gap: 20px;
  }
  .card {
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    background: #fff;
    padding: 30px 15px;
    border-radius: 10px;
    box-shadow: 0 2px 8px rgba(0,0,0,0.12);
    text-align: center;
    transition: 0.3s;
  }
  .card:hover { transform: scale(1.05); }
  .price { color: #27ae60; font-weight: bold; }

  @media (max-width: 992px) {                /* tablet */
    .gallery { grid-template-columns: repeat(2, 1fr); }
  }
  @media (max-width: 600px) {                /* mobile */
    .gallery { grid-template-columns: 1fr; }
  }
</style>
</head>
<body>
  <h1>Our Products</h1>
  <div class="gallery">
    <div class="card"><h3>Product 1</h3><p class="price">$19.99</p></div>
    <div class="card"><h3>Product 2</h3><p class="price">$29.99</p></div>
    <div class="card"><h3>Product 3</h3><p class="price">$39.99</p></div>
    <div class="card"><h3>Product 4</h3><p class="price">$49.99</p></div>
    <div class="card"><h3>Product 5</h3><p class="price">$59.99</p></div>
    <div class="card"><h3>Product 6</h3><p class="price">$69.99</p></div>
    <div class="card"><h3>Product 7</h3><p class="price">$79.99</p></div>
    <div class="card"><h3>Product 8</h3><p class="price">$89.99</p></div>
  </div>
</body>
</html>
```

Question 3: Three-Section Homepage Using Flexbox

Task: Header with evenly spaced links, three boxes in main, rotate on hover, footer pinned to bottom.

Key points

- justify-content: space-around spaces the navigation links evenly.
- The body is a flex column with min-height:100vh and main has flex:1, which pushes the footer to the bottom.
- flex-wrap plus flex-basis keeps the three boxes balanced on any screen size.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Homepage</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body {
    font-family: Arial, sans-serif;
    min-height: 100vh;
    display: flex;
    flex-direction: column;
  }
  header {
    display: flex;
    justify-content: space-around;
    padding: 20px;
    background: #34495e;
  }
  header a { color: #fff; text-decoration: none; font-weight: bold; }

  main {
    flex: 1;                        /* fills space, footer stays at bottom */
    display: flex;
    flex-wrap: wrap;
    justify-content: center;
    align-items: center;
    gap: 25px;
    padding: 40px 20px;
  }
  .box {
    flex: 1 1 250px;
    max-width: 350px;
    min-height: 180px;
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    background: #3498db;
    color: #fff;
    border-radius: 10px;
    text-align: center;
    padding: 20px;
    transition: transform 0.3s;
  }
  .box:hover { transform: rotate(2deg); }

  footer {
    width: 100%;
    text-align: center;
    padding: 15px;
    background: #2c3e50;
    color: #fff;
  }
</style>
</head>
<body>
  <header>
    <a href="#">Home</a>
    <a href="#">Services</a>
    <a href="#">Projects</a>
    <a href="#">Contact</a>
  </header>
```

```
  <main>
    <div class="box"><h2>Services</h2><p>What we offer.</p></div>
    <div class="box"><h2>Projects</h2><p>Our recent work.</p></div>
    <div class="box"><h2>Contact</h2><p>Get in touch.</p></div>
  </main>

  <footer>&copy; 2026 My Website</footer>
</body>
</html>
```

Question 4: Dashboard Layout Using CSS Grid

Task: Full-width header, left sidebar, main area with 4 boxes (one spanning two columns), gap, fr units, hover scale + shadow.

Key points

- The page grid uses grid-template-areas: the header spans both columns and the sidebar takes a fixed left column.
- The content area is a 2-column grid of 4 boxes. Box 1 uses grid-column: span 2; Box 2 spans two rows so no empty cell is left.
- gap and fr units control spacing and widths; hover applies scale() and box-shadow.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Dashboard</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body { font-family: Arial, sans-serif; min-height: 100vh; }

  .dashboard {
    display: grid;
    grid-template-columns: 1fr 4fr;           /* sidebar : content */
    grid-template-rows: 70px 1fr;
    grid-template-areas:
      "header  header"
      "sidebar content";
    grid-gap: 15px;
    min-height: 100vh;
    padding: 15px;
    background: #ecf0f1;
  }
  .header {
    grid-area: header;
    background: #2c3e50;
    color: #fff;
    display: flex;
    align-items: center;
    padding: 0 20px;
    border-radius: 8px;
  }
  .sidebar {
    grid-area: sidebar;
    background: #34495e;
    border-radius: 8px;
    padding: 20px;
  }
  .sidebar ul { list-style: none; }
  .sidebar li { margin-bottom: 15px; }
  .sidebar a { color: #fff; text-decoration: none; }
  .sidebar a:hover { text-decoration: underline; }

  .content {
    grid-area: content;
    display: grid;
    grid-template-columns: 1fr 1fr;
    grid-gap: 15px;
  }
  .box {
    background: #fff;
    border-radius: 8px;
    padding: 25px;
    display: flex;
    justify-content: center;
    align-items: center;
    font-size: 1.2rem;
    transition: transform 0.3s, box-shadow 0.3s;
  }
  .box:hover {
```

```
    transform: scale(1.04);
    box-shadow: 0 8px 20px rgba(0,0,0,0.3);
  }
  .box1 { grid-column: span 2; background: #3498db; color: #fff; }
  .box2 { grid-row: span 2; }

  @media (max-width: 700px) {
    .dashboard {
      grid-template-columns: 1fr;
      grid-template-rows: auto;
      grid-template-areas: "header" "sidebar" "content";
    }
    .content { grid-template-columns: 1fr; }
    .box1, .box2 { grid-column: auto; grid-row: auto; }
  }
</style>
</head>
<body>
  <div class="dashboard">
    <header class="header"><h2>My Dashboard</h2></header>

    <aside class="sidebar">
      <ul>
        <li><a href="#">Overview</a></li>
        <li><a href="#">Analytics</a></li>
        <li><a href="#">Reports</a></li>
        <li><a href="#">Settings</a></li>
      </ul>
    </aside>

    <main class="content">
      <div class="box box1">Box 1 (spans 2 columns)</div>
      <div class="box box2">Box 2</div>
      <div class="box box3">Box 3</div>
      <div class="box box4">Box 4</div>
    </main>
  </div>
</body>
</html>
```

Question 5: Pricing Section Using Flexbox

Task: Three horizontal cards, bigger highlighted middle card, hover rise, fade-in with @keyframes, stack below 750px.

Key points

- The middle card is enlarged with transform: scale(1.08) and given a different background color.
- The hover rule keeps the scale and adds translateY(-10px) so the middle card still rises smoothly.
- @keyframes fadeIn animates only opacity, so it does not clash with the transform rules.
- Below 750px flex-direction becomes column and the cards stack.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Pricing</title>
<style>
  * { box-sizing: border-box; }
  body { font-family: Arial, sans-serif; margin: 0; padding: 40px 20px; background: #f4f6f8; }
  h1 { text-align: center; margin-bottom: 40px; }

  .pricing {
    display: flex;
    justify-content: center;
    align-items: center;
    gap: 30px;
  }
  .plan {
    width: 280px;
    background: #fff;
    padding: 35px 25px;
    text-align: center;
    border-radius: 12px;
    box-shadow: 0 3px 10px rgba(0,0,0,0.15);
    transition: transform 0.3s ease, box-shadow 0.3s ease;
    animation: fadeIn 1.2s ease-in;
  }
  .plan:hover {
    transform: translateY(-10px);
    box-shadow: 0 12px 25px rgba(0,0,0,0.25);
  }
  .plan h2 { margin-top: 0; }
  .price { font-size: 2rem; font-weight: bold; margin: 15px 0; }
  .plan ul { list-style: none; padding: 0; line-height: 2; }
  .plan button {
    padding: 10px 25px;
    border: none;
    border-radius: 6px;
    background: #3498db;
    color: #fff;
    cursor: pointer;
  }

  .featured {                          /* middle card */
    background: #2c3e50;
    color: #fff;
    transform: scale(1.08);
    padding: 45px 25px;
  }
  .featured:hover { transform: scale(1.08) translateY(-10px); }
  .featured button { background: #f1c40f; color: #000; }

  @keyframes fadeIn {
    from { opacity: 0; }
    to   { opacity: 1; }
  }

  @media (max-width: 750px) {
    .pricing { flex-direction: column; }
    .featured { transform: none; }
    .featured:hover { transform: translateY(-10px); }
```

```
  }
</style>
</head>
<body>
  <h1>Choose Your Plan</h1>
  <section class="pricing">
    <div class="plan">
      <h2>Basic</h2>
      <p class="price">$9</p>
      <ul><li>1 Project</li><li>5 GB Storage</li><li>Email Support</li></ul>
      <button>Select</button>
    </div>
    <div class="plan featured">
      <h2>Pro</h2>
      <p class="price">$29</p>
      <ul><li>10 Projects</li><li>50 GB Storage</li><li>Priority Support</li></ul>
      <button>Select</button>
    </div>
    <div class="plan">
      <h2>Premium</h2>
      <p class="price">$59</p>
      <ul><li>Unlimited Projects</li><li>500 GB Storage</li><li>24/7 Support</li></ul>
      <button>Select</button>
    </div>
  </section>
</body>
</html>
```

Question 6: Responsive Blog Layout Using CSS Grid

Task: Header, left sidebar with categories, two posts side by side, footer, grid-template-areas, sidebar below main under 800px.

Key points

- grid-template-areas names the header, sidebar, main and footer regions so the layout reads like a map.
- Under 800px the areas are redefined so the sidebar comes after main.
- gap, padding and margin provide even spacing; the posts sit in their own 2-column grid.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Blog</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body { font-family: Arial, sans-serif; background: #f4f6f8; }

  .container {
    display: grid;
    grid-template-columns: 250px 1fr;
    grid-template-areas:
      "header  header"
      "sidebar main"
      "footer  footer";
    gap: 20px;
    padding: 20px;
    min-height: 100vh;
    grid-template-rows: auto 1fr auto;
  }
  header {
    grid-area: header;
    display: flex;
    justify-content: space-between;
    align-items: center;
    background: #2c3e50;
    color: #fff;
    padding: 20px;
    border-radius: 8px;
  }
  header a { color: #fff; margin-left: 15px; text-decoration: none; }

  aside {
    grid-area: sidebar;
    background: #fff;
    padding: 20px;
    border-radius: 8px;
  }
  aside h3 { margin-bottom: 10px; }
  aside li { margin: 8px 0 8px 18px; }

  main {
    grid-area: main;
    display: grid;
    grid-template-columns: 1fr 1fr;      /* two posts side by side */
    gap: 20px;
    align-content: start;
  }
  article {
    background: #fff;
    padding: 20px;
    border-radius: 8px;
  }
  article h2 { margin-bottom: 10px; }

  footer {
    grid-area: footer;
    background: #34495e;
    color: #fff;
    text-align: center;
```

```
    padding: 15px;
    border-radius: 8px;
  }

  @media (max-width: 800px) {
    .container {
      grid-template-columns: 1fr;
      grid-template-areas:
        "header"
        "main"
        "sidebar"
        "footer";
    }
    main { grid-template-columns: 1fr; }
  }
</style>
</head>
<body>
  <div class="container">
    <header>
      <h1>My Blog</h1>
      <nav><a href="#">Home</a><a href="#">Posts</a><a href="#">About</a></nav>
    </header>

    <aside>
      <h3>Categories</h3>
      <ul><li>Technology</li><li>Travel</li><li>Food</li><li>Lifestyle</li></ul>
    </aside>

    <main>
      <article>
        <h2>First Blog Post</h2>
        <p>Short summary of the first post goes here.</p>
      </article>
      <article>
        <h2>Second Blog Post</h2>
        <p>Short summary of the second post goes here.</p>
      </article>
    </main>

    <footer>Contact: info@myblog.com | +91 98765 43210</footer>
  </div>
</body>
</html>
```

Question 7: CSS Loading Animation Using Only div Elements

Task: Three circles bouncing up and down, staggered delays, centered with Flexbox, infinite animation.

Key points

- @keyframes bounce moves each circle with transform: translateY().
- animation-iteration-count: infinite repeats the motion forever.
- animation-delay of 0s, 0.2s and 0.4s starts the circles one after another to create the wave effect.
- The loader is centered both ways using a flex container that fills the viewport.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Loader</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body {
    height: 100vh;
    display: flex;
    justify-content: center;
    align-items: center;
    background: #1e272e;
  }
  .loader {
    display: flex;
    gap: 12px;
  }
  .circle {
    width: 20px;
    height: 20px;
    border-radius: 50%;
    background: #00d2d3;
    animation-name: bounce;
    animation-duration: 0.8s;
    animation-timing-function: ease-in-out;
    animation-iteration-count: infinite;
  }
  .circle:nth-child(2) { animation-delay: 0.2s; }
  .circle:nth-child(3) { animation-delay: 0.4s; }

  @keyframes bounce {
    0%, 100% { transform: translateY(0); }
    50%      { transform: translateY(-25px); }
  }
</style>
</head>
<body>
  <div class="loader">
    <div class="circle"></div>
    <div class="circle"></div>
    <div class="circle"></div>
  </div>
</body>
</html>
```

Question 8: Photo Gallery Using Grid With Hover Zoom

Task: auto-fit/minmax grid, images fill cells, zoom on hover, figcaption below each image, auto-adjusting layout.

Key points

- repeat(auto-fit, minmax(200px, 1fr)) lets the browser decide how many columns fit, so no media queries are needed.
- width:100%, height:100% and object-fit: cover make each image fill its cell completely.
- transition: transform 0.5s ease with scale(1.1) on hover; overflow:hidden on the wrapper keeps the zoom inside the cell.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Photo Gallery</title>
<style>
  * { box-sizing: border-box; }
  body { font-family: Arial, sans-serif; margin: 0; padding: 30px; background: #f4f6f8; }
  h1 { text-align: center; }

  .gallery {
    display: grid;
    grid-template-columns: repeat(auto-fit, minmax(200px, 1fr));
    gap: 20px;
  }
  figure { margin: 0; }
  .img-box {
    height: 200px;
    overflow: hidden;              /* keeps zoom inside the cell */
    border-radius: 8px;
  }
  .img-box img {
    width: 100%;
    height: 100%;
    object-fit: cover;             /* image fills the cell completely */
    display: block;
    transition: transform 0.5s ease;
  }
  .img-box img:hover { transform: scale(1.1); }
  figcaption {
    text-align: center;
    margin-top: 8px;
    color: #555;
  }
</style>
</head>
<body>
  <h1>Photo Gallery</h1>
  <div class="gallery">
    <figure>
      <div class="img-box"><img src="https://picsum.photos/id/11/400/300" alt="Photo 1"></div>
      <figcaption>Caption for photo 1</figcaption>
    </figure>
    <figure>
      <div class="img-box"><img src="https://picsum.photos/id/12/400/300" alt="Photo 2"></div>
      <figcaption>Caption for photo 2</figcaption>
    </figure>
    <figure>
      <div class="img-box"><img src="https://picsum.photos/id/13/400/300" alt="Photo 3"></div>
      <figcaption>Caption for photo 3</figcaption>
    </figure>
    <figure>
      <div class="img-box"><img src="https://picsum.photos/id/14/400/300" alt="Photo 4"></div>
      <figcaption>Caption for photo 4</figcaption>
    </figure>
    <figure>
      <div class="img-box"><img src="https://picsum.photos/id/15/400/300" alt="Photo 5"></div>
      <figcaption>Caption for photo 5</figcaption>
    </figure>
    <figure>
```

```
      <div class="img-box"><img src="https://picsum.photos/id/16/400/300" alt="Photo 6"></div>
      <figcaption>Caption for photo 6</figcaption>
    </figure>
  </div>
</body>
</html>
```

Question 9: Card Flip Animation Using CSS 3D Transforms

Task: One card flips 180 degrees on hover; front has title + image, back has text; perspective 1000px; centered with Flexbox.

Key points

- perspective: 1000px on the wrapper gives the 3D depth; transform-style: preserve-3d on the inner card keeps both faces in 3D space.
- Both faces are positioned absolutely and use backface-visibility: hidden so only one side is visible at a time.
- The back face is pre-rotated with rotateY(180deg); on hover the inner card rotates rotateY(180deg) with a 0.8s transition.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Flip Card</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body {
    height: 100vh;
    display: flex;
    justify-content: center;
    align-items: center;
    background: #dfe6e9;
    font-family: Arial, sans-serif;
  }
  .card {
    width: 300px;
    height: 380px;
    perspective: 1000px;
  }
  .card-inner {
    position: relative;
    width: 100%;
    height: 100%;
    transform-style: preserve-3d;
    transition: transform 0.8s;
  }
  .card:hover .card-inner { transform: rotateY(180deg); }

  .front, .back {
    position: absolute;
    width: 100%;
    height: 100%;
    backface-visibility: hidden;
    -webkit-backface-visibility: hidden;
    border-radius: 12px;
    box-shadow: 0 6px 18px rgba(0,0,0,0.25);
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    padding: 20px;
    text-align: center;
  }
  .front { background: #fff; }
  .front img {
    width: 100%;
    height: 240px;
    object-fit: cover;
    border-radius: 8px;
    margin-top: 15px;
  }
  .back {
    background: #2d3436;
    color: #fff;
    transform: rotateY(180deg);
  }
</style>
```

```
</head>
<body>
  <div class="card">
    <div class="card-inner">
      <div class="front">
        <h2>Mountain View</h2>
        <img src="https://picsum.photos/300/240" alt="Mountain">
      </div>
      <div class="back">
        <h2>About</h2>
        <p>A peaceful mountain landscape perfect for relaxing and
           enjoying nature away from the busy city life.</p>
      </div>
    </div>
  </div>
</body>
</html>
```

Question 10: Responsive Layout Combining Flexbox and Grid

Task: Flex header, 2-column Grid (article + sidebar), full-width footer, three flex boxes in article, @keyframes title animation, single column on mobile.

Key points

- Flexbox handles one-dimensional rows (header and the three boxes); Grid handles the two-dimensional page structure.
- main uses grid-template-columns: 3fr 1fr for Article + Sidebar and collapses to 1fr on mobile.
- The article title uses a @keyframes slideUp animation that fades in while moving up.

Solution (HTML + CSS)

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Flexbox + Grid Layout</title>
<style>
  * { margin: 0; padding: 0; box-sizing: border-box; }
  body {
    font-family: Arial, sans-serif;
    min-height: 100vh;
    display: flex;
    flex-direction: column;
    background: #f4f6f8;
  }
  /* Header: Flexbox */
  header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    padding: 20px 40px;
    background: #2c3e50;
    color: #fff;
  }
  .logo { font-size: 1.5rem; font-weight: bold; }
  header nav a { color: #fff; text-decoration: none; margin-left: 20px; }

  /* Main: Grid (Article + Sidebar) */
  main {
    flex: 1;
    display: grid;
    grid-template-columns: 3fr 1fr;
    gap: 20px;
    padding: 20px;
  }
  article, aside {
    background: #fff;
    padding: 20px;
    border-radius: 8px;
  }
  /* Title animation */
  article h1 {
    margin-bottom: 20px;
    animation: slideUp 1s ease-out;
  }
  @keyframes slideUp {
    from { opacity: 0; transform: translateY(30px); }
    to   { opacity: 1; transform: translateY(0); }
  }
  /* Three boxes inside article: Flexbox */
  .boxes {
    display: flex;
    gap: 15px;
  }
  .boxes .box {
    flex: 1;
    padding: 30px 15px;
    text-align: center;
    background: #3498db;
    color: #fff;
    border-radius: 8px;
```

```
  }
  /* Footer */
  footer {
    width: 100%;
    text-align: center;
    padding: 15px;
    background: #34495e;
    color: #fff;
  }
  /* Mobile: single column */
  @media (max-width: 768px) {
    main { grid-template-columns: 1fr; }
    .boxes { flex-direction: column; }
    header { flex-direction: column; gap: 10px; }
    header nav a { margin: 0 8px; }
  }
</style>
</head>
<body>
  <header>
    <div class="logo">MyLogo</div>
    <nav><a href="#">Home</a><a href="#">Blog</a><a href="#">Contact</a></nav>
  </header>

  <main>
    <article>
      <h1>Welcome to Our Website</h1>
      <p style="margin-bottom:20px">Main article content goes here.</p>
      <div class="boxes">
        <div class="box">Box 1</div>
        <div class="box">Box 2</div>
        <div class="box">Box 3</div>
      </div>
    </article>
    <aside>
      <h3>Sidebar</h3>
      <p>Links, ads or extra information.</p>
    </aside>
  </main>

  <footer>&copy; 2026 My Website. All rights reserved.</footer>
</body>
</html>
```