

Pramo Jewels

Error Response Standards

Document ID: PJ-ERR-001

Version: 1.0

Status: Approved for Development

Field	Value
Project	Pramo Jewels Premium E-Commerce Platform
Purpose	Define standardized API error responses and error handling conventions
Audience	Backend Developers, Frontend Developers, Mobile Developers, QA
Version	1.0

Standard Error Codes

HTTP	Application Code	Meaning	Client Action
400	BAD_REQUEST	Malformed request	Correct request payload
401	UNAUTHORIZED	Authentication required	Login again / provide token
403	FORBIDDEN	Insufficient permissions	Request proper access
404	NOT_FOUND	Requested resource missing	Verify identifier
409	CONFLICT	Duplicate/conflicting resource	Resolve conflict
422	VALIDATION_ERROR	Input validation failed	Correct invalid fields
429	RATE_LIMITED	Too many requests	Retry after delay
500	INTERNAL_ERROR	Unexpected server error	Retry later / contact support
503	SERVICE_UNAVAILABLE	Temporary outage	Retry after maintenance

JSON Error Format

All API errors should return: success: false message: Human-readable summary error.code: Machine-readable code error.details: Validation or contextual details request_id: Correlation identifier for support

Validation Errors

Return field-level validation messages keyed by field name. Avoid exposing implementation details.

Security

Never expose stack traces, SQL queries, secrets, internal file paths or sensitive user information in API responses.

Logging

Log full server-side exceptions with correlation IDs, user ID (when available), endpoint, IP address and timestamp.

Localization

Keep error codes stable while allowing user-facing messages to be translated into multiple languages.

Retry Guidance

Include Retry-After headers for rate limiting and maintenance windows where applicable.

Consistency

All services, webhooks and admin APIs must follow the same response structure and naming conventions.