

SIMATS ENGINEERING

ASSESSMENT TOOL 1

COURSE CODE: CSA14

COURSE NAME: COMPILER DESIGN

COURSE OUTCOME COVERED

CO3: *Analyze syntax-directed translation method using synthesized and inherited attributes to generate a Parser Tree. (BL4)*

Assessment Tool Weightage: 40%

QUESTIONS:5

Total Marks:100

Annexure A

EXPERIMENTS

Code of Conduct:

*I _____ (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.
I understand that any violation of academic integrity rules will result in disciplinary action.*

Signature of the student:

Annexure A

EXPERIMENTS

Q1. You are developing a compiler-based desk calculator that evaluates arithmetic expressions using syntax-directed definitions (SDD).

The system should:

- (i) Accept an arithmetic expression with operators +, -, *, / and parentheses
- (ii) Use syntax-directed evaluation to compute values based on operator precedence
- (iii) Optimize evaluation by reducing unnecessary temporary computations
- (iv) Display the final result of the expression

Demonstrate how SDD rules (synthesized attributes) are used for expression evaluation.

SDD

Grammar with semantic rules:

$E \rightarrow E + T$	$\{ E.val = E1.val + T.val \}$
$E \rightarrow E - T$	$\{ E.val = E1.val - T.val \}$
$E \rightarrow T$	$\{ E.val = T.val \}$
$T \rightarrow T * F$	$\{ T.val = T1.val * F.val \}$
$T \rightarrow T / F$	$\{ T.val = T1.val / F.val \}$
$T \rightarrow F$	$\{ T.val = F.val \}$
$F \rightarrow (E)$	$\{ F.val = E.val \}$
$F \rightarrow digit$	$\{ F.val = digit \}$


```
C:\Users\ACER\OneDrive\Documents\cm1.cpp - [Executing] - Dev-C++ 5.11
File Edit Search View Project Execute Tools AStyle Window Help
Project
Enter arithmetic expression: 2*4+5
Final Result = 13

-----
Process exited after 101.7 seconds with return value 0
Press any key to continue . . . |
```

Q2. In a compiler, postfix expressions are evaluated during code generation using stack-based bottom-up evaluation.

Write a C program that:

- (i) Evaluates a postfix expression
- (ii) Demonstrates S-attributed definition evaluation
- (iii) Shows how intermediate results are computed



```
Enter postfix expression: 25+
Push 2
Push 5
2 + 5 = 7
Final Result = 7

-----
Process exited after 8.309 seconds with return value 0
Press any key to continue . . .
```

Q3. You are designing a parser that uses L-attributed definitions, where inherited attributes are passed from parent to child.

Write a C program that:

- (i). Evaluates a simple expression like $a + b * c$
- (ii) Uses function parameters to simulate inherited attributes
- (iii). Ensures correct precedence handling
- (iv). Demonstrates top-down evaluation logic

Explain how inherited attributes influence computation.

```
C:\Users\ACER\OneDrive\Documents\cm1.cpp - [Executing] - Dev-C++ 5.11  
C:\Users\ACER\OneDrive\Doc  
Expression: a + b * c  
a = 2  
b = 3  
c = 4  
Result = 14  
  
-----  
Process exited after 0.08261 seconds with return value 0  
Press any key to continue . . . |  
  
Line: 56 Col: 2 Sel: 0 Lines: 56 Length: 883 Insert Done parsing in 0.032 seconds  
14:27 10/08/2026
```

Q4. In a compiler, it is important to check whether two type expressions are equivalent.

Write a C program that:

(i). Accepts two type expressions (e.g., `int`, `float`, `int*`)

(ii). Compares them for **type equivalence**

(iii). Displays whether they are:

(a). Equivalent

(b). Not equivalent

Extend the logic to handle pointer types (`int*`, `float*`).

```
C:\Users\ACER\OneDrive\Documents\cm1.cpp - [Executing] - Dev-C++ 5.11
File Edit Search View Project Execute Tools AStyle Window Help
(globals) IDB-GCC 4.9.2 64-bit Release
Project Classes
C:\Users\ACER\OneDrive\Doc x + v
Enter first type: int
Enter second type: int
Equivalent

-----
Process exited after 10.86 seconds with return value 0
Press any key to continue . . . |
Line: 59
```

Q5. You are building a semantic analyzer that detects type errors in arithmetic expressions.

Write a C program that:

- (i). Accepts two operands and their types
- (ii). Checks whether the operation (e.g., +, *) is valid
- (iii). Reports:
 - (a). Valid expression
 - (b). Type error (e.g., `int + char*`)

Demonstrate how compilers detect semantic errors during type checking

```

C:\Users\ACER\OneDrive\Documents\cm1.cpp - [Executing] - Dev-C++ 5.11
Enter first operand type: int
Enter operator (+, -, *, /):
+
Enter second operand type: +
Expression: int + +
Type error

-----
Process exited after 27.15 seconds with return value 0
Press any key to continue . . .

```

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25	Demonstrates thorough understanding and effectively integrates multiple concepts/technologies	Good understanding with proper integration of most concepts	Basic understanding; limited or partial integration	Poor understanding; unable to integrate concepts
Experimental Design	30	Well-planned, systematic implementation with optimal solution	Correct implementation with minor issues	Basic implementation with errors or inefficiencies	Incorrect or incomplete implementation
Use of Tools	20	Effective and advanced use of tools/technologies with proper configuration	Appropriate use of tools with correct execution	Limited or inconsistent use of tools	Incorrect or minimal use of tools
Analysis of Results	15	Insightful analysis with accurate interpretation and validation of results	Good analysis with reasonable interpretation	Basic analysis with limited insights	Poor or incorrect analysis of results
Documentation	10	Clear, well-structured documentation with diagrams, code, and results	Organized documentation with necessary details	Basic documentation with missing details	Poor or incomplete documentation

