

Ex No: 2 BUILD A SIMPLE NEURAL NETWORKS

Aim:

To build a simple neural network using Keras/TensorFlow.

Procedure:

1. Download and load the dataset.
2. Perform analysis and preprocessing of the dataset.
3. Build a simple neural network model using Keras/TensorFlow.
4. Compile and fit the model.
5. Perform prediction with the test dataset.
6. Calculate performance metrics.

Program:

```
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_score, confusion_matrix
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense
import pandas as pd
dataset = pd.read_csv('diabetes.csv')
X = dataset.iloc[:, 0:8].values
y = dataset.iloc[:, 8].values
model = Sequential()
model.add(Dense(12, input_shape=(8,), activation='relu'))
model.add(Dense(8, activation='relu'))
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_score, confusion_matrix
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense
import pandas as pd
dataset = pd.read_csv('diabetes.csv')
X = dataset.iloc[:, 0:8].values
y = dataset.iloc[:, 8].values
model = Sequential()
model.add(Dense(12, input_shape=(8,), activation='relu'))
model.add(Dense(8, activation='relu'))
model.add(Dense(1, activation='sigmoid'))
model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])
model.fit(X, y, epochs=150, batch_size=10, verbose=0)
predictions = (model.predict(X) > 0.5).astype(int)
for i in range(5):
    print('%s => %d (expected %d)' % (X[i].tolist(), predictions[i], y[i]))
accuracy = accuracy_score(y, predictions)
precision = precision_score(y, predictions)
recall = recall_score(y, predictions)
f1 = f1_score(y, predictions)
conf_matrix = confusion_matrix(y, predictions)
print(f'Accuracy: {accuracy:.2f}')
print(f'Precision: {precision:.2f}')
print(f'Recall: {recall:.2f}')
print(f'F1 Score: {f1:.2f}')
print(f'Confusion Matrix:\n{conf_matrix}')
model.add(Dense(1, activation='sigmoid'))
```

```

model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])
model.fit(X, y, epochs=150, batch_size=10, verbose=0)
predictions = (model.predict(X) > 0.5).astype(int)
for i in range(5):
    print('%s => %d (expected %d)' % (X[i].tolist(), predictions[i], y[i]))
accuracy = accuracy_score(y, predictions)
precision = precision_score(y, predictions)
recall = recall_score(y, predictions)
f1 = f1_score(y, predictions)
conf_matrix = confusion_matrix(y, predictions)
print(f'Accuracy: {accuracy:.2f}')
print(f'Precision: {precision:.2f}')
print(f'Recall: {recall:.2f}')
print(f'F1 Score: {f1:.2f}')
print(f'Confusion Matrix:\n{conf_matrix}')

```

Output:

```

[6.0, 148.0, 72.0, 35.0, 0.0, 33.6, 0.627, 50.0] => 1 (expected 1)
[1.0, 85.0, 66.0, 29.0, 0.0, 26.6, 0.351, 31.0] => 0 (expected 0)
[8.0, 183.0, 64.0, 0.0, 0.0, 23.3, 0.672, 32.0] => 1 (expected 1)
[1.0, 89.0, 66.0, 23.0, 94.0, 28.1, 0.167, 21.0] => 0 (expected 0)
[0.0, 137.0, 40.0, 35.0, 168.0, 43.1, 2.288, 33.0] => 0 (expected 1)
Accuracy: 0.77
Precision: 0.74
Recall: 0.51
F1 Score: 0.60
Confusion Matrix:
[[451  49]
 [131 137]]

```

Result:

Thus the program for building a simple neural network was executed successfully.