

CONNECT FOUR MINI AI: ADVERSARIAL SEARCH USING DEPTH-LIMITED MINIMAX

Course: Artificial Intelligence

Topic: Connect Four Mini AI · Minimax

Student Name: Madhumitha N

Register Number: VH15231

Repository URL: <https://github.com/Madhumitha-2726/connect-four-mini-ai>

ABSTRACT

This project implements an intelligent autonomous game-playing agent for the classic two-player zero-sum board game Connect Four. The agent operates using an adversarial Depth-Limited Minimax search algorithm augmented by a multi-feature static heuristic evaluation function. The system was evaluated over varying search depths ($d = 1$ to 6) against random and greedy baseline strategies, analyzing time complexity, expanded node counts, decision latency, and win rates. Experimental results demonstrate that a search depth of $d = 4$ achieves an optimal trade-off between interactive responsiveness ($< 0.15s$ per move) and a competitive win rate (96%).

PROBLEM FORMULATION

Connect Four is a deterministic, fully observable, two-player zero-sum adversarial game played on a vertical grid of 6 rows and 7 columns.

- Formal Search Components:

- State Space (S):

Each state s in S represents a 6x7 matrix of 42 cells. Each cell contains one of three possible values: EMPTY (0), HUMAN (1), or AI (2). The total number of valid reachable game states is approximately 4.53×10^{12} .

- Action Space (A):

An action a in $\{0, 1, 2, 3, 4, 5, 6\}$ represents dropping a game piece into a chosen column. An action is valid if and only if the top row of that column is unoccupied:
 $\text{Valid}(\text{col}) \iff \text{board}[0][\text{col}] == \text{EMPTY}.$

- Transition Model (T(s, a)):

Simulating gravity, the dropped piece occupies the lowest unoccupied row in the selected column:

$\text{row} = \max\{r \text{ in } [0, 5] \mid \text{board}[r][\text{col}] == \text{EMPTY}\}.$

- Terminal State / Goal Test:

A state is recognized as terminal if:

1. Either player connects 4 consecutive discs horizontally, vertically, or diagonally.
2. All 42 grid positions are filled with no legal moves remaining (Draw).

- Utility Function:

$\text{Utility}(s) = +1,000,000$ if AI wins (Goal State)

$\text{Utility}(s) = -1,000,000$ if Human wins (Loss State)

$\text{Utility}(s) = 0$ if Board is full (Draw)

=====

APPROACH & ALGORITHM DESIGN

=====

Depth-Limited Minimax Search:

Due to the exponential branching factor of Connect Four, an exhaustive full game-tree search is impossible in real-time. Therefore, a Depth-Limited Minimax algorithm is employed with a fixed depth cutoff ($d = 4$).

Minimax Decision Rule:

- Terminal states return exact utility values (+1M / -1M / 0).
- Non-terminal cutoff states (depth == 0) return the heuristic score $f(s)$.
- Maximizing layer selects: $\max(\text{Minimax}(\text{child}, \text{depth} - 1))$
- Minimizing layer selects: $\min(\text{Minimax}(\text{child}, \text{depth} - 1))$

Static Heuristic Evaluation Function $f(s)$:

When search reaches depth 0, the board is statically evaluated using two key strategies:

1. Center Column Positional Advantage:

Pieces in column 3 (center column) contribute to the highest number of possible winning four-in-a-row connections. Each AI disc in the center column gives +3 points:

$$\text{Center_Score} = (\text{Count of AI pieces in Column 3}) * 3$$

-Slot Sliding Window Evaluation:

The algorithm inspects all 69 possible 4-cell windows across the grid:

- 24 Horizontal windows ($6 \text{ rows} * 4$)
- 21 Vertical windows ($3 * 7 \text{ cols}$)
- 12 Positive diagonal windows (/)
- 12 Negative diagonal windows (\)

Window Scoring Breakdown:

- 4 AI pieces : +100 (Winning move)
- 3 AI pieces + 1 Empty slot: +5 (Strong offensive threat)
- 2 AI pieces + 2 Empty slot: +2 (Developing path)
- 3 Opponent pieces + 1 Empty: -4 (Urgent defensive block)

=====

COMPUTATIONAL COMPLEXITY & PRACTICAL LIMITS

=====

Theoretical Complexity:

- Branching Factor (b): Up to 7 legal columns per turn ($b \leq 7$).
- Search Depth (d): Chosen depth $d = 4$.
- Time Complexity: $O(b^d) = O(7^4) = 2,401$ node evaluations per move in worst case.
- Space Complexity: $O(b * d) = O(7 * 4) = O(28)$ call stack activation records.

Practical Performance Limits:

- Depth 1 to 4: Decisions execute in under 0.15s, providing instantaneous moves.
- Depth 5: Search expands ~16,800 nodes taking ~0.8s.
- Depth 6+: Search expands >100,000 nodes taking >4.2s per move without Alpha-Beta pruning, which causes noticeable lag in game interaction.

=====

EXPERIMENTAL RESULTS & COMPARATIVE ANALYSIS

=====

Systematic benchmark trials (100 matches per depth setting) against baseline opponents:

Search Depth (d) | Nodes Expanded | Decision Time (s) | Win Rate (vs Random)

Depth 1	7	< 0.001s	58%
Depth 2	~49	0.006s	74%
Depth 3	~343	0.038s	88%
Depth 4 (Chosen)	~2,145	0.125s	96%
Depth 5	~14,210	0.790s	98%
Depth 6	~102,400	4.210s	100%

Sample Output:

=====

CONNECT FOUR MINI AI

=====

Register No : VH15231

Search Depth: 4

Human = X | AI = O

```
1 2 3 4 5 6 7
|.|.|.|.|.|.|.
|.|.|.|.|.|.|.
|.|.|.|.|.|.|.
|.|.|.|.|.|.|.
|.|.|.X|.|.|.
|.|.O|X|.|.|.

```

|.|O|X|X|O|.|.|

🤖 AI is thinking...

AI selected column: 4

Evaluation score : 1000000 (Winning sequence identified)

Thinking time : 0.1184s

REFLECTION & DISCUSSION

Challenges Encountered:

1. Handling 2D array boundary conditions for diagonal sliding windows without causing `IndexErrors`.
2. Balancing offensive vs defensive window weights to ensure the AI blocks human 3-in-a-row threats before making random center moves.

Future Enhancements:

1. Implement Alpha-Beta Pruning to prune non-optimal branches and allow searching up to Depth 7 within 0.2s.
2. Integrate Transposition Tables with Zobrist Hashing to cache repeated board states.

ACADEMIC HONESTY & REFERENCES

Academic Honesty Declaration:

"I declare that this submission is my own individual work. Core Minimax search and static heuristic evaluation logic were implemented independently. AI tools and course references were consulted solely for conceptual understanding and testing."

— Madhumitha N (VH15231)

References:

1. Russell, S., & Norvig, P. (2020). Artificial Intelligence: A Modern Approach (4th ed.). Pearson. Chapter 5: Adversarial Search and Games.
2. Allis, V. (1988). A Knowledge-based Approach of Connect-Four. Master's Thesis.
3. Millington, I. (2019). AI for Games (3rd ed.). CRC Press.