



Power your data-driven apps.  
Get started >



Run >

```
<!DOCTYPE html>
<html>
<head>
<title>Page Title</title>
</head>
<body>

<h1>This is a Heading</h1>
<p>This is a paragraph.</p>

</body>
</html><!DOCTYPE html>
<html>
<head>
  <title>Three Tabs using Flask</title>
  <link
```

# This is a Heading

This is a paragraph.

## Flask App with Three Tabs

Tab 1

Tab 2

Tab 3

### Content for Tab 1

This is the first tab.



Power your data-driven apps.  
Get started >



Run >

```
<link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>
<div class="container mt-5">
  <h2 class="mb-4">Flask App with Three
  Tabs</h2>
  <ul class="nav nav-tabs" id="myTab"
  role="tablist">
    <li class="nav-item"
    role="presentation">
      <button class="nav-link
  active" id="tab1-tab" data-bs-
  toggle="tab" data-bs-target="#tab1"
  href="#tab1" type="button" data-bs-toggle="tab">Tab 1</li>
    <li class="nav-item"
    role="presentation">
      <button class="nav-link" id="tab2-tab" data-bs-
  toggle="tab" data-bs-target="#tab2"
  href="#tab2" type="button" data-bs-toggle="tab">Tab 2</li>
    <li class="nav-item"
    role="presentation">
      <button class="nav-link" id="tab3-tab" data-bs-
  toggle="tab" data-bs-target="#tab3"
  href="#tab3" type="button" data-bs-toggle="tab">Tab 3</li>
  </ul>
  <div class="tab-content">
    <div class="tab-pane active" id="tab1">
      <h3>Content for Tab 1</h3>
      <p>This is the first tab.</p>
    </div>
    <div class="tab-pane" id="tab2">
      <h3>Content for Tab 2</h3>
      <p>This is the second tab.</p>
    </div>
    <div class="tab-pane" id="tab3">
      <h3>Content for Tab 3</h3>
      <p>This is the third tab.</p>
    </div>
  </div>
</div>
```

## This is a Heading

This is a paragraph.

## Flask App with Three Tabs

Tab 1

Tab 2

Tab 3

### Content for Tab 1

This is the first tab.



Power your data-driven apps.  
Get started >



Run >

```
<li class="nav-item"
role="presentation">
  <button class="nav-link"
id="tab2-tab" data-bs-toggle="tab" data-
bs-target="#tab2" type="button"
role="tab">Tab 2</button>
</li>
<li class="nav-item"
role="presentation">
  <button class="nav-link"
id="tab3-tab" data-bs-toggle="tab" data-
bs-target="#tab3" type="button"
role="tab">Tab 3</button>
</li>
</ul>
<div class="tab-content p-3 border
```

## This is a Heading

This is a paragraph.

## Flask App with Three Tabs

Tab 1

Tab 2

Tab 3

### Content for Tab 2

This is the second tab.



Power your data-driven apps.  
Get started >



Run >

```
</div>
<div class="tab-pane fade"
id="tab3" role="tabpanel">
  <h4>Content for Tab 3</h4>
  <p>This is the third tab.</p>
</div>
</div>
</div>
<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/js/bootstrap.bundle.min.js"
></script>
</body>
</html>
```

## This is a Heading

This is a paragraph.

## Flask App with Three Tabs

Tab 1

Tab 2

Tab 3

### Content for Tab 3

This is the third tab.