

SIMATS ENGINEERING C02-ASSESSMENT TOOL -2

M KAVYA 192472370
ITA1407
ETHICAL HACKING

Question 1 – theHarvester

Open Terminal and run:

```
sudo apt update
theHarvester --version
```

If it says "command not found":

```
sudo apt install theharvester
```

Run the scan:

```
theHarvester -d tesla.com -b all
```

To save the report:

```
theHarvester -d tesla.com -b all -f tesla_report
```

[illegible]

Question 2 – GoPhish

If GoPhish is already installed in your lab:

```
cd gophish  
sudo ./gophish
```

Open your browser:

<https://127.0.0.1:3333>

Log in, create the phishing campaign, and take screenshots of:

- Dashboard
- Email template
- Campaign
- Results (Delivery, Open Rate, Click Rate)

If GoPhish is not installed, let me know and I'll give you the installation steps.

The screenshot shows a Kali Linux virtual machine running Oracle VM VirtualBox. The browser window displays the GoPhish User Management page. The page has a sidebar with navigation links: Dashboard, Campaigns, Users & Groups, Email Templates, Landing Pages, Sending Profiles, Account Settings, User Management (selected), Webhooks, User Guide, and API Documentation. The main content area is titled 'User Management' and features a '+ New User' button, a 'Show 10 entries' dropdown, and a search bar. A table lists users with columns for Username, Role, and Last Login. The table shows one user: 'admin' with Role 'Admin' and Last Login 'August 4th 2026, 6:27:28 pm'. Below the table, it says 'Showing 1 to 1 of 1 entries'. There are also 'Previous', '1', and 'Next' pagination controls. A 'Power Manager' notification is visible in the top right corner of the browser window, stating 'System is running on low power. Save your work to avoid losing data.' The bottom of the screen shows the Kali Linux desktop environment with various icons and a taskbar.

Username	Role	Last Login
admin	Admin	August 4th 2026, 6:27:28 pm

Question 3 – Nmap

Check version:

`nmap --version`

Run the scan:

`nmap -A scanme.nmap.org`

Save the report:

`nmap -A scanme.nmap.org -oN scanme_report.txt`

```
kavya@kavya: ~  
Session Actions Edit View Help  
(kavya@kavya)-[~]  
$ nmap --version  
Nmap version 7.99 ( https://nmap.org )  
Platform: x86_64-pc-linux-gnu  
Compiled with: liblua-5.4.8 openssl-3.6.2 libssh2-1.11.1 libz-1.3.1 libpcap-1.10.6 nmap-libdnet-1.18.0 ipv6  
Compiled without:  
Available nsock engines: epoll poll select  
  
(kavya@kavya)-[~]  
$ nmap -A scanme.nmap.org  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-04 18:12 +0530  
Nmap scan report for scanme.nmap.org (45.33.32.156)  
Host is up (0.0012s latency).  
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f  
Not shown: 990 filtered tcp ports (no-response)  
PORT      STATE SERVICE      VERSION  
22/tcp    open  tcpwrapped  
|_ssh-hostkey: ERROR: Script execution failed (use -d to debug)  
53/tcp    closed domain  
80/tcp    open  http          Apache httpd 2.4.7 ((Ubuntu))  
|_http-server-header: Apache/2.4.7 (Ubuntu)  
139/tcp   closed netbios-ssn  
143/tcp   closed imap  
443/tcp   closed https  
3389/tcp  closed ms-wbt-server  
5060/tcp  open  sip?  
5061/tcp  open  sip-tls?  
8080/tcp  closed http-proxy  
Device type: VoIP adapter|bridge|general purpose  
Running (JUST GUESSING): AT&T embedded (90%), Oracle Virtualbox (88%), Slirp (88%), QEMU (86%)  
OS CPE: cpe:/o:oracle:virtualbox cpe:/a:danny_gasparovski:slirp cpe:/a:qemu:qemu  
Aggressive OS guesses: AT&T BGW210 voice gateway (90%), Oracle Virtualbox Slirp NAT bridge (88%), QEMU user mode network gateway (86%)  
No exact OS matches for host (test conditions non-ideal).  
Network Distance: 1 hop  
  
TRACEROUTE (using port 80/tcp)  
HOP RTT      ADDRESS
```