

TE IT

Name : Omkar Gurav

Roll no : 8048

Deadlock Avoidance Using Semaphores: Implement the deadlock-free solution to Dining Philosophers problem to illustrate the problem of deadlock and/or starvation that can occur when many synchronized threads are competing for limited resources.

```
#include<stdio.h>
```

```
#include<semaphore.h>
```

```
#include<pthread.h>
```

```
#define N 5
```

```
#define THINKING 0
```

```
#define HUNGRY 1
```

```
#define EATING 2
```

```
#define LEFT (ph_num+4)%N
```

```
#define RIGHT (ph_num+1)%N
```

```
sem_t mutex;
```

```
sem_t S[N];
```

```
int state[N];
```

```
int phil_num[N]={0,1,2,3,4};
```

```
void *philospher(void *num)
```

```
{
    while(1)
    {
        int *i = num;
        sleep(1);
        take_fork(*i);
        sleep(0);
        put_fork(*i);
    }
}
```

```
void take_fork(int ph_num)
```

```
{
    sem_wait(&mutex);
    state[ph_num] = HUNGRY;
    printf("Philosopher %d is Hungry \n",ph_num+1);
    test(ph_num);
    sem_post(&mutex);
    sem_wait(&S[ph_num]);
    sleep(1);
}
```

```
void test(int ph_num)
```

```
{
    if(state[ph_num] == HUNGRY && state[LEFT] != EATING && state[RIGHT] !=
EATING)
    {
```

```
        state[ph_num] = EATING;

        sleep(2);

        printf("Philosopher %d Takes Fork %d and %d
\n",ph_num+1,LEFT+1,ph_num+1);

        printf("Philosopher %d is Eating \n",ph_num+1);

        sem_post(&S[ph_num]);

    }

}
```

```
void put_fork(int ph_num)

{

    sem_wait(&mutex);

    state[ph_num] = THINKING;

    printf("Philosopher %d Putting Fork %d and %d Down
\n",ph_num+1,LEFT+1,ph_num+1);

    printf("Philosopher %d is Thinking \n",ph_num+1);

    test(LEFT);

    test(RIGHT);

    sem_post(&mutex);

}
```

```
int main()

{

    int i;

    pthread_t thread_id[N];

    sem_init(&mutex,0,1);

    for(i=0;i<N;i++)

    {
```

```
        sem_init(&S[i],0,0);
    }
    for(i=0;i<N;i++)
    {
        pthread_create(&thread_id[i],NULL,philospher,&phil_num[i]);
        printf("Philosopher %d is Thinking \n",i+1);
    }
    for(i=0;i<N;i++)
    {
        pthread_join(thread_id[i],NULL);
    }
}
```

Output:

Philosopher 1 is Thinking

Philosopher 2 is Thinking

Philosopher 3 is Thinking

Philosopher 4 is Thinking

Philosopher 5 is Thinking

Philosopher 1 is Hungry

Philosopher 1 Takes Fork 5 and 1

Philosopher 1 is Eating

Philosopher 2 is Hungry

Philosopher 4 is Hungry

Philosopher 4 Takes Fork 3 and 4

Philosopher 4 is Eating

Philosopher 3 is Hungry

Philosopher 5 is Hungry

Philosopher 1 Putting Fork 5 and 1 Down

Philosopher 1 is Thinking

Philosopher 2 Takes Fork 1 and 2

Philosopher 2 is Eating

Philosopher 4 Putting Fork 3 and 4 Down

Philosopher 4 is Thinking

Philosopher 5 Takes Fork 4 and 5

Philosopher 5 is Eating

Philosopher 1 is Hungry

Philosopher 2 Putting Fork 1 and 2 Down

Philosopher 2 is Thinking

Philosopher 3 Takes Fork 2 and 3

Philosopher 3 is Eating

Philosopher 4 is Hungry

Philosopher 5 Putting Fork 4 and 5 Down

Philosopher 5 is Thinking

Philosopher 1 Takes Fork 5 and 1

Philosopher 1 is Eating

Philosopher 3 Putting Fork 2 and 3 Down

Philosopher 3 is Thinking

Philosopher 4 Takes Fork 3 and 4

Philosopher 4 is Eating

Philosopher 2 is Hungry

Philosopher 5 is Hungry

Philosopher 1 Putting Fork 5 and 1 Down

Philosopher 1 is Thinking

Philosopher 2 Takes Fork 1 and 2

Philosopher 2 is Eating

Philosopher 3 is Hungry

Philosopher 4 Putting Fork 3 and 4 Down

Philosopher 4 is Thinking

Philosopher 5 Takes Fork 4 and 5

Philosopher 5 is Eating

Philosopher 2 Putting Fork 1 and 2 Down

Philosopher 2 is Thinking

Philosopher 3 Takes Fork 2 and 3

Philosopher 3 is Eating

Philosopher 1 is Hungry

Philosopher 4 is Hungry

Philosopher 5 Putting Fork 4 and 5 Down

Philosopher 5 is Thinking

Philosopher 1 Takes Fork 5 and 1

Philosopher 1 is Eating

Philosopher 2 is Hungry

Philosopher 3 Putting Fork 2 and 3 Down

Philosopher 3 is Thinking

Philosopher 4 Takes Fork 3 and 4

Philosopher 4 is Eating

Philosopher 5 is Hungry

Philosopher 1 Putting Fork 5 and 1 Down

Philosopher 1 is Thinking

Philosopher 2 Takes Fork 1 and 2

Philosopher 2 is Eating

Philosopher 3 is Hungry

Philosopher 4 Putting Fork 3 and 4 Down

Philosopher 4 is Thinking