Program 3

Aim: Configure default route, static route to the Router (Part 1).

Topology, Procedure and Observation:



Output :- Ping 20.0.0.1 .

Pinging 20.0.0.1 with 32 bytes of data:
Reply from 10.0.0.3: Destination host unreachable.
Reply from 10.0.0.3: Destination host unreachable.
" " " " .
" " " " .
Request time out.
Ping statics for 20.0.0.2:
Packets: Sent = 4, Recieved = 0, Lost = 4 (100% loss),

Ping 20.0.0.2

Pinging 20.0.0.1 with 32 bytes of data:
Reply from 10.0.0.3: Destination host unreachable.
" " " " " .
" " " " " .
Request time out.
Ping statics for 20.0.0.2:
Packets: Sent = 4, Recieved = 0, Lost = 4 (100% loss).

Ping 10.0.0.3

Pinging 10.0.0.3 with 32 bytes of data.
Reply from 10.0.0.3: bytes = 32 time = 0 ms TTL = 255
" " " " .
" " " " .
" " " " .
Ping statics for 10.0.0.3.
packets: Sent = 4, Recieved = 4, Lost = 0 (0% loss),
Approximate round trip times in mms:-
Min = 0ms, max = 0ms, Avg = 0ms.

Screen Shots: