SQL

by

APNA COLLEGE

Database



Database is collection of data in a format that can be easily accessed (Digital)

A software application used to manage our DB is called DBMS (Database Management System)

APNA COLLEGE

Types of Databases

Relational

Data stored in tables



Non-relational (NoSQL)

data not stored in tables



** We use SQL to work with relational DBMS

APNA COLLEGE

What is SQL?



Structured Query Language

SQL is a programming language used to interact with relational databases.

It is used to perform **CRUD** operations :

Create


Read

Update

Delete

APNA COLLEGE

Database Structure



APNA COLLEGE

What is a table?

Student table

RollNo	Name	Class	DOB	Gender	City	Marks
1	Nanda	X	1995-06-06	M	Agra	551
2	Saurabh	XII	1993-05-07	M	Mumbai	462
3	Sonal	XI	1994-05-06	F	Delhi	400
4	Trisla	XII	1995-08-08	F	Mumbai	450
5	Store	XII	1995-10-08	M	Delhi	369
6	Marisla	XI	1994-12-12	F	Dubai	250
7	Neha	X	1995-12-08	F	Moscow	377
8	Nishant	X	1995-06-12	M	Moscow	489

APNA COLLEGE

Creating our First Database

Our first SQL Query

CREATE DATABASE *db_name;*

DROP DATABASE *db_name;*



Creating our First Table

```
USE db_name;

CREATE TABLE table_name (
    column_name1 datatype constraint,
    column_name2 datatype constraint,
    column_name2 datatype constraint
);
```

```
CREATE TABLE student (
  id INT PRIMARY KEY,
  name VARCHAR(50),
  age INT NOT NULL
);
```

APNA COLLEGE

SQL Datatypes

They define the type of values that can be stored in a column

DATATYPE	DESCRIPTION	USAGE
CHAR	string(0-255), can store characters of fixed length	CHAR(50)
VARCHAR	string(0-255), can store characters up to given length	VARCHAR(50)
BLOB	string(0-65535), can store binary large object	BLOB(1000)
INT	integer(-2,147,483,648 to 2,147,483,647)	INT
TINYINT	integer(-128 to 127)	TINYINT
BIGINT	integer(-9,223,372,036,854,775,808 to 9,223,372,036,854,775,807)	BIGINT
BIT	can store x-bit values. x can range from 1 to 64	BIT(2)
FLOAT	Decimal number - with precision to 23 digits	FLOAT
DOUBLE	Decimal number - with 24 to 53 digits	DOUBLE
BOOLEAN	Boolean values 0 or 1	BOOLEAN
DATE	date in format of YYYY-MM-DD ranging from 1000-01-01 to 9999-12-31	DATE
YEAR	year in 4 digits format ranging from 1901 to 2155	YEAR

APNA COLLEGE

SQL Datatypes

Signed & Unsigned

TINYINT UNSIGNED (0 to 255)

TINYINT (-128 to 127)

APNA COLLEGE

Types of SQL Commands

DDL (Data Definition Language) : create, alter, rename, truncate & drop

DQL (Data Query Language) : select

DML (Data Manipulation Language) : select, insert, update & delete

DCL (Data Control Language) : grant & revoke permission to users

TCL (Transaction Control Language) : start transaction, commit, rollback etc.

APNA COLLEGE

Database related Queries

CREATE DATABASE *db_name;*

CREATE DATABASE IF NOT EXISTS *db_name;*

```
CREATE DATABASE IF NOT EXISTS college;
```

DROP DATABASE *db_name;*

DROP DATABASE IF EXISTS *db_name;*

SHOW DATABASES*;*

SHOW TABLES*;*

APNA COLLEGE

Table related Queries

Create

```
CREATE TABLE table_name (
    column_name1 datatype constraint,
    column_name2 datatype constraint,
);
```

```sql
CREATE TABLE student (
    rollno INT PRIMARY KEY,
    name VARCHAR(50)
);
```

APNA COLLEGE

Table related Queries

Select & View ALL columns

SELECT * FROM *table_name;*

```sql
SELECT * FROM student;
```

APNA COLLEGE

Table related Queries

Insert

INSERT INTO *table_name*
(colname1, colname2);
VALUES
(col1_v1, col2_v1),
(col1_v2, col2_v2);

```sql
INSERT INTO student
(rollno, name)
VALUES
(101, "karan"),
(102, "arjun");
```



Keys 

Primary Key

It is a column (or set of columns) in a table that uniquely identifies each row. (a unique id)

There is only 1 PK & it should be NOT null.

Foreign Key

A foreign key is a column (or set of columns) in a table that refers to the primary key in another table.

There can be multiple FKs.

FKs can have duplicate & null values.

APNA COLLEGE

Keys

table1 - Student

id	name	cityId	city
101	karan	1	Pune
102	arjun	2	Mumbai
103	ram	1	Pune
104	shyam	3	Delhi

table2 - City

id	city_name
1	Pune
2	Mumbai
3	Delhi

APNA COLLEGE

Constraints

SQL constraints are used to specify rules for data in a table.

NOT NULL columns cannot have a null value

```
col1 int NOT NULL
```

UNIQUE all values in column are different

```
col2 int UNIQUE
```

PRIMARY KEY makes a column unique & not null but used only for one

```
id int PRIMARY KEY
```

```
CREATE TABLE temp (
  id int not null,
  PRIMARY KEY (id)
);
```

APNA COLLEGE

Constraints

FOREIGN KEY prevent actions that would destroy links between tables

```sql
CREATE TABLE temp (
  cust_id int,
  FOREIGN KEY (cust_id) references customer(id)
);
```

DEFAULT sets the default value of a column

```sql
salary INT DEFAULT 25000
```

APNA COLLEGE

Constraints

CHECK it can limit the values allowed in a column

```sql
CREATE TABLE city (
  id INT PRIMARY KEY,
  city VARCHAR(50),
  age INT,
  CONSTRAINT age_check CHECK (age >= 18 AND city="Delhi")
);
```

```sql
CREATE TABLE newTab (
  age INT CHECK (age >= 18)
);
```

APNA COLLEGE

Create this sample table

```sql
CREATE DATABASE college;
USE college;

CREATE TABLE student (
   rollno INT PRIMARY KEY,
   name VARCHAR(50),
   marks INT NOT NULL,
   grade VARCHAR(1),
   city VARCHAR(20)
);
```

Insert this data

```sql
INSERT INTO student
(rollno, name, marks, grade, city)
VALUES
(101, "anil", 78, "C", "Pune"),
(102, "bhumika", 93, "A", "Mumbai"),
(103, "chetan", 85, "B", "Mumbai"),
(104, "dhruv", 96, "A", "Delhi"),
(105, "emanuel", 12, "F", "Delhi"),
(106, "farah", 82, "B", "Delhi");
```

APNA COLLEGE

Select in Detail

used to select any data from the database

Basic Syntax

```
SELECT col1, col2 FROM table_name;
```

To Select ALL

```
SELECT * FROM table_name;
```



Where Clause

To define some conditions

SELECT *col1, col2* **FROM** *table_name*
WHERE *conditions;*

```
SELECT * FROM student WHERE marks > 80;
SELECT * FROM student WHERE city = "Mumbai";
```

APNA COLLEGE

Where Clause

Using Operators in WHERE

Arithmetic Operators : +(addition) , -(subtraction), *(multiplication), /(division), %(modulus)

Comparison Operators : = (equal to), != (not equal to), > , >=, <, <=

Logical Operators : AND, OR , NOT, IN, BETWEEN, ALL, LIKE, ANY

Bitwise Operators : & (Bitwise AND), | (Bitwise OR)



Operators

AND (to check for both conditions to be true)

```sql
SELECT * FROM student WHERE marks > 80 AND city = "Mumbai";
```

OR (to check for one of the conditions to be true)

```sql
SELECT * FROM student WHERE marks > 90 OR city = "Mumbai";
```

APNA COLLEGE

Operators

Between (selects for a given range)

```sql
SELECT * FROM student WHERE marks BETWEEN 80 AND 90;
```

In (matches any value in the list)

```sql
SELECT * FROM student WHERE city IN ("Delhi", "Mumbai");
```

NOT (to negate the given condition)

```sql
SELECT * FROM student WHERE city NOT IN ("Delhi", "Mumbai");
```

APNA COLLEGE

Limit Clause

Sets an upper limit on number of (tuples)rows to be returned

```sql
SELECT * FROM student LIMIT 3;
```

SELECT *col1, col2* **FROM** *table_name*
LIMIT *number;*

APNA COLLEGE

Order By Clause

To sort in ascending (ASC) or descending order (DESC)

```
SELECT * FROM student
ORDER BY city ASC;
```

SELECT *col1, col2* **FROM** *table_name*
ORDER BY *col_name(s)* **ASC;**

APNA COLLEGE

Aggregate Functions

Aggregare functions perform a calculation on a set of values, and return a single value.

- COUNT( )
- MAX( )
- MIN( )
- SUM( )
- AVG( )

Get Maximum Marks

```
SELECT max(marks)
FROM student;
```

Get Average marks

```
SELECT avg(marks)
FROM student;
```

APNA COLLEGE

Group By Clause

Groups rows that have the same values into summary rows.
It collects data from multiple records and groups the result by one or more column.

*Generally we use group by with some *aggregation function*.

Count number of students in each city

```
SELECT city, count(name)
FROM student
GROUP BY city;
```

APNA COLLEGE

Having Clause

Similar to Where i.e. applies some condition on rows.
Used when we want to apply any condition after grouping.

Count number of students in each city where max marks cross 90.

```
SELECT count(name), city
FROM student
GROUP BY city
HAVING max(marks) > 90;
```

APNA COLLEGE

General Order

SELECT *column(s)*

FROM *table_name*

WHERE *condition*

GROUP BY *column(s)*

HAVING *condition*

ORDER BY *column(s)* **ASC;**

APNA COLLEGE

Having Clause

Similar to Where i.e. applies some condition on rows.
Used when we want to apply any condition after grouping.

Count number of students in each city where max marks cross 90.

```
SELECT count(name), city
FROM student
GROUP BY city
HAVING max(marks) > 90;
```

APNA COLLEGE

Table related Queries

Update (to update existing rows)

```
UPDATE table_name
SET col1 = val1, col2 = val2
WHERE condition;
```

```sql
UPDATE student
SET grade = "O"
WHERE grade = "A";
```

APNA COLLEGE

Table related Queries

Delete (to delete existing rows)

DELETE FROM *table_name*
WHERE *condition;*

```sql
DELETE FROM student
WHERE marks < 33;
```

APNA COLLEGE

Cascading for FK

On Delete Cascade

When we create a foreign key using this option, it deletes the referencing rows in the child table when the referenced row is deleted in the parent table which has a primary key.

On Update Cascade

When we create a foreign key using UPDATE CASCADE the referencing rows are updated in the child table when the referenced row is updated in the parent table which has a primary key.

```
CREATE TABLE student (
  id INT PRIMARY KEY,
  courseID INT,
  FOREIGN KEY(courseID) REFERENCES course(id)
  ON DELETE CASCADE
  ON UPDATE CASCADE
);
```

APNA COLLEGE

Table related Queries

Alter (to change the schema)

ADD Column

```
ALTER TABLE table_name
ADD COLUMN column_name datatype constraint;
```

DROP Column

```
ALTER TABLE table_name
DROP COLUMN column_name;
```

RENAME Table

```
ALTER TABLE table_name
RENAME TO new_table_name;
```

APNA COLLEGE

Table related Queries

CHANGE Column (rename)

```
ALTER TABLE table_name
CHANGE COLUMN old_name new_name new_datatype new_constraint;
```

MODIFY Column (modify datatype/ constraint)

```
ALTER TABLE table_name
MODIFY col_name new_datatype new_constraint;
```

APNA COLLEGE

ADD Column

```sql
ALTER TABLE student
ADD COLUMN age INT NOT NULL DEFAULT 19;
```

DROP Column

```sql
ALTER TABLE student
DROP COLUMN stu_age;
```

MODIFY Column

```sql
ALTER TABLE student
MODIFY age VARCHAR(2);
```

RENAME Table

```sql
ALTER TABLE student
RENAME TO stu;
```

CHANGE Column (rename)

```sql
ALTER TABLE student
CHANGE age stu_age INT;
```

APNA COLLEGE

Table related Queries

Truncate (to delete table's data)

```
TRUNCATE TABLE table_name ;
```

```
UPDATE student
SET grade = "0"
WHERE grade = "A";
```


APNA COLLEGE

Joins in SQL


Join is used to combine rows from two or more tables, based on a related column between them.




Types of Joins




Inner Join



Left Join



Right Join




Full Join

Outer Joins

APNA COLLEGE

Inner Join

Returns records that have matching values in both tables



Syntax

```
SELECT column(s)
FROM tableA
INNER JOIN tableB
ON tableA.col_name = tableB.col_name;
```

APNA COLLEGE

Inner Join

Example

```
SELECT *
FROM student
INNER JOIN course
ON student.student_id = course.student_id;
```

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science


Result

student_id	name	course
102	bob	english
103	casey	science

APNA COLLEGE

Left Join

Returns all records from the left table, and the matched records from the right table



Syntax

```
SELECT column(s)
FROM tableA
LEFT JOIN tableB
ON tableA.col_name = tableB.col_name;
```

APNA COLLEGE

Left Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science

```
SELECT *
FROM student as s
LEFT JOIN course as c
ON s.student_id = c.student_id;
```


Result

student_id	name	course
101	adam	*null*
102	bob	english
103	casey	science

APNA COLLEGE

Right Join

Returns all records from the right table, and the matched records from the left table



Syntax

```
SELECT column(s)
FROM tableA
RIGHT JOIN tableB
ON tableA.col_name = tableB.col_name;
```

APNA COLLEGE

Right Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science

Result


student_id	course	name
102	english	bob
105	math	*null*
103	science	casey
107	computer science	*null*

```
SELECT *
FROM student as s
RIGHT JOIN course as c
ON s.student_id = c.student_id;
```

APNA COLLEGE

Full Join

Returns all records when there is a match in either left or right table



Syntax in MySQL

```
SELECT * FROM student as a
LEFT JOIN course as b
ON a.id = b.id
UNION
SELECT * FROM student as a
RIGHT JOIN course as b
ON a.id = b.id;
```

LEFT JOIN

UNION

RIGHT JOIN

APNA COLLEGE

Full Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course


student_id	course
102	english
105	math
103	science
107	computer science

Result


student_id	name	course
101	adam	*null*
102	bob	english
103	casey	science
105	*null*	math
107	*null*	computer science

APNA COLLEGE


Think & Ans



Qs: Write SQL commands to display the right exclusive join :



Left Exclusive Join



Right Exclusive Join

```sql
SELECT *
FROM student as a
LEFT JOIN course as b
ON a.id = b.id
WHERE b.id IS NULL;
```

APNA COLLEGE

Self Join

It is a regular join but the table is joined with itself.

Syntax

```
SELECT column(s)
FROM table as a
JOIN table as b
ON a.col_name = b.col_name;
```

APNA COLLEGE

Self Join

Example

Employee

id	name	manager_id
101	adam	103
102	bob	104
103	casey	*null*
104	donald	103

```sql
SELECT a.name as manager_name, b.name
FROM employee as a
JOIN employee as b
ON a.id = b.manager_id;
```

Result

APNA COLLEGE

Union

It is used to combine the result-set of two or more SELECT statements.
Gives UNIQUE records.

To use it :

- **every SELECT should have same no. of columns**
- **columns must have similar data types**
- **columns in every SELECT should be in same order**

Syntax


SELECT *column(s)* FROM ***tableA***
UNION
SELECT *column(s)* FROM **tableB**

APNA COLLEGE

SQL Sub Queries

A Subquery or Inner query or a Nested query is a query within another SQL query.

It involves 2 select statements.



Syntax

```
SELECT column(s)
FROM table_name
WHERE col_name operator
( subquery );
```

APNA COLLEGE

SQL Sub Queries

Example

Get names of all students who scored more than class average.

Step 1. Find the avg of class
Step 2. Find the names of students with marks > avg

rollno	name	marks
101	anil	78
102	bhumika	93
103	chetan	85
104	dhruv	96
105	emanuel	92
106	farah	82

APNA COLLEGE

SQL Sub Queries

Example

Find the names of all students with even roll numbers.

Step 1. Find the even roll numbers
Step 2. Find the names of students with even roll no

rollno	name	marks
101	anil	78
102	bhumika	93
103	chetan	85
104	dhruv	96
105	emanuel	92
106	farah	82

APNA COLLEGE

SQL Sub Queries

Example with FROM

Find the max marks from the students of Delhi

Step 1. Find the students of Mumbai
Step 2. Find their max marks using the sublist in step 1

rollno	name	marks	city
101	anil	78	Pune
102	bhumika	93	Mumbai
103	chetan	85	Mumbai
104	dhruv	96	Delhi
105	emanuel	92	Delhi
106	farah	82	Delhi

APNA COLLEGE

MySQL Views

A view is a virtual table based on the result-set of an SQL statement.

```sql
CREATE VIEW view1 AS
SELECT rollno, name FROM student;

SELECT * FROM view1;
```

*A view always shows up-to-date data. The database engine recreates the view, every time a user queries it.

APNA COLLEGE