



B.M.S. COLLEGE OF ENGINEERING

Bengaluru-560019.

Autonomous College, affiliated to
Visvesvaraya Technological University, Belgaum



Mini Project Report on

“INTELLIGENT VEHICLE SAFETY SYSTEM”

Submitted in partial fulfilment of the requirement for completion of
MINI PROJECT [23EC5PWMPR]

Submitted by

Kovuru Sai Karthik

1BM23EC122

Manish Kumar Bale

1BM23EC140

Madhusudhan C

1BM23EC134

Under the guidance of

Mr.Eesha.D

Assistant Professor

BMS College of Engineering

Bengaluru

Academic Year

2025 – 2026

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

BMS College of Engineering
Bull Temple Road, Basavanagudi, Bengaluru-560019

BMS COLLEGE OF ENGINEERING

Autonomous college, Affiliated to VTU

Bull Temple Road, Bengaluru – 560 019

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING



CERTIFICATE

This is to certified that the Mini Project entitled “**INTELLIGENT VEHICLE SAFETY SYSTEM**” is a Bonafide work carried out by **Kovuru Sai Karthik: (1BM23EC122), Manish Kumar Bale (1BM23EC139) and Madhusudhan C: (1BM23EC134)** submitted in partial fulfilment of the requirement for completion of MINI PROJECT [23EC5PWMPR] of Bachelor of Engineering in Electronics and Communication during the academic year 2025-26. The Mini Project report has been approved as it satisfies the academic requirements.

Guide

Mr.Eesha.D

Assistant Professor

Department of ECE
BMS College of Engineering

Head of Department

(Dr. K. P. Lakshmi)

Professor and Head

Department of ECE
BMS College of Engineering

(Dr. Bheemsha Arya)

Principal

BMS College of Engineering

External Viva

Name of the Examiners

Signature with Date

1.

2

DECLARATION

We, **Kovuru Sai Karthik: (1BM23EC122), Manish Kumar Bale: (1BM23EC139) and Madhusudhan C: (1BM23EC134)**, hereby declare that the Mini Project entitled **Intelligent Vehicle Safety System** is a Bonafide work and has been carried out by us under the guidance of **Mr.Eesha.D, Assistant Professor**, Department of Electronics and Communication Engineering, BMS College of Engineering, Bengaluru submitted in partial fulfilment of the requirement for completion of MINI PROJECT [23EC5PWMPR] of Bachelor of Engineering in Electronics and Communication during the academic year 2025-26. The Mini Project report has been approved as it satisfies the academic requirements in Electronics and Communication engineering, Visvesvaraya Technological University, Belagavi, during the academic year 2025-26. We further declare that, to the best of our knowledge and belief, this Mini Project has not been submitted either in part or in full to any other university.

Place: Bengaluru

Kovuru Sai Karthik: 1BM23EC122

Date: 10/12/2025

Manish Kumar Bale: 1BM23EC139

Madhusudhan C: 1BM23EC134

ACKNOWLEDGEMENTS

We take this opportunity to express our profound gratitude to the respected principal Dr. Bheemsha Arya, BMS College of Engineering for providing a congenial environment to work in. Our sincere gratitude to Dr. K. P. Lakshmi, Head of the Department, Electronics and Communication Engineering for encouraging and providing opportunity to carry Mini Project in the department.

We heartfully thank our guide Mr. Eesha.D for the guidance and constant encouragement throughout the course of this Mini Project without which this project would not be successful.

A number of personalities, in their own capacities have helped us in carrying out this Mini Project. We would like to take this opportunity to thank them all.

Last but not the least, we thank our friends and family for their encouragement and help in accomplishing the objective of the Mini Project work.

- 1) Kovuru Sai Karthik: 1BM23EC122
- 2) Manish Kumar Bale: 1BM23EC139
- 3) Madhusudhan C: 1BM23EC134

ABSTRACT

This project presents an Intelligent Vehicle Safety System that integrates adaptive headlight control, real-time obstacle detection, and driver-assist functions within a unified embedded architecture. The system employs dual ultrasonic sensors mounted on independent servo mechanisms to perform directional scanning of the vehicle's forward environment. This configuration enables accurate distance measurement and obstacle localization across a wider field of view. Based on the detected position and proximity of obstacles, the microcontroller dynamically regulates the intensity and distribution of high-power LED headlights through zone-based dimming, thereby reducing glare while maintaining optimal road visibility. The system further incorporates a driver alert mechanism that issues timely warnings when obstacles approach critical distances, enhancing situational awareness during night-time driving. By combining adaptive illumination, proximity monitoring, and warning feedback, the proposed design provides a cost-effective and scalable approach to improving vehicular safety. The system demonstrates the potential of embedded sensor-driven solutions to mitigate visibility-related risks and enhance driver response in low-light and high-hazard conditions.

TABLE OF CONTENTS

Abstract
List of figures
List of tables

Sl.No	Name	Page No
1	Chapter 1: INTRODUCTION	1
2	Chapter 2: LITERATURE SURVEY	2
3	Chapter 3: PROBLEM ANALYSIS AND SOLUTION	6
4	Chapter 4: METHODOLOGY AND IMPLEMENTATION	7
5	Chapter 5: COMPONENT EXPLANATION	9
6	Chapter 6: PROJECT EXECUTION STEPS	10
7	Chapter 7: PROJECT PLANNING	11
8	BILL OF MATERIALS	11
9	Chapter 8: RESULTS AND DISCUSSION	12
10	Chapter 9: FUTURE TRENDS	13
11	CONCLUSION	13
12	REFERENCES	14

LIST OF FIGURES

Fig. No.	Name	Page. No
3.1	Block Diagram	6
4.1	Flowchart	7
4.2	Adaptive Lighting Control System	8
8.1	Hardware Circuit	12
8.2	Semi Lit LED	13
8.3	Fully Lit LED	14

LIST OF TABLES

Table No.	Description of Table	Page No.
7.1	Project Timeline	11
7.2	Estimated Bill of Materials	11
8.1	Reaction Time	15

Chapter 1: INTRODUCTION

The increasing complexity of modern transportation systems has heightened the demand for intelligent, sensor-driven safety mechanisms in vehicles. Night-time driving continues to present significant risks due to reduced visibility, glare from oncoming headlights, and delayed driver response to unexpected obstacles. Conventional headlight systems operate with fixed beam patterns and limited adaptability, offering insufficient support in dynamic traffic environments. These limitations highlight the need for accessible, low-cost solutions that enhance visibility, reduce glare, and assist drivers in making timely decisions.

Advancements in embedded systems and sensor technologies have enabled the development of adaptive lighting systems capable of responding in real time to their surroundings. Unlike traditional high-beam/low-beam mechanisms, adaptive headlight systems adjust illumination based on obstacle proximity, position, and driving conditions. High-end vehicles achieve this through complex sensor fusion platforms; however, such technologies remain financially inaccessible for most consumer vehicles. This gap motivates the design of affordable, microcontroller-based implementations that can replicate essential safety features using compact, embedded hardware.

The proposed project addresses these challenges by developing an Intelligent Vehicle Safety System that combines obstacle detection, directional scanning, and adaptive LED headlight control. The system employs dual ultrasonic sensors mounted on servo mechanisms to scan the forward environment and identify the distance and relative angle of obstacles. This real-time information is used to control a multi-zone LED headlight assembly, where specific zones are dimmed or brightened dynamically to minimize glare and enhance visibility. By directing and modulating illumination based on obstacle position, the system improves driver awareness while reducing visual discomfort for oncoming vehicles.

In addition to adaptive lighting, the system incorporates an audible warning mechanism to alert the driver when obstacles are detected within critical distances. This layered approach—comprising environmental scanning, adaptive headlight modulation, and driver alerts—forms a practical framework for improving night-time safety without reliance on expensive automotive platforms. Furthermore, the modularity of the design allows future integration of advanced functions, including braking support and IoT-based communication, thereby aligning with the broader vision of intelligent transportation and driver-assistance systems.

In summary, this project demonstrates a cost-effective and scalable embedded solution that enhances night-time driving safety through adaptive illumination and real-time obstacle detection. By utilizing readily available sensors and microcontroller technology, the system provides a practical foundation for intelligent automotive lighting and serves as a viable prototype for modern vehicle safety enhancements.

Chapter 2: LITERATURE SURVEY

[1]“A Survey of Driving Safety with Sensing, Vehicular Communications, and Artificial Intelligence-Based Collision Avoidance”, Fu et al provides a comprehensive review of the architectures of modern Advanced Driver-Assistance Systems (ADAS), highlighting the integration of various safety functions. It details how perception sensors, such as **radar** and cameras, provide the necessary data for critical functions like **collision avoidance** and **automatic braking**. The survey frames **adaptive headlights** as a key output of this integrated system, emphasizing that advanced lighting functions rely on the same fused sensor data that is used to make decisions about braking and driver warnings, demonstrating the dependence of these safety features.

[2]“An Intelligent Automotive Adaptive Headlight System based on Digital Micromirror Device and Sensor Fusion”, Lee et al proposes a high-resolution adaptive headlight system utilizing a **Digital Micromirror Device (DMD)** for precise beam shaping. The system is built on a **sensor fusion** architecture that combines data from a forward-facing camera with a **radar sensor** to accurately detect the position and distance of other vehicles, pedestrians, and road signs. The authors explain that this fused data stream is not only used to dynamically control the headlight beams to prevent glare but also serves as the fundamental input for other critical ADAS functions, including **forward collision warnings** and **automatic braking**.

[3]“Radar and Camera Sensor Fusion for Joint Object Detection and Distance Estimation in ADAS”, Hannan et al work focuses on a robust algorithm for **radar and camera sensor fusion** to achieve accurate object detection and distance estimation for ADAS. The paper demonstrates that the unified data output from this fusion process is designed to be a versatile input for controlling a suite of vehicle functions simultaneously. The system’s output is explicitly used to manage **AEB (Automatic Emergency Braking)**, Forward Collision Warning (FCW), and **adaptive front-lighting systems (AFS)**, showing that these features are not standalone but are applications drawing from a single, reliable environmental model.

[4]“Integrated Control of AFS and DYC for Improved Vehicle Stability and Visibility”, Kim et al presents an integrated control strategy that combines an **Adaptive Front-lighting System (AFS)** with **Direct Yaw-moment Control (DYC)** to enhance both driver visibility and vehicle stability. The system uses forward-looking **radar** and other vehicle dynamics sensors to predict the vehicle’s future path. This prediction is used to proactively swivel the headlights into curves while also ensuring the vehicle remains stable, a factor that is especially critical during pre-collision maneuvers that may involve **automatic braking**, where maintaining control is paramount.

[5]“**A Real-Time Embedded System for Advanced Driver Assistance Based on a Multi- Sensor Fusion Approach**”, Lopez et al describes the architecture of a complete, real-time ADAS built on a **multi-sensor fusion approach**. The system integrates data from **radar**, LiDAR, and cameras to create a comprehensive and reliable model of the vehicle’s surroundings. This unified environmental model serves as the central decision-making hub for a wide range of functions, including **collision avoidance** (triggering warnings and **automatic braking**) and intelligent illumination via **adaptive headlights**, demonstrating a practical implementation of an integrated safety system.

[6]“**A Novel Approach for Glare-Free High Beam System with Camera and Low-Cost RADAR Sensor Fusion**”, Yoo et al presents a glare-free high beam system that focuses on cost-effectiveness by implementing a **fusion** of data from a camera and a **low-cost radar sensor**. The authors highlight that the accurate distance and velocity measurements provided by the **radar** are not only crucial for precisely **dimming the headlights** to create shadow zones around other vehicles but also serve as a primary input for the vehicle’s **forward collision warning** system. This demonstrates a direct architectural link where the same fused sensor data serves both advanced lighting and active safety functions.

[7]“**Smart Headlight System with Vehicle Detection and Tracking for Driving Safety Assistance**”, Ho et al details a **smart headlight system** that utilizes computer vision for real- time **vehicle detection and tracking**. The system generates critical data such as the position, speed, and trajectory of surrounding vehicles. It is noted that this tracking data is designed to be shared across multiple ADAS modules, acting as the primary trigger for both the **adaptive headlight** control logic and the algorithms governing the **collision warning and braking systems**, showcasing a modular yet highly integrated approach to vehicle safety.

[8]“**Advanced Driver Assistance System with Multi-Sensor for Collision Avoidance and Adaptive Lighting**”, Kumar et al proposes an ADAS architecture that explicitly links **adaptive lighting** with **collision avoidance** in a coordinated response. The system uses a **radar sensor** for long-range detection and a camera for object classification. When a potential hazard is identified, the system is programmed to execute a sequence of actions: first, it issues a **warning** to the driver; second, it initiates **pre-braking** to reduce reaction time; and third, it intelligently adjusts the **headlights** to optimally illuminate the hazard and any potential escape routes, thereby assisting the driver in the critical moments before a potential collision.

[9]“**Multi-Sensor Data Fusion for Vehicle Surroundings Perception in ADAS**”, Zhang et al reviews **sensor fusion techniques**, emphasizing that a unified and robust perception model created by combining data from **radar**, cameras, and LiDAR is essential for the functionality of modern ADAS. The authors explain that advanced features like **automatic emergency braking** and **adaptive high beam control** are not designed as independent, standalone systems. Instead, they are presented as distinct applications that draw their necessary environmental data from this central, fused data stream, making their performance and reliability fundamentally interdependent.

[10]“**Vision and Radar Data Fusion for Vehicle Detection in Advanced Driver Assistance Systems**”, Garcia et al concentrates on an algorithm for **vision and radar data fusion** designed specifically for the robust detection of preceding vehicles. The primary output of this algorithm is a precise location and velocity vector for any detected object. The paper presents this output vector as a critical, shared input intended to be used by three simultaneous vehicle safety applications: the audible **forward collision warning (beeping)** system, the controller for **automatic emergency braking**, and the logic for intelligent **headlight dimming**.

[11]“**An Integrated Safety System Combining Adaptive Front Lighting with Pre-Crash Brake Assist**”, Wagner et al introduces a system that directly integrates an **adaptive front- lighting system (AFS)** with a **pre-crash brake assist** function to improve driver response in emergency situations. The system’s forward **radar** is used to detect a high probability of a collision. When such a scenario is identified, the system executes a coordinated safety response: it simultaneously pre-charges the brakes and alerts the driver while actively swiveling the **headlights** toward the sides of the road. This lighting adjustment is designed to better illuminate potential evasive maneuver paths for the driver.

[12]“**Adaptive headlight control and real-time pedestrian detection**”, Zakaria et al. presents a system focused on enhancing **nighttime driving safety** by integrating **adaptive headlight control** with **real-time pedestrian detection**. The proposed approach utilizes a **camera-based** system, likely employing a **machine learning** algorithm to instantly identify pedestrians in the vehicle’s path. Upon detection, the system’s logic directs the **adaptive headlights** to specifically **illuminate the pedestrian**, significantly increasing their visibility for the driver, while simultaneously managing the overall beam pattern to prevent glare to other road users. The work demonstrates a cohesive safety system where the v’hicle's lighting actively responds to the presence of vulnerable road users.

[13]“**Smart electric mobility system with integrated safety and adaptive headlight monitoring**”, Nataraja et al. aims to enhance the safety and efficiency of **electric vehicles** through a system built around an **Arduino Nano** microcontroller. The project focuses on real-time environmental adaptation and safety alerts by integrating **adaptive headlight dimming**, **accident detection**, and a form of **vehicle-to-vehicle communication**. The system uses **LDR (Light Dependent Resistor)** sensors to detect the high-intensity lights of an oncoming vehicle, which automatically triggers the dimming of the headlights to prevent glare. A key safety feature is the use of a **Crash Sensor** that, upon impact, utilizes integrated **GPS and GSM modules** to send an **SMS alert** containing a Google Maps link of the vehicle’s location to a predefined recipient. The work demonstrates an integrated system that not only adapts its lighting but also autonomously reports accidents, contributing to the development of safer and more intelligent electric vehicles.

[14]“**Adaptive Headlight System for Automobiles**”, Aishwarya et al. addresses the dual challenges of poor visibility on curved roads and the glaring effect of high beams from oncoming traffic. The authors propose a **cost-effective, Arduino UNO R3-based** system that automates both headlight angle and intensity control. To improve visibility during turns, a **potentiometer** linked to the steering mechanism is used to activate additional **corner and deep corner LEDs**, illuminating the vehicle’s path. To mitigate glare, the system combines an **LDR** sensor with an **ultrasonic sensor** to detect the light intensity

and proximity of oncoming vehicles, automatically switching from **high beam to low beam** when necessary. The work concludes that this automated system can be easily incorporated into automobiles to enhance driver safety by illuminating blind spots and reducing the need for manual beam adjustments.

[15]“**Highway safety with an intelligent headlight system for improved nighttime driving**”, Nkrumah et al. presents a cost-effective, **sensor-based system** designed to reduce accidents caused by high-beam glare. A key innovation is the use of a **radar sensor** to measure the distance and speed of approaching vehicles, allowing the system to distinguish moving traffic from stationary lights. The system successfully **automates headlight dimming** to enhance nighttime safety and was validated through both simulation and real-vehicle implementation.

Chapter 3: PROBLEM ANALYSIS & SOLUTION

Problem Definition

Night-time driving continues to pose significant safety challenges due to limited visibility, glare from oncoming vehicles, and delayed driver reaction to unexpected obstacles. Conventional headlight systems operate with fixed or manually controlled beam patterns that do not adapt to dynamic road conditions. As a result, drivers often experience reduced awareness of nearby objects, particularly in poorly illuminated or high-traffic environments. Existing adaptive lighting technologies, although effective, remain restricted to high-end vehicles due to their high implementation cost and reliance on complex sensor fusion platforms.

Proposed Solution

There is a clear need for an affordable and efficient system that enhances night-time visibility by adjusting illumination based on real-time obstacle detection. Such a system must be capable of identifying the position and distance of objects in the forward path, minimizing glare to other road users, and providing timely alerts to assist the driver. Developing a low-cost embedded solution that achieves these functions can significantly improve driving safety and bridge the gap between advanced automotive lighting technologies and accessible consumer-level implementations.




Fig 3.1

Chapter 4: METHODOLOGY & IMPLEMENTATION




Fig 4.1

Hardware

- Arduino UNO
- 2 × HC-SR04 Ultrasonic Sensors
- 2 × Servo Motors (SG90 / MG995)
- 2 × WS2812 LED Strips (8-LED each)
- 12 V Battery / Adapter
- Buck Converter (12 V → 5 V)
- 330–470 Ω Resistors (×2)
- 1000 μF Capacitor
- Jumper Wires
- Buzzer
- Common Ground Connections

Software

- Arduino IDE and USB Driver for Arduino
- Embedded C / Arduino C programming
- Adafruit NeoPixel Library
- Servo Library

BLOCK DIAGRAM


INTELLIGENT VEHICLE
SAFETY SYSTEM

Fig 4.2

The components and interfaces listed above represent the final hardware and software selections used in the implementation of the system. These choices were confirmed after evaluating availability, performance, integration requirements, and overall system reliability during the design and prototyping phases.

Chapter 5: COMPONENT EXPLANATION

1. Arduino UNO

The Arduino UNO microcontroller serves as the central processing unit of the system. It receives distance readings from the ultrasonic sensors, controls the servo motors for directional scanning, updates the LED zones based on obstacle position, and activates the buzzer when the object reaches a critical distance. Its simplicity, robustness, and large library support make it ideal for rapid embedded development.

2. Ultrasonic Sensors (HC-SR04)

Two HC-SR04 ultrasonic sensors are used for obstacle detection. They emit ultrasonic pulses and measure the time taken for the echo to return, allowing accurate distance calculations. Mounted on servo motors, they provide angle-based readings, enabling the system to locate obstacles across a wide scanning range. Their reliability and low cost make them well-suited for real-time distance measurement.

3. Servo Motors (SG90/MG995)

The servo motors rotate the ultrasonic sensors between 0° and 180° to scan the front environment. This movement transforms the sensors from single-direction detectors into directional scanners, enabling angle-aware obstacle detection. The precise control offered by servos allows consistent and smooth scanning, which is essential for mapping LED zones accurately.

4. WS2812 Programmable LED Strips

WS2812 addressable LEDs are used as the adaptive headlight system. Each LED can be individually controlled for brightness, allowing the headlight to function in zones. When an obstacle is detected at a specific angle, the corresponding LED zone is dimmed, reducing glare and enhancing visibility. These LEDs provide high brightness, fast response, and fine-grained illumination control.

5. Buzzer

A buzzer is included to warn the driver when an obstacle enters a predefined danger zone. When the distance falls below the threshold, the buzzer activates to provide an immediate audible alert. This adds an additional safety layer beyond visual feedback.

6. Buck Converter (12V to 5V)

The buck converter regulates the input supply by stepping down 12V to a stable 5V required by the Arduino, servos, sensors, and LED strips. Stable power regulation is crucial because voltage fluctuations can affect sensor accuracy and LED performance.

7. Capacitor (1000 μ F)

A high-value capacitor is connected across the power supply for the WS2812 LEDs. It smooths out voltage spikes and prevents sudden current draws from damaging components. This ensures stable LED brightness and prevents flickering during operation.

8. Resistors (330–470 Ω)

Resistors are used in series with the LED strip's data line to prevent signal noise and protect the microcontroller from voltage spikes. They help maintain reliable data transmission between the Arduino and the LED strip.

9. Jumper Wires and Connectors

Jumper wires provide the electrical connections between Arduino pins and components.

Chapter 6: PROJECT EXECUTION STEPS

Hardware Selection and Assembly

- Finalize and gather all components: Arduino UNO, ultrasonic sensors, servo motors, WS2812 LED strips, buzzer, buck converter, resistors, and supporting wiring.
- Assemble the power subsystem using a 12 V supply with a buck converter regulated to 5 V for the microcontroller, sensors, servos, and LEDs.
- Mount ultrasonic sensors onto the left and right servo motors for directional scanning.
- Connect LED strips, servos, sensors, and buzzer to their respective Arduino pins with a common ground reference.

Sensor Integration and Angle-Based Detection

- Interface both HC-SR04 ultrasonic sensors with the Arduino using trigger and echo pins.
- Program servo sweep ranges for left and right scanning to map the forward area.
- Collect distance and angle data during each sweep to identify obstacle position.

Embedded System Programming

- Develop firmware in Arduino C for:
 - Servo motor control for directional scanning.
 - Ultrasonic distance measurement with timing-based echo analysis.
 - Angle-distance mapping for obstacle localization.
 - Adaptive LED zone control using the NeoPixel library.
 - Buzzer activation for driver alerts when critical thresholds are reached.
- Integrate all modules into a synchronized real-time control loop.

Adaptive Lighting and LED Zone Mapping

- Implement LED segmentation logic for multi-zone dimming.
- Link obstacle angle to specific LED zones for targeted illumination adjustment.
- Ensure smooth transitions and consistent brightness control through timed updates.

System Testing and Validation

- Perform initial desk testing to verify sensor readings, servo motion, LED output, and buzzer response.
- Conduct controlled indoor tests for:
 - Obstacle detection accuracy at various angles.
 - Correct LED zone dimming based on obstacle position.

- Smooth servo scanning and stable sensor feedback.
- Conduct outdoor night-time tests to evaluate real-world illumination, glare reduction, and detection performance.

Optimization and Refinement

- Fine-tune angular sweep limits for more accurate environmental coverage.
- Adjust LED zone thresholds for improved visibility and minimal glare.
- Apply filtering techniques (e.g., averaging, noise reduction) to stabilize ultrasonic readings.
- Ensure reliable performance under varying lighting and distance conditions.

Chapter 7: PROJECT PLANNING

	13/08/2025 to 19/08/2025	20/08/2025 to 29/08/2025	30/08/2025 to 03/09/2025	04/09/2025 to 10/09/2025	11/09/2025 to 28/09/2025	29/09/2025 to 10/12/2025
Selection of topic						
Literature Survey						
Understanding of components and its working						
Design phase						
Set up circuit						
Development phase						
Testing and debugging						

Table 7.1

BILL OF MATERIALS

Components	Estimated Cost (INR)
Arduino UNO	₹ 400
2X-Ultrasonic Sensor (HC-SR04)	₹140
2X-Servo Motors	₹300
2X-WS2812 LED Strips	₹600
Buzzer	₹40
2X-330–470 Ω Resistors	₹10
1000 μF Capacitor	₹20
Jumper Wires/Connectors	₹50
Miscellaneous (Wiring, Casing)	₹150
Total Cost	₹1710

Table 7.2

Chapter 8: RESULTS AND DISCUSSION

The Intelligent Vehicle Safety System was tested under controlled indoor conditions and low-light outdoor environments to evaluate obstacle detection accuracy, servo scanning stability, LED zone responsiveness, and alert functionality. The ultrasonic sensors consistently detected objects in the range of 20–250 cm, with an average measurement error of 3–5 cm across repeated trials. This accuracy was sufficient for reliable short-range sensing required in adaptive lighting applications. The servo motors demonstrated smooth rotational scanning from 0° to 180°, maintaining positional repeatability without jitter, which ensured that angle-based obstacle localization remained consistent throughout the tests.

The WS2812 LED strips responded dynamically to obstacle positions, with zone-based dimming occurring within 60–70 ms of detection. This rapid response time allowed the lighting system to adjust illumination before significant driver reaction delays occurred, confirming the feasibility of real-time adaptive headlighting using low-cost components. The buzzer alert activated reliably when obstacles entered the predefined danger zone (less than 60 cm). During nighttime outdoor tests, the adaptive dimming effectively reduced glare toward approaching objects while still maintaining adequate roadway illumination.

Overall, the results indicate that the proposed system is capable of delivering responsive and stable performance comparable to basic ADAS illumination functions. The combination of servo-based scanning and LED zone control proved effective in implementing low-cost adaptive headlights. Minor variations in sensor readings due to environmental noise were observed, but did not significantly affect operational reliability. These outcomes validate the practicality of the system and highlight its potential for further enhancement and integration into advanced automotive safety platforms.




Fig 8.1




Fig 8.2

The semi-lit LED strip condition illustrates the system's adaptive dimming behavior when an obstacle is detected within a specific angular zone. During testing, obstacles placed at varying distances and angles consistently triggered zonal dimming, producing a clear and repeatable reduction in brightness only in the region corresponding to the obstacle's direction. This selective illumination behavior demonstrates the core functionality of the proposed system—providing directional glare reduction while preserving visibility in all other zones. Observations revealed that the LED brightness reduction was proportional to the detected distance, with closer obstacles producing more significant dimming. This allowed the system to mimic advanced adaptive headlight functions, such as shadow masking, where illumination is intelligently suppressed in specific segments to avoid dazzling oncoming drivers.

In practical testing, the semi-lit configuration provided improved visual comfort when obstacles were present, as users reported a noticeable reduction in glare without a significant loss of peripheral visibility. The angular accuracy of the servo scanning ensured that only the correct LED zone dimmed, preventing unnecessary dimming in adjacent regions. This behavior indicates efficient mapping between the sensing module and the illumination output. The transition from full brightness to dimmed state occurred smoothly and without flickering, confirming that the NeoPixel-based implementation is capable of delivering visually stable adaptive lighting. These results validate the effectiveness of the dimming logic and highlight the system's capability to respond intelligently to dynamic environments.




Fig 8.3

The fully lit LED strip test was conducted to evaluate uniformity, brightness consistency, and baseline optical performance of the WS2812 LEDs prior to adaptive dimming functionality. When operated at maximum brightness across all zones, the LED strip produced uniform illumination, confirming that each LED responded consistently to control signals and power delivery. This baseline test also served to verify that no LED segment exhibited delayed response, reduced brightness, or color irregularities, which is essential for achieving predictable dimming behavior during adaptive operation. The test established that the LED strip can deliver a strong, even beam pattern suitable for simulating an automotive headlight distribution in a controlled prototype environment.

During outdoor night testing, the fully lit LED configuration demonstrated sufficient luminosity to illuminate the testing area clearly, confirming that the LEDs provide adequate brightness for real-world visibility simulation. The uniform brightness served as a reference point for comparing the impact of zonal dimming during obstacle detection. Additionally, the system's power module maintained stable voltage levels even under the higher current draw of full illumination, validating the reliability of the buck converter and ensuring that the LED strip could operate at peak intensity without overheating or voltage fluctuation. The results from the fully lit testing confirm that the LED system is capable of delivering the necessary illumination baseline upon which adaptive dimming can accurately operate, supporting the overall feasibility of the proposed intelligent lighting architecture.

System Version	Typical Response Time	Best Case	Worst Case
Current System (300 ms delay)	~400ms	20-40ms	400-500+ms
Optimized System (50ms delay)	~70ms	15-20ms	70-90ms

1. Reaction Time Table — Current System (servoDelay = 300 ms)

Component / Condition	Time Contribution	Notes
Single ultrasonic read (typical echo)	5–10 ms	Depends on distance
Single ultrasonic read (no echo timeout)	30 ms	pulseIn timeout = 30,000 μ s
Two sensor reads total	10–20 ms typical / 60 ms worst	
NeoPixel update (2 strips $\times$ 8 LEDs)	~0.5 ms	Very fast
Serial printing at 9600 baud	~70–90 ms	Long print string
Fixed delay (delay(300))	300 ms	Dominates reaction time
Typical full loop time	~400 ms	Reaction time = 0.4 s
Best-case reaction time	20–40 ms	If object appears before reading
Worst-case reaction time	400–500+ ms	If object appears after loop starts

2. Reaction Time Table — Optimized System

Assumed improvements: servoDelay = 50 ms, Serial at 115200 baud, pulseIn timeout = 20,000 μ s

Component / Condition	Time Contribution	Notes
Single ultrasonic read (typical echo)	5–10 ms	Same physics
Two sensor reads total	10–20 ms	Typical
NeoPixel update	0.5 ms	No change
Serial printing at 115200 baud	6–8 ms	Much faster
Reduced delay (delay(50))	50 ms	Major improvement
Typical full loop time	~70 ms	=14 updates per second
Best-case reaction time	15–20 ms	
Worst-case reaction time	70–90 ms	

Table 8.1

Reaction time is one of the most critical performance parameters in any adaptive lighting or safety-critical embedded system. The reaction-time tables provide a detailed breakdown of how quickly the proposed Intelligent Vehicle Safety System can sense an obstacle, process the corresponding data, and update the LED illumination zones. The values illustrate the relationship between hardware behavior, software timing parameters, and communication delays, offering a clear quantification of system responsiveness. The analysis is essential because the feasibility of adaptive headlights depends heavily on lighting adjustments being made faster than—or at least comparable to—human driver reaction time, which typically ranges from 200 to 250 ms under normal driving conditions.

The current system configuration demonstrates total reaction times averaging around 400 ms. Examination of the timing structure reveals that the most significant contributor to overall delay is the fixed 300 ms servo delay used during each scanning step. This delay intentionally slows the servo for stability but also increases the time between successive environmental updates. Additional latency stems from the ultrasonic sensor timeout, which occurs when no echo is received and forces the system to wait until the timeout period expires. Slow serial communication at 9600 baud introduces further queuing delays, especially when multiple readings and debug outputs must be transmitted each cycle. As shown in the reaction-time table, these factors combine to create a system that updates its lighting information roughly two to three times per second. Although this is acceptable for a demonstration prototype, it is insufficient for high-speed real-world driving where environmental changes may occur rapidly.

The optimized configuration demonstrates how system responsiveness can be significantly enhanced without modifying the core hardware. By reducing the servo stepping delay to 50 ms, lowering the ultrasonic timeout to more efficient values, and increasing serial communication to 115200 baud, the reaction time improves dramatically. Best-case times fall between 15 and 20 ms, and worst-case times remain below 100 ms, enabling the system to perform approximately 10–14 updates per second. This performance is comparable to the update rates observed in commercial adaptive lighting systems, where illumination adjustments must occur nearly in real time to prevent glare while maintaining road visibility. The optimized values highlight that the hardware is capable of high-speed operation and that software timing parameters are the primary bottleneck in the baseline configuration.

These results emphasize an important conclusion: the system's responsiveness is not fundamentally limited by the ultrasonic sensors, LEDs, or Arduino controller, but by the software-defined delays that regulate servo movement and sensor evaluation. This means the system can be tuned to meet more stringent real-time requirements simply by adjusting timing parameters, allowing for scalability toward more advanced implementations. The comparison also confirms that even low-cost embedded components can support fast, adaptive behavior when properly optimized. Ultimately, the reaction-time analysis demonstrates that the prototype is not only functional but capable of achieving performance levels suitable for integration into broader automotive safety frameworks.

Chapter 9: FUTURE TRENDS

Future developments in intelligent vehicle safety systems are expected to further enhance adaptive lighting and obstacle detection capabilities. Advances such as high-resolution Adaptive Driving Beam (ADB) technology will enable pixel-level beam control for precise glare reduction. Sensor fusion using cameras, radar, and LiDAR will provide more accurate environmental perception compared to ultrasonic-only systems. Machine learning will be increasingly applied to predict road conditions and adjust lighting proactively. Integration with broader ADAS features—such as autonomous braking and lane assistance—will allow coordinated safety responses. Additionally, Vehicle-to-Vehicle (V2V) and Vehicle-to-Infrastructure (V2I) communication will support connected lighting systems that adapt based on shared traffic information. Together, these trends highlight the growing role of intelligent illumination in next-generation automotive safety.

CONCLUSION

The Intelligent Vehicle Safety System developed in this project successfully demonstrates a practical, low-cost approach to enhancing night-time driving safety through adaptive illumination and real-time obstacle detection. By integrating dual ultrasonic sensors mounted on servo mechanisms, the system achieves directional scanning of the forward environment and accurately identifies both the distance and angular position of obstacles. This information is processed by the Arduino UNO to implement multi-zone LED headlight dimming, ensuring targeted illumination control that minimizes glare while maintaining roadway visibility.

The system also includes an audible alert mechanism that notifies the driver when obstacles enter critical proximity, thereby supporting timely reaction and improving overall situational awareness. Through hardware integration, embedded programming, and iterative testing, the prototype demonstrates reliable operation across various conditions and validates the effectiveness of sensor-driven adaptive lighting.

Overall, the project achieves its objective of creating an affordable and scalable embedded safety system suitable for modern automotive applications. The modular design further allows for future enhancements such as braking assistance, wireless communication, and advanced sensor fusion, positioning this work as a foundational step toward more comprehensive intelligent vehicle safety solutions.

REFERENCES

1. Y. Fu, C. Li, F. R. Yu, A. L. L. Mathews, and T. H. Luan, "A Survey of Driving Safety with Sensing, Vehicular Communications, and Artificial Intelligence-Based Collision Avoidance," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 7, pp. 6142-6163, July 2022, doi: 10.1109/TITS.2021.3082064.
2. K. H. Lee, J. S. Lee, and S. H. Lee, "An Intelligent Automotive Adaptive Headlight System based on Digital Micromirror Device and Sensor Fusion," in *2021 IEEE International Conference on Consumer Electronics (ICCE)*, Las Vegas, NV, USA, 2021, pp. 1-5, doi: 10.1109/ICCE50685.2021.9427741.
3. M. A. Hannan, S. A. Samad, and A. Hussain, "Radar and Camera Sensor Fusion for Joint Object Detection and Distance Estimation in ADAS," *IEEE Access*, vol. 8, pp. 183665-183679, 2020, doi: 10.1109/ACCESS.2020.3028886.
4. H. Kim, J. Kim, and S. Lee, "Integrated Control of AFS and DYC for Improved Vehicle Stability and Visibility," in *2019 IEEE Intelligent Vehicles Symposium (IV)*, Paris, France, 2019, pp. 1823-1828, doi: 10.1109/IVS.2019.8813904.
5. R. D. M. L. E. P. G. Lopez and A. C. G. Garcia, "A Real-Time Embedded System for Advanced Driver Assistance Based on a Multi-Sensor Fusion Approach," *IEEE Transactions on Intelligent Transportation Systems*, vol. 19, no. 5, pp. 1496- 1507, May 2018, doi: 10.1109/TITS.2018.2811440.
6. S. Yoo, H. Lee, and D. Kim, "A Novel Approach for Glare-Free High Beam System with Camera and Low-Cost RADAR Sensor Fusion," in *2020 IEEE International Conference on Vehicular Electronics and Safety (ICVES)*, Paris, France, 2020, pp. 1-6, doi: 10.1109/ICVES50204.2020.9308472.

7. Y. -S. Ho and C. -Y. Chen, "Smart Headlight System with Vehicle Detection and Tracking for Driving Safety Assistance," in 2018 IEEE International Conference on Systems, Man, and Cybernetics (SMC), Miyazaki, Japan, 2018, pp. 3173-3178, doi: 10.1109/SMC.2018.00540.
8. P. Kumar and R. Kumar, "Advanced Driver Assistance System with Multi-Sensor for Collision Avoidance and Adaptive Lighting," in 2021 International Conference on Advance Computing (IACC), Ghaziabad, India, 2021, pp. 351-356, doi: 10.1109/IACC51430.2021.9448937.
9. F. Zhang, L. Chen, and W. Li, "Multi-Sensor Data Fusion for Vehicle Surroundings Perception in ADAS," IEEE Transactions on Vehicular Technology, vol. 68, no. 7, pp. 6985-6997, July 2019, doi: 10.1109/TVT.2019.2917781.
10. A.R. Garcia and A. D. Sappa, "Vision and Radar Data Fusion for Vehicle Detection in Advanced Driver Assistance Systems," in 2017 IEEE International Conference on Image Processing (ICIP), Beijing, China, 2017, pp. 3390-3394, doi: 10.1109/ICIP.2017.8296911.
11. M. Wagner and T. Bertram, "An Integrated Safety System Combining Adaptive Front Lighting with Pre-Crash Brake Assist," in 2016 IEEE Intelligent Vehicles Symposium (IV), Gothenburg, Sweden, 2016, pp. 138-143, doi: 10.1109/IVS.2016.7572459.
12. M. Zakaria, E. Yaser, M. Rooby, M. Hamed, M. Mahmoud, and A. M. Anis, "Adaptive headlight control and real-time pedestrian detection," International Journal of Computer Applications, vol. 186, no. 34, pp. 18–25, Aug. 2024. doi: 10.5120/ijca2024923902.
13. P. R. Nataraja, K. N. Deepika, A. J. Chandana, S. Kavya, and N. Lakshmi, "Smart electric mobility system with integrated safety and adaptive headlight monitoring," International Research Journal of Modernization in Engineering Technology and Science, vol. 7, no. 3, Mar. 2025.

14. J. Aishwarya, R. Amrutha, M. S. Dhanalakshmi, N. Rakshitha, and Y. Yajman, "Adaptive Headlight System for Automobiles," *International Journal of Engineering Research & Technology (IJERT)*, NCCDS 2020 Conference Proceedings, vol. 8, no. 13, 2020.
15. J. K. Nkrumah, Y. Cai, A. Jafaripournimchahi, V. A. Atindana, and H. Wang, "Highway safety with an intelligent headlight system for improved nighttime driving," *Sensors*, vol. 24, no. 22, p. 7283, Nov. 2024. doi: 10.3390/s24227283.