

A20-22 L EVO kv924

Product description and features

The 8, 10 and 14-pole outrunner motors of the A20 series are available in 4 lengths (S, M, L, XL), with a voltage range of 7.2V to 12.6V. As a result, they cover a wide range of applications from the 250g indoor model up to the 1.5kg electric glider. The A20 series is double ball bearing mounted, has an interchangeable 3mm shaft and can be front or back mounted.

The weight-optimised high-end motor A20-22 L EVO kv924 with a weight of only 55g is ideal for motor models up to 600g and gliders up to 900g.

Accessories

You will find the appropriate controller, batteries and a suitable propeller in the accessories tab.

Delivery contents

1x A20-22 L EVO kv924, accessories for front and backmount, prop driver and instructions.

Drive Recommendations

A20-22 L EVO kv924		
Item no.: 97800007		
Propeller	APC SF 10x4,7	ACC 11x6
LiPo	3S	3S
Voltage [V]	11,0	11,0
Current [A]	15,0	17,0
Power [W]	165	187
RPM	7230	7200
Controller [A]	20	20
Timing [°]	20-25	20-25

Motraxx SR555SHP-3247S-75 Universal Brushed elektrisk motor



min. Betriebsspannung	10,0 VDC
max. Betriebsspannung	14,0 VDC
Nennspannung	12,0 VDC
Leerlaufdrehzahl	5.887 rpm
Leerlaufstrom	0,25 A
Haltestrom	8,56 A
Haltemoment	172,50 mNm
max. Ausgangsleistung	24,2 W
Polzahl	5
Entstörkondensator(en)	2 x 47 nF
Bürstenart	Kohlebürsten
Lastmoment	25,20 mNm
Lastdrehzahl	5.024 rpm
Laststrom	1,46 A
minimale Breite oder Durchmesser	36,0 mm

Produktserie: 550-Serie