ANATOMY OF THE AGENTIC STACK

Architecting Modern AI Systems for Production



NotebookLM

AUTONOMY IS A SPECTRUM, NOT A TOGGLE SWITCH

True agentic loops are rare. **80–90%** of **production AI systems** are **structured workflows** handling **predictable pipelines**, with agent behavior layered on top strictly for edge cases and unstructured inputs.



ENGINEERING WHITE PAPER – SYSTEM ARCHITECTURE v1.4
ASPECT RATIO: 16:9

NotebookLM

DISTINGUISHING STRUCTURE FROM AUTONOMY

	AI WORKFLOWS	AI AGENTS
CONTROL FLOW	**Predefined, explicit** code paths. 	Dynamic, autonomous **loops.** 
DECISION MAKING	Hard-coded logic & fixed branches. 	LLM-driven **reasoning** & reflection. 
TOOL USAGE	Orchestrated sequentially by code.	Autonomously selected mid-task. 
ERROR RECOVERY	Static fallback branches. 	Iterative retry with new strategies based on tool feedback. 
IDEAL SCENARIO	Data pipelines, routing, predictable document generation. 	Complex research, open-ended bug fixing, unstructured environment exploration.

ENGINEERING WHITE PAPER – SYSTEM ARCHITECTURE v1.5
ASPECT RATIO: 16:9

NotebookLM

WORKFLOW vs. AGENT DECISION MATRIX: A STRUCTURED APPROACH

DEFINING THE PATH **TO AUTOMATION**



THE GOLDEN RULE:
Use workflows for structure and reliability.

Use agents for the unknown and exploratory.

NotebookLM

THE TWO HALVES OF THE MODERN AGENT

An agent cannot function with just one half. Model Context Protocol (MCP) provides the raw tools to interact with the world. Agent Skills provide the procedural knowledge of when and how to use those tools.



ROLE	**Skills** = Procedural Knowledge & Instruction	**MCP** = Connectivity & Data Access
FORMAT	**Skills** = Markdown + YAML (SKILL.md)	**MCP** = JSON-RPC / SDKs
EXECUTION	**Skills** = Runs in the model's context window	**MCP** = Runs as local/remote server processes
EXAMPLE	**Skills** = Invoice Reconciler (SOP for checking IDs)	**MCP** = Stripe-MCP (Exposes the actual API)

NotebookLM

MCP ACTS AS THE UNIVERSAL ADAPTER FOR AI CONNECTIVITY

Instead of writing custom API wrappers for every combination of LLM and external tool, the Model Context Protocol standardizes the exchange. It handles discovery, schema definition, and tool invocation so the agent only sees a uniform, structured interface.



NotebookLM

CONTINUOUS AUTONOMOUS EXECUTION

The agent iterates autonomously through exploration, planning, execution, and verification. However, this infinite loop carries a hidden architectural constraint: token accumulation.



NotebookLM

THE CONTEXT WINDOW CRISIS

Claude's context window holds the entire conversation, including every message, file read, and command output. During a single debugging session, a monolithic agent can generate tens of thousands of tokens. As the context window fills, performance inevitably degrades, instructions are forgotten, and costs skyrocket.



NotebookLM

ISOLATING OVERHEAD WITH SUBAGENTS

To preserve the primary context window, heavy investigative work is delegated. Subagents run in entirely separate context windows with restricted toolsets, crunching massive amounts of data and returning only the synthesized answers back to the main thread.



NotebookLM

ARCHITECTURAL TRADEOFFS IN AGENT SCALING

	MONOLITHIC AGENT	SUBAGENT ARCHITECTURE (CLAUDE CODE)	MULTI-AGENT SWARMS (RUFLO/ANN)
CONTEXT ISOLATION	 Single shared context window.	 Isolated windows for specific tasks.	 Hierarchical, distributed context nodes.
TOKEN COST	HIGH (RAPID CONTEXT DEGRADATION).	MEDIUM (REDUCES MAIN-THREAD COST).	HIGH (MASSIVE COORDINATION OVERHEAD)
CAPABILITIES	Cheap to start, prone to hallucination on long tasks.	Delegates heavy reads, cannot spawn recursive subagents.	Capable of enterprise-scale feature development.
DRIFT CONTROL	Requires manual human intervention.	 Relies on main thread verification.	 Requires Raft consensus and Queen node state management.

NotebookLM

NATIVE MCP LACKS ENTERPRISE GOVERNANCE

As teams scale from a few integrations to full production, native MCP breaks down. It lacks centralized governance, cross-team identity management, and audit observability. A code-review agent shouldn't see production database tools, but native MCP has no mechanism to restrict this visibility.



WARNING: CHAOTIC TOPOLOGY - UNMANAGEABLE AT SCALE

NotebookLM

RESTORING ORDER WITH MCP GATEWAYS

Gateways sit between the agent layer and the tool layer. They enforce authentication, restrict tool visibility based on specific agent identity, apply rate limits, and provide the crucial audit trails required for compliance and debugging.



⚠ WARNING: ORDERLY TOPOLOGY - MANAGEABLE AT SCALE

NotebookLM

INTELLIGENT TASK ROUTING LIMITS API EXPENDITURE

Advanced orchestrators use semantic routing and local WebAssembly (WASM) to intercept simple code edits. By bypassing the LLM entirely for basic transforms, teams can reduce token usage by 30-50% and extend context limits drastically.



NotebookLM

COORDINATING SWARMS AND PREVENTING GOAL DRIFT

In highly complex tasks, agents organize into hierarchical swarms. “Queen” nodes validate worker against original goals, enforcing short task cycles and strict verification gates to prevent agents from spiraling into hallucinations.



Requires Raft/Byzantine consensus to maintain authoritative state and prevent conflicting decisions.

NotebookLM

SELF-EVOLVING SYSTEMS VIA TEXTUAL BACKPROPAGATION

Treating multi-agent systems like layered neural networks allows for continuous learning. In the backward phase, agents refine both global coordination and local prompts through iterative textual feedback, fundamentally evolving their roles and improving accuracy post-deployment.



ENGINEERING WHITE PAPER - SYSTEM ARCHITECTURE v1.8
ASPECT RATIO: 16:9

NotebookLM

THE UNIFIED AGENTIC STACK (2026)

A complete, production-ready architecture
standardizing discovery, execution, and security.



NotebookLM

THE ARCHITECT'S PLAYBOOK

1. DEFAULT TO WORKFLOWS

Hardcode the structure, use **agents** exclusively for the unstructured gaps.



2. PROTECT THE CONTEXT WINDOW

Ruthlessly isolate heavy data exploration into specialized **subagents**.



3. SEPARATE BRAINS FROM HANDS

Define workflows via **Skills**, and connect to data exclusively via **MCP**.



4. GOVERN THE SWARM

Never expose raw MCP directly to production **swarms**.
Gateways are mandatory for identity, security, and auditability.



NotebookLM