



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 03

Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

- **State Space:** The actual problem environment containing all possible states.
- **Search Tree:** The algorithm's exploration structure built from those states during the search process. It represents the possible action sequences being investigated to find a solution.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

The reached set solves the problem of repeatedly exploring the same states in a graph. In graph search, different paths can lead to the same state, creating cycles and duplicate work. By storing every already-explored state in the reached set, the algorithm avoids revisiting those states and converts the search from a tree search into a more efficient graph search.

Without the reached set, the DFS agent could become trapped in loops. For example, in a grid environment, DFS might move from one position to another and then return to a previously visited position repeatedly. Since DFS explores deeply before backtracking, it could spend a very long time following cycles and may never reach the food pellet, even if a valid path exists. The reached set prevents this by ensuring each grid state is expanded only once.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

In the simulation, BFS (Breadth-First Search) generates a path that is usually direct and shortest, while DFS (Depth-First Search) often produces longer, winding paths with unnecessary movements.

BFS is guaranteed to be optimal in this grid because it explores all possible states level by level from the starting position. It first checks all positions that are one step away, then all positions two steps away, and so on. Since every movement in the grid has the same cost (one step), the first time BFS reaches the food pellet, it has found the path with the minimum number of actions.

DFS, on the other hand, explores one branch as deeply as possible before backtracking. It does not compare path lengths and may follow a long route away from the food before discovering a shorter alternative. Although DFS can eventually find a solution, it is not guaranteed to find the shortest path, resulting in winding and suboptimal routes in the simulation.

4. (Evaluate) If we scaled `visual_grid_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

- **BFS/UCS:** Memory-efficient in finding optimal paths? No — they require large memory because they store many frontier nodes, but they guarantee optimal solutions (under the correct conditions).
- **DFS:** Memory-efficient? Yes — it stores fewer nodes, but it may produce longer, inefficient paths and can take much longer to find the goal.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING