

Package ‘aocseq’

January 7, 2025

Type Package

Title A package designed for the analysis of single cell RNA sequencing data, can be used to model gene expression changes caused by the activation of cells.

Version 0.1.0

Author Mae Woods, Noah Crooks

Maintainer <mae.woods@bcm.edu>

Description Software initially developed to process data of the activation of cells and sequencing.

License BSD2

Encoding UTF-8

LazyData true

Imports Seurat, matrixStats, readr, Rcpp, stats, BiocParallel, Matrix, MASS, VGAM, bbmle, gamlss, maxLik, pscl

RoxygenNote 7.3.2

R topics documented:

AnnotateCellTypes	2
CellTypeLoop	3
ClassifyCells	4
ClassifyCellTypes	5
CombineData	6
construct_tree	7
DEsingle	8
e_step	10
GetGeneSignature	10
GetSpecificCells	11
GMM_demux	11
Iso_forest	12
MakeReference	13
m_step	14
NormalizationScore	14
percent_outlier	15
QCPlot	15
SaveHeatmap	16
segmentPlot	17
SetCellType	18
UMAPReduce	18

Index**20**

AnnotateCellTypes	<i>List clonotypes and the proportion of cells expressing a choice of marker genes at normalized counts greater than the control</i>
-------------------	--

Description

This function will read in Seurat objects processed by `aocseq::CombineData` and generate a ranked spreadsheet of clonotypes grouped by CDR3 beta sequence. The table displays the percentage of CD4 and CD8 cells expressing a choice of marker genes at normalized counts greater than the control.

Usage

```
AnnotateCellTypes(
  Clonal_Obs,
  goi,
  cellType = "cdr3_na",
  goi.threshold = 0.975,
  TCR = TRUE,
  index.control.input = 1,
  conditions = 1,
  path = "",
  names.spreadsheet = c(-1),
  preset = 1,
  threshold.entry = FALSE
)
```

Arguments

<code>Clonal_Obs</code>	A Seurat object pre-processed with <code>aocseq::CombineData</code> .
<code>goi</code>	A marker of interest.
<code>goi.threshold</code>	Threshold of the goi normalized control counts per cell.
<code>conditions</code>	Number of experiments within <code>ClonalData</code> object
<code>path</code>	String. Directory of the table output.
<code>names.spreadsheet</code>	List. Control and sample names.
<code>preset</code>	Bool. If set to 1, the control is part of the dataset. If 0, a threshold value for each condition must be set.
<code>threshold.entry</code>	List. List of thresholds for each condition if <code>preset</code> is 0.
<code>index.control</code>	List. Index of the control sequencing sample for each condition.

Value

A data frame containing clonotypes and summary statistics of transcript expression.

CellTypeLoop	<i>Return a data frame of meta data associated with single cell data sets that contains a distance from a reference that is determined using the isolation forest algorithm</i>
--------------	---

Description

This function will return the percentage of cells that are outliers when compared to a reference data set.

Usage

```
CellTypeLoop(  
  cell.data,  
  cell.types,  
  reference.data,  
  genes,  
  ntrees,  
  maxheight,  
  solver = TRUE,  
  subsample.count = ncol(reference.data) + 1,  
  cutoff = 0.75  
)
```

Arguments

<code>cell.data</code>	A Seurat object containing cells that are to be assigned a distance.
<code>cell.types</code>	A list of the cell types (currently this is clonotypes).
<code>reference.data</code>	Normalized reference data.
<code>genes</code>	Genes to pull from the query dataset.
<code>ntrees</code>	Number of trees used for the isolation forest.
<code>maxheight</code>	Maximum height used for the isolation forest.
<code>subsample.count</code>	Subsampling number for isolation forest.
<code>cutoff</code>	Maximum cutoff.

Value

A Seurat object containing metadata with the Rscore.

ClassifyCells	<i>Return the Rscore of single cells in a query dataset compared to reference</i>
---------------	---

Description

This function will compute the response score (Rscore) for each single cell in samples that have been activated and sequenced. For each cell in the reference, we construct the positive definite covariance matrix of the reference data set reference.data. Takes as input two Seurat objects, one containing the query cells and another containing the reference. A gene list used to construct the distance and output path for plotting. Other parameters are listed for debugging, but can be left as default values. there are different functions for different genesets

Usage

```
ClassifyCells(
  output.array,
  reference.data,
  gene.list,
  cell.types = c(),
  distance = 0,
  scramble = FALSE,
  withSCT = FALSE,
  ntrees = 10,
  maxheight = 20,
  PRINT = FALSE,
  file.path = ".",
  verbose = TRUE
)
```

Arguments

output.array	A Seurat object containing cells that are to be assigned an Rscore.
reference.data	Matrix of doubles. Reference data used to calculate the Rscore.
gene.list	Vector. List of genes in the gene signature.
scramble	Bool. To asses the effect of the gene signature on the Rscore, select a random set of genes and compute their distance from the reference data.
verbose	Print progress bars and output
normalized.array	A matrix of query data normalized counts.

Value

A Seurat object containing metadata with the Rscore.

ClassifyCellTypes	<i>Combine single cell data and annotate with cell labels based on functionality</i>
-------------------	--

Description

This function will read in Seurat objects that have been processed with aocseq, and accompanying annotation tables to classify clonotypes using distance scores. Takes as input gene expression from scRNAseq and VDJ enrichment. Outputs a classification table that lists samples and each clonotype classified.

Usage

```
ClassifyCellTypes(  
  Clonal_Obs,  
  Clonotypes,  
  within.sample = FALSE,  
  method = "ZINB",  
  goi = c("IFNG"),  
  percentile = 0.01,  
  path = "",  
  path.glist = "",  
  reference = matrix(nrow = 1, ncol = 1),  
  verbose = TRUE  
)
```

Arguments

Clonal_Obs	A seurat object. Pre-processed with aocseq.
Clonotypes	Table. An annotation table from the aocseq package.
method	Vector of "ZINB", "Mahalanobis", "z-score" and "Taxi cab". "ZINB" can be used without a reference dataset.
goi	Gene. Gene of interest (goi). For use with "ZINB" classification.
percentile	Double. Percentile cutoff for distance based scoring metrics.
path	Directory for output tables.
verbose	Print progress bars and output.

Value

A Seurat object list containing metadata and VDJ annotations.

CombineData

*Combine single cell data and annotate with cell labels based on functionality***Description**

This function will read in 10X genomics outputs from cellranger and combine multiple Seurat objects, assigning labels based on additional tables stored in csv format. Takes as input gene expression from scRNAseq and VDJ enrichment. A gene list used to estimate specificity can be chosen and is application specific. Other parameters are listed for debugging, but can be left as default values.

Usage

```
CombineData(
  gex.path,
  marker.gene,
  vdj.path = c(),
  threshold.cutoff = 0.975,
  file.saved = "samples.rds",
  index.control = 1,
  c.index = c(-1),
  sample.name = c(-1),
  preset = 1,
  threshold.entry = 0,
  demultiplex = FALSE,
  demultiplex.index = c(),
  nameshashtags = c(),
  n.ht.per.sample = 1,
  tenX_conversion = "true",
  nFeature_RNA_lower = 100,
  nFeature_RNA_upper = 10000,
  nvariable_features = 3000,
  percent.mt_upper = 5,
  data.input = "raw",
  upperQ = 0.95,
  lowerQ = 0.05,
  verbose = TRUE,
  QC_plots = FALSE
)
```

Arguments

<code>gex.path</code>	path to gene expression data in the format of cellranger feature barcode matrices
<code>marker.gene</code>	list of marker genes used for specificity analysis
<code>vdj.path</code>	path to VDJ expression data in the format of cellranger csv files
<code>threshold.cutoff</code>	list of marker genes used for specificity analysis
<code>file.saved</code>	directory for storing Seurat object RDS files
<code>index.control</code>	index of the control sequencing sample

c.index	index of the control sequencing sample
sample.name	index of the control sequencing sample
preset	If set to 1, preset determines the threshold for cutoff if a control is included in the assay. If set to 0 a cutoff is set by the threshold.entry, which defines what value is high for all samples. If set to 2 a cutoff is set per sample using
threshold.entry	Double. Sets the percentile above which gene expression is labelled as high.
demultiplex	Boolean value used to indicate if the data was hashtagged
demultiplex.index	Boolean value used to indicate if the data was hashtagged
n.ht.per.sample	Boolean value used to indicate if the data was hashtagged
tenX_conversion	Boolean value used to indicate if the data was hashtagged
nFeature_RNA_lower	Boolean value used to indicate if the data was hashtagged
nFeature_RNA_upper	Boolean value used to indicate if the data was hashtagged
nvariable_features	Boolean value used to indicate if the data was hashtagged
percent.mt_upper	Boolean value used to indicate if the data was hashtagged
verbose	Print progress bars and output
QC_plots	Print progress bars and output
names.hashtag	Boolean value used to indicate if the data was hashtagged

Value

A Seurat object list containing metadata and VDJ annotations.

construct_tree	<i>Build a binary tree from a numerical data frame</i>
----------------	--

Description

This function will build a binary tree from a numerical data frame and return a data frame containing each unique data point from the input data and the height at which each data point becomes "isolated" (reaches an external node) or the max_height.

Usage

```
construct_tree(data, current_height, max_height, kurtosis = TRUE)
```

Arguments

data	a numerical data frame
current_height	a parameter which tracks the current height of a given construct_tree instance, allows for recursive calling of the function
max_height	the maximum height the tree will grow to before stopping
kurtosis	splits the data based on the kurtosis over the maximum gene distribution across the cells in the input data.

Value

a data frame containing the data for each unique point in the input data and the height at which that point was isolated

DEsingle	<i>This is a copy of DEsingle that was lifted from the original package, see https://bioconductor.org/packages/release/bioc/html/DEsingle.html and included in the aocseq package with modifications for package compatibility DEsingle: Detecting differentially expressed genes from scRNA-seq data This function is used to detect differentially expressed genes between two specified groups of cells in a raw read counts matrix of single-cell RNA-seq (scRNA-seq) data. It takes a non-negative integer matrix of scRNA-seq raw read counts or a SingleCellExperiment object as input. So users should map the reads (obtained from sequencing libraries of the samples) to the corresponding genome and count the reads mapped to each gene according to the gene annotation to get the raw read counts matrix in advance.</i>
----------	---

Description

This is a copy of DEsingle that was lifted from the original package, see <https://bioconductor.org/packages/release/bioc/html/DEsingle.html> and included in the aocseq package with modifications for package compatibility DEsingle: Detecting differentially expressed genes from scRNA-seq data This function is used to detect differentially expressed genes between two specified groups of cells in a raw read counts matrix of single-cell RNA-seq (scRNA-seq) data. It takes a non-negative integer matrix of scRNA-seq raw read counts or a SingleCellExperiment object as input. So users should map the reads (obtained from sequencing libraries of the samples) to the corresponding genome and count the reads mapped to each gene according to the gene annotation to get the raw read counts matrix in advance.

Usage

```
DEsingle(counts, group, goi, parallel = FALSE, BPPARAM = bpparam())
```

Arguments

counts	A non-negative integer matrix of scRNA-seq raw read counts or a SingleCellExperiment object which contains the read counts matrix. The rows of the matrix are genes and columns are samples/cells.
group	A vector of factor which specifies the two groups to be compared, corresponding to the columns in the counts matrix.
parallel	If FALSE (default), no parallel computation is used; if TRUE, parallel computation using BiocParallel, with argument BPPARAM.
BPPARAM	An optional parameter object passed internally to <code>bplapply</code> when <code>parallel=TRUE</code> . If not specified, <code>bpparam()</code> (default) will be used.

Value

A data frame containing the differential expression (DE) analysis results, rows are genes and columns contain the following items:

- theta_1, theta_2, mu_1, mu_2, size_1, size_2, prob_1, prob_2: MLE of the zero-inflated negative binomial distribution's parameters of group 1 and group 2.
- total_mean_1, total_mean_2: Mean of read counts of group 1 and group 2.
- foldChange: total_mean_1/total_mean_2.
- norm_total_mean_1, norm_total_mean_2: Mean of normalized read counts of group 1 and group 2.
- norm_foldChange: norm_total_mean_1/norm_total_mean_2.
- chi2LR1: Chi-square statistic for hypothesis testing of H0.
- pvalue_LR2: P value of hypothesis testing of H20 (Used to determine the type of a DE gene).
- pvalue_LR3: P value of hypothesis testing of H30 (Used to determine the type of a DE gene).
- FDR_LR2: Adjusted P value of pvalue_LR2 using Benjamini & Hochberg's method (Used to determine the type of a DE gene).
- FDR_LR3: Adjusted P value of pvalue_LR3 using Benjamini & Hochberg's method (Used to determine the type of a DE gene).
- pvalue: P value of hypothesis testing of H0 (Used to determine whether a gene is a DE gene).
- pvalue.adj.FDR: Adjusted P value of H0's pvalue using Benjamini & Hochberg's method (Used to determine whether a gene is a DE gene).
- Remark: Record of abnormal program information.

Author(s)

Zhun Miao.

See Also

[DEtype](#), for the classification of differentially expressed genes found by [DEsingle](#).

[TestData](#), a test dataset for DEsingle.

Examples

```
# Load test data for DEsingle
data(TestData)

# Specifying the two groups to be compared
# The sample number in group 1 and group 2 is 50 and 100 respectively
group <- factor(c(rep(1,50), rep(2,100)))

# Detecting the differentially expressed genes
results <- DEsingle(counts = counts, group = group)

# Dividing the differentially expressed genes into 3 categories
results.classified <- DEtype(results = results, threshold = 0.05)
```

e_step	<i>e_step</i>
--------	---------------

Description

e_step

Usage

```
e_step(x, mu.vector, sd.vector, alpha.vector)
```

Arguments

sd.vector	Vector containing the mean of each component
alpha.vector	Vector containing the mixing weights of each component

Value

Named list containing the loglik and posterior.df

GetGeneSignature	<i>Export differential gene expression from several different samples and phenotypes</i>
------------------	--

Description

This function will take a set of annotation spreadsheets and export differential expression between different cell types labelled by their marker genes. Currently the phenotypic separation is CD4 and CD8, but the reader is encouraged to generate as many subsets as needed for downstream analysis.

Usage

```
GetGeneSignature(
  Clonal_Obs,
  clonotype.path,
  save.dir,
  goi,
  FClim = 0,
  specific.pval = 10^(-5),
  bystander.pval = 10^(-2),
  set.min.pct = 0.25,
  logfc.threshold = 0
)
```

Arguments

Clonal_Obs	A Seurat object pre-processed with aocseq::CombineData.
clonotype.path	Character array. Directory of an aocseq clonotype annotation table.
save.dir	Directory for storing differentially expressed genes.
goi	Character array. Gene name, a marker of interest.
verbose	Print progress

Value

return an assay containing predicted expression value in the data slot

GetSpecificCells	<i>Subsets a SEURAT object based on a list of meta data for the CD4 and CD8 subsets</i>
------------------	---

Description

This function will read in Seurat objects processed by traceseq::AnnotateClonotypes or any other software based on cell annotation and subset the SEURAT array accordingly

Usage

```
GetSpecificCells(Clonal_Obs, expression, phenotype, tcrseq, goi_v)
```

Arguments

Clonal_Obs	A Seurat object.
expression	Choice of "high" or "unassigned".
phenotype	CD4 or CD8 clasification.
tcrseq	List of TCRs to mark clonotypes included in the analysis.
goi_v	Gene of interest.

Value

A subset of a Seurat object processed with aocseq.

GMM_demux	<i>Flexible implementation of the GMM demux algorithm</i>
-----------	---

Description

Demultiplex arbitrary number of hashtags

Usage

```
GMM_demux(
  s.name,
  data,
  hashtag.index,
  nameshashtags,
  set.col.name = "Hashtags",
  Seurat_Object = FALSE
)
```

Arguments

s.name	Input data. 10x object with hashtags
data	Input data. 10x object with hashtags
hashtag.index	list containing positions of hashtags to be demultiplexed
nameshashtags	Subsets of the sample for new orig.ident
set.col.name	Subsets of the sample for new orig.ident
Seurat_Object	Name of the sample

Value

A Seurat object that has been split by hastagged demultiplexing.

Iso_forest	<i>Build many trees on samples from data and average the heights</i>
------------	--

Description

Build many trees on samples from data and average the heights

Usage

```
Iso_forest(
  data,
  num_trees,
  max_height,
  subsample_count = nrow(data),
  kurtosis_param = TRUE
)
```

Arguments

data	a numerical data frame
num_trees	the number of trees to build and average over
max_height	the maximum height each tree will grow to before stopping
subsample_count	the size of the random sample that a tree will be built on. Cannot be larger than the number of rows in the data
kurtosis_param	splits the data based on the kurtosis over the maximum gene distribution across the cells in the input data.

Value

a data frame containing the data for each unique point in the input data and the average height at which that point was isolated

MakeReference	<i>These are functions to produce reference datasets to compute a response score of activated or perturbed T cells.</i>
---------------	---

Description

This function returns a matrix of normalized gene expression along the rows and cells along the columns.

Usage

```
MakeReference(
  cell.data,
  gene.list,
  cell.type.list,
  celltype = cdr3_na,
  threshold = 0.975,
  n.inlist = 10,
  cellcycle = FALSE,
  SCT = FALSE,
  verbose = TRUE
)
```

Arguments

<code>cell.data</code>	List of Seurat objects. Seurat objects containing expression data processed. by aocseq that will be used to score query T cell response.
<code>gene.list</code>	List of genes to be included in the reference matrix.
<code>cell.type.list</code>	Character list. List of cell types to include in the reference data.
<code>celltype</code>	Cell type to access metadata of reference dataset.
<code>n.inlist</code>	Number of genes with high expression in each cell included in the reference matrix.
<code>cellcycle</code>	Adds Seurat cell cycle phase to reference data.
<code>SCT</code>	Returns reference matrix in sctransform space.
<code>verbose</code>	Print progress bars and output.

Value

A reference matrix.

m_step	Maximization Step of the EM Algorithm
--------	---------------------------------------

Description

Update the Component Parameters

Usage

```
m_step(x, posterior.df)
```

Arguments

x	Input data.
posterior.df	Posterior probability data.frame.

Value

Named list containing the mean (mu), variance (var), and mixing weights (alpha) for each component.

NormalizationScore	<i>This function normalizes the data from the R implementation of the isolation forest</i>
--------------------	--

Description

This function normalizes the data from the R implementation of the isolation forest

Usage

```
NormalizationScore(df)
```

Arguments

df	A data frame containing isolation forest distances
----	--

Value

Normalized values

percent_outlier	<i>Return a data frame of meta data associated with single cell data sets that contains a distance from a reference</i>
-----------------	---

Description

This function will return the percentage of cells that are outliers when compared to a reference data set.

Usage

```
percent_outlier(
  test_set,
  reference.data,
  genes,
  ntrees,
  maxheight,
  subsample.count = ncol(reference.data) + 1,
  cutoff = 0.75
)
```

Arguments

reference.data	Normalized reference data.
genes	Genes to pull from the query dataset.
ntrees	Number of trees used for the isolation forest.
maxheight	Maximum height used for the isolation forest.
subsample.count	Subsampling number for isolation forest.
cutoff	Maximum cutoff.
cell.data	A Seurat object containing cells that are to be assigned a distance.
cell.types	A list of the cell types (currently this is clonotypes).

Value

A data frame with the percentage of cells that are outliers

QCPlot	<i>QC plot</i>
--------	----------------

Description

This function will take a set of annotation spreadsheets and export differential expression between different cell types labelled by their marker genes. Currently the phenotypic separation is CD4 and CD8, but the reader is encouraged to generate as many subsets as needed for downstream analysis.

Usage

```
QCPlot(
  Clonal_Obs,
  nFeature_RNA_lower = 100,
  nFeature_RNA_upper = 10000,
  nCount_RNA_lower = 100,
  nCount_RNA_upper = 10000,
  percent.mt_upper = 5
)
```

Arguments

`Clonal_Obs` A Seurat object pre-processed with `aocseq::CombineData`.

`clonotype.path` Character array. Directory of an aocseq clonotype annotation table.

`save.dir` Directory for storing differentially expressed genes.

`goi` Character array. Gene name, a marker of interest.

`verbose` Print progress

Value

return an assay containing predicted expression value in the data slot

SaveHeatmap	<i>This function will take a set of annotation spreadsheets and export differential expression between different cell types labelled by their marker genes. Currently the phenotypic separation is CD4 and CD8, but the reader is encouraged to generate as many subsets as needed for downstream analysis.</i>
-------------	---

Description

This function will take a set of annotation spreadsheets and export differential expression between different cell types labelled by their marker genes. Currently the phenotypic separation is CD4 and CD8, but the reader is encouraged to generate as many subsets as needed for downstream analysis.

Usage

```
SaveHeatmap(
  Resting.cells,
  Act.ref,
  CellsInRef,
  path.glist,
  heatmap.path,
  verbose = TRUE
)
```

Arguments

verbose	Print progress
Clonal_Obs	A Seurat object pre-processed with aocseq::CombineData.
clonotype.path	Character array. Directory of an aocseq clonotype annotation table.
save.dir	Directory for storing differentially expressed genes.
goi	Character array. Gene name, a marker of interest.

Value

return an assay containing predicted expression value in the data slot

segmentPlot	<i>Functions to plot data stored in clonal objects at normalized counts greater than the control</i>
-------------	--

Description

Functions to plot data stored in clonal objects at normalized counts greater than the control

Usage

```
segmentPlot(
  SummaryTable,
  names = c("S1", "S2"),
  segment.names = c("S1", "S2"),
  n.segments = 50,
  tune.gap = 0.005,
  segment.names.spacer = "16mm",
  percentage.spacer.1 = "14mm",
  percentage.spacer.2 = "13mm",
  segment.col = c("green", "blue"),
  ribbon.hue = "pink",
  path = "circos.pdf"
)
```

Arguments

SummaryTable	A Seurat object pre-processed with aocseq::CombineData.
names	A marker of interest.
n.segments	Threshold of the goi normalized control counts per cell.
tune.gap	List. Index of the control sequencing sample for each condition.
segment.names.spacer	Number of experiments within ClonalData object
percentage.spacer.1	String. Directory of the table output.
percentage.spacer.2	List. Control and sample names.

<code>segment.col</code>	Bool. If set to 1, the control is part of the dataset. If 0, a threshold value for each condition must be set.
<code>ribbon.hue</code>	List. List of thresholds for each condition if preset is 0.
<code>path</code>	Path to outpt file.

Value

A data frame containing clonotypes and summary statistics of transcript expression.

<code>SetCellType</code>	<i>This function determines what constitutes an outlier and what does not in the isolation forest algorithm</i>
--------------------------	---

Description

This function determines what constitutes an outlier and what does not in the isolation forest algorithm

Usage

```
SetCellType(cell.data, cell.types)
```

Arguments

<code>cell.data</code>	A Seurat Object
<code>cell.types</code>	Single cell metadata

Value

Normalized values

<code>UMAPReduce</code>	<i>Export differential gene expression from several different samples and phenotypes</i>
-------------------------	--

Description

This function will take a set of annotation spreadsheets and export differential expression between different cell types labelled by their marker genes. Currently the phenotypic separation is CD4 and CD8, but the reader is encouraged to generate as many subsets as needed for downstream analysis.

Usage

```
UMAPReduce(  
  Clonal_Obs,  
  save.dir = ".",  
  clonotypes = c(),  
  ident.list = c("orig.ident"),  
  rseed = 356,  
  ur.nfeatures = 500,  
  preload = FALSE,  
  preloadpath = "."  
)
```

Arguments

Clonal_Obs	A Seurat object pre-processed with aocseq::CombineData.
save.dir	Directory for storing differentially expressed genes.
clonotype.path	Character array. Directory of an aocseq clonotype annotation table.
goi	Character array. Gene name, a marker of interest.
verbose	Print progress

Value

return an assay containing predicted expression value in the data slot

Index

* Annotation & quality control

CombineData, [6](#)

* Annotation

AnnotateCellTypes, [2](#)

SetCellType, [18](#)

* Routine functions

construct_tree, [7](#)

e_step, [10](#)

m_step, [14](#)

NormalizationScore, [14](#)

* Routine functions

Iso_forest, [12](#)

* Single cell analysis

CellTypeLoop, [3](#)

ClassifyCells, [4](#)

ClassifyCellTypes, [5](#)

GetGeneSignature, [10](#)

GetSpecificCells, [11](#)

MakeReference, [13](#)

percent_outlier, [15](#)

* Statistical inference

DEsingle, [8](#)

GMM_demux, [11](#)

* Visualization

QCPlot, [15](#)

SaveHeatmap, [16](#)

segmentPlot, [17](#)

UMAPReduce, [18](#)

* annotation

ClassifyCellTypes, [5](#)

AnnotateCellTypes, [2](#)

bplapply, [8](#)

bpparam, [8](#)

CellTypeLoop, [3](#)

ClassifyCells, [4](#)

ClassifyCellTypes, [5](#)

CombineData, [6](#)

construct_tree, [7](#)

DEsingle, [8](#), [9](#)

DEtype, [9](#)

e_step, [10](#)

GetGeneSignature, [10](#)

GetSpecificCells, [11](#)

GMM_demux, [11](#)

Iso_forest, [12](#)

m_step, [14](#)

MakeReference, [13](#)

NormalizationScore, [14](#)

percent_outlier, [15](#)

QCPlot, [15](#)

SaveHeatmap, [16](#)

segmentPlot, [17](#)

SetCellType, [18](#)

TestData, [9](#)

UMAPReduce, [18](#)