

Stage L3:  
Implementing the Core Chase for **Horn- $\mathcal{ALCH}$**

Maël Abily  
Computer Science Department  
ENS Lyon

Supervised by:  
David Carral and Jean-François Baget  
Permanent researchers at INRIA

July 26, 2021

# Contents

1	Introduction	2
2	Facts	3
3	Existential Rules	4
4	The Chase	5
5	The Merge Chase	9
5.1	Horn- $\mathcal{ALCH}$	9
6	Conclusion	18

## 1 Introduction

During my studies at ENS de Lyon, I did a research internship in computer science during six weeks. I did this internship at INRIA, in the GRAPHIK team (GRAPHIK means Graphs for Inferences on Knowledge), supervised by David Carral and Jean-François Baget. I thank them for the time they took with me during these six weeks to orient myself in my research and answer all the questions I had. I also thank the whole GRAPHIK team who welcomed and integrated me for this internship.

GRAPHIK's research work focuses on databases thanks to knowledge representation and reasoning (knowledge means set of data). The subject of my internship, entitled "Implementing the Core Chase for the Description Logic ALC", looks for an algorithm that reasons on a specific type of data to answer an important problem in database.

Knowledge representation and reasoning is the field of artificial intelligence dedicated to representing information about the world in a form that a computer system can utilize to solve complex tasks such as diagnosing a medical condition or having a dialog in a natural language. The conjunctive query entailment is an important issue in knowledge representation and reasoning. This problem can be described in a first order logic background. We work on conjunctive formulas that are formulas constructed only with conjunction and existential quantification; and queries that are conjunctive formulas without free variables. The answer of a query is either yes or no. For example, the formula  $\exists y. Human(y) \wedge IsTheBrotherOf(Pierre, y)$  is a query asking if Pierre has a parent. We also work on existential rules that are formulas of the form  $\forall \vec{x}. \forall \vec{y}. (A(\vec{x}, \vec{y}) \rightarrow \exists \vec{z}. B(\vec{x}, \vec{z}))$  where  $\vec{u}$  represents a tuple of variables. A theory  $T$  will then be a set of existential rules and conjunctive formulas. Note that in practice, a lot of formulas can be expressed via conjunctive formulas.

est ce  
qu'on peut  
copier des  
phrases de  
Wikipédia ?

We can now define the problem of conjunctive query entailment: Given a theory  $T$  and a query  $Q$  determine if  $T$  entails the query  $Q$ . For example, the theory  $T = \{Mother(Marie), \forall x. (Mother(x) \rightarrow \exists y. IsTheParentOf(x, y))\}$  entails the query  $Q = \exists x. IsTheParentOf(Marie, x)$ . We usually use reasoning algorithms to answer the conjunctive query entailment. By definition, a theory  $T$  entails a query  $Q$  if every model of  $T$  is a model of  $Q$ . However, we cannot compute all models because  $T$  can have an infinite number of models.

To deal with this problem, we can compute an universal model of the theory  $T$ . That is a model of  $T$  that is entailed by all the models of  $T$ . If a such model  $U$  exists, we just need to show that  $U$  entails  $Q$  to conclude that  $T$  entails  $Q$ . Hence, to solve query entailment, we just have to compute a finite universal model  $U$  for a given input  $T$  and check if  $U$  entails  $Q$ . To compute these models, we can use the chase. In this document, we present several variants of this algorithm: the oblivious chase, the restricted chase and

then the core chase. The last chase is the best in the sense that it is the only one that terminates if and only if there exists a finite universal model.

Nevertheless, the core chase is more complicated to implement because we have to look for global endomorphisms in the set of facts produced by the core chase. We will then focus on a restricted type of theory  $T$  (that is called **Horn- $\mathcal{ALCH}$**  theory) where the set of conjunctive formulas is ground (that is there is no free-variable in the formula) and where the rules contained in  $T$  are **Horn- $\mathcal{ALCH}$**  axioms.

We present a new variant of the chase for **Horn- $\mathcal{ALCH}$**  theories which is also guaranteed to terminate if the input theory admits a finite universal model and is much easier to implement. In the core chase, one has to look for global endomorphisms in the sets of facts produced by the chase whereas in the merge chase, we only need to look for very local endomorphisms, which are much simpler to compute.

**Horn- $\mathcal{ALCH}$**  is a fragment of description logics that is widely used in the context of knowledge reasoning. Description logics are fragments of first-order logic with unary and binary predicates, and are the main tools for reasoning about theories. They are mostly fragments of first-order logic.

First of all, we will define in section 2, 3, and 4 the usefull notions for this paper and give some well known properties. Then, we will move on our contributions in section 5.

## 2 Facts

We consider a set of variables **Vars**, a set of constants **Csts**, and a set of predicates **Preds**, that are pairwise disjoint. A *term* is a variable or a constant. We note **Terms** the set of terms. If  $t_1, \dots, t_n$  are terms and  $P$  is a predicate of arity  $n$ , then  $P(t_1, \dots, t_n)$  is an *atom*. The atom  $P(t_1, \dots, t_n)$  is *ground* if  $t_1, \dots, t_n$  are constants. We can now define a factbase that is a notion omnipresent in all the paper.

**Definition 2.1.** A *factbase*  $F$  is an existentially closed conjunction of atoms, that is, a formula that does not contain occurrences of free variables and is of the form  $\exists x_1, \dots, x_n. P_1(t_1^1, \dots, t_{k_1}^1) \wedge \dots \wedge P_m(t_1^m, \dots, t_{k_m}^m)$  where  $t_i^j$  are terms and  $P_i$  are predicates. A factbase is *ground* if each of its atoms is ground.

Note that, we do consider factbases that are not ground, unlike other authors. Consequently, the notions of Boolean conjunctive queries and factbases coincide. For convenience, we identify factbases as sets of atoms, which allows us to use operators from set theory. For example, we identify the factbase  $\exists x, y, z. x.P(x) \wedge Q(x, a) \wedge R(y, z, b)$  with the set of facts  $\{P(x), Q(x, a), R(y, z, b)\}$ . For a formula  $A$ , let **Vars**( $A$ ), **Csts**( $A$ ), and **Terms**( $A$ ) be the sets of variables, constants, and terms that occur in  $A$ , respectively.

A *substitution*  $\sigma : X \rightarrow \mathbf{Terms}$  is a function where  $X$  is a set of variables. For example  $\{x \mapsto z, y \mapsto a\}$  is a substitution from  $\{x, y\}$  to **Terms**. By extension:

- if  $c \in \mathbf{Csts}$ , then  $\sigma(c) = c$ ,
- if  $x \in \mathbf{Vars} \setminus X$ ,  $\sigma(x) = x$ ,
- if  $f = P(t_1, \dots, t_n)$  is an atom, then  $\sigma(f) = P(\sigma(t_1), \dots, \sigma(t_n))$ , and
- if  $F = \{f_1, \dots, f_n\}$  is a factbase, then  $\sigma(F) = \{\sigma(f_1), \dots, \sigma(f_n)\}$ .

This definition leads us to the central notion of homomorphism.

**Definition 2.2.** For two factbases  $F$  and  $G$ , a *homomorphism* from  $F$  to  $G$  is a substitution  $\sigma : \mathbf{Vars}(F) \rightarrow \mathbf{Terms}$  where  $\sigma(F) \subseteq G$ .

An *isomorphism*  $h$  from  $F$  to  $G$  is a bijective homomorphism where its inverse is a homomorphism from  $G$  to  $F$ . For the remainder of this paper, we identify sets of facts that are unique up to isomorphism.

**Definition 2.3.** A factbase  $F$  *entails* another factbase  $G$  (often noted  $F \models G$ ) if each interpretation satisfying  $F$  satisfies  $G$ .  $F$  is *equivalent* to  $G$  if  $F \models G$  and  $G \models F$ .

Intuitively, if  $F \models G$ , then  $F$  is logically stronger than  $G$  and from  $F$ , we can deduce  $G$ . In this document, the notion of interpretation is not a central notion because in our fragment of first-order logic, we have convenient characterisation. For example, to know if  $F \models G$ , we use the following theorem.

**Theorem 2.1** (Homomorphism Theorem). A factbase  $F$  *entails* another factbase  $G$  if and only if there exists a homomorphism from  $G$  to  $F$ .

The previous theorem has been proved in ([1], Theorem 6.2.3). For example, the factbase  $F = \{P(b, a), A(x)\}$  entails the factbase  $G = \{P(x, a), P(y, z)\}$  due to the homomorphism  $\{x \mapsto b, y \mapsto b, z \mapsto a\}$ .

For a factbase  $F$ , let  $id_F$  be the substitution mapping each variable in  $\mathbf{Vars}(F)$  to itself. And for a substitution  $\sigma$  defined on a factbase  $G$  containing  $F$ , let  $\sigma|_F$  be the maximal subset of  $\sigma$  defined only on  $\mathbf{Vars}(F)$ .

**Definition 2.4.** A factbase  $G$  is a *retract* of another factbase  $F$  if  $G \subseteq F$  and  $G \models F$ . A *retraction* from  $F$  to  $G$  is a homomorphism  $\sigma$  from  $F$  to  $G$  such that  $\sigma|_G = id_G$ .  $G$  is a *strict retract* of  $F$  if  $G$  is a retract of  $F$  and  $G \neq F$ .

If  $G$  is a retract of  $F$ , then  $G$  is as logically strong as  $F$  and yet smaller. We impose that  $\sigma|_G = id_G$  in the definition of retractions because it helps us in the proof of Proposition 5.6 thanks to the well known property:

**Proposition 2.1.** *The factbase  $G$  is a retract of the factbase  $F$  if and only if  $G \subseteq F$  and there exists a retraction from  $F$  to  $G$ .*

A core of a factbase  $F$  is then one of the smallest retract of  $F$ :

**Definition 2.5.** If a factbase  $F$  does not contain a strict retract, then we say that  $F$  is a *core*. A *core* of a factbase  $F$  is a subset of  $F$  that is a core.

The core of  $F$  is one of the smallest sets of facts that is as logically strong as  $F$ . The cores of a finite factbase  $F$  are unique up to isomorphism. Hence, we speak of “the” core of a factbase. The factbase  $G = \{B(x, y), R(y, z)\}$  is the core of  $F = \{B(x, y), R(y, z), B(x, w), R(w, z)\}$  because (1)  $G \subseteq F$ , (2)  $\{x \mapsto x, y \mapsto y, z \mapsto z, w \mapsto y\}$  is a homomorphism from  $F$  to  $G$ , so  $G$  is a retract of  $F$ , and (3) all strict subsets of  $G$  are not retracts of  $G$ . Note that  $\{B(x, w), R(w, z)\}$  is also the core of  $F$  and is indeed isomorphic to  $G$  due to the homomorphism  $\{x \mapsto x, y \mapsto w, z \mapsto z\}$ .

### 3 Existential Rules

For a tuple of variable  $\vec{x}$ , we note  $A(\vec{x})$  a formula where the set of free variables is  $\vec{x}$ . An existential rule is a formula of the form  $A \rightarrow B$ , more exactly:

**Definition 3.1.** Let  $\vec{x}$ ,  $\vec{y}$ , and  $\vec{z}$  be some tuples of variables that are pairwise disjoint. An (*existential*) *rule*  $\alpha$  is a first-order formula of the form

$$\forall \vec{x}. \forall \vec{y}. (A(\vec{x}, \vec{y}) \rightarrow \exists \vec{z}. B(\vec{x}, \vec{z}))$$

where  $A(\vec{x}, \vec{y})$  and  $B(\vec{x}, \vec{z})$  are conjunctions of atoms. We define  $body(\alpha) = A$  and  $head(\alpha) = B$ .

We omit the universal quantifiers when representing existential rules. A knowledge base represents then a set of rules and a set of facts:

**Definition 3.2.** A *knowledge base*  $K$  is a pair  $(R, F)$  where  $R$  is a set of existential rules and  $F$  is a ground factbase.

A factbase  $F$  *entails* a rule  $\alpha$  if each interpretation satisfying  $F$  satisfies  $\alpha$ . We will note  $F \models R$  if  $F$  entails each rule of the rule set  $R$ . Again, we will not have to manipulate interpretations because the following theorem is use in pratice to determine if  $F \models \alpha$ :

**Theorem 3.1.** A factbase  $F$  *entails* a rule  $\alpha = A(\vec{x}, \vec{y}) \rightarrow \exists \vec{z}. B(\vec{x}, \vec{z})$  if and only if for every homomorphism  $\sigma$  from  $A$  to  $F$ , there exists an extension of  $\sigma$  that is a homomorphism from  $B$  to  $F$ .

For example, the factbase  $F = \{A(c, d), B(c, e)\}$  entails the rule  $\alpha = A(x, y) \rightarrow \exists z. B(x, z)$  because  $\sigma = \{x \mapsto c, y \mapsto d\}$  is the only homomorphism from  $A(x, y)$  to  $F$ , and  $\hat{\sigma} = \sigma \cup \{z \mapsto e\}$  is an extension of  $\sigma$  that is a homomorphism from  $B(x, z)$  to  $F$ .

**Definition 3.3** (Model and universality). A factbase  $M$  is a *model* for a knowledge base  $K = (R, F)$  if  $M \models F$  and  $M \models R$ . The factbase  $U$  is *universal* for  $K$  if for every model  $M$  of  $K$ ,  $M \models U$ .

We often talk of *universal models* of a knowledge base  $K$ ; that is, factbases that are both a model and universal for  $K$ .

**Example 3.1.** If we pose  $K = (\{A(x) \rightarrow \exists z. R(x, z) \wedge A(z)\}, \{A(b)\})$ , then an universal model for  $K$  is

$$U = \{A(b), R(b, x_0)\} \cup \{A(x_i) \mid i \in \mathbb{N}\} \cup \{R(x_i, x_{i+1}) \mid i \in \mathbb{N}\}$$

Note that the knowledge base  $K$  does not admit finite universal models.

**Definition 3.4** (Entailment). A knowledge base  $K$  *entails* a factbase  $B$  (often noted  $K \models B$ ) if for each model  $M$  of  $K$ ,  $M \models B$ .

We can use universal models to solve the conjunctive query entailment:

**Proposition 3.1.** A knowledge base  $K$  *entails* a factbase  $B$  if there exists a universal model  $U$  for  $K$  such that  $U \models B$ .

An important problem that we want to solve is: Given a knowledge base  $K = (R, F)$  and a factbase  $Q$ , does  $K \models Q$ ? It is well-known that this problem is undecidable ([2], theorem 4).

## 4 The Chase

The process of applying rules on a factbase in order to infer more knowledge is called forward chaining. Forward chaining in existential rules is usually achieved via a family of algorithms called the chase. It can be seen as a two-steps process. It first repeatedly applies rules to the set of facts (and eventually computes sometimes the core to supress redundant facts). Then it looks for an answer to the query in this saturated set of facts. This saturated set of facts is an universal model of the knowledge base. The chase is sound and complete; so it must be non-terminating since the problem of entailment is undecidable. To determine how we apply a rule to a set of fact, we introduce the notion of trigger:

**Definition 4.1** (Trigger). Let  $T$  be a rule set,  $\alpha$  be a rule,  $\sigma$  be a substitution, and  $F$  be a factbase. The tuple  $t = (\alpha, \sigma)$  is an *oblivious trigger* for  $F$  if:

- the domain of  $\sigma$  is the set of all variables occurring in  $Body(\alpha)$ .
- $\sigma$  is a homomorphism from  $Body(\alpha)$  to  $F$ .

In this case, we say that  $t$  is *applicable* on  $F$ .

The tuple  $t = (\alpha, \sigma)$  is a *restricted trigger* for  $F$  if  $t$  is an oblivious trigger for  $F$  and if for all  $\hat{\sigma}$  that extend  $\sigma$  over  $\mathbf{Vars}(Head(\alpha))$ ,  $\hat{\sigma}(Head(\alpha)) \not\subseteq F$ .

Notice that a restricted trigger is also an oblivious trigger. We will use the term *trigger* to talk about the oblivious and the restricted trigger. The chase considers triggers to infer new knowledge from an initial factbase. We explain now how it would apply a trigger, giving rise to the notion of application.

**Definition 4.2** (application). Let  $F$  be a factbase and  $t = (\alpha, \sigma)$  be a trigger where  $\alpha$  is of the form  $A(\vec{x}, \vec{y}) \rightarrow \exists \vec{z}. B(\vec{x}, \vec{z})$ . We pose  $\sigma^s$  the substitution that extends  $\sigma$  over  $\mathbf{Vars}(Head(\alpha))$  such that for  $z \in \vec{z}$ ,  $\sigma^s(z) = f_\alpha^z(\sigma(\vec{x}))$  where  $f_\alpha^z(\sigma(\vec{x}))$  is a fresh variable unique with respect to the trigger  $t = (\alpha, \sigma)$  and the variable  $z$ .

The factbase  $\mathbf{appl}(F, t) = F \cup \sigma^s(Head(\alpha))$  is called an *application* on the factbase  $F$  through the trigger  $t = (\alpha, \sigma)$ . We say that the trigger  $t$  is *useless* on  $F$  if  $\mathbf{appl}(F, t) = F$ .

We use a naming convention that resembles function symbols because this will be convenient when we will discuss about a new variant of the chase.

For example, if we have the rule  $\alpha = A(x, y) \rightarrow \exists z. B(x, z)$ , the factbase  $F = \{A(b, c)\}$ , and the substitution  $\sigma = \{x \mapsto b, y \mapsto c\}$ , then  $(\alpha, \sigma)$  is a restricted trigger for  $F$ . We have then

$$\mathbf{appl}(F, (\alpha, \sigma)) = \{A(b, c), B(b, f_\alpha^z(b, c))\}$$

It is well known that the application preserves the universality:

**Proposition 4.1.** *Let  $K$  be a knowledge base,  $M$  be a model of  $K$ ,  $F$  be a factbase such that  $M \models F$ , and  $t$  be an oblivious trigger. We have then  $M \models \mathbf{appl}(F, t)$ .*

We can now define the oblivious and restricted chase, that are also defined in [3]. A sequence of rule applications is called a derivation. In this paper, we differentiate between oblivious derivations and restricted derivations:

**Definition 4.3** (Derivation). An *oblivious derivation* (respectively a *restricted derivation*) for a knowledge base  $K = (F, R)$  is a (possibly infinite) sequence  $D = F_0, F_1, F_2, \dots$  where

- $F_0, F_1, \dots$  are factbases such that  $F_i \subsetneq F_{i+1}$ .
- $F_0 = F$ .
- For all  $i > 0$ ,  $F_i = \mathbf{appl}(F_{i-1}, t_i)$  where  $t_i$  is an oblivious trigger (resp. a restricted trigger).

A fair derivation guarantees that we consider every possible application:

**Definition 4.4.** The oblivious (resp. restricted) derivation  $D = F_0, F_1, F_2, \dots$  is *fair* if for every  $i$  and every oblivious (resp. restricted) trigger  $t$  for  $F_i$ , there exists  $k \geq i$  such that  $t$  is useless on  $F_k$  (resp.  $t$  is not anymore a restricted trigger for  $F_k$ ). An *oblivious chase* (resp. a *restricted chase*) for a knowledge base  $K = (F, R)$  is a fair oblivious (resp. restricted) derivation  $D = F_0, F_1, F_2, \dots$

For every oblivious chase derivation  $D = F_0, F_1, F_2, F_3, \dots$  for  $K$ , we have  $F_0 \subseteq F_1 \subseteq F_2 \subseteq \dots$ . The set  $\cup_i F_i$  does not depend on the derivation  $D$  since for each  $F_i$  and for each trigger  $t$  for  $F_i$ , there exists  $k > i$  such that  $t$  is useless on  $F_k$ . We can then pose  $Obl(K) = \cup_{i \in \mathbb{N}} F_i$  and we say that the oblivious chase *terminates* if  $Obl(K)$  is finite. It is well known that:

**Theorem 4.1.** For a knowledge base  $K$ ,  $Obl(K)$  is an universal model of  $K$ .

Consequently, the oblivious chase can be used to solve query entailment. It is more difficult to define the result of the restricted chase because the result depends on the order of the application of the rules. We define

$$Res(K) = \{\cup_{i \in \mathbb{N}} F_i \mid D = F_0, F_1, F_2, \dots \text{ is a restricted chase for } K\}$$

We say that the restricted chase *terminates* if there exists an element in  $Res(K)$  that is finite. It is well known that:

**Theorem 4.2.** For a knowledge base  $K$  and for every  $U \in Res(K)$ ,  $U$  is an universal model of  $K$ .

We present an example to showcase that the restricted chase may terminate even when the oblivious chase does not:

**Example 4.1.** Suppose that we have the knowledge base  $K = (\{\alpha = A(x, y) \rightarrow \exists z. A(y, z) \wedge A(z, y)\}, \{A(a, b)\})$ . An oblivious chase derivation is  $F_0, F_1, F_2, \dots$  where

- $F_0 = F$ ,
- $t_1 = (\alpha, \{x \mapsto a, y \mapsto b\})$  is an oblivious trigger for  $F_0$ ,
- $F_1 = \mathbf{appl}(F_0, t_1) = \{A(a, b), A(b, z_1), A(z_1, b)\}$  where  $z_1 = f_\alpha^z(a, b)$ ,
- $t_2 = (\alpha, \{x \mapsto b, y \mapsto z_1\})$  is an oblivious trigger for  $F_1$ ,
- $F_2 = \mathbf{appl}(F_1, t_2) = F_1 \cup \{A(z_1, z_2), A(z_2, z_1)\}$  where  $z_2 = f_\alpha^z(b, z_1)$ ,
- $\dots$

It will never terminate because each new atom brings new rule applications. So the oblivious chase does not terminate on  $K$  whereas the restricted chase terminates. A restricted chase derivation is  $F_0, F_1$  where  $F_0 = F$ ,  $t_1 = (\alpha, \{x \mapsto a, y \mapsto b\})$ , and  $F_1 = \mathbf{appl}(F_0, t_1) = \{A(a, b), A(b, z_{t_1}), A(z_{t_1}, b)\}$ . This derivation is fair because there is not anymore any restricted trigger for  $F_1$ , so we have  $F_1 \in Res(K)$ .

This theorem follows from results in [3]:

**Theorem 4.3.** A knowledge base  $K$  entails a factbase  $B$  if  $Obl(K) \models B$  or if there exists  $U \in Res(K)$  such that  $U \models B$ . Conversely, if a knowledge base  $K$  entails a factbase  $B$ , then  $Obl(K) \models B$  and for every  $U \in Res(K)$ ,  $U \models B$

The core chase terminates more often than the oblivious and restricted chase since the core chase terminates when the knowledge base admits a finite universal model. It has been firstly defined in [4].

**Definition 4.5** (Core derivation and fairness). A *core derivation* for a knowledge base  $K = (R, F)$  is a (possibly infinite) sequence  $D = F_0, F_1, F_2, \dots$  where  $F_0 = F$ , and for  $i > 0$ , either  $F_i = \mathbf{appl}(F_{i-1}, t_i)$  is obtained by an application with  $t_i$  an oblivious trigger, or  $F_i$  is the core of  $F_{i-1}$ .

The core derivation  $D$  is *fair* if:

- For every  $i$ , for every oblivious trigger  $t$  for  $F_i$ , there exists  $k$  such that  $t$  is useless on  $F_k$ ; or there exists  $k > i$  such that  $t$  is not anymore an oblivious trigger for  $F_k$ .
- For every  $i$ , there exists  $k \geq i$  such that  $F_k$  is a core.

Note that in the first condition, we can have  $k < i$  because in a chase derivation a fact can be removed. The second condition is essential to guarantee the termination of a fair core derivation when there exists a finite universal model.

**Definition 4.6.** A *core chase* for a knowledge base  $K = (R, F)$  is a fair core derivation  $D = F_0, F_1, F_2, \dots$ . The core chase *terminates* on  $K$  if it is a finite core derivation.

The article [4] has proven that the result of the core chase for a knowledge base is unique up to isomorphism. Therefore, we can define the result of the core chase:

**Definition 4.7.** If the core chase terminates on  $K$  due to the finite core derivation  $D = F_0, F_1, F_2, \dots, F_i$ , then we pose  $\text{Core}(K) = F_i$ . Otherwise, if the core chase does not terminate,  $\text{Core}(K)$  is undefined.

The following theorem highlights why the core chase has been introduced. It has been proven in ([4], theorem 7).

**Theorem 4.4.** The knowledge base  $K = (R, F)$  admits a finite universal model if and only if the core chase algorithm terminates on  $K$ .

We present an example to showcase that the core chase may terminate even when the restricted chase does not:

**Example 4.2.** Suppose that we have the knowledge base  $K = (\{\alpha = A(x, y) \rightarrow \exists z.(A(x, x) \wedge A(y, z))\}, \{A(a, b)\})$ . A restricted chase derivation is  $F_0, F_1, F_2, \dots$  where

- $F_0 = F$ ,
- $t_1 = (\alpha, \{x \mapsto a, y \mapsto b\})$  is a restricted trigger for  $F_0$ ,
- $F_1 = \mathbf{appl}(F_0, t_1) = F_0 \cup \{A(a, a), A(b, z_1)\}$  where  $z_1 = f_\alpha^z(a, b)$ ,
- $t_2 = (\alpha, \{x \mapsto b, y \mapsto z_1\})$  is a restricted trigger for  $F_1$ ,
- $F_2 = \mathbf{appl}(F_1, t_2) = F_1 \cup \{A(b, b), A(z_1, z_2)\}$  where  $z_2 = f_\alpha^z(b, z_1)$ ,
- $t_3 = (\alpha, \{x \mapsto z_1, y \mapsto z_2\})$  is a restricted trigger for  $F_2$ ,
- $F_3 = \mathbf{appl}(F_2, t_3) = F_2 \cup \{A(z_1, z_1), A(z_2, z_3)\}$  where  $z_3 = f_\alpha^z(z_1, z_2)$ ,
- $\dots$

It will never terminate because each new atom brings new restricted triggers. The core chase terminates on  $K$ : a core chase derivation is  $F_0, F_1, F_2, F_3, F_4, F_5$  where

- $F_0 = F$ ,
- $t_1 = (\alpha, \{x \mapsto a, y \mapsto b\})$  is an oblivious trigger for  $F_0$ ,
- $F_1 = \mathbf{appl}(F_0, t_1) = F_0 \cup \{A(a, a), A(b, z_1)\}$  where  $z_1 = f_\alpha^z(a, b)$ ,
- $t_2 = (\alpha, \{x \mapsto b, y \mapsto z_1\})$  is an oblivious trigger for  $F_1$ ,
- $F_2 = \mathbf{appl}(F_1, t_2) = F_1 \cup \{A(b, b), A(z_1, z_2)\}$  where  $z_2 = f_\alpha^z(b, z_1)$ ,
- $t_3 = \{x \mapsto a, y \mapsto a\}$  is an oblivious trigger for  $F_2$ ,  $F_3 = \mathbf{appl}(F_2, t_3)$ ,  $t_4 = \{x \mapsto b, y \mapsto b\}$  is an oblivious trigger for  $F_3$ , and  $F_4 = \mathbf{appl}(F_3, t_4) = F_2 \cup \{A(a, f_\alpha^z(a, a)), A(b, f_\alpha^z(b, b))\}$
- $F_5 = \text{Core}(F_4) = \{A(a, a), A(a, b), A(b, b)\}$ .

There is not anymore any oblivious trigger for  $F_5$  so the derivation is fair. Consequently the core chase terminates on  $K$ .



$$a : A, B \xrightarrow{R, T} b : C \xrightarrow{R} z$$

Figure 1: Factbase Representation

## 5 The Merge Chase

The core chase always terminates when there exists a finite universal model but this chase is very expensive in time because computing the core of a factbase is hard. Therefore we are presenting a more efficient way to solve this problem in the particular case of **Horn- $\mathcal{ALCH}$** .

**Definition 5.1.** For a factbase  $F$  and a term  $t$ , let  $\mathbf{Preds}_F^1(t)$  be the set of unary predicates  $P$  such that  $P(t) \in F$ . For two terms  $t$  and  $u$ , we note  $\mathbf{Preds}_F^2(t, u)$  the set of binary predicates  $P$  such that  $P(t, u) \in F$ .

For a factbase  $F$  and some  $t, u \in \mathbf{Terms}(F)$ , let  $\mathbf{Preds}_F^1(t) = \{P \mid P(t) \in F\}$  and  $\mathbf{Preds}_F^2(t, u) = \{P \mid P(t, u) \in F\}$ .

In this section, we only consider factbases with predicates of arity one or two. Hence, we will represent a factbase  $F$  by a labelled graph  $G = (V, E)$  where  $V = \{t \mid t \in \mathbf{Terms}\}$  and  $E = \{(t, u) \mid t, u \in \mathbf{Terms} \wedge \mathbf{Preds}_F^2(t, u) \neq \emptyset\}$ . We label each vertex  $v \in V$  with the predicates in  $\mathbf{Preds}_F^1(v)$  and each edge  $(t, u)$  with the predicates in  $\mathbf{Preds}_F^2(t, u)$ . For example, we represent  $F = \{A(a), B(a), R(a, b), T(a, b), C(b), R(b, z)\}$  by the Figure 1.

### 5.1 Horn- $\mathcal{ALCH}$

**Definition 5.2 (Horn- $\mathcal{ALCH}$  axioms).** A **Horn- $\mathcal{ALCH}$  axiom** is an existential rule of one of the following forms:

$$\begin{array}{llll} A(x) \wedge B(x) \rightarrow C(x) & (C_{\wedge}) & R(x, y) \wedge B(y) \rightarrow A(x) & (\exists_{-}) \\ A(x) \wedge R(x, y) \rightarrow B(y) & (\forall_{+}) & R(x, y) \wedge S(x, y) \rightarrow V(x, y) & (R_{\wedge}) \\ A(x) \rightarrow \exists y. R(x, y) \wedge B(y) & (\exists_{+}) & & \end{array}$$

A **Horn- $\mathcal{ALCH}$  knowledge base**  $K = (R, F)$  is a knowledge base where  $R$  is a set of **Horn- $\mathcal{ALCH}$  axioms** and  $F$  contains only predicates of arity one or two.

**Horn- $\mathcal{ALCH}$**  has been introduced in [5]. Note that the type  $(\exists_{+})$  is the only type of rule that features existentially quantified variables. To introduce the merge chase, we first define the notion of mergeable variable. We then describe the atomic merging operation that merges a mergeable variable on a term. This atomic operation is used to define the merging that does atomic merging until it is not possible anymore. The merge chase is then a core chase where we replace the core operation by the merging. We want to show that the merge chase for a **Horn- $\mathcal{ALCH}$  knowledge base**  $K$  computes a finite universal model when it terminates and that it terminates if and only if there exists a finite universal model for  $K$ .

**Definition 5.3 (Mergeable variable).** For two terms  $u$  and  $v$  appearing in a factbase  $F$ ,  $u$  is *mergeable* on  $v$  in  $F$  if:

- $u \neq v$  and  $u$  is a variable,
- $\mathbf{Preds}_F^1(u) \subseteq \mathbf{Preds}_F^1(v)$ , and

peut etre  
remplace par  
"absorb".  
"merge  
on" sounds  
weird; see  
[https://forum.  
wordreference.  
com/threads/absorb-merge-on](https://forum.wordreference.com/threads/absorb-merge-on)




Figure 2: Atomic Merging Example

- there exists a term  $t$  such that  $\mathbf{Preds}_F^2(t, u) \neq \emptyset$  and  $\mathbf{Preds}_F^2(t, u) \subseteq \mathbf{Preds}_F^2(t, v)$ .

In this case, we say that  $u$  is a *mergeable variable*.

For a term  $t$  and a variable  $x$ , we say that  $t \prec x$  if  $x$  is of the form  $f_\alpha^y(t)$ . We write  $\prec^+$  to denote the transitive closure of  $\prec$  and we note  $\mathbf{Desc}(t) = \{y \in \mathbf{Vars} \mid t = y \vee t \prec^+ y\}$ .

**Definition 5.4** (atomic merging). If a variable  $x$  is mergeable on a term  $t$  in a factbase  $F$ , then we note  $h_{x/t}$  the substitution defined on  $\mathbf{Vars}(F)$  such that

- for every variable  $y$  in  $\mathbf{Desc}(x)$ ,  $h_{x/t}(y)$  is the variable  $y$  where the occurrence of  $x$  is replaced by  $t$ , and
- for every variable  $y$  not in  $\mathbf{Desc}(x)$ ,  $h(y) = y$ .

The *atomic merging* of  $x$  on  $t$  in  $F$  produces  $h_{x/t}(F)$

When  $x$  is mergeable on  $t$  in  $F$ , for each trigger  $tr = (\alpha, \sigma)$  applied on  $F$  where the range of  $\sigma$  is included in  $\mathbf{Desc}(x)$ , the trigger  $h_{x/t}(tr) = (\alpha, h_{x/t} \circ \sigma)$  has been or will be applied. Therefore, all the facts containing variables in  $\mathbf{Desc}(x)$  are or will be redundant. But we do not want to suppress all these facts because we know that if they are not yet in the facts that contain variables in  $\mathbf{Desc}(t)$ , they would be computed. Instead, we would like to “recycle” these facts. That is this intuition that leads us to define atomic merging.

For example, in the Figure 2,  $f_\alpha^y(a)$  is mergeable on  $b$  in the left factbase. The atomic merging of  $f_\alpha^y(a)$  on  $b$  in this factbase produces the right factbase. The following definition describes the operation that will replace the computation of the core in the core chase. We will show that for a chase derivation  $D = F_0, \dots, F_k$  of  $K$ , if we apply our operation on  $F_k$ , then it computes the core of a factbase that could have been produced by continuing the derivation  $D$ .

**Definition 5.5.** For a factbase  $F$ , a *merge* sequence of  $F$  is a sequence  $F_0, \dots, F_n$  of factbases such that:

- $F_0 = F$ .
- For  $i \in \{1, \dots, n\}$ , the factbase  $F_i$  is the atomic merging of a variable  $x$  on a term  $t$  in  $F_{i-1}$ .
- The factbase  $F_n$  does not contain a mergeable variable.

Then,  $\text{Merge}(F) = F_n$ .

je ne suis pas convaincu par ce que j'ai écrit dans ce paragraphe




Figure 3: Merging Example

The result of the *Merge* operation is unique up to isomorphism.

**Example 5.1.** In the Figure 3, we merge the factbase of the left. The variable  $f_\alpha^z(a)$  is mergeable on  $b$ , an atomic merging of  $f_\alpha^z(a)$  on  $b$  yields the factbase of the middle. Now,  $f_\beta^z(b)$  is mergeable on  $c$ , an atomic merging of  $f_\beta^z(b)$  on  $c$  produces the factbase of the right. The last factbase is the result of the merge since it does not contain any mergeable variable.

We can now consider two new chases:

**Definition 5.6** (derivation). A *merge derivation* for a **Horn-ALCH** knowledge base  $K = (R, F)$  is a (possibly infinite) sequence  $D = F_0, F_1, F_2, \dots$  where  $F_0 = F$ , and for  $i > 0$ , either  $F_i = \mathbf{appl}(F_{i-1}, t_i)$  is obtained by an application with  $t_i$  an oblivious trigger, or  $F_i$  is obtained by the merging of  $F_{i-1}$ .  $D$  is *fair* if:

- For every  $i$ , for every oblivious trigger  $t$  applicable on  $F_i$ , there exists  $k \leq i$  or  $k > i$  such that  $t$  is useless on  $F_k$ ; or there exists  $k > i$  such that  $t$  is not anymore an oblivious trigger for  $F_k$ .
- For every  $i$ , there exists  $k \geq i$  such that  $F_k$  is a core.

A *merge chase* for a knowledge base  $K = (R, F)$  is a fair atomic merge derivation (resp. a fair merge derivation)  $D = F_0, F_1, F_2, \dots$ .

We also introduce the *atomic merge chase* in order to simplify a futur proof, and to show that we can be more flexible on the use of the merge chase. The atomic merge chase is a merge chase where we use the atomic merge operation instead of the merge operation.

**Definition 5.7.** The atomic merge chase (resp. the merge chase) *terminates* on  $K$  if it is a finite derivation  $D = F_0, F_1, F_2, \dots, F_k$ . We note, in this case,  $\mathbf{MC}(K) = F_k$  the result of the merge chase.

The result of the merge chase is unique up to isomorphism. The type  $(\exists_+)$  is the only type of **Horn-ALCH** rules that leads to the introduction of one existentially variable when we apply a rule of this type. Therefore:

**Proposition 5.1.** Consider a variable  $t$  that occurs in a merge chase derivation  $D$  of some **Horn-ALCH** knowledge base  $K$ . Then,  $t$  is of the form  $f_\alpha^y(u)$  where  $u$  is a term,  $\alpha$  is a rule of the form  $(\exists_+)$  in  $K$ , and  $y$  is the only existentially quantified variable occurring in  $\alpha$ . Moreover,  $u$  is the only term in  $D$  such that  $u \prec t$ .




Figure 4: Illustration of the proof

**Proposition 5.2.** *For a factbase  $F$  that occurs in a merge chase derivation of some **Horn-ALCH** knowledge base,  $\prec^+$  is a strict partial order over the set of terms of  $F$ .*

*Proof.* Suppose for a contradiction that there exists a term  $t$  such that  $t \prec^+ t$ . There exists then  $n \in \mathbb{N} \setminus \{0\}$  and terms  $t_0, \dots, t_n$  such that  $t = t_0 \prec t_1 \prec \dots \prec t_n = t$ . By Proposition 5.1, there exists rules  $\alpha_1, \dots, \alpha_n$  and variables  $v_1, \dots, v_n$  such that  $t_n = f_{\alpha_n}^{v_n}(f_{\alpha_{n-1}}^{v_{n-1}}(\dots f_{\alpha_1}^{v_1}(t_0) \dots))$ . It is a contradiction since  $t_0 = t$  and  $t_n = t$ . Therefore  $\prec^+$  is irreflexive. By construction,  $\prec^+$  is transitive; So  $\prec^+$  is a strict partial order  $\square$

We have shown in the proof that the graph induced by  $\prec$  does not contain any cycle. We obtain the following result from Propositions 5.1 and 5.2:

**Proposition 5.3.** *For a factbase  $F$  that occurs in a merge chase derivation of some **Horn-ALCH** knowledge base, the graph induced by  $\prec$  is a forest of trees and the root of each tree is a constant.*

We define the notion of tree of a term  $t$  that is all the facts containing only variables in  $\mathbf{Desc}(t)$ :

**Definition 5.8** (Tree). For a term  $t$  occurring in a chase derivation of the **Horn-ALCH** knowledge base  $K$ , we pose:

$$\begin{aligned} \text{Tree}_F(t) = & \{A(u) \mid A(u) \in F \wedge u \in \mathbf{Desc}(t)\} \cup \\ & \{R(u, x) \mid R(u, x) \in F \wedge u, x \in \mathbf{Desc}(t)\} \end{aligned}$$

We show that the atomic merge chase computes only universal models thanks to the two next propositions.

**Proposition 5.4.** *Let  $D = F_0, F_1, \dots, F_m$  be an atomic merge chase derivation of a knowledge base  $K$  and let  $x$  be a variable mergeable on a term  $t$  in  $F_m$ . Then, there exists an atomic merge chase derivation  $D'$  of the form  $D, E$  (where  $E$  is a sequence of factbases) such that:*

1. *Consider some factbase  $F \in E$  and its predecessor  $G$  in  $D'$ . Then, there is an oblivious trigger  $t = (\alpha, \sigma)$  for  $G$  such that  $F = \mathbf{appl}(G, t)$ .*
2. *The last element of  $E$  is the factbase  $F_m \cup h_{x/t}(\text{Tree}_{F_m}(x))$ .*

We pose  $\mathbf{Fut}(F_m, t, x) = F_m \cup h_{x/t}(\text{Tree}_{F_m}(x))$ .

Graphically, in the Figure 4, if we note  $A = \text{Tree}_{F_m}(t)$  and  $B = \text{Tree}_{F_m}(x)$ , then we want do an atomic merge derivation from the left factbase to the right factbase.

To prove the Proposition 5.4, we will look all the triggers dealing with the variables in  $\mathbf{Desc}(x)$  and apply them on the variables in  $\mathbf{Desc}(t)$  if the triggers have not already been applied.

*Proof.* In order to define an atomic merge chase sequence such as  $D'$ , we first introduce some sequences of oblivious triggers:

- Let  $t_1 = (\alpha_1, \sigma_1), \dots, t_n = (\alpha_n, \sigma_n)$  be the maximal sequence of oblivious triggers such that: (1) for each  $1 \leq i \leq n$ , there is some  $1 \leq j \leq m$  such that  $\mathbf{appl}(F_j, t_i) = F_{j+1}$ ; (2) if  $F_k = \mathbf{appl}(F_{k-1}, t_i)$  and  $F_l = \mathbf{appl}(F_{l-1}, t_j)$  for some  $i, j \in \{1, \dots, n\}$  and some  $1 \leq k < l \leq m$ , then  $i < j$ ; and (3) the range of  $\sigma_i$  is a subset of  $\mathbf{Desc}(x)$  for each  $1 \leq i \leq n$ .
- Let  $t'_1, \dots, t'_o$  be the maximal subsequence of  $(\alpha_1, h_{x/t} \circ \sigma_1), \dots, (\alpha_n, h_{x/t} \circ \sigma_n)$  that are not useless triggers for  $F_m$

$t'_1, \dots, t'_o$  are the triggers that

Let  $F_{m+i} = \mathbf{appl}(F_{m+i-1}, t'_i)$  for each  $1 \leq i \leq o$ . We show via induction that the sequence  $D' = D, F_{m+1}, \dots, F_{m+o}$  satisfies conditions 1. and 2. stated in the proposition.

Suppose for  $1 \leq i \leq n$  that  $D, F_{m+1}, \dots, F_{m+i-1}$  is an atomic merge derivation such that the triggers  $t'_1, \dots, t'_{i-1}$  are useless for  $F_{m+i-1}$ . There exists  $1 \leq j \leq n$  such that the trigger  $t'_i$  is equal to  $h_{x/t}(t_j)$ . The oblivious trigger  $h_{x/t}(t_j)$  is not useless for  $F_{m+i-1}$ . Depending on the form of the rule  $\alpha_j$ , there exists five different cases:

- If  $\alpha_j$  is of the form  $A(u) \rightarrow \exists v. R(u, v) \wedge B(v)$ . We have  $A(\sigma_j(u)) \in F_m$ .
  - If  $\sigma_j(u) = x$ , then  $A(x) \in F_m$ . As  $t$  is a strong sibling of  $x$  in  $F_m$ ,  $A(t) \in F_m$ . So  $A(h_{x/t}(\sigma_j(u))) \in F_{m+i-1}$  since  $h_{x/t}(\sigma_j(u)) = t$ .
  - If  $x \prec^+ \sigma_j(u)$ , then the fact  $A(\sigma_j(u))$  is in  $\sigma_k^s(\text{Head}(\alpha_k))$  where  $k < j$ . By induction hypothesis,  $h_{x/t}(t_j)$  is useless for  $F_{m+i-1}$  so  $A(h_{x/t}(\sigma_j(u))) \in F_{m+i-1}$ .

Therefore  $h_{x/t}(t_j)$  is an oblivious trigger for  $F_{m+r(i-1)}$ .

- If  $\alpha_j$  is of the form  $A_1(u) \wedge A_2(u) \rightarrow B(u)$ . We have  $A_1(\sigma_j(u)), A_2(\sigma_j(u)) \in F_m$ .
  - If  $\sigma_j(u) = x$ , then  $A_1(x), A_2(x) \in F_m$ . As  $t$  is a strong sibling of  $x$  in  $F_m$ , we have  $A_1(t), A_2(t) \in F_m$ . So  $A_1(h_{x/t}(\sigma_j(u))), A_2(h_{x/t}(\sigma_j(u))) \in F_{m+r(i-1)}$  since  $h_{x/t}(\sigma_j(u)) = t$ .
  - If  $x \prec^+ \sigma_j(u)$ , then the facts  $A_1(\sigma_j(u))$  and  $A_2(\sigma_j(u))$  are in  $\sigma_j^s(\text{Head}(\alpha_j))$  where  $j < i$ . We have then  $A_1(h_{x/t}(\sigma_j(u))), A_2(h_{x/t}(\sigma_j(u))) \in B'_{i-1}$  so by induction hypothesis,  $A_1(h_{x/t}(\sigma_j(u))), A_2(h_{x/t}(\sigma_j(u))) \in F_{m+r(i-1)}$ .

Therefore  $h_{x/t}(t_j)$  is an oblivious trigger for  $F_{m+r(i-1)}$ .

- If  $\alpha_j$  is of the form  $A(u) \wedge R(u, v) \rightarrow B(v)$ .
  - If  $\sigma_j(u) = x$ , then  $A(x) \in F_m$ . As  $t$  is a strong sibling of  $x$  in  $F_m$ ,  $A(t) \in F_m$ . Thus  $A(h_{x/t}(\sigma_j(u))) \in F_{m+r(i-1)}$ .
  - If  $x \prec^+ \sigma_j(u)$ , then the fact  $A(\sigma_j(u))$  is in  $\sigma_j^s(\text{Head}(\alpha_j))$  where  $j < i$ . We have then  $A(h_{x/t}(\sigma_j(u))) \in B'_{i-1}$  so by induction hypothesis,  $A(h_{x/t}(\sigma_j(u))) \in F_{m+r(i-1)}$ .

The fact  $R(\sigma_j(u), \sigma_j(v))$  is in  $\sigma_j^s(\text{Head}(\alpha_j))$  where  $j < i$ . We have then  $R(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v))) \in B'_{i-1}$  so by induction hypothesis,  $R(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v))) \in F_{m+r(i-1)}$ .

Therefore, the facts  $A(h_{x/t}(\sigma_j(u)))$  and  $R(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v)))$  are in  $F_{m+r(i-1)}$ . Thus  $h_{x/t}(t_j)$  is an oblivious trigger for  $F_{m+r(i-1)}$ .

j'ai pas eu le temps de modifier les autres cas mais ils sont presque pareil

- If  $\alpha_j$  is of the form  $R(u, v) \wedge B(v) \rightarrow A(u)$ .  $\sigma_j(u) \neq x$  since  $A(t) \in F_m$

The facts  $R(\sigma_j(u), \sigma_j(v)), B(\sigma_j(v))$  have been introduced by oblivious triggers in  $\{tr_1, \dots, tr_{i-1}\}$ . So, by induction hypothesis, the facts  $R(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v)))$  and  $B(h_{x/t}(\sigma_j(v)))$  are in  $F_{m+r(i-1)}$ . Therefore  $h_{x/t}(t_j)$  is an oblivious trigger for  $F_{m+r(i-1)}$ .

- If  $\alpha_j$  is of the form  $R_1(u, v) \wedge R_2(u, v) \rightarrow S(u, v)$ .

The facts  $R_1(\sigma_j(u), \sigma_j(v)), R_2(\sigma_j(u), \sigma_j(v))$  are in  $\sigma_j^s(Head(\alpha_j))$  where  $j < i$ . We have then  $R_1(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v))), R_2(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v))) \in B'_{i-1}$  so by induction hypothesis,  $R_1(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v))), R_2(h_{x/t}(\sigma_j(u)), h_{x/t}(\sigma_j(v))) \in F_{m+r(i-1)}$ .

As  $h_{x/t}(t_j)$  is an oblivious trigger for  $F_{m+i-1}$ ,  $D_i$  is an atomic merge derivation. By definition of an application, we have  $h_{x/t} \circ \sigma_j^s(Head(\alpha_j)) \subseteq F_{m+r(i)}$  and so  $B'_i = B_{i-1} \cup h_{x/t} \circ \sigma_j^s(Head(\alpha_j)) \subseteq F_{m+i}$ . Therefore,  $H(i)$  is true.

We have proved the heredity. So,  $D_n$  is the oblivious derivation that we was looking for. We have  $F_{m+k} = F_m \cup h_{x/t}(Tree_{F_m}(x))$ .

□

**Proposition 5.5.** *Let  $D = F_0, F_1, \dots, F_m$  be an atomic merge chase derivation for the knowledge base  $K$ . Assume that  $x$  is mergeable on  $t$  in  $F_m$ , the atomic merging of  $x$  on  $t$  in  $F_m$  is a retract of  $\mathbf{Fut}(F_m, t, x)$ .*

*Proof.* The atomic merging of  $x$  on  $t$  in  $F_m$  is  $h_{x/t}(F_m)$ . By the Proposition 5.4,  $\mathbf{Fut}(F_m, t, x) = F_m \cup h_{x/t}(Tree_{F_m}(x))$ . So,  $h_{x/t}(F_m) \subseteq \mathbf{Fut}(F_m, t, x)$  since  $\mathbf{Fut}(F_m, t, x) = Tree_{F_m}(x) \cup h_{x/t}(F_m)$ . Finally, as  $h_{x/t}(\mathbf{Fut}(F_m, t, x)) = h_{x/t}(F_m)$ , we have that  $h_{x/t}(F_m) \models \mathbf{Fut}(F_m, t, x)$ .

□

The following theorem is a corollary of Propositions 5.4 and 5.5:

**Theorem 5.1.** *Let  $D = F_0, F_1, \dots$  be an atomic merge chase derivation for the knowledge base  $K$ . The factbases  $F_0, F_1, \dots$  are universal for  $K$ .*

*Proof.* We prove the proposition by induction. By definition of a model,  $M \models F_0$  so the initial step is true. Suppose that  $M \models F_{n-1}$ , where  $n > 0$ , and that  $F_{n-1}$  is not the last factbase of the derivation  $D$ .

- If  $F_n = \mathbf{appl}(F_{n-1}, t)$ , where  $t = (\alpha, \sigma)$  is an oblivious trigger, by Proposition 4.1,  $M \models F_n$ .
- If  $F_n$  is the atomic merging of a variable  $x$  on a term  $t$  in  $F_{n-1}$ , then according to Proposition 5.4, there exists factbases  $G_0, \dots, G_k$  such that (1)  $G_0 = F_{n-1}$ , (2)  $G_k = \mathbf{Fut}(F_{n-1}, t, x)$ , and (3) for  $0 \leq i \leq k-1$ ,  $G_{i+1} = \mathbf{appl}(G_i, t)$  where  $t$  is an oblivious trigger for  $G_i$ . We have then by direct induction on  $0 \leq i \leq k$  and by Proposition 4.1,  $M \models G_i$ . Therefore  $M \models \mathbf{Fut}(F_{n-1}, t, x)$ , so  $M$  is a model of the atomic merging of  $x$  on  $t$  in  $F_{n-1}$  (that is  $F_n$ ) since, by Proposition 5.5,  $F_n$  is a subset of  $\mathbf{Fut}(F_{n-1}, t, x)$ .

□

The main reason to prefer the merge chase instead of the atomic merge chase is that unless the atomic merging operations are applied exhaustively, the merge chase may not terminate on inputs that admit finite universal models:

**Theorem 5.2.** *There exists a **Horn-ALCH** knowledge base and an infinite atomic merge chase derivation for  $K$  such that  $K$  admits a finite universal model.*




Figure 5: Example where the atomic merge chase is not efficient

*Proof.* Let  $F = \{R(a, b), R(b, a), A(a), A(b)\}$  and  $R = \{\alpha = A(x) \rightarrow \exists y. R(x, y) \wedge A(y), \beta = B(x) \rightarrow A(x)\}$ . We consider for the knowledge base  $K = (R, F)$ , the atomic merge chase derivation  $F_0 = F, F_1, F_2, \dots$

- We applied to  $F_0$  the oblivious trigger  $t_1 = (\alpha, \{x \mapsto a\})$ ;
- we then applied to  $F_1$ , the oblivious trigger  $t_2 = (\alpha, \{x \mapsto f_\alpha^y(a)\})$  giving rise to the first factbase of the Figure 5;
- we then apply the oblivious trigger  $t_3 = (\beta, \{x \mapsto b\})$  to obtain the factbase  $F_3$ ;
- At this moment,  $f_\alpha^y(a)$  is mergeable on  $b$  so we do an atomic merging of  $f_\alpha^y(a)$  on  $b$  to get  $F_4$  that is the second factbase of the figure;
- $F_5$  is obtained by the application of the oblivious trigger  $t_4 = (\alpha, \{x \mapsto f_\alpha^y(b)\})$  and  $F_6$  by the oblivious trigger  $t_5 = (\alpha, \{x \mapsto f_\alpha^y(f_\alpha^y(b))\})$ ,  $F_6$  is the third factbase of the figure;
- At this moment,  $f_\alpha^y(b)$  is mergeable on  $a$  so we do an atomic merging of  $f_\alpha^y(b)$  on  $a$  to get  $F_7$  that is the last factbase of the figure;
- We can repeat this infinitely.

But  $K$  admits a finite universal model:  $U = F \cup \{B(b)\}$ .

□

Improve write-up; discuss. is it better ?

We want now prove that a merging computes a core:

**Proposition 5.6.** *For a factbase  $G$  that occurs in a merge chase derivation of some Horn-ALCH knowledge base,  $\text{Merge}(G)$  is a core.*

*Proof.* Suppose for a contradiction that  $\text{Merge}(G)$  is not a core. There exists a factbase  $G' \subsetneq \text{Merge}(G)$  such that  $G'$  is a retract of  $\text{Merge}(G)$ . By Proposition 2.1, there exists then a retraction  $h$  from  $\text{Merge}(G)$  to  $G'$ . We have  $\text{var}(\text{Merge}(G)) \setminus \text{var}(G') \neq \emptyset$ . Let  $x$  be a  $\prec$ -minimal variable of this set. The term  $x$  is a variable, so has been introduced by the chase due to a rule of the form  $(\exists_+)$ , so there exists a term  $t$  such that  $t \prec x$ .

- We have  $\mathbf{Preds}_{Merge(G)}^2(t, x) \neq \emptyset$ . By  $\prec$ -minimality of  $x$ ,  $t \in \mathbf{Vars}(G')$ . So, as  $h$  is a retraction:  $h(t) = t$ , so for  $R \in \mathbf{Preds}_{Merge(G)}^2(t, x)$ ,  $h(R(t, x)) = R(t, h(x)) \in Merge(G)$  and so  $R \in \mathbf{Preds}_{Merge(G)}^2(t, h(x))$ . Thus  $\mathbf{Preds}_{Merge(G)}^2(t, x) \subseteq \mathbf{Preds}_{Merge(G)}^2(t, h(x))$ .
- As  $\mathbf{Preds}_{Merge(G)}^2(t, x) \subseteq \mathbf{Preds}_{Merge(G)}^2(t, h(x))$  and  $\mathbf{Preds}_{Merge(G)}^2(t, x) \neq \emptyset$ , we have  $t \prec h(x)$ .
- $x \notin G'$  and  $h(x) \in G'$  so  $h(x) \neq x$ .
- Let  $A \in \mathbf{Preds}_{Merge(G)}^1(x)$ .  $h(A(x)) \in Merge(G)$  so  $A(h(x)) \in Merge(G)$  so  $\mathbf{Preds}_{Merge(G)}^1(x) \subseteq \mathbf{Preds}_{Merge(G)}^1(h(x))$ .

Consequently,  $x$  is mergeable on  $h(x)$  in  $Merge(G)$  which results on a contradiction. Hence,  $Merge(G)$  is a core.  $\square$

$Merge(G)$  is a core but not necessarily the core of  $G$ . We need the following lemma to prove that the merge chase computes an universal model:

**Proposition 5.7.** *Let  $D = F_0, \dots, F_k, \dots$  be an atomic merge chase derivation of a knowledge base  $K$ ,  $\alpha$  be a rule, and  $\sigma$  be a substitution such that  $\sigma(\text{Body}(\alpha)) \subseteq F_k$ . There exists then  $n \geq 0$  and a substitution  $\hat{\sigma}$  prolonging  $\sigma$  such that for all  $j \geq n$ ,  $\hat{\sigma}(\text{Head}(\alpha)) \subseteq F_j$ .*

*Proof.* As the derivation  $D$  is fair, there exists  $n \geq 0$  such that  $\mathbf{appl}(F_n, t) = F_n$ ; thus  $\sigma^s(\text{Head}(\alpha)) \subseteq F_n$ . We show by induction that for  $n \leq j$ , there exists a substitution  $\hat{\sigma}$  prolonging  $\sigma$  such that  $\hat{\sigma}(\text{Head}(\alpha)) \subseteq F_j$ . The initialisation is true with  $\hat{\sigma} = \sigma^s$ . Assume that there exists a substitution  $\hat{\sigma}$  prolonging  $\sigma$  such that  $\hat{\sigma}(\text{Head}(\alpha)) \subseteq F_{j-1}$  where  $n < j$ . If  $F_j = \mathbf{appl}(F_{j-1}, t)$  where  $t$  is an oblivious trigger, then  $\hat{\sigma}(\text{Head}(\alpha)) \subseteq F_j$  since  $F_{j-1} \subseteq F_j$ . If  $F_j$  is the atomic merging of the variable  $x$  on the term  $t$  in  $F_{j-1}$ , then  $F_j = h_{x/t}(F_{j-1})$ . Therefore  $h_{x/t}(\hat{\sigma}(\text{Head}(\alpha))) \subseteq F_j$  and so  $h_{x/t} \circ \hat{\sigma}$  is the substitution that we are looking for. The heredity is proved.  $\square$

**Proposition 5.8.** *The merge chase computes a finite universal model of  $K$  when it terminates.*

*Proof.* Let  $D = F_0, \dots, F_n$  be a merge chase for  $K = (R, G)$ .

- The merge chase never take off ground facts and  $G = F_0$  so  $G \subseteq F_n$ . We have then  $F_n \models G$ . Suppose that there exists a rule  $\alpha$  in  $R$  and a substitution  $\sigma$  such that  $F_n \models \sigma(\text{Body}(\alpha))$ . Then by Proposition 5.7, there exists a substitution  $\hat{\sigma}$  prolonging  $\sigma$  such that  $\hat{\sigma}(\text{Head}(\alpha)) \subseteq F_n$ . We can conclude that  $F_n \models R$ , so  $F_n$  is a model of  $K$ .
- According to Proposition 5.1,  $F_n$  is a universal model of  $K$ .
- $F_n$  is finite.

$\square$

**Proposition 5.9.** *If there exists a finite universal model for a **Horn-ALCH** knowledge base  $K = (R, F)$ , then the merge chase terminates.*

*Proof.* • Suppose for a contradiction that  $K$  admits a finite universal model  $U$  for  $K$  and does not admit a finite merge chase sequence. There exists so an infinite merge chase sequence  $D = F_0, F_1, \dots$

- A term  $t$  is *redundant* with respect to this sequence if  $t \in \mathbf{Terms}(F_i)$  and  $t \notin \mathbf{Terms}(F_j)$  for some  $i < j$ .



- For each  $i$ , let  $G_i$  be the maximal subset of  $F_i$  that does not contain redundant terms.
- We pose  $M = \cup_i G_i$ . For a model  $N$  of  $K$  and for  $i \in \mathbb{N}$ , there exists a homomorphism  $h_i$  from  $F_i$  to  $N$  since  $F_i$  is universal for  $K$  by Proposition 5.1. As  $G_i \subseteq F_i$ ,  $h_i$  is a homomorphism from  $G_i$  to  $N$ . Finally,  $\cup_i h_i$  is a homomorphism from  $M$  to  $N$  so  $M$  is universal for  $K$ .
- Constants cannot be redondants, so  $F \subseteq M$  since  $G_0 = F$ . We have then  $M \models F$ . Suppose that there exists a rule  $\alpha$  in  $R$  and a substitution  $\sigma$  such that  $M \models \sigma(\text{Body}(\alpha))$ . There exists then  $n \geq 0$  such that  $G_n \models \sigma(\text{Body}(\alpha))$  so  $F_n \models \sigma(\text{Body}(\alpha))$  since  $G_n \subseteq F_n$ . Then by Proposition 5.7, for  $k \geq n$ , there exists a substitution  $\sigma_k$  prolonging  $\sigma$  such that  $\sigma_k(\text{Head}(\alpha)) \subseteq F_k$ . If  $\alpha$  is not of the form  $(\exists_+)$ , then  $\sigma_k = \sigma$ . As all the variables in the range of  $\sigma$  are in  $\mathbf{Vars}(M)$ , they are not redundant and so  $\sigma(\text{Head}(\alpha)) \subseteq G_n \subseteq M$ . Otherwise  $\alpha$  is of the form  $A(x) \rightarrow \exists y. R(x, y) \wedge B(y)$ . We have then  $\sigma_k = \sigma \cup \{y \mapsto f_\beta^y(\sigma(x))\}$  with  $\beta$  a rule in  $R$ . There is a finite number of rules in  $R$  and once a variable is merged, it does not reappear, therefore there exists  $k \geq n$  such that for all  $i \geq k$ ,  $\sigma_i = \sigma_k$ . Then  $\sigma_k(y)$  is not redundant and as all the variables in the range of  $\sigma$  are in  $\mathbf{Vars}(M)$ , they are not redundant, so  $\sigma_k(\text{Head}(\alpha)) \subseteq G_k \subseteq M$ . We can conclude that  $M \models R$ , so  $M$  is an universal model of  $K$ .
- As  $M$  is an universal model of  $K$ ,  $M \models U$ . There exists then a homomorphism  $h$  from  $U$  to  $M$ . As  $U$  is finite, the factbase  $h(U) \subseteq M$  is also finite. The sequence  $G_0, G_1, \dots$  is monotonic (that is  $G_0 \subseteq G_1 \subseteq \dots$ ) so there exist  $i$  such that  $h(U) \subseteq G_i$ . We have then  $F_i \models h(U)$  since  $G_i \subseteq F_i$ . We have  $h(U) \models U$ , so  $F_i \models U$ .
- As  $D$  is fair, there exists  $j \geq i$  such that  $F_j$  is a core.
- By proposition 5.1,  $F_j$  is universal for  $K$  so  $U \models F_j$ . We have  $F_j \models U$  since  $F_j \models F_i$ , so  $F_j$  is isomorphe to the core of  $U$ . Therefore  $F_j$  is an universal model for  $K$ .
- There exists a finite number of triggers for  $F_j$  and  $D$  is fair. So, there exists  $k \geq j$  such that all the triggers for  $F_j$  has been applied in the derivation  $F_0, F_1, \dots, F_k$ . Note that this step is necessary to garanttee the first condition in the Definition 5.6 of fairness.
- As  $D$  is fair, there exists  $l \geq k$  such that  $F_l$  is a core. As  $F_j$  is a model for  $K$ ,  $F_l = F_j$ .
- The derivation  $F_0, \dots, F_l$  is then fair so it is a finite merge chase sequence that leads us to a contradiction.

□

The following theorem is then a direct consequence of Propositions 5.8 and 5.9.

**Theorem 5.3.** The merge chase computes an universal model if and only if there exists an universal model.

We will now describe a deterministic algorithm to merge a factbase:

**Definition 5.9 (Merging).** Let  $F$  be a factbase that occurs in a merge chase derivation

of the knowledge base  $K$ .

---

**Algorithm 1:** Merge( $F$ ):

---

```

1 Let Vars( $F$ ) =  $\{x_1, \dots, x_n\}$  be such that  $(x_i \prec^+ x_j) \Rightarrow i < j$  ;
2 for  $i = 1$  to  $n$  do
3   if  $x_i$  is still a variable in  $F$  then
4     for all term  $t$  such that  $x_i$  is mergeable on  $t$  do
5        $F \leftarrow$  the atomic merging of  $x_i$  on  $t$  in  $F$ .
6     end
7   end
8 end
9 return  $F$ 

```

---

At line 1, we can sort terms like that because, by proposition 5.2,  $\prec^+$  is a strict partial order over the set of variables of  $F$ .

Note that the application of an atomic merge may result in new mergeable variables. Therefore, we have to be carefull about the order of the variables in the Algorithm 1. In the Example 5.1, if we treat  $f_\beta^z(f_\alpha^z(a))$  before  $f_\alpha^z(a)$ , then at the moment where we treat  $f_\beta^z(f_\alpha^z(a))$ , it does not have any term  $t$  yet such that  $f_\beta^z(f_\alpha^z(a))$  is mergeable on  $t$ . At the end, we get the factbase of the middle and we will not have merged every possible mergeable variable.

The Example 5.2 shows the importance of doing a total merging. We have to prove that our merging algorithm does a total merging:

**Proposition 5.10.** *Let  $G$  be a factbase that occurs in a chase derivation of the knowledge base  $K$ . There does not exists a term  $t$  and a variable  $x$  such that  $x$  is mergeable on  $t$  in  $\text{Merge}(G)$ .*

*Proof.* Suppose for a contradiction that there exists a term  $t$  and a variable  $x$  such that  $x$  is mergeable on  $t$  in  $\text{Merge}(G)$ , that is, there exists a term  $t'$  such that  $\mathbf{Preds}_{\text{Merge}(G)}^2(t', x) \neq \emptyset$  and  $\mathbf{Preds}_{\text{Merge}(G)}^2(t', x) \subseteq \mathbf{Preds}_{\text{Merge}(G)}^2(t', t)$ . This case can happen only if  $x$  became mergeable after that  $x$  has been traited by the merging algorithm. Thus, during the merging, there has been an atomic merging on  $t'$ . Let  $y$  be the variable merged on  $t'$  such that  $y \prec x$ . We note  $G^1$  the factbase just before the atomic merging of  $y$  on  $t'$  and we note  $G^2$  the factbase just after the atomic merging. There exists a term  $t_0$  such that  $\mathbf{Preds}_{G^1}^2(t_0, y) \neq \emptyset$  and  $\mathbf{Preds}_{G^1}^2(t_0, y) \subseteq \mathbf{Preds}_{G^1}^2(t_0, t')$ . The factbase  $G^1$  is in the left of the Figure 6 and the factbase  $G^2$  is in the right (we do not represent all the graphs):

We have  $t_0 \prec t' \prec t$  and  $t_0 \prec y \prec x$  so  $x$  should have been treated by the algorithm after the merging of  $t'$  and  $y$  so the algorithm will merge  $x$  on  $t$ . It is a contradiction.  $\square$

## 6 Conclusion

## References

- [1] Serge Abiteboul, Richard Hull, and Victor Vianu. *Foundations of Databases: The Logical Level*. Addison-Wesley Longman Publishing Co., Inc., USA, 1st edition, 1995.
- [2] Catriel Beeri and Moshe Y. Vardi. The implication problem for data dependencies. In *Proceedings of the 8th Colloquium on Automata, Languages and Programming*, page 73–85, Berlin, Heidelberg, 1981. Springer-Verlag.
- [3] A. Cali, G. Gottlob, and M. Kifer. Taming the infinite chase: Query answering under expressive relational constraints. *Journal of Artificial Intelligence Research*, 48:115–174, Oct 2013.




Figure 6: Illustration of the proof

- [4] Alin Deutsch, Alan Nash, and Jeffrey B. Remmel. The chase revisited. In Maurizio Lenzerini and Domenico Lembo, editors, *Proceedings of the Twenty-Seventh ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems, PODS 2008, June 9-11, 2008, Vancouver, BC, Canada*, pages 149–158. ACM, 2008.
- [5] Markus Krötzsch, Sebastian Rudolph, and Pascal Hitzler. Complexities of horn description logics. *ACM Trans. Comput. Log.*, 14(1):2:1–2:36, 2013.