

M3ADMIN Reference Guide

M3AD-02

August 2026

Version 1.0.0

Preface

About This Guide

M3 Admin is a comprehensive command-line administration tool for the Maestro environment. It provides centralized management capabilities for multi-cloud infrastructure, enabling administrators to manage applications, parents, tenants, credentials, and resources across AWS, Azure, Google Cloud Platform, and private cloud environments.

This Reference Guide provides users with the overview of the available M3 Admin CLI commands, their purpose, parameters, and usage examples.

The guide is generated automatically based on the CLI tool state at the moment of the Guide creation.

Target Audience

The guide is designed for Maestro administrative users who have the responsibility to perform configuration and setup tasks, maintenance works and assisting users with matters beyond the self-service scope.

Related Documents

- For the information about M3 Admin CLI tool setup, configuration, and usage, refer to M3 Admin User Guide.
- For the information about Maestro tool usage via a command line interface, see M3 CLI User Guide.

Table of Contents

- **[CLI] m3admin**
 - **[Group] application** - *The Application group is used to manage AWS, AZURE, and GCP credentials*
 - **[Group] parent** - *Operates parent entities*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] validate_credentials
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] describe_credentials_template
 - [Command] get_type_params
 - [Command] get_types
 - [Command] rotate_credentials
 - [Command] update
 - **[Group] approval** - *The approval group is used to set up the approval mechanism*
 - [Command] approvers_available_for_requester
 - [Command] disable_mechanism
 - [Command] enable_mechanism
 - [Command] set_approval_link_protection
 - **[Group] aws** - *The AWS group is used to manage resources of the AWS cloud provider (activation/deactivation of tenants, managing instance metrics, managing tenant security groups)*
 - [Command] activate
 - [Command] activate_region
 - [Command] add_image
 - [Command] configure_athena
 - [Command] deactivate
 - [Command] delete_image
 - [Command] delete_security_groups
 - [Command] deploy_security_groups
 - [Command] describe_security_groups
 - [Command] manage_cost_allocation_tags
 - [Command] manage_currency
 - [Command] manage_security_group_in_region
 - [Command] repair_security_groups
 - [Command] reset_vm_counters
 - [Command] set_instance_profile
 - [Command] validate_vm_counters
 - **[Group] azure** - *Manages Azure-related resources including billing, enrolment, credentials, etc*
 - [Command] activate
 - [Command] activate_region
 - [Command] add_image
 - [Command] create_diagnostic_account_storage
 - [Command] create_resource_group

- [Command] create_subscription_network_security_configuration
- [Command] create_subscription_resource_group
- [Command] deactivate
- [Command] delete_diagnostic_account_storage
- [Command] delete_image
- [Command] delete_resource_group
- [Command] delete_subscription_network_security_configuration
- [Command] delete_subscription_resource_group
- [Command] deploy_security_groups
- [Command] describe_diagnostic_account_storage
- [Command] list_image_versions
- [Command] list_offers
- [Command] list_publishers
- [Command] list_skus
- [Command] manage_currency
- [Command] reset_vm_counters
- [Command] rotate_diagnostic_storage_credentials
- [Command] rotate_storage_credentials
- [Command] update_tenant_id
- [Command] validate_vm_counters
- **[Group] billing** - *[Installable Module] Manages billing quotas, configuration, processing status, and record aggregation for specified periods*
 - **[Group] setting** - *Manages Billing environment settings*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] add_cost_center
 - [Command] add_tenant_to_customer
 - [Command] adjustment
 - [Command] adjustment_configure
 - [Command] aggregate_yearly_records
 - [Command] all_resources_costs_report
 - [Command] archive_big_query
 - [Command] archive_collection
 - [Command] budget
 - [Command] close_month
 - [Command] close_month_for_account
 - [Command] configure
 - [Command] configure_gcp_big_query
 - [Command] delete_kpi
 - [Command] describe_azure_billing_config
 - [Command] describe_business_units
 - [Command] describe_month
 - [Command] describe_tenant_business_unit
 - [Command] export_aws

- [Command] export_azure
- [Command] export_google
- [Command] export_status
- [Command] get_currency
- [Command] get_sources
- [Command] get_top_accounts_report
- [Command] health_check
- [Command] manage_eo_account
- [Command] price_quota
- [Command] pricing_policy
- [Command] publisher_check
- [Command] radar_aggregate
- [Command] reset_billing
- [Command] send_cloud_radar_report
- [Command] send_low_instance_utilization_report
- [Command] send_monthly_analytic_optimization_report
- [Command] send_sponsors_reports
- [Command] send_units_reports
- [Command] set_azure_billing_config
- [Command] set_kpi
- [Command] thread_server_config
- [Command] timeline
- [Command] update_reports_config
- [Command] upload_aws_china_billing
- [Command] upload_azure_billing
- **[Group] chef** - *[Installable Module] Manages Chef-related resources and configurations*
 - **[Group] setting** - *Manages Chef environment settings*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] add_configuration
 - [Command] assign_configuration
 - [Command] delete_client
 - [Command] delete_configuration
 - [Command] describe_configuration
 - [Command] get_client
 - [Command] set_configuration
 - [Command] unassign_configuration
 - [Command] update_configuration
 - [Command] update_role
- **[Group] configure** - *Manages m3admin. Resource configuration in services such as AWS lambda, SNS, queue configuration in Rabbit MQ, audit configuration*
 - [Command] activate_cf_audit
 - [Command] activate_ec2_audit
 - [Command] activate_guardduty

- [Command] activate_iam_audit
- [Command] activate_tenant_cf_audit
- [Command] activate_tenant_ec2_audit
- [Command] activate_tenant_guarddduty
- [Command] activate_tenant_iam_audit
- [Command] add_tenant_permission
- [Command] cognito_set_permissions
- [Command] create_audit_and_rpc_queues
- [Command] create_audit_queue
- [Command] create_rpc_queues
- [Command] deactivate_cf_audit
- [Command] deactivate_ec2_audit
- [Command] deactivate_guarddduty
- [Command] deactivate_tenant_cf_audit
- [Command] deactivate_tenant_ec2_audit
- [Command] deactivate_tenant_guarddduty
- [Command] delete_tenant_permission
- **[Group] education** - *[Installable Module] Manages educational resources: labs, sandboxes, triggers, quarantine, cloud configurations, and system access*
 - **[Group] application** - *Manages application entities within the education system*
 - [Command] add
 - **[Group] azure** - *Manages Azure subscriptions within the education system*
 - [Command] add_worker
 - [Command] check_providers
 - [Command] onboard_subscription
 - [Command] register_providers
 - [Command] remove_worker
 - **[Group] cicd** - *Manages CI/CD pipeline configurations for task deployment resources*
 - **[Group] taskconfig** - *Manages task deployment resource config entries*
 - [Command] delete
 - [Command] upsert
 - **[Group] configure** - *Configures education system settings: accounts, logging, notifications, and IAM roles*
 - [Command] account_info
 - [Command] ci_account_info
 - [Command] cleanup_info
 - [Command] lab_account_logging_info
 - [Command] lab_admin_iam_info
 - [Command] sep_s3_root
 - [Command] sqs_notifications
 - [Command] stack_set_info
 - **[Group] lab** - *Manages lab tenant lifecycle: activation, deactivation, and description*
 - [Command] activate
 - [Command] deactivate
 - [Command] describe
 - [Command] prolong
 - **[Group] parent** - *Manages parent entities within the education system*

- [Command] add
 - [Command] update
- [Group] **quarantine** - *Manages and monitors quarantine measures, including account details and logs*
 - [Command] describe
 - [Command] describe_logs
- [Group] **sandbox** - *Manages sandboxes: allocate, release, or create*
 - [Group] **deployment** - *Manages sandbox deployments: update and describe*
 - [Command] delete
 - [Command] describe
 - [Command] separate
 - [Command] update
 - [Command] allocate
 - [Command] create
 - [Command] health
 - [Command] register
 - [Command] release
 - [Command] unregister
- [Group] **support** - *Manages system accounts and privileged access within the education platform*
 - [Command] add_sys_account
 - [Command] delete_sys_account
 - [Command] list_sys_account
 - [Command] privileged_access
- [Group] **trigger** - *Manages triggers: add, delete, and describe SQS triggers for automated event responses*
 - [Command] add_sqs
 - [Command] delete
 - [Command] describe
 - [Command] disable
 - [Command] enable
- [Command] audit
- [Command] move_accounts
- [Command] onboard_organization
- [Command] run_infrastructure_check
- [Group] **enterprise** - *Manages enterprise-related resources*
 - [Command] activate
 - [Command] activate_region
 - [Command] deactivate
 - [Command] delete_image
- [Group] **environment** - *Manages environment*
 - [Group] **server** - *The server subgroup contains commands related to Maestro server configuration and its services management*
 - [Command] add_jmx_access
 - [Command] add_profiles
 - [Command] configure_access
 - [Command] configure_metrics
 - [Command] delete_jmx_access

- [Command] delete_profiles
- [Command] deregister
- [Command] deregister_m3admin_configuration
- [Command] deregister_mail_configuration
- [Command] deregister_mongo
- [Command] deregister_rabbit_configuration
- [Command] deregister_sdk_configuration
- [Command] describe
- [Command] describe_jmx_access
- [Command] describe_m3admin_configuration
- [Command] describe_mail_configuration
- [Command] describe_mongo
- [Command] describe_profiles
- [Command] describe_rabbit_configuration
- [Command] describe_sdk_configuration
- [Command] disable
- [Command] enable
- [Command] evict_cache
- [Command] register
- [Command] register_m3admin_configuration
- [Command] register_mail_configuration
- [Command] register_mongo
- [Command] register_rabbit_configuration
- [Command] register_sdk_configuration
- [Command] register_terraform_versions
- [Command] start_consuming
- [Command] stop_consuming
- [Command] update
- [Command] update_jmx_access
- [Command] update_m3admin_configuration
- [Command] update_mail_configuration
- [Command] update_mongo
- [Command] update_profiles
- [Command] update_rabbit_configuration
- [Command] update_sdk_configuration
- [Group] **setting** - *Manages environment settings*
 - [Command] add
 - [Command] add_available_cloud_provider
 - [Command] add_aws_activation_settings
 - [Command] add_azure_activation_settings
 - [Command] add_default_tenant
 - [Command] add_default_tenant_group
 - [Command] add_google_activation_settings
 - [Command] add_resolved_resource_name
 - [Command] add_resource_by_alias
 - [Command] configure_service

- [Command] delete
- [Command] delete_aws_activation_settings
- [Command] delete_azure_activation_settings
- [Command] delete_google_activation_settings
- [Command] describe
- [Command] describe_aws_activation_settings
- [Command] describe_azure_activation_settings
- [Command] describe_google_activation_settings
- [Command] save_private_cloud_metrics
- [Command] update
- [Command] update_aws_activation_settings
- [Command] update_azure_activation_settings
- [Command] update_google_activation_settings
- [Command] add_application
- [Command] add_customer
- [Command] add_domain_auth_mapping
- [Command] add_environment_testers
- [Command] add_parent
- [Command] add_permission_group
- [Command] add_region
- [Command] add_tenant_to_tenant_group
- [Command] api_gateway_request_logging
- [Command] audit
- [Command] block_users
- [Command] change_customer_display_name
- [Command] configure_customer_admins
- [Command] delete_application
- [Command] delete_customer
- [Command] delete_customer_admins
- [Command] delete_parent
- [Command] delete_permission_group
- [Command] delete_region
- [Command] delete_sdk_key
- [Command] delete_secured_file_with_setting
- [Command] delete_tenant_from_tenant_group
- [Command] deploy_db_initial_data
- [Command] deploy_dictionaries
- [Command] deploy_s3_initial_data
- [Command] deploy_ui
- [Command] deregister_customer_access_key
- [Command] deregister_nessus_server
- [Command] describe_application
- [Command] describe_customer_admins
- [Command] describe_parent
- [Command] describe_sdk_key
- [Command] describe_vendor

- [Command] disable_autoscaling
- [Command] disable_instances_termination_protection
- [Command] disable_maintenance_mode
- [Command] disable_metric
- [Command] download_deploy_output
- [Command] enable_autoscaling
- [Command] enable_maintenance_mode
- [Command] enable_metric
- [Command] find_deployment_object
- [Command] generate_sdk_key
- [Command] link_parent_to_application
- [Command] list_customers
- [Command] list_users
- [Command] manage_vendor
- [Command] prolong_sdk_key
- [Command] purge_s3_buckets
- [Command] register_api_id
- [Command] register_api_stage
- [Command] register_bundle
- [Command] register_customer_access_key
- [Command] register_identity_pool_id
- [Command] register_identity_pool_id_v2
- [Command] register_instance
- [Command] register_nessus_server
- [Command] register_notification_application
- [Command] register_notification_application_v2
- [Command] register_resources
- [Command] register_s3_bucket
- [Command] register_sdk_key
- [Command] register_ui_bucket
- [Command] register_ui_bucket_v2
- [Command] register_ui_components
- [Command] remove_ssm_parameter
- [Command] save_secured_file_with_setting
- [Command] save_secured_parameter
- [Command] set_available_features_to_customer
- [Command] set_elastic_ip
- [Command] set_hardware_credit_support
- [Command] set_location_configuration
- [Command] set_proxy_host
- [Command] set_sdk_key_autorotation
- [Command] set_security_groups
- [Command] show_api_gateway_id
- [Command] status
- [Command] update_application
- [Command] update_parent

- [Command] validate_db_initial_data
- **[Group] google** - *Manages Google-related resources*
 - [Command] activate
 - [Command] activate_region
 - [Command] add_image
 - [Command] apply_sku_id_configuration
 - [Command] create_firewall_rules
 - [Command] create_network
 - [Command] deactivate
 - [Command] delete_image
 - [Command] delete_network
 - [Command] describe_network
 - [Command] describe_sku_id_configuration
 - [Command] describe_subnetwork
 - [Command] manage_alpha_locations
 - [Command] manage_workspace
 - [Command] remove_sku_id_configuration
 - [Command] reset_vm_counters
 - [Command] validate_vm_counters
- **[Group] hardware** - *Manages hardware-related resources*
 - [Command] activate
 - [Command] activate_region
 - [Command] deactivate
 - [Command] delete_image
- **[Group] maintenance** - *[Installable Module] Manages Maestro environment state and maintenance operations*
 - **[Group] setting** - *Manages Maintenance environment settings*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] check_billing_lock
 - [Command] lock_billing
 - [Command] unlock_billing
 - [Command] update_maestro_stage_throttling
- **[Group] notifications** - *[Installable Module] Manages notification settings and configurations*
 - **[Group] setting** - *Manages Notifications environment settings*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] add_group_mapping
 - [Command] add_mail_settings
 - [Command] add_receivers_stub
 - [Command] add_subscriber
 - [Command] configure_bcc

- [Command] `configure_black_list`
- [Command] `configure_customer_notifications`
- [Command] `configure_notifications`
- [Command] `configure_sender`
- [Command] `delete_customer_notifications`
- [Command] `delete_group_mapping`
- [Command] `delete_mail_config`
- [Command] `delete_mail_settings`
- [Command] `delete_receivers_stub`
- [Command] `delete_subscriber`
- [Command] `describe_black_list`
- [Command] `describe_customer_notifications`
- [Command] `describe_group_mapping`
- [Command] `describe_mail_config`
- [Command] `describe_mail_settings`
- [Command] `describe_notification_group`
- [Command] `describe_receivers_stub`
- [Command] `describe_subscriptions`
- [Command] `get_customer_dls`
- [Command] `set_customer_dls`
- [Command] `set_mail_config`
- [Command] `subscribe`
- [Command] `unset_customer_dls`
- [Command] `unsubscribe`
- [Command] `update_mail_settings`
- [Command] `update_receivers_stub`
- [Command] `update_subscriber`
- [Group] **nutanix** - *Manages nutanix-related resources*
 - [Command] `activate`
 - [Command] `activate_region`
 - [Command] `add_image`
 - [Command] `deactivate`
 - [Command] `delete_image`
 - [Command] `describe_image`
- [Group] **openstack** - *Manages OPENSTACK-related resources*
 - [Command] `activate`
 - [Command] `activate_region`
 - [Command] `add_image`
 - [Command] `add_parameters_to_region`
 - [Command] `add_public_image`
 - [Command] `add_region_metrics`
 - [Command] `deactivate`
 - [Command] `delete_image`
 - [Command] `delete_region_metrics`
 - [Command] `describe_image`
 - [Command] `describe_region_metrics`

- [Command] reset_vm_counters
- [Command] update_region_metrics
- [Command] validate_vm_counters
- **[Group] paas** - *Manages PaaS-related resources*
 - **[Group] configuration** - *Manages the configuration for the auto-configuration script bucket*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] add_service_support
 - [Command] add_service_usage
 - [Command] delete_init_script
 - [Command] delete_service
 - [Command] delete_service_parameter
 - [Command] describe_init_script
 - [Command] describe_service
 - [Command] describe_service_parameter
 - [Command] register_service
 - [Command] register_service_parameter
 - [Command] update_service
 - [Command] upload_init_script
- **[Group] patch** - *Manages patch-related commands*
 - [Command] patch_database
- **[Group] permissions** - *[Installable Module] Manages user permissions and access control*
 - **[Group] setting** - *Manages Permission environment settings*
 - [Command] add
 - [Command] delete
 - [Command] describe
 - [Command] update
 - [Command] add_console_service_mapping
 - [Command] add_group
 - [Command] add_position_to_tenant
 - [Command] add_user
 - [Command] assign_position
 - [Command] block_user
 - [Command] delete_console_service_mapping
 - [Command] delete_group
 - [Command] delete_mapping
 - [Command] delete_position_from_tenant
 - [Command] delete_title_position_mapping
 - [Command] delete_user
 - [Command] delete_user_auth_password
 - [Command] describe_available_positions
 - [Command] describe_blocked_user_config
 - [Command] describe_group
 - [Command] describe_mapping

- [Command] describe_title_position_mapping
- [Command] describe_user
- [Command] describe_user_permissions
- [Command] get_blocked_user
- [Command] set_blocked_user_config
- [Command] set_console_mapping
- [Command] set_mapping
- [Command] set_tenant_position_status
- [Command] set_title_position_mapping
- [Command] set_user_auth_password
- [Command] unassign_position
- [Command] unblock_user
- [Command] update_group
- [Group] **private** - *[Installable Module] Manages private agent configurations and operations*
 - [Group] **nutanix** - *Manages Nutanix resources via private agent*
 - [Group] **image** - *Manages images in Nutanix tenants*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] list
 - [Group] **region** - *Manages Nutanix regions and their management status*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] get_management_status
 - [Command] list
 - [Command] set_management_status
 - [Group] **shape** - *Manages VM shapes in Nutanix regions*
 - [Command] clean
 - [Command] list
 - [Command] set
 - [Group] **tenant** - *Manages Nutanix tenants, their health checks, and management status*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] get_health_check_result
 - [Command] get_management_status
 - [Command] list
 - [Command] set_management_status
 - [Group] **openstack** - *Manages OPENSTACK resources via private agent*
 - [Group] **image** - *Manages images in OPENSTACK regions*
 - [Command] create
 - [Command] list
 - [Group] **projectmeta** - *Manages admin project metadata for OPENSTACK regions*
 - [Command] add_image
 - [Command] create

- [Command] delete_image
 - [Command] get
- **[Group] rabbit** - *Manages RabbitMQ configuration for OPENSTACK regions*
 - [Command] get_config
 - [Command] set_config
- **[Group] region** - *Manages OPENSTACK regions and service tenant configuration*
 - [Command] create
 - [Command] get
 - [Command] get_service_tenant
 - [Command] list
 - [Command] set_management_status
 - [Command] set_service_tenant
- **[Group] security** - *Manages security mode configurations for OPENSTACK regions and tenants*
 - [Command] configure
 - [Command] delete
 - [Command] describe
 - [Command] set_tenant_mode
- **[Group] shape** - *Manages VM shapes in OPENSTACK regions*
 - [Command] create
 - [Command] list
- **[Group] tenant** - *Manages OPENSTACK tenants, users, and network configuration*
 - [Command] configure_network
 - [Command] create
 - [Command] create_user
 - [Command] get
 - [Command] get_user
 - [Command] list
 - [Command] set_management_status
- **[Group] user** - *Manages admin user configuration for OPENSTACK regions*
 - [Command] get
 - [Command] set
- **[Group] system** - *Manages by private agent system related resources*
 - [Command] register_agent
 - [Command] set_tenant_describer_mode
 - [Command] sync_private_images
- **[Group] vmware** - *Manages VMware resources via private agent*
 - **[Group] organization** - *Manages VMware organizations and tenant linkage*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] link
 - [Command] unlink
 - [Command] update
 - **[Group] quota** - *Manages resource quotas for VMware tenants*
 - [Command] create

- [Command] delete
 - [Command] get
 - [Command] update
- **[Group] rabbit** - *Manages RabbitMQ configuration for VMware regions*
 - [Command] get_config
 - [Command] set_config
- **[Group] region** - *Manages VMware region configurations*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] get_management_status
 - [Command] list
 - [Command] set_management_status
- **[Group] shape** - *Manages VM shapes for VMware tenants*
 - [Command] clean
 - [Command] list
 - [Command] set
- **[Group] template** - *Manages VM templates in VMware regions*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] list
 - [Command] set_alias
- **[Group] tenant** - *Manages tenants in VMware regions*
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] get_health_check
 - [Command] get_management_status
 - [Command] get_usage
 - [Command] list
 - [Command] set_management_status
- **[Group] vdc** - *Manages Virtual Data Centers in VMware regions*
 - [Command] add_readonly
 - [Command] get
 - [Command] list_cloud
 - [Command] list_configured
 - [Command] remove_readonly
- **[Group] vsphere** - *Manages vSphere resources via private agent*
 - **[Group] region** - *Manages vSphere regions, management status, and network configuration*
 - [Command] add_network
 - [Command] create
 - [Command] delete
 - [Command] get
 - [Command] get_management_status
 - [Command] list

- [Command] set_management_status
- **[Group] shape** - *Manages VM shapes in vSphere regions*
 - [Command] clean
 - [Command] list
 - [Command] set
- **[Group] tenant** - *Manages vSphere tenants, health checks, images, and management status*
 - [Command] create
 - [Command] create_image
 - [Command] delete
 - [Command] get
 - [Command] get_health_check_result
 - [Command] get_management_status
 - [Command] list
 - [Command] set_management_status
- **[Group] region** - *Manages regions-related resources*
 - [Command] add_virt_profile
 - [Command] delete_virt_profile
 - [Command] describe
 - [Command] describe_virt_profile
 - [Command] update_virt_profile
- **[Group] security** - *Manages security platforms Maestro is integrated with*
 - [Command] activate_custodian_for_tenant
 - [Command] add_qualys_cloud_view_policy
 - [Command] add_qualys_configuration
 - [Command] deactivate_custodian_for_tenant
 - [Command] delete_qualys_cloud_view_policy
 - [Command] delete_qualys_configuration
 - [Command] describe_qualys_configuration
 - [Command] manage_qualys_excluded_controls
 - [Command] manage_qualys_recommended_controls
 - [Command] set_qualys_platform
 - [Command] update_qualys_configuration
- **[Group] tenant** - *Manages tenants*
 - [Command] add_contacts
 - [Command] add_vpc
 - [Command] check_status
 - [Command] deactivate_region
 - [Command] delete_chef_configuration
 - [Command] delete_contacts
 - [Command] delete_instance_quota
 - [Command] delete_volume_quota
 - [Command] describe
 - [Command] describe_chef_configuration
 - [Command] describe_contacts
 - [Command] describe_instance_quota

- [Command] describe_regions
- [Command] describe_terraform
- [Command] describe_type
- [Command] describe_volume_quota
- [Command] disable
- [Command] rename
- [Command] set_deactivation_request_date
- [Command] set_instance_quota
- [Command] set_region_hidden_attribute
- [Command] set_tenant_state_attribute
- [Command] set_type
- [Command] set_volume_quota
- [Command] update_contacts
- [Group] **uisdk** - *Manages Javascript UI SDK for API Gateway*
 - [Command] add_customer_icon
 - [Command] delete
 - [Command] delete_customer_icon
 - [Command] describe_customer_icon
 - [Command] generate
 - [Command] list_versions
 - [Command] publish
 - [Command] save_current_native_version
 - [Command] update_customer_icon
- [Group] **vclouddirector** - *Manages vCloudDirector-related (Vmware) resources*
 - [Command] activate
 - [Command] activate_region
 - [Command] add_image
 - [Command] deactivate
 - [Command] delete_image
 - [Command] describe_image
- [Group] **vsphere** - *Manages vsphere-related resources*
 - [Command] activate
 - [Command] activate_region
 - [Command] add_image
 - [Command] deactivate
 - [Command] delete_image
 - [Command] describe_image
- [Group] **workspace** - *Manages workspaces-related resources*
 - [Command] activate
 - [Command] activate_region
 - [Command] deactivate
- [Command] disable_autocomplete
- [Command] enable_autocomplete
- [Command] get_operation_status - *Returns request execution status by ID from long-running operations*
- [Command] mode

- [Command] policy

Detailed Command Reference

Group: m3admin

Usage:

```
m3admin [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--version	flag	X	False	Show the version and exit.

[↑ Back to Table of Contents](#)

Group: m3admin application

Description:

The Application group is used to manage AWS, AZURE, and GCP credentials

Usage:

```
m3admin application
```

[↑ Back to Table of Contents](#)

Group: m3admin application parent

Description:

Operates parent entities

Usage:

```
m3admin application parent
```

[↑ Back to Table of Contents](#)

Command: m3admin application parent add

Description:

Adds parent entity

Usage:

```
m3admin application parent add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	✓	-	* Id of the application
--type	choice	✓	-	* Parent type. Available choices: AWS_MANAGEMENT, AWS_ATHENA, AWS_COST_EXPLORER, AZURE_ENTERPRISE_BILLING, AZURE_USAGE_DETAILS, AZURE_RATE_CARDS, AZURE_CSP_BILLING, AZURE_CSP_PARTNER, AZURE_MANAGEMENT, AZURE_AD_SSO,

Option	Type	Req	Default	Description
				AZURE_BILLING_EXPORT, GCP_BILLING_SERVICE, GCP_SECURITY, GCP_MANAGEMENT, GCP_RESELLER
--description, -d	string	✓	-	* Parent description
--account_name, -an	string	✗	-	Should be specified for AZURE_ENTERPRISE_BILLING type.
--customer_id, -cid	string	✓	-	* Customer ID
--meta	json	✗	-	Parent meta JSON string
--json	flag	✗	False	Use this parameter to show command's response in a JSON view.
--table	flag	✗	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application parent delete

Description:

Deletes parent entity

Usage:

```
m3admin application parent delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	✓	-	* Customer ID
--parent_id, -pid	string	✓	-	* Id of the parent
--force, -F	flag	✗	False	Flag for force delete parent
--json	flag	✗	False	Use this parameter to show command's response in a JSON view.
--table	flag	✗	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application parent describe

Description:

Describes parent entity

Usage:

```
m3admin application parent describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	✓	-	* Customer ID

Option	Type	Req	Default	Description
--parent_id, -pid	string	X	-	Id of the parent
--type	choice	X	-	Parent type. Available choices: AWS_MANAGEMENT, AWS_ATHENA, AWS_COST_EXPLORER, AZURE_ENTERPRISE_BILLING, AZURE_USAGE_DETAILS, AZURE_RATE_CARDS, AZURE_CSP_BILLING, AZURE_CSP_PARTNER, AZURE_MANAGEMENT, AZURE_AD_SSO, AZURE_BILLING_EXPORT, GCP_BILLING_SERVICE, GCP_SECURITY, GCP_MANAGEMENT, GCP_RESELLER
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application parent update

Description:

Updates parent entity

Usage:

```
m3admin application parent update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--parent_id, -pid	string	✓	-	* Id of the parent
--application_id, -aid	string	X	-	Id of the application
--type	choice	X	-	Parent type. Available choices: AWS_MANAGEMENT, AWS_ATHENA, AWS_COST_EXPLORER, AZURE_ENTERPRISE_BILLING, AZURE_USAGE_DETAILS, AZURE_RATE_CARDS, AZURE_CSP_BILLING, AZURE_CSP_PARTNER, AZURE_MANAGEMENT, AZURE_AD_SSO, AZURE_BILLING_EXPORT, GCP_BILLING_SERVICE, GCP_SECURITY, GCP_MANAGEMENT, GCP_RESELLER
--description, -d	string	X	-	Parent description.
--customer_id, -cid	string	✓	-	* Customer ID
--meta	json	X	-	Parent meta JSON string
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application parent validate_credentials**Description:**

Checks that credentials are valid for existing application/parent

Usage:

```
m3admin application parent validate_credentials [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--parent_type, -ptype	choice	X	-	Parent type. Available choices: billing, management
--tenant, -tn	string	X	-	* The display name of the tenant to which linked parent
--cloud, -c	string	X	-	* The type of the tenant cloud to which linked parent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application add**Description:**

Adds application through a single interface. Please, use 'application get_type_params' to list which parameters are required for different 'type' parameter option. Instead of provide parameters you can use '--secret_key_path' to provide credential file and 'application describe_credentials_template' command helps you with template

Usage:

```
m3admin application add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	✓	-	* Customer ID
--type	choice	✓	-	* Application type. Available choices: AWS_ROLE, AWS_CREDENTIALS, AZURE_CREDENTIALS, AZURE_ENROLMENT, AZURE_CERTIFICATE, GCP_COMPUTE_ACCOUNT, GCP_SERVICE_ACCOUNT
--description, -d	string	✓	-	* Application description
--secret_key, -skey	string	X	-	Secret key value. Allowed if "--secret_key_path" is not specified. Allowed format is "Escaped Json". Example in bash: -skey '{"accessKeyId":"your_key_here"}'
--secret_key_path, -skpath	string	X	-	Path to file with credentials. Allowed if "--secret_key" is not specified. Allowed file extension - .json, .pfx. Maximum file size: 3 Mb
--password, -pwd	string	X	-	Password for *.pfx certificate. Applicable only for AZURE_CERTIFICATE application type
--account_number, -anum	string	X	-	AWS account ID. Should be specified for AWS types

Option	Type	Req	Default	Description
--role	string	X	-	AWS role name. Should be specified for AWS_ROLE type
--enrolment_number, -enumber	string	X	-	Enrolment number. Required for AZURE_ENROLMENT type
--tenant_id, -tid	string	X	-	Azure tenant id. Should be specified for AZURE types
--client_id, -client	string	X	-	Azure client id. Should be specified for AZURE types
--admin_project_id, -apid	string	X	-	Admin project id number. Should be specified for GCP types
--force, -F	flag	X	False	Force flag for skipping credentials validation
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application delete

Description:

Deletes application by ID

Usage:

```
m3admin application delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	✓	-	* Customer ID
--application_id, -aid	string	✓	-	* Id of the application
--force, -F	flag	X	False	Force flag for force delete application
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application describe

Description:

Describes application

Usage:

```
m3admin application describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--customer_id, -cid	string	✓	-	* Customer ID
--application_id, -aid	string	X	-	Id of the application
--type	choice	X	-	Application type. Available choices: AWS_ROLE, AWS_CREDENTIALS, AZURE_CREDENTIALS, AZURE_ENROLMENT, AZURE_CERTIFICATE, GCP_COMPUTE_ACCOUNT, GCP_SERVICE_ACCOUNT, CUSTODIAN
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application describe_credentials_template

Description:

Returns the template for the 'secret_key_path' parameter of 'application add' command by the application credentials type

Usage:

```
m3admin application describe_credentials_template [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--type	choice	✓	-	* Application credentials type. Available choices: ['AWS_CREDENTIALS', 'AZURE_CREDENTIALS', 'AZURE_RATE_CARDS', 'AZURE_ENROLMENT', 'GCP_COMPUTE_ACCOUNT', 'GCP_SERVICE_ACCOUNT', 'AZURE_CERTIFICATE']
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin application get_type_params

Description:

Returns the list of the 'application add' command required parameters by the application credentials type

Usage:

```
m3admin application get_type_params [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--type	choice	✓	-	* Application type. Available choices: AWS_ROLE, AWS_CREDENTIALS, AZURE_CREDENTIALS, AZURE_ENROLMENT, AZURE_CERTIFICATE,

Option	Type	Req	Default	Description
				GCP_COMPUTE_ACCOUNT, GCP_SERVICE_ACCOUNT
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin application get_types*

Description:

Returns all available types applicable to the 'type' parameter to the 'application add' command

Usage:

```
m3admin application get_types [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin application rotate_credentials*

Description:

Rotates credential keys for application entity

Usage:

```
m3admin application rotate_credentials [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	✓	-	* Customer ID
--application_id, -aid	string	✓	-	* Id of the application
--secret_key, -skey	string	X	-	Secret key value. Allowed formats are: Text or Escaped Json
--secret_key_path, -skpath	string	X	-	Path to the file with secret key value. Allowed file extension - <i>.json</i> , <i>.pfx</i> . Maximum file size: 3 Mb
--password, -pwd	string	X	-	Password for *.pfx certificate. Applicable only for AZURE_CERTIFICATE application type
--force, -F	flag	X	False	Force flag for skipping credentials validation
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin application update*

Description:

Updates application parameters

Usage:

```
m3admin application update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	✓	-	* Id of the application
--type	choice	✓	-	* Application type. Available choices: AWS_ROLE, AWS_CREDENTIALS, AZURE_CREDENTIALS, AZURE_ENROLMENT, AZURE_CERTIFICATE, GCP_COMPUTE_ACCOUNT, GCP_SERVICE_ACCOUNT
--description, -d	string	X	-	Application description
--customer_id, -cid	string	X	-	Customer ID
--account_number, -anum	string	X	-	AWS account ID. Should be specified for AWS types
--role	string	X	-	AWS role name. Should be specified for AWS_ROLE type
--enrolment_number, -enumber	string	X	-	Enrolment number. Required for AZURE_ENROLMENT type
--tenant_id, -tid	string	X	-	Azure tenant id. Should be specified for AZURE types
--client_id, -client	string	X	-	Azure client id
--admin_project_id, -apid	string	X	-	Admin project id number. Should be specified for GCP types
--force, -F	flag	X	False	Force flag for skipping credentials validation
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin approval

Description:

The approval group is used to set up the approval mechanism

Usage:

```
m3admin approval
```

[↑ Back to Table of Contents](#)

Command: *m3admin approval approvers_available_for_requester*

Description:

Manages availability of approvers for requesters

Usage:

```
m3admin approval approvers_available_for_requester [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--state	choice	X	-	* State that will be applied. Available choices: enabled, disabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin approval disable_mechanism*

Description:

Disables Approval Mechanism

Usage:

```
m3admin approval disable_mechanism [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin approval enable_mechanism*

Description:

Enables Approval Mechanism

Usage:

```
m3admin approval enable_mechanism [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin approval set_approval_link_protection**Description:**

Turns on/off protection on approval link. If protection is enabled, only an authorized user is able to approve the action. Otherwise, anybody who has an approval link is able to approve an action

Usage:

```
m3admin approval set_approval_link_protection [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--state	choice	X	-	* State that will be applied. Available choices: enabled, disabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin aws**Description:**

The AWS group is used to manage resources of the AWS cloud provider (activation/deactivation of tenants, managing instance metrics, managing tenant security groups)

Usage:

```
m3admin aws
```

[↑ Back to Table of Contents](#)

Command: m3admin aws activate**Description:**

Activates an AWS Tenant

Usage:

```
m3admin aws activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Name of Tenant to activate
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--display_name, -dn	string	X	-	* Tenant display name for UI
--activation_date, -adate	string	X	-	Specify the date of activation. Format “yyyy-mm-dd”
--tenant_customer, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as personal
--project_type	choice	X	NOT_BILLABLE	Project type. Default value: “NOT_BILLABLE”. Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--account_number, -acc	string	X	-	* Account number
--paying_account_number, -pacc	string	X	-	Paying account number
--unreachable, -U	flag	X	False	Marks the tenant unreachable
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws activate_region**Description:**

Activates region in a tenant

Usage:

```
m3admin aws activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--default_for_common_costs, -D	flag	X	False	Marks region as default for common costs
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws add_image**Description:**

Registers an AWS image in Maestro and specifies an alias for it

Usage:

```
m3admin aws add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Image name
--description, -d	string	X	-	* Image description
--group, -g	choice	X	-	* Image group: [PUBLIC, ENTERPRISE]. Available choices: PUBLIC, ENTERPRISE
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag "--all_regions" is specified)
--ssm_path, -path	string	X	-	Path to SSM parameter which contains AWS image ID
--filter, -fltr	string	X	-	Used to search for an image by provided filters. Filters should be provided in the following template: filter_name:filter_value, example: architecture:arm64. Multiple values allowed (e.g. --filter 'architecture:x86_64' --filter 'platform:windows').
--os_type, -os	string	X	-	Type of the operation system. Should be specified with filter parameter
--ami_id, -aid	string	X	-	AWS image ID
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin aws configure_athena*

Description:

Configures Athena for a specified account. Used by Maestro Billing Engine

Usage:

```
m3admin aws configure_athena [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	X	-	* Id of the application
--customer_id, -cid	string	X	-	* Customer ID
--region, -r	string	X	-	* Name of the region
--result_bucket, -rb	string	X	-	* Name of the result bucket name
--cost_and_usage_report_bucket, -cub	string	X	-	* Name of the cost and usage report bucket
--database, -db	string	X	-	* Name of the database
--collection, -coll	string	X	-	* Name of the collection
--billing_source, -bsource	choice	X	-	* Billing source. Available choices: ATHENA_CUR_LEGACY, ATHENA_CUR2
--bill_from, -bfrom	string	X	-	* The date of start billing from. Format "yyyy-mm"
--period, -per	choice	X	MONTH	Period for costs. Available choices: DAY, TWO_DAYS, THREE_DAYS, WEEK, MONTH
--hourly_database, -hdb	string	X	-	Name of the DB that contains hourly detailed info
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin aws deactivate*

Description:

Deactivates a specified tenant in Maestro

Usage:

```
m3admin aws deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenant which will be deactivated
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws delete_image

Description:

Deletes AWS Image

Usage:

```
m3admin aws delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions
--cloud, -c	string	X	AWS	Cloud provider. Default is AWS
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws delete_security_groups

Description:

Removes security groups for a specified tenant

Usage:

```
m3admin aws delete_security_groups [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	[]	Region name. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin aws deploy_security_groups*

Description:

Sets up security groups for a specified tenant

Usage:

```
m3admin aws deploy_security_groups [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	[]	Region name. Multiple values allowed (e.g. --region value1 --region value2)
--vpc_id	string	X	-	VPC ID. If not present, the default VPC is selected
--sg_config_file_path, -spath	string	X	-	Path to security group config json file
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin aws describe_security_groups*

Description:

Describes security groups for a specified tenant

Usage:

```
m3admin aws describe_security_groups [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	[]	Region name. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin aws manage_cost_allocation_tags***Description:**

Configures billing cost allocation tags

Usage:

```
m3admin aws manage_cost_allocation_tags [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: ADD, DESCRIBE, DISABLE, REMOVE
--name	string	X	-	AWS Athena tag column name
--key	string	X	-	Our tag mapping key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin aws manage_currency***Description:**

Turns on or off AWS currency rate

Usage:

```
m3admin aws manage_currency [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--aws_account_number, -awsan	string	X	-	* AWS account number
--aws_table_name, -awstn	string	X	-	* AWS table name
--action, -a	choice	X	-	* Action. Available choices: UPDATE, DESCRIBE
--year, -year	string	X	-	Year
--month, -m	string	X	-	Month
--currency	string	X	-	Currency
--rate	string	X	-	Rate
--disable, -D	flag	X	False	Disable
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws manage_security_group_in_region**Description:**

Manages AWS security group within a specific region for a tenant

Usage:

```
m3admin aws manage_security_group_in_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* AWS region name
--action, -a	choice	X	-	* Action. Available choices: ADD, DELETE
--vpc_id	string	X	-	VPC ID. Required for ADD action
--security_group, -sg	string	X	-	Security group name. Required for ADD action
--security_group_id, -sid	string	X	-	Security group ID. Required for DELETE action
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws repair_security_groups**Description:**

Repairs security groups for a specified tenant

Usage:

```
m3admin aws repair_security_groups [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	[]	Region name. Multiple values allowed (e.g. --region value1 --region value2)
--vpc_id	string	X	-	VPC ID. If not present, the default VPC is selected
--sg_config_file_path, -spath	string	X	-	Path to security group config json file
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws reset_vm_counters**Description:**

Checks counter values on whether they correspond to real instances quantity and synchronizes if the values are different

Usage:

```
m3admin aws reset_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws set_instance_profile**Description:**

Sets a profile name for an EC2 instance with pre-defined roles

Usage:

```
m3admin aws set_instance_profile [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Instance profile name name
--tenant, -tn	string	X	-	* Tenant display name
--force, -F	flag	X	False	-
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin aws validate_vm_counters**Description:**

Checks whether counter values correspond to real instances quantity

Usage:

```
m3admin aws validate_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin azure**Description:**

Manages Azure-related resources including billing, enrolment, credentials, etc

Usage:

```
m3admin azure
```

[↑ Back to Table of Contents](#)

Command: m3admin azure activate**Description:**

Activates an Azure tenant

Usage:

```
m3admin azure activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Name of Tenant to activate
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--display_name, -dn	string	X	-	* Tenant display name for UI
--activation_date, -adate	string	X	-	Specify the date of activation. Format “yyyy-mm-dd”
--tenant_customer, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as personal
--project_type	choice	X	NOT_BILLABLE	Project type. Default value: “NOT_BILLABLE”. Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--subscription_id, -sid	string	X	-	* Subscription id
--tenant_id, -tid	string	X	-	Tenant id number
--account_name, -an	string	X	-	Account name
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure activate_region**Description:**

Activates region in a tenant

Usage:

```
m3admin azure activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--default_for_common_costs, -D	flag	X	False	Marks region as default for common costs
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure add_image**Description:**

Registers an Azure image in Maestro and specifies an alias for it

Usage:

```
m3admin azure add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Image name. (Will not updated in case the flag “--rewrite” flag is specified. Needed only for searching an existed image)
--description, -d	string	X	-	* Image description
--group, -g	choice	X	-	* Image group: [PUBLIC, ENTERPRISE]. Available choices: PUBLIC, ENTERPRISE
--os_type, -os	string	X	-	* Type of the operation system
--publisher, -pub	string	X	-	* Image publisher. Example: Canonical, OpenLogic, MicrosoftWindowsServer
--offer	string	X	-	* Image offer. Example: UbuntuServer, CentOS, WindowsServer
--sku	string	X	-	* Image sku. (Example: 14.04.4-LTS, 6.6, 2008-R2-SP1)
--version, -v	string	X	-	* Image version. Example: 14.04.201604060
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag “--all_regions” is specified)
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin azure create_diagnostic_account_storage*****Description:**

Creates a Storage Account in Azure tenant for each activated region. Used for storing detailed metrics data

Usage:

```
m3admin azure create_diagnostic_account_storage [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--storage_type, -stype	choice	X	storage_v2	Storage type. The default is [storage_v2]. Available choices: storage, storage_v2, blob_storage
--sku	choice	X	standard_gr s	Stock Keeping Unit (SKU). The default is [standard_grs]. These represent the different shapes of the product. Available choices: premium_lrs, standard_grs, standard_lrs, standard_rags, standard_zrs
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin azure create_resource_group*****Description:**

Creates a resource group, resource group name by default is m3-custom-images

Usage:

```
m3admin azure create_resource_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name to use it's credentials for Azure account
--region, -r	string	X	-	Region name
--resource_group, -resgrp	string	X	m3-custom- images	Resource group name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure create_subscription_network_security_configuration**Description:**

Creates subscription network security configuration

Usage:

```
m3admin azure create_subscription_network_security_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--sg_config_file_path, -spath	string	X	-	Path to security group config json file. Config file format: [{"n":String,"d":String,"ii": [{"d":String, "ip":String}]}, {"n":String,"d":String,"ii": [{"d":String, "ip":String}]}]
--deploy_sg, -D	flag	X	False	If 'True' initiates the security groups deployment
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure create_subscription_resource_group**Description:**

Creates a resource group of a specified subscription

Usage:

```
m3admin azure create_subscription_resource_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure deactivate**Description:**

Deactivates a specified tenant in Maestro

Usage:

```
m3admin azure deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenant which will be deactivated
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure delete_diagnostic_account_storage**Description:**

Deletes a Storage Account in Azure tenant for each activated region

Usage:

```
m3admin azure delete_diagnostic_account_storage [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure delete_image**Description:**

Deletes AZURE Image

Usage:

```
m3admin azure delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions
--cloud, -c	string	X	AZURE	Cloud provider. Default is AZURE
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure delete_resource_group*

Description:

Deletes a resource group for a specified subscription

Usage:

```
m3admin azure delete_resource_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--resource_group, -resgrp	string	X	m3-custom-images	Resource group name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure delete_subscription_network_security_configuration*

Description:

Deletes a network security configuration for a specified subscription

Usage:

```
m3admin azure delete_subscription_network_security_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure delete_subscription_resource_group*

Description:

Deletes a resource group for a specified subscription

Usage:

```
m3admin azure delete_subscription_resource_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure deploy_security_groups

Description:

Creates or updates a security group for a specified region

Usage:

```
m3admin azure deploy_security_groups [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--sg_config_file_path, -spath	string	X	-	Path to security group config json file
--region, -r	string	X	[]	A region name, or several region names to configure security groups in them. Default is an empty list - means that security groups will be configured for all available regions. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin azure describe_diagnostic_account_storage

Description:

Describes all storage accounts in Azure by the tenant display name

Usage:

```
m3admin azure describe_diagnostic_account_storage [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure list_image_versions*

Description:

Lists Azure image versions for certain publishers, offers, and SKU numbers

Usage:

```
m3admin azure list_image_versions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--publisher, -pub	string	X	-	* Publisher name
--offer, -o	string	X	-	* Offer name
--sku	string	X	-	* SKU name
--email, -e	string	X	-	The email to which the letter will be sent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure list_offers*

Description:

Lists Azure offers for certain publishers

Usage:

```
m3admin azure list_offers [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--publisher, -pub	string	X	-	* Publisher name
--email, -e	string	X	-	The email to which the letter will be sent

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure list_publishers*

Description:

Lists Azure publishers

Usage:

```
m3admin azure list_publishers [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--email, -e	string	X	-	The email to which the letter will be sent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure list_skus*

Description:

Lists Azure SKU numbers for certain publishers and offers

Usage:

```
m3admin azure list_skus [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--publisher, -pub	string	X	-	* Publisher name
--offer, -o	string	X	-	* Offer name
--email, -e	string	X	-	The email to which the letter will be sent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin azure manage_currency*****Description:**

Turns on or off Azure currency rate

Usage:

```
m3admin azure manage_currency [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--enrolment_number, -enumber	string	X	-	Enrolment number
--action, -a	choice	X	-	* Action. Available choices: UPDATE, DESCRIBE
--year, -year	string	X	-	Year
--month, -m	string	X	-	Month
--currency	string	X	-	Currency
--rate	string	X	-	Rate
--disable, -D	flag	X	False	Disable
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin azure reset_vm_counters*****Description:**

Checks counter values on whether they correspond to real instances quantity and synchronizes if the values are different

Usage:

```
m3admin azure reset_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin azure rotate_diagnostic_storage_credentials*****Description:**

Rotate credentials for Diagnostic Storage Account in Azure tenant

Usage:

```
m3admin azure rotate_diagnostic_storage_credentials [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure rotate_storage_credentials*

Description:

Rotates credentials for Storage Account in Azure tenant

Usage:

```
m3admin azure rotate_storage_credentials [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--storage_account, -sa	string	X	-	* Storage account name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure update_tenant_id*

Description:

Updates Azure subscription credentials in Maestro tenant

Usage:

```
m3admin azure update_tenant_id [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--tenant_id, -tid	string	X	-	* Azure tenant id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin azure validate_vm_counters*

Description:

Checks whether counter values correspond to real instances quantity

Usage:

```
m3admin azure validate_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin billing**Description:**

[Installable Module] Manages billing quotas, configuration, processing status, and record aggregation for specified periods

Usage:

```
m3admin billing
```

[↑ Back to Table of Contents](#)

Group: m3admin billing setting**Description:**

Manages Billing environment settings

Usage:

```
m3admin billing setting
```

[↑ Back to Table of Contents](#)

Command: m3admin billing setting add**Description:**

Sets Billing related settings

Usage:

```
m3admin billing setting add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing setting delete**Description:**

Deletes Billing related settings

Usage:

```
m3admin billing setting delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing setting describe

Description:

Describes Billing related settings

Usage:

```
m3admin billing setting describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	Setting key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing setting update

Description:

Updates Billing related settings

Usage:

```
m3admin billing setting update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing add_cost_center

Description:

Adds/updates a cost center related to the selected region

Usage:

```
m3admin billing add_cost_center [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Region names. Multiple values allowed (e.g. --region value1 --region value2)
--cost_center, -costc	string	X	-	* Cost center name
--rewrite, -R	flag	X	False	Do not fail if cost center with specified name is already exists
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing add_tenant_to_customer**Description:**

Sets a list of tenants for the specified customer to obtain summary reports. Used during billing month closure

Usage:

```
m3admin billing add_tenant_to_customer [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing adjustment**Description:**

Sets an adjustment for a specified tenant

Usage:

```
m3admin billing adjustment [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: ADD, REMOVE, GET

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--account_id, -aid	string	X	-	AWS account id
--cloud, -c	choice	X	-	Cloud provider for setting credit to default for common costs zone: AWS, AZURE, GOOGLE. Available choices: AWS, AZURE, GOOGLE
--region, -r	string	X	-	Region name
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--value	float	X	-	Value of adjustment
--duration	integer	X	1	* Duration in months. Apply adjustment during several months starting from the specified month
--credit_type, -ctype	choice	X	-	* Type of the adjustment [PREPAYMENT, SURCHARGE, HARDWARE_UP_1000, EPAM_AZURE_DISCOUNT, SLA_DISCOUNT]. Available choices: PREPAYMENT, SURCHARGE, HARDWARE_UP_1000, EPAM_AZURE_DISCOUNT, SLA_DISCOUNT]
--description, -d	string	X	-	* Description
--currency_native, -C	flag	X	False	Specifies that the current currency rate will be used to retrieve cost in USD. Applicable for Azure cloud
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing adjustment_configure*

Description:

Updates adjustment for the specified tenant

Usage:

```
m3admin billing adjustment_configure [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--credit_type, -ctype	choice	X	-	* Type of the adjustment [PREPAYMENT, SURCHARGE, PROJECT_DISCOUNT]. Available choices: PREPAYMENT, SURCHARGE, PROJECT_DISCOUNT
--region, -r	string	X	-	* Region name
--tenant, -tn	string	X	-	* Specify Tenant partial or full display name
--description, -d	string	X	-	* Description
--from_date	string	X	-	* From date. Format "yyyy-mm-dd"

Option	Type	Req	Default	Description
--to_date	string	X	-	To date. Format “yyyy-mm-dd”
--value_type, -vtype	choice	X	-	* Value type [DISCOUNT_IN_PERCENTS, SURCHARGE_IN_PERCENTS]. Available choices: DISCOUNT_IN_PERCENTS, SURCHARGE_IN_PERCENTS
--value	float	X	-	* Value of adjustment
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing aggregate_yearly_records

Description:

Calculates the total amount of expenses by projects/regions. The result can be found in a table “resourcebillingrecords” of MongoDB

Usage:

```
m3admin billing aggregate_yearly_records [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer (1979 to 9999)	X	-	* Year
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing all_resources_costs_report

Description:

Sends or updates data for forecast or monthly expenses report on all resources

Usage:

```
m3admin billing all_resources_costs_report [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: SEND, UPDATE, UPDATE_METRICS
--date, -date	string	X	-	* Specify the date. Format “yyyy-mm-dd”

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant display name
--monthly, -M	flag	X	False	Send report for specified month
--email, -e	string	X	-	Email address to send report to
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing archive_big_query*

Description:

Archives data in Google BigQuery for the specified account

Usage:

```
m3admin billing archive_big_query [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--admin_project_id, -apid	string	X	-	Admin project id number
--table_id, -tid	string	X	-	Big query table id
--year, -year	integer (1979 to 2050)	X	-	Year. Must be specified with month
--month, -m	integer (1 to 12)	X	-	Month. Must be specified with year
--archivation	choice	X	-	Archivation state. Must be specified if “year” and “month” parameters not provided. Available choices: enabled, disabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing archive_collection*

Description:

Archives outdated documents of the specified collection

Usage:

```
m3admin billing archive_collection [OPTIONS]
```


Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--name	choice	X	-	* Collection name to archive. Available choices: BillingTimeLines, DailyResourceBillingRecords, DailyResourceTagBillingRecords
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing budget**Description:**

Manages budgets for the specified tenant

Usage:

```
m3admin billing budget [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: CHANGE_UPDATE_CRON, CREATE_BUDGET_FOR_QUOTA, DESCRIBE_BUDGETS, LIST_BUDGETS, PROCESS_QUOTAS, REMOVE_BUDGETS, REMOVE_BUDGET_BY_NAME, REMOVE_BUDGET_FOR_QUOTA
--cloud, -c	choice	X	-	* Cloud. Available choices: AWS, AZURE, GOOGLE
--tenant, -tn	string	X	-	* Tenant display name
--key	string	X	-	Key (quota id / budget name / cron)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing close_month**Description:**

Closes the billing month and sends summary reports to responsible people for all accounts

Usage:

```
m3admin billing close_month [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer (1979 to 9999)	X	-	* Year
--month, -m	integer (1 to 12)	X	-	* Month
--skip_aws_accounts, -S	flag	X	False	Do not check the AWS account duplicates
--skip_aws_common_costs_tenants, -A	flag	X	False	Do not check the AWS common cost tenant duplicates
--skip_tenant_types	flag	X	False	Do not check the tenant types consistency
--skip_cost_centers, -C	flag	X	False	Do not check cost centers
--send_account_reports, -R	flag	X	False	Generate and send account reports
--aggregate_monitoring_only, -M	flag	X	False	Aggregate monitoring only
--ignore_download_errors, -I	flag	X	False	Ignore custom_output.py during AWS and Azure reports downloading
--ignore_billing_file_errors, -B	flag	X	False	Ignore custom_output.py during checking billing files on emptiness, files with custom_output.py will not be included by default
--include_empty_files, -E	flag	X	False	Include empty files to “Billing month is closed” report
--force, -F	flag	X	False	Skip sanity validation for dates
--dry_run, -D	flag	X	False	Close month in “dry run” mode: month status will not be changed and all reports will be sent to “dry_run_email” (dry_run_email have to be specified in case using dry_run mode)
--dry_run_email	string	X	-	Email address to send close billing month reports. Should be specified only with “dry_run” flag
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing close_month_for_account*

Description:

Closes the billing month for the specified account

Usage:

```
m3admin billing close_month_for_account [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer (1979 to	X	-	* Year

Option	Type	Req	Default	Description
	9999)			
--month, -m	integer (1 to 12)	X	-	* Month
--account_id, -aid	string	X	-	* Account id from MongoDB for report generation
--email, -e	string	X	-	* Email address to send report to
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing configure

Description:

Configures billing

Usage:

```
m3admin billing configure [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--describe, -D	flag	X	False	Describe BillingConfig
--aws_athena_update_schedule, -aus	string	X	-	Aws Athena update schedule (cron)
--aws_cost_explorer_update_schedule, -ceus	string	X	-	Aws Cost Explorer update schedule (cron)
--aws_cost_column, -awsc	choice	X	-	Choose blended or unblended Athena column name. Available choices: BlendedCost, UnBlendedCost
--aws_update_period	choice	X	-	Aws update period. Available choices: DAY, TWO_DAYS, THREE_DAYS, WEEK, MONTH
--azure_update_schedule	string	X	-	Azure update schedule (cron)
--customize_report_structure, -crs	string	X	-	Customize report structure (via json)
--supported_service, -sservice	string	X	-	Azure update schedule (cron)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing configure_gcp_big_query

Description:

Configures GCP Big Query for a specified account

Usage:

```
m3admin billing configure_gcp_big_query [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	✓	-	* Id of the application
--customer_id, -cid	string	X	-	* Customer ID
--admin_project_id, -apid	string	X	-	* Admin Project id
--billing_account_id, -baid	string	X	-	* Billing account id (format 000000-AAAAAA-222222)
--dataset_id, -did	string	X	-	* Dataset id
--table_id, -tid	string	X	-	* Table id
--resource_table_id, -rtid	string	X	-	* Resource table id
--bill_from, -bfrom	string	X	-	* The date of start billing from. Format “yyyy-mm”
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing delete_kpi

Description:

Deletes billing KPI

Usage:

```
m3admin billing delete_kpi [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--year, -y	integer (1979 to 9999)	X	-	* Year
--month, -m	integer (1 to 12)	X	-	* Month
--day, -d	integer (1 to 31)	X	-	Day
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin billing describe_azure_billing_config*****Description:**

Describes Azure billing access information

Usage:

```
m3admin billing describe_azure_billing_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--enrolment_id, -eid	string	X	-	Enrolment ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin billing describe_business_units*****Description:**

Describes the configuration of business unit reports

Usage:

```
m3admin billing describe_business_units [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin billing describe_month*****Description:**

Describes information about the status for the specified month

Usage:

```
m3admin billing describe_month [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -y	integer (1979 to 9999)	X	-	* Year

Option	Type	Req	Default	Description
--month, -m	integer (1 to 12)	X	-	* Month
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing describe_tenant_business_unit*

Description:

Describes information about the tenant's business unit

Usage:

```
m3admin billing describe_tenant_business_unit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--include_history, -H	flag	X	False	Flag. If set, includes historical data in the description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing export_aws*

Description:

Configures billing data export for a specified AWS tenant

Usage:

```
m3admin billing export_aws [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--disable, -D	flag	X	False	Flag for deactivation
--bucket, -b	string	X	-	* Bucket name for exported billing files
--encrypt_bucket, -E	flag	X	False	Bucket name for exported billing files
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing export_azure*

Description:

Configures export of billing data for a specified Azure account

Usage:

```
m3admin billing export_azure [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--deactivate, -D	flag	X	False	Indicates if deactivation is needed
--storage_account, -sa	string	X	-	Storage account name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing export_google*

Description:

Configures billing export for the specified Google tenant

Usage:

```
m3admin billing export_google [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--deactivate, -D	flag	X	False	Indicates if deactivation is needed
--dataset, -d	string	X	-	Dataset name
--dataset_table, -dt	string	X	-	Table name in dataset in BigQuery
--granularity, -gran	choice	X	PROJECT	Billing export granularity level. By default set as PROJECT. Available choices: PROJECT, RESOURCE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing export_status*

Description:

Receives export of billing data for a specified AWS/AZURE/GOOGLE tenant

Usage:

```
m3admin billing export_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	* Cloud name. Available choices: AWS, AZURE, GOOGLE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing get_currency

Description:

Describes currency for cloud in specified month

Usage:

```
m3admin billing get_currency [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -y	integer (1979 to 9999)	X	-	* Year
--month, -m	integer (1 to 12)	X	-	* Month
--cloud, -c	choice	X	-	* Cloud. Available choices: AWS, AZURE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing get_sources

Description:

Displays the sources for a specific Cloud for all customers, or for a specific customer if an ID is provided

Usage:

```
m3admin billing get_sources [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Cloud. Available choices: AWS, AZURE, GOOGLE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing get_top_accounts_report*

Description:

Displays the names of top accounts which were charged the most money

Usage:

```
m3admin billing get_top_accounts_report [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--number	integer	X	10	Number of the accounts to display. By default: 10
--email, -e	string	X	-	The email to which the letter will be sent. If not specified - report will be shown in CLI response
--show_detailed, -sd	flag	X	False	Show detailed report
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing health_check*

Description:

Initiates the Billing Health Check

Usage:

```
m3admin billing health_check [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -y	integer (2010 to 2050)	X	-	* Year
--month, -m	integer (1 to 12)	X	-	* Month

Option	Type	Req	Default	Description
--group, -g	string	X	-	Name of the group mapping. (multiple). Multiple values allowed (e.g. --group value1 --group value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing manage_eo_account

Description:

Command to perform actions with EO Account

Usage:

```
m3admin billing manage_eo_account [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--account_id, -aid	string	X	-	* EO Account id
--action, -a	choice	X	-	* Action to perform. Available choices: add_tenants, remove_tenants
--tenant, -tn	string	X	-	Tenant display name. Multiple values allowed (e.g. --tenant value1 --tenant value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing price_quota

Description:

Manages price quota

Usage:

```
m3admin billing price_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: ADD, DESCRIBE
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	Region name
--type	choice	X	-	* Quota type. Available choices: SINGLE, ALL, ALL_AWS, ALL_AZURE, ALL_GOOGLE, ALL_YANDEX, ALL_PRIVATE, EACH, EACH_AWS, EACH_AZURE,

Option	Type	Req	Default	Description
				EACH_GOOGLE, EACH_YANDEX, EACH_PRIVATE, DAILY_ALL_AWS, DAILY_ALL_AZURE, DAILY_ALL_GOOGLE, DAILY_ALL_OPENSTACK
--activate, -A	flag	X	False	Activates quota
--deactivate, -D	flag	X	False	Deactivates quota
--stop, -S	flag	X	False	Quota exceed action STOP [true, false]
--allow_after_approve, -L	flag	X	False	Quota exceed action ALLOW_AFTER_APPROVE [true, false]
--deny_run_vm, -R	flag	X	False	Quota exceed action DENY_RUN_VM [true, false]
--quota	string	X	-	Quota amount - maximum allowed monthly cost for the project in the selected region
--notification, -n	string	X	-	Quota notifications, [90%, 100%] by default. For several notifications repeat the parameter. Multiple values allowed (e.g. --notification value1 --notification value2)
--tag	string	X	-	Tag
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing pricing_policy*

Description:

Manages pricing policy for the specified region

Usage:

```
m3admin billing pricing_policy [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: GET, UPDATE, CHECK, CHANGE_TIME_UNIT_TO_PER_SECOND
--region, -r	string	X	-	* Region name for pricing policy
--file	string	X	-	Path to the file to be processed
--email, -e	string	X	-	The email to which the letter will be sent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing publisher_check*

Description:

Checks publisher events consistency

Usage:

```
m3admin billing publisher_check [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--day, -day	integer	X	-	Day
--hour	integer	X	-	Hour
--group, -g	string	X	-	* Group type
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing radar_aggregate

Description:

Recalculates billing for a specified month of a year in a specified region

Usage:

```
m3admin billing radar_aggregate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer (1979 to 9999)	X	-	* Year
--month, -m	integer (1 to 12)	X	-	* Month
--region, -r	string	X	-	Region name or cloud provider: AWS, AZURE, GOOGLE, OPEN_STACK, HPOO, CSA, EXOSCALE, HARDWARE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing reset_billing

Description:

Resets billing for a specified AWS, Azure, Google, or OpenStack account

Usage:

```
m3admin billing reset_billing [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Cloud name. Available choices: AWS, AZURE, AZURE_PARTNER, GOOGLE, PRIVATE, YANDEX, MONGO_ATLAS, ALL
--recalculate_from, -rfrom	string	X	-	* Specify the month which should be reset. Format “yyyy-mm-dd”
--account_number, -anum	string	X	-	Number of the AWS paying account
--enrolment_number, -enumber	string	X	-	Number of the Azure enrolment
--azure_reset_metadata, -A	flag	X	False	For Azure account specify should CSV reports be re-downloaded or not
--google_admin_project_id, -gpid	string	X	-	ID of the Google project
--reset_sequentially, -R	flag	X	False	This flag enables billing reset month by month till specified date
--remove_credits, -C	flag	X	False	This flag allows to remove Google native credits
--reset_day, -D	flag	X	False	This flag allows to reset the specified day (only for PRIVATE cloud per tenant)
--tenant, -tn	string	X	-	Specify tenant display name. Multiple values allowed (e.g. --tenant value1 --tenant value2)
--region, -r	string	X	-	Specify region display name (only for PRIVATE cloud per tenant). Multiple values allowed (e.g. --region value1 --region value2)
--resource_id, -rid	string	X	-	Specify resource id (only for PRIVATE cloud per tenant). Multiple values allowed (e.g. --resource_id value1 --resource_id value2)
--customer_id, -cid	string	X	-	Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing send_cloud_radar_report**Description:**

Initiates sending the Cloud Radar report for a specified month of a year by a specified region

Usage:

```
m3admin billing send_cloud_radar_report [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--day, -day	integer	X	-	* Day
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing send_low_instance_utilization_report*

Description:

Initiates sending the Low Instance Utilization report

Usage:

```
m3admin billing send_low_instance_utilization_report [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing send_monthly_analytic_optimization_report*

Description:

Initiates sending the Monthly Analytic report for a specified month of a year

Usage:

```
m3admin billing send_monthly_analytic_optimization_report [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing send_sponsors_reports*

Description:

Initiates sending sponsors reports for a specified month of a year

Usage:

```
m3admin billing send_sponsors_reports [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing send_units_reports*

Description:

Initiates sending business units reports for a specified month of a year

Usage:

```
m3admin billing send_units_reports [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--year, -year	integer	X	-	* Year
--month, -m	integer	X	-	* Month
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing set_azure_billing_config*

Description:

Updates Azure billing access configuration

Usage:

```
m3admin billing set_azure_billing_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	X	-	* Id of the application
--customer_id, -cid	string	X	-	* Customer ID
--enrolment_number, -enumber	string	X	-	Number of the Azure enrolment
--bill_from, -bfrom	string	X	-	* The date of start billing from. Format “yyyy-mm”
--export_creation_allowed, -A	flag	X	False	Use when several environments (DEV, QA, PROD) uses the same storage. Only one environment should create export config
--export_name, -name	string	X	billing_report	Name of the export configuration, prefix for billing reports. Default: billing_report
--scope, -s	string	X	-	* Scope for billing report
--resource_group, -resgrp	string	X	-	* Resource group where Azure storage account created
--storage_account, -sa	string	X	-	* Azure storage account for billing reports
--storage_account_subscription_id, -id	string	X	-	* Subscription id where storage account created
--container	string	X	-	* Container from the storage account
--root_folder_path, -path	string	X	-	* Root folder from the storage account
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing set_kpi**Description:**

Sets billing KPI

Usage:

```
m3admin billing set_kpi [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--records	string	X	-	NOTE: m3admin API mode use only. The parameter that specifies records to set. Please specify the list of records in the usual JSON format
--file_records	string	X	-	NOTE: m3modular or m3admin standalone mode use only. The parameter that specifies records to set. Please

Option	Type	Req	Default	Description
				specify the path to the JSON file with records
--year, -y	integer (1979 to 9999)	X	-	* Year
--month, -m	integer (1 to 12)	X	-	* Month
--day, -d	integer (1 to 31)	X	-	Day
--kpi_type, -t	choice	X	-	KPI type. Available choices: DIAL, MOBILE, TIERED, SWIFTSTACK, REPORT_PORTAL
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing_thread_server_config

Description:

Manages configuration of server billing thread

Usage:

```
m3admin billing_thread_server_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--node, -n	string	X	-	* Node name
--action, -a	choice	X	-	* Action. Available choices: CHANGE, REMOVE, DESCRIBE
--cloud_type, -ctype	choice	X	-	Cloud type. Available choices: AWS, AZURE, AZURE_PARTNER, GOOGLE, PRIVATE, YANDEX, MONGO_ATLAS
--sub_cloud_type, -stype	choice	X	-	Sub cloud type. Available choices: AWS, AWS_COST_EXPLORER, AZURE_ENROLMENT, AZURE_BILLING_EXPORT, AZURE_RATE_CARDS, AZURE_CSP, GOOGLE, PRIVATE, PRIVATE_BY_TAG, AZURE_USAGE_DETAILS, YANDEX, MONGO_ATLAS
--customer_id, -cid	string	X	-	* Customer ID
--thread_count, -tcount	integer	X	-	Thread count
--thread_strategy	choice	X	BY_REMAINDER	Thread strategy. Available choices: BY_REMAINDER, BY_ORGANIZATION
--consequentially	choice	X	-	Enable parallel billing flow consequentially (for all clouds). Available choices: ENABLE, DISABLE
--bill_to, -bto	string	X	-	Bill to (for private billing) yyyy-mm-dd
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing timeline*

Description:

Manages timelines for specified resources

Usage:

```
m3admin billing timeline [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action. Available choices: CHECK, CLOSE, FIX, OPEN
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--resource	string	X	-	* Resource operational id. Multiple values allowed (e.g. --resource value1 --resource value2)
--resource_type, -rtype	choice	X	-	* Resource type. Available choices: INSTANCE, HARDWARE, ENTERPRISE, VOLUME, MACHINE_IMAGE, MOBILE, HARDWARE_DEVICE
--date, -date	string	X	-	Fix from. Format 'yyyy-mm-dd'. Applicable for action FIX
--write, -W	flag	X	False	Enables writing to the Data Base. If the property is not specified, the command will only find open timelines by specified parameters, but won't close them (useful for timelines investigation purposes). Applicable for action CLOSE
--ignore_state, -l	flag	X	False	Flag to ignore resource state. Applicable for action CLOSE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin billing update_reports_config*

Description:

Updates configuration for business units reports

Usage:

```
m3admin billing update_reports_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--unit	string	X	-	* Business unit name
--recipient	string	X	-	* Recipients for report, multiple parameter. Required for report's config updating. Multiple values allowed (e.g. –recipient value1 –recipient value2)
--custom, -C	flag	X	False	Custom report conf which includes all not specified in conf units
--threshold	integer	X	1000	Minimum required monthly chargeback(threshold). Default: 1000
--add, -A	flag	X	False	Option for adding specified unit
--remove, -R	flag	X	False	Option for removing specified unit. Required only -u(–unit) parameter
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing upload_aws_china_billing

Description:

Uploads AWS China billing information

Usage:

```
m3admin billing upload_aws_china_billing [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* AWS China billing action. Action: [CHECK, UPLOAD]. Available choices: CHECK, UPLOAD
--year, -year	integer	X	-	* Year of the billing
--month, -m	integer	X	-	* Moth of the billing
--account, -acc	string	X	-	* AWS account name
--region, -r	string	X	-	* Region name
--bucket, -b	string	X	-	* Bucket name
--file	string	X	-	* Name of the previously uploaded via scp CSV report
--rate	float	X	-	* Exchange rate. All costs will be multiplied by this rate to get value in USD
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin billing upload_azure_billing**Description:**

Uploads Azure billing information to AWS S3 service

Usage:

```
m3admin billing upload_azure_billing [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	* Action: [UPLOAD, CHANGE_API_VERSION]. Available choices: UPLOAD, CHANGE_API_VERSION
--api_version	choice	X	-	* Api version: [V1(... to 01.07.2015), V2(from 01.07.2015), V3(from 01.11.2017)]. Available choices: V1, V2, V3
--account, -acc	string	X	-	* Aws account name
--bucket, -b	string	X	-	* Bucket with uploaded report
--zone	string	X	-	* Zone where bucket was created
--file	string	X	-	* Name of the CSV report
--enrolment_number, -enumber	string	X	-	* AZURE enrolment number
--year, -year	string	X	-	* Year of the billing
--month, -m	string	X	-	* Moth of the billing
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin chef**Description:**

[Installable Module] Manages Chef-related resources and configurations

Usage:

```
m3admin chef
```

[↑ Back to Table of Contents](#)

Group: m3admin chef setting**Description:**

Manages Chef environment settings

Usage:

```
m3admin chef setting
```

[↑ Back to Table of Contents](#)

Command: m3admin chef setting add**Description:**

Sets Chef related settings

Usage:

```
m3admin chef setting add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef setting delete**Description:**

Deletes Chef related settings

Usage:

```
m3admin chef setting delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef setting describe

Description:

Describes Chef related settings

Usage:

```
m3admin chef setting describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	Setting key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef setting update

Description:

Updates Chef related settings

Usage:

```
m3admin chef setting update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef add_configuration

Description:

Registers Chef server configuration

Usage:

```
m3admin chef add_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server_id, -sid	string	X	-	* Chef Server FQDN
--certificate	string	X	-	SSL cert. Required if you use self-signed certificate
--organization	string	X	-	* Chef Server organization name.
--validation_pem	string	X	-	* Path to chef organization validation key
--api_username	string	X	-	* Admin username on the Chef Server
--auth	string	X	-	* Path to the private key of admin user on the Chef Server
--threshold	integer	X	-	Alert threshold. Default: 5
--version, -v	string	X	-	* Chef Server version.
--service_id, -seid	string	X	-	Service id of EPC chef configuration.
--default, -D	flag	X	False	Mode. If True - the Chef Server is default.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef assign_configuration**Description:**

Assigns Chef server configuration

Usage:

```
m3admin chef assign_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server_id, -sid	string	X	-	* Chef Server FQDN.
--region, -r	string	X	-	* Name or list of names of the regions which is/are served by chef server. Multiple values allowed (e.g. --region value1 --region value2).
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef delete_client**Description:**

Removes Chef client

Usage:

```
m3admin chef delete_client [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--region, -r	string	X	-	* Region name
--instance_id, -iid	string	X	-	Instance id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef delete_configuration**Description:**

Removes Chef server configuration

Usage:

```
m3admin chef delete_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server_id, -sid	string	X	-	* Chef Server FQDN
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef describe_configuration**Description:**

Describes Chef server configuration

Usage:

```
m3admin chef describe_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--server_id, -sid	string	X	-	Chef Server FQDN. If missing - all configurations will be described
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef get_client

Description:

Gets Chef client

Usage:

```
m3admin chef get_client [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--region, -r	string	X	-	* Region name
--instance_id, -iid	string	X	-	Instance id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin chef set_configuration

Description:

Sets Chef configuration in tenant setting CHEF_CONFIGURATION

Usage:

```
m3admin chef set_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--disable_type, -dtype	choice	X	NONE	Name of the type to disable in the region. Available choices: ALL, WINDOWS, LINUX, NONE

Option	Type	Req	Default	Description
--chef_server_id, -cid	string	X	-	Id of the Chef server
--mode	choice	X	DEFAULT	Name of the type to disable in the region. Available choices: DEFAULT, EPC, USER
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin chef unassign_configuration*

Description:

Unassigns Chef server configuration

Usage:

```
m3admin chef unassign_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server_id, -sid	string	X	-	* Chef Server FQDN.
--region, -r	string	X	-	* Name or list of names of the regions which is/are served by chef server. Multiple values allowed (e.g. --region value1 --region value2).
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin chef update_configuration*

Description:

Updates Chef server configuration

Usage:

```
m3admin chef update_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server_id, -sid	string	X	-	* Chef Server FQDN
--certificate	string	X	-	SSL cert. Required if you use self-signed certificate
--organization	string	X	-	Chef Server organization name.
--validation_pem	string	X	-	Path to chef organization validation key
--api_username	string	X	-	Admin username on the Chef Server

Option	Type	Req	Default	Description
--auth	string	X	-	Path to the private key of admin user on the Chef Server
--threshold	integer	X	-	Alert threshold. Default: 5
--version, -v	string	X	-	Chef Server version.
--service_id, -seid	string	X	-	Service id of EPC chef configuration.
--default, -D	flag	X	False	Mode. If True - the Chef Server is default.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin chef update_role*

Description:

Updates Chef role

Usage:

```
m3admin chef update_role [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--region, -r	string	X	-	* Region name
--instance_id, -iid	string	X	-	* Instance id
--role	string	X	-	* Role name
--override, -O	flag	X	False	Override if exists
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin configure

Description:

Manages m3admin. Resource configuration in services such as AWS lambda, SNS, queue configuration in Rabbit MQ, audit configuration

Usage:

```
m3admin configure
```

[↑ Back to Table of Contents](#)

Command: m3admin configure activate_cf_audit

Description:

Creates SNS topics in specified regions and sets up SNS trigger for a lambda function

Usage:

```
m3admin configure activate_cf_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be created
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Name of lambda that would be subscribed to sns topic
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure activate_ec2_audit

Description:

Activates ec2 audit by creating SNS topics and cw rules in specified regions and adding permissions to Lambda

Usage:

```
m3admin configure activate_ec2_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be created
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Name of lambda that would be subscribed to sns topic
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure activate_guarddduty*

Description:

Activates GuardDuty by creating SNS topics and CW rules in specified regions and adding permissions to Lambda

Usage:

```
m3admin configure activate_guarddduty [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be created
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Name of lambda that would be subscribed to sns topic
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure activate_iam_audit*

Description:

Activates IAM audit by creating SNS topics and CW rules in specified regions and adding permissions to Lambda

Usage:

```
m3admin configure activate_iam_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be created
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Name of lambda that would be subscribed to sns topic
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure activate_tenant_cf_audit*

Description:

Activates tenant CF audit by adding tenant permission to SNS topic policy

Usage:

```
m3admin configure activate_tenant_cf_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would receive cf audit
--region, -r	string	X	-	* Regions name where topic exist. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure activate_tenant_ec2_audit*

Description:

Activates tenant CF audit by creating CW rules in specified regions, adding permissions to event buss in a home account

Usage:

```
m3admin configure activate_tenant_ec2_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to activate ec2 audit. Optional. Should be specified if config property use_remote_tenant_config set to true
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--rule	string	X	-	* Cloudwatch rule name
--target_role_arn, -tarn	string	X	-	Arn of existing role for Cloudwatch rule target. If not specified the access role will be used
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure activate_tenant_guardduty**Description:**

Activates tenant GuardDuty by creating CW rules in specified regions

Usage:

```
m3admin configure activate_tenant_guardduty [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to activate guardduty. Optional. Should be specified if config property use_remote_tenant_config set to true
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--rule	string	X	-	* Cloudwatch rule name
--target_role_arn, -tarn	string	X	-	Arn of existing role for Cloudwatch rule target. If not specified the access role will be used
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure activate_tenant_iam_audit**Description:**

Activates tenant IAM audit by creating CW rules in specified regions and adding permissions to event buss in home account

Usage:

```
m3admin configure activate_tenant_iam_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to activate iam audit. Optional. Should be specified if config property use_remote_tenant_config set to true
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--rule	string	X	-	* Cloudwatch rule name
--target_role_arn, -tarn	string	X	-	Arn of existing role for Cloudwatch rule target. If not specified the access role will be used
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure add_tenant_permission**Description:**

Adds permission for tenant account to write events to home event bus

Usage:

```
m3admin configure add_tenant_permission [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Regions name where permissions will be set. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure cognito_set_permissions**Description:**

Creates or updates specified policy and attaches it to Cognito role

Usage:

```
m3admin configure cognito_set_permissions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--role	string	X	cognito_auth	Name of the cognito role
--policy	string	X	CustomCognitoAPIG...	Name of the policy that would be attached to role
--policy_content_path, -ppath	string	X	-	Path to file with policy content
--api_gateway, -apigw	string	X	maestro3	Name of api gateway name
--override, -O	flag	X	False	Path to file with policy content
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure create_audit_and_rpc_queues**Description:**

Declares m3admin RPC request/response and audit queues in a specified Rabbit instance

Usage:


```
m3admin configure create_audit_and_rpc_queues [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--connection_url, -curl	string	X	-	* URL that contains credentials, host, port and virtual host of rabbit instance. Format of the URI:amqp://username:password@host:port/<_host>[?query-string]
--audit_queue, -aq	string	X	-	* Name of the m3admin audit queue
--request_queue, -reqq	string	X	-	* Name of the m3admin request queue
--response_queue, -respq	string	X	-	* Name of the m3admin response queue
--timeout	integer	X	60	Timeout limit in seconds for response from server. Default value is 60
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure create_audit_queue*

Description:

Declares m3admin audit queue in a specified Rabbit instance

Usage:

```
m3admin configure create_audit_queue [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--queue, -q	string	X	-	* Name of the m3admin audit queue
--connection_url, -curl	string	X	-	* URL that contains credentials, host, port and virtual host of rabbit instance
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure create_rpc_queues*

Description:

Declares m3admin RPC request and response queues in a specified Rabbit instance

Usage:

```
m3admin configure create_rpc_queues [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--request_queue, -reqq	string	X	-	* Name of the m3admin request queue
--response_queue, -respq	string	X	-	* Name of the m3admin response queue
--connection_url, -curl	string	X	-	* URL that contains credentials, host, port and virtual host of rabbit instance
--timeout	integer	X	60	Timeout limit in seconds for response from server. Default value is 60
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure deactivate_cf_audit

Description:

Removes SNS topics in specified regions and removes all their subscriptions. Removes permission from lambda

Usage:

```
m3admin configure deactivate_cf_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be removed
--region, -r	string	X	-	* Regions name where topic would be removed. Multiple values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Lambda name that was subscribed to topic
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure deactivate_ec2_audit

Description:

Deactivates EC2 audit by removing SNS topics, CW rules in specified regions and permission from Lambda

Usage:

```
m3admin configure deactivate_ec2_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be created
--region, -r	string	X	-	* Regions name where topic would be created. Multiple

Option	Type	Req	Default	Description
				values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Name of lambda that would be subscribed to sns topic
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure deactivate_guarddduty

Description:

Deactivates GuardDuty by removing SNS topics, CW rules in specified regions and permission from Lambda

Usage:

```
m3admin configure deactivate_guarddduty [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that would be created
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--lambda_name, -lname	string	X	-	* Name of lambda that would be subscribed to sns topic
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin configure deactivate_tenant_cf_audit

Description:

Adds tenant permission to the SNS topic policy

Usage:

```
m3admin configure deactivate_tenant_cf_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic, -top	string	X	-	* Name of the sns topic that was receive cf audit
--region, -r	string	X	-	* Regions name where topic exist. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin configure deactivate_tenant_ec2_audit`

Description:

Deactivates tenant EC2 audit by removing CW rules in specified regions and permission from event bus in home account

Usage:

```
m3admin configure deactivate_tenant_ec2_audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to deactivate ec2 audit. Optional. Should be specified if config property use_remote_tenant_config set to true
--region, -r	string	X	-	* Regions name where topic would be created. Multiple values allowed (e.g. --region value1 --region value2)
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin configure deactivate_tenant_guardduty`

Description:

Deactivates tenant GuardDuty by removing cw rules in specified regions

Usage:

```
m3admin configure deactivate_tenant_guardduty [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to deactivate guardduty. Optional. Should be specified if config property use_remote_tenant_config set to true
--region, -r	string	X	-	* Regions name where topic will be removed. Multiple values allowed (e.g. --region value1 --region value2)
--rule	string	X	-	* Cloudwatch rule name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin configure delete_tenant_permission*

Description:

Removes tenant permission by removing permission for tenant account to write events to home event bus

Usage:

```
m3admin configure delete_tenant_permission [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Regions name where permissions will be remove. Multiple values allowed (e.g. --region value1 --region value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education**Description:**

[Installable Module] Manages educational resources: labs, sandboxes, triggers, quarantine, cloud configurations, and system access

Usage:

```
m3admin education
```

[↑ Back to Table of Contents](#)

Group: m3admin education application**Description:**

Manages application entities within the education system

Usage:

```
m3admin education application
```

[↑ Back to Table of Contents](#)

Command: m3admin education application add**Description:**

Adds application entity

Usage:

```
m3admin education application add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--app_type, -at	choice	X	-	* Application type. Available choices: AWS_ROLE, AWS_INSTANCE_PROFILE, AWS_CREDENTIALS
--description, -d	string	X	-	* Application description
--secret_key, -skey	string	X	-	Application credentials. Required for AWS_CREDENTIALS application type
--role_name, -rn	string	X	-	Application role name. Example: DeveloperAccessRole
--account_number, -an	string	X	-	Application account number. Example: 960173513640
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education azure**Description:**

Manages Azure subscriptions within the education system

Usage:

```
m3admin education azure
```

[↑ Back to Table of Contents](#)

Command: m3admin education azure add_worker**Description:**

Registers a pre-provisioned Azure Entra ID application into the system's worker pool to be used for automated task verification and infrastructure deployments

Usage:

```
m3admin education azure add_worker [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--client_id, -client	string	X	-	* Public, globally unique for the Azure App Registration
--application_id, -aid	string	X	-	* Internal Entra ID for the application's global blueprint
--service_principal_id, -spid	string	X	-	* Internal Entra ID for the Enterprise Application
--parent_id, -pid	string	X	-	* Parent ID. Required type: AZURE_SANDBOX_MANAGEMENT
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education azure check_providers**Description:**

Checks and syncs the registration status of all required Azure resource providers

Usage:

```
m3admin education azure check_providers [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--subscription_id, -sid	string	X	-	* Azure subscription ID to check providers for
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education azure onboard_subscription**Description:**

Onboards a new Azure subscription

Usage:

```
m3admin education azure onboard_subscription [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--parent_id, -pid	string	X	-	* Parent ID. Required type: AZURE_SANDBOX_MANAGEMENT
--subscription_id, -sid	string	X	-	* Azure subscription ID to onboard
--usage_mode, -umode	choice	X	-	* Defines how the subscription will be utilized. Allowed values are SHARED (allocated to multiple users) or DEDICATED (allocated to a single user/purpose). Available choices: SHARED, DEDICATED
--max_users, -mu	integer (1 to 500)	X	-	Maximum number of users allowed for this subscription. This parameter is only applicable when usage mode is set to SHARED
--description, -d	string	X	-	Subscription description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education azure register_providers

Description:

Initiates registration of all required Azure resource providers for the specified subscription

Usage:

```
m3admin education azure register_providers [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--subscription_id, -sid	string	X	-	* Azure subscription ID to register providers for
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education azure remove_worker

Description:

Deregisters an Azure Entra ID application from the system's worker pool

Usage:


```
m3admin education azure remove_worker [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--client_id, -client	string	X	-	* Public, globally unique for the Azure App Registration
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education cicd**Description:**

Manages CI/CD pipeline configurations for task deployment resources

Usage:

```
m3admin education cicd
```

[↑ Back to Table of Contents](#)

Group: m3admin education cicd taskconfig**Description:**

Manages task deployment resource config entries

Usage:

```
m3admin education cicd taskconfig
```

[↑ Back to Table of Contents](#)

Command: m3admin education cicd taskconfig delete**Description:**

Deletes a task deployment resource config entry from the database

Usage:

```
m3admin education cicd taskconfig delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic_id	string	X	-	* Unique ID of the topic
--sandbox_type, -st	choice	X	-	* Sandbox type the artifact targets. Available choices: one_student, many_students
--resource_type, -rt	choice	X	-	* Deployment resource type. Available choices: ORGANIZATIONAL_UNIT, TERRAFORM_TEMPLATE
--task_id	string	X	-	Unique ID of the task. Omit for a topic-level default config
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin education cicd taskconfig upsert*

Description:

Creates or updates a task deployment resource config entry in the database

Usage:

```
m3admin education cicd taskconfig upsert [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--topic_id	string	X	-	* Unique ID of the topic
--sandbox_type, -st	choice	X	-	* Sandbox type the artifact targets. Available choices: one_student, many_students
--resource_type, -rt	choice	X	-	* Deployment resource type. Available choices: ORGANIZATIONAL_UNIT, TERRAFORM_TEMPLATE
--s3_key, -s3k	string	X	-	* Full S3 object key of the uploaded artifact
--version_id	string	X	-	* S3 VersionId returned by the PutObject response
--task_id	string	X	-	Unique ID of the task. Omit for a topic-level default config
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin education configure*

Description:

Configures education system settings: accounts, logging, notifications, and IAM roles

Usage:

```
m3admin education configure
```

[↑ Back to Table of Contents](#)

Command: *m3admin education configure account_info*

Description:

Configures the settings for creating new AWS accounts, including thresholds, naming conventions, and email patterns

Usage:

```
m3admin education configure account_info [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--free_account_threshold, -fat	string	X	-	* Threshold percentage for the pool of unused AWS accounts. If the number of free accounts drops below this threshold, the system will automatically create new AWS accounts to refill the pool
--current_account_count, -cac	string	X	-	* Current count of already created accounts
--account_name_pattern, -anp	string	X	-	* Pattern used for naming new accounts. Use "<>" in the place where the account number should be inserted
--account_email_pattern, -aep	string	X	-	* Pattern for the email addresses used for creating new AWS accounts. Use "<>" where the account number should be substituted
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure ci_account_info

Description:

Configures the CI account by specifying the AWS regions and SSM parameters for storing CI and lab admin credentials

Usage:

```
m3admin education configure ci_account_info [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--ci_credentials_ssm_region, -cicssmr	string	X	-	* AWS region for the SSM storing CI account credentials
--ci_credentials_ssm_parameter_name, -cicssmpn	string	X	-	* SSM parameter name for storing CI account credentials
--lab_credentials_ssm_region, -labcssmr	string	X	-	* AWS region for the SSM that stores lab admin IAM user credentials in the CI account
--lab_credentials_ssm_parameter_prefix, -labcssmpp	string	X	-	* Prefix for the SSM parameter name that stores lab admin IAM user credentials
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure cleanup_info

Description:

Configure the cleanup job by specifying the job queue and job definition

Usage:

```
m3admin education configure cleanup_info [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_queue, -jq	string	X	-	* Job queue where the cleanup job is submitted
--job_definition, -jd	string	X	-	* Job definition used by cleanup job. This value can be one of definition-name or definition-name:revision. If the revision is not specified, then the latest active revision is used
--region, -r	string	X	-	AWS region. Default: us-east-1
--custom_script_name, -csn	string	X	-	Name of the custom cleanup script
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure lab_account_logging_info**Description:**

Configures logging settings for lab accounts using a specified event bus

Usage:

```
m3admin education configure lab_account_logging_info [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--logging_event_bus_arn, -lebar	string	X	-	* ARN for the event bus used in lab account logging
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure lab_admin_iam_info**Description:**

Configures IAM settings for lab admin users, specifying their usernames and associated AWS-managed policies

Usage:

```
m3admin education configure lab_admin_iam_info [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--username, -u	string	X	-	* Username of the lab admin IAM user
--policy_arn, -parn	string	X	-	* ARN of the AWS-managed policy for the lab admin user
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure sep_s3_root

Description:

Configures the S3 root URL for the education system's configuration storage

Usage:

```
m3admin education configure sep_s3_root [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--root_url, -url	string	X	-	* URL pointing to the S3
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure sqs_notifications

Description:

Configures SQS notifications for specified admin actions, detailing where and how the notifications should be sent upon action completion

Usage:

```
m3admin education configure sqs_notifications [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	string	X	-	* Admin action for which you want to receive a result notification
--parent_id, -pid	string	X	-	* Parent ID. Only parent entities of type TASK_MANAGER_INTEGRATION are allowed
--sqs_url, -sqsu	string	X	-	* AWS SQS URL where notification of action completion will be sent
--payload_mapper, -pm	string	X	-	Path to a JSON file that outlines the mapping for notification fields to server response fields. Example: { "serverField1": "notificationField1", "serverField2": "notificationField2", ... }

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education configure stack_set_info

Description:

Configures info about sandbox system infrastructure CloudFormation StackSet

Usage:

```
m3admin education configure stack_set_info [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--stack_set_name, -ssn	string	X	-	* Sandbox system infrastructure StackSet name
--region, -r	string	X	-	* AWS region in which the StackSet is defined
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education lab

Description:

Manages lab tenant lifecycle: activation, deactivation, and description

Usage:

```
m3admin education lab
```

[↑ Back to Table of Contents](#)

Command: m3admin education lab activate

Description:

Activates a lab tenant for a specified course, lab, and user, setting up the necessary AWS resources in the specified regions

Usage:

```
m3admin education lab activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--course_id, -cid	string	X	-	* Unique ID of the course associated with the lab tenant
--lab_id, -lid	string	X	-	* Unique ID of the lab tenant to be activated

Option	Type	Req	Default	Description
--user_id, -uid	string	X	-	* User ID of the individual for whom the lab tenant is being activated
--region, -r	string	X	-	* Specify AWS regions where the lab tenant will be activated. Multiple values allowed (e.g., -r us-east-1 -r eu-west-1)
--ttl_minutes, -ttl_min	string	X	-	* Time-to-live in minutes for the lab tenant activation
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education lab deactivate

Description:

Deactivates a lab tenant

Usage:

```
m3admin education lab deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--course_id, -cid	string	X	-	* Unique ID of the course associated with the lab tenant
--lab_id, -lid	string	X	-	* Unique ID of the lab tenant to be reanimated
--user_id, -uid	string	X	-	* User ID of the individual for whom the lab tenant is being reanimated
--region, -r	string	X	-	* Specify AWS regions where the lab tenant will be reanimated. Multiple values allowed (e.g., -r us-east-1 -r eu-west-1)
--account_id, -aid	string	X	-	* Unique ID of the AWS account associated with the lab tenant to be deactivated
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education lab describe

Description:

Describes lab tenants

Usage:

```
m3admin education lab describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--lab_id, -lid	string	X	-	Unique ID of the lab tenant to be described
--account_id, -aid	string	X	-	Unique ID of the AWS account associated with the lab tenant to be described
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education lab prolong

Description:

Prolongs the lab current expiration by the provided additional time

Usage:

```
m3admin education lab prolong [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--account_id, -aid	string	✓	-	Unique ID of the AWS account associated with the lab tenant to be described
--extra_ttl_minutes, -e_ttl_min	integer	✓	-	The additional time, in minutes, that you wish to add to lab's current expiration
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education parent

Description:

Manages parent entities within the education system

Usage:

```
m3admin education parent
```

[↑ Back to Table of Contents](#)

Command: m3admin education parent add

Description:

Adds parent entity

Usage:

```
m3admin education parent add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--application_id, -aid	string	X	-	* Application ID
--parent_type, -pt	choice	X	-	* Parent type. Available choices: SANDBOX_MANAGEMENT, SANDBOX_CONFIGURATION, SANDBOX_CLEANUP, TASK_MANAGER_INTEGRATION, SANDBOX_USAGE_LOGGING, AZURE_SANDBOX_MANAGEMENT
--description, -d	string	X	-	* Parent description
--meta	json	X	-	Parent meta JSON string
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education parent update

Description:

Updates parent entity

Usage:

```
m3admin education parent update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--parent_id, -cid	string	X	-	* Parent ID
--application_id, -aid	string	X	-	* New Application ID to associate with the specified parent entity
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education quarantine

Description:

Manages and monitors quarantine measures, including account details and logs

Usage:

```
m3admin education quarantine
```

[↑ Back to Table of Contents](#)

Command: m3admin education quarantine describe**Description:**

Describes quarantine accounts

Usage:

```
m3admin education quarantine describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education quarantine describe_logs**Description:**

Describes quarantine logs

Usage:

```
m3admin education quarantine describe_logs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--days_interval, -di	integer (7 to 30)	X	-	Specify the number of days to retrieve quarantine logs (between 7 and 30 days)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education sandbox**Description:**

Manages sandboxes: allocate, release, or create

Usage:

```
m3admin education sandbox
```

[↑ Back to Table of Contents](#)

Group: m3admin education sandbox deployment**Description:**

Manages sandbox deployments: update and describe

Usage:

```
m3admin education sandbox deployment
```

[↑ Back to Table of Contents](#)

Command: *m3admin education sandbox deployment delete*

Description:

Deletes the sandbox deployment for a running course

Usage:

```
m3admin education sandbox deployment delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--deployment_resource_id, -drid	string	X	-	* Unique ID of the deployment resource
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin education sandbox deployment describe*

Description:

Describes the sandbox deployment for a running course

Usage:

```
m3admin education sandbox deployment describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--deployment_resource_id, -drid	string	X	-	Unique ID of the deployment resource. If specified, other filter params can not be used
--deployment_resource_type, -drt	choice	X	-	Type of the deployment resource. Available choices: ORGANIZATIONAL_UNIT, TERRAFORM_TEMPLATE
--task_id	string	X	-	Unique ID of the task
--topic_id	string	X	-	Unique ID of the topic
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin education sandbox deployment separate*

Description:

Separates the sandbox deployment for a running course

Usage:

```
m3admin education sandbox deployment separate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--deployment_resource_id, -drid	string	X	-	* Unique ID of the deployment resource
--task_id	string	X	-	Unique ID of the task
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox deployment update

Description:

Updates the sandbox deployment for a running course

Usage:

```
m3admin education sandbox deployment update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--deployment_resource_id, -drid	string	X	-	* Unique ID of the deployment resource
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox allocate

Description:

Allocate sandbox resources for a running course

Usage:

```
m3admin education sandbox allocate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--run_id, -rid	string	X	-	* Unique ID of the run course
--amount, -amt	integer	X	-	* Amount

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Specify AWS regions where the run course will be activated. Multiple values allowed (e.g., -r us-east-1 -r eu-west-1)
--sandbox_type, -st	choice	X	-	* Sandbox type. Available choices: one_student, many_students
--topic_id	string	X	-	* Unique ID of the topic
--life_time	integer (1 to 1440)	X	-	* Sandbox lifetime in minutes. Valid values: 1 to 1440
--task_id	string	X	-	Unique ID of the task
--user_id, -uid	string	X	-	User ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox create

Description:

Creates sandbox resources for running a course

Usage:

```
m3admin education sandbox create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--amount, -amt	integer	X	1	Amount of sandboxes to be created. Default value: 1
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox health

Description:

Describes the health status of sandbox configurations. If the sandbox ID parameter is provided, returns the health state of the specified sandbox. Otherwise, the command outputs a list of all unhealthy sandboxes

Usage:

```
m3admin education sandbox health [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--sandbox_id, -sid	string	X	-	The sandbox ID for which to describe the configuration state
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox register

Description:

Registers a sandbox for the specified account

Usage:

```
m3admin education sandbox register [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--account_id, -aid	string	X	-	* Unique ID of the AWS account
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox release

Description:

Release sandbox resources for running a course

Usage:

```
m3admin education sandbox release [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--run_id, -rid	string	X	-	* Unique ID of the run course
--sandbox_usage_id, -suid	string	X	-	List of sandbox usage IDs corresponding to the sandboxes that need to be released. If this parameter is left empty and the run is closed, the remaining infrastructure will automatically be cleared
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education sandbox unregister**Description:**

Unregisters the sandbox for the specified account

Usage:

```
m3admin education sandbox unregister [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--account_id, -aid	string	X	-	* Unique ID of the AWS account
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education support**Description:**

Manages system accounts and privileged access within the education platform

Usage:

```
m3admin education support
```

[↑ Back to Table of Contents](#)

Command: m3admin education support add_sys_account**Description:**

Registers a new system account info in the platform by associating a cloud-native account identifier with a human-readable alias and a cloud provider

Usage:

```
m3admin education support add_sys_account [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* The cloud provider this account belongs to. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--alias	string	X	-	* A unique, human-readable name that identifies the role or purpose of this account within the platform (e.g., logging, workspaces). Must be unique per cloud provider
--native_id, -nid	string	X	-	* The cloud-native account/resource identifier
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education support delete_sys_account

Description:

Removes an existing system account info from the platform by its cloud provider and alias. The combination of cloud and alias must match a previously registered system account

Usage:

```
m3admin education support delete_sys_account [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* The cloud provider the account belongs to. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--alias	string	X	-	* The human-readable name of the system account to remove
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education support list_sys_account

Description:

Lists registered system account infos, with optional filtering by cloud provider and/or alias

Usage:

```
m3admin education support list_sys_account [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	Filter results to accounts registered under a specific cloud provider. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--alias	string	X	-	Filter results to the account with this specific alias
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education support privileged_access

Description:

Grants temporary privileged access either to a sandbox environment (identified by its ID) or to a system account (identified by its alias)

Usage:

```
m3admin education support privileged_access [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* The cloud provider the target belongs to. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--sandbox_id, -sid	string	X	-	The unique identifier of the sandbox to gain privileged access to. Cannot be used together with --alias
--alias	string	X	-	The alias of the system account to gain privileged access to (e.g., logging, shared-services). Cannot be used together with --sandbox-id
--duration_minutes	integer	X	-	The duration of the privileged access session in minutes. Defaults to 60. Maximum allowed value: 720 (12 hours)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin education trigger

Description:

Manages triggers: add, delete, and describe SQS triggers for automated event responses

Usage:

```
m3admin education trigger
```

[↑ Back to Table of Contents](#)

Command: m3admin education trigger add_sqs

Description:

Adds an SQS trigger

Usage:

```
m3admin education trigger add_sqs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--action, -a	string	X	-	* Admin action designated for execution
--parent_id, -pid	string	X	-	* Parent ID. Only parent entities of type TASK_MANAGER_INTEGRATION are allowed
--sqs_url, -sqsu	string	X	-	* AWS SQS URL from which the messages are received
--payload_mapper, -pm	string	X	-	Path to a JSON file that outlines the mapping for SQS message fields to server command fields. Example: { "serverField1": { "alternativeName": "messageField1" }, "serverField2": { "alternativeName": "messageField2", "defaultValue": 5 }, ... }
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education trigger delete

Description:

Deletes the specified trigger

Usage:

```
m3admin education trigger delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--trigger_id, -tid	string	X	-	* ID of the trigger to be deleted
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education trigger describe

Description:

Describes the specified triggers

Usage:

```
m3admin education trigger describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--trigger_id, -tid	string	X	-	ID of the trigger to be described
--action, -a	string	X	-	Admin action designated for execution
--trigger_type, -tt	choice	X	-	Type of the trigger. Available choices: SQS

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education trigger disable

Description:

Disables the specified trigger

Usage:

```
m3admin education trigger disable [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--trigger_id, -tid	string	X	-	* ID of the trigger to be disabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education trigger enable

Description:

Enables the specified trigger

Usage:

```
m3admin education trigger enable [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--trigger_id, -tid	string	X	-	* ID of the trigger to be enabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin education audit

Description:

Retrieve audit information for a specified resource within a defined time frame.

At least one filter must be provided: --resource_id, --event_status, or --event_name.

Documentation: https://kb.epam.com/display/EPMCEOOS/%5BSS_EE%5D+Audit

Usage:

```
m3admin education audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--from_date, -from	string	X	-	Start of time range. Must be in the past and within last 30 days. Defaults to 24 hours ago. Format: yyyy-mm, yyyy-mm-dd, or yyyy-mm-dd hh
--to_date, -to	string	X	-	End of time range. Requires --from_date. Max 7-day range. Defaults to current time. Format: yyyy-mm, yyyy-mm-dd, or yyyy-mm-dd hh
--event_name, -evname	string	X	-	Filter by event name (e.g., CREATE_SANDBOX, CLEANUP_SANDBOX). See docs for allowed values
--event_status, -evst	string	X	-	Filter by outcome. Use FAILED for finding system errors. See docs for allowed values
--resource_id, -resid	string	X	-	Filter by primary resource ID
--include_related, -inrel	flag	X	False	Expands search to related resources. Requires --resource_id
--limit, -lim	integer (1 to 200)	X	50	Max events to return (1-200). Default: 50
--offset, -off	integer (≥ 0)	X	0	Skip N events for pagination. Default: 0
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin education move_accounts*

Description:

Moves specified AWS accounts to a new destination

Usage:

```
m3admin education move_accounts [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--account_id, -aid	string	X	-	* Unique IDs of the AWS accounts to be moved. Multiple values allowed (e.g., -aid ... -aid ...)
--destination, -dest	choice	X	-	* Target location to which the specified accounts will be moved. Choices: ['POOL', 'QUARANTINE']. Available choices: POOL, QUARANTINE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin education onboard_organization*

Description:

Sets up an AWS organization for system interaction, configuring units and roles for lab management

Usage:

```
m3admin education onboard_organization [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--account_pool_unit_id, -apuid	string	X	-	* Unique ID of the organizational unit holding unused AWS accounts
--lab_unit_id, -luid	string	X	-	* Unique ID for the top-level organizational unit for labs
--organization_role, -or	string	X	-	* Role name for managing lab accounts
--resource_prefix, -rp	string	X	-	* Prefix for naming resources
--quarantine_unit_id, -quid	string	X	-	* Unique ID for the top-level organization for quarantined accounts
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin education run_infrastructure_check*

Description:

Initiates the specified infrastructure check

Usage:

```
m3admin education run_infrastructure_check [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--checker_type, -cht	choice	X	-	* The type of infrastructure check to perform. Allowed values: STACK_SET_DRIFT, ORGANIZATIONAL_UNITS_USAGE. Available choices: STACK_SET_DRIFT, ORGANIZATIONAL_UNITS_USAGE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin enterprise**Description:**

Manages enterprise-related resources

Usage:

```
m3admin enterprise
```

[↑ Back to Table of Contents](#)

Command: m3admin enterprise activate**Description:**

Activates ENTERPRISE tenant

Usage:

```
m3admin enterprise activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE". Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin enterprise activate_region**Description:**

Activates ENTERPRISE region in tenant

Usage:

```
m3admin enterprise activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin enterprise deactivate*

Description:

Deactivates ENTERPRISE tenant

Usage:

```
m3admin enterprise deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenant which will be deactivated
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin enterprise delete_image*

Description:

Removes image in Maestro

Usage:

```
m3admin enterprise delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Image name
--tenant, -tn	string	X	-	Tenant display name
--region, -r	string	X	-	* Virtualization region. Specify "ALL" to delete image in all regions
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Group: m3admin environment**Description:**

Manages environment

Usage:

```
m3admin environment
```

[↑ Back to Table of Contents](#)

Group: m3admin environment server**Description:**

The server subgroup contains commands related to Maestro server configuration and its services management

Usage:

```
m3admin environment server
```

[↑ Back to Table of Contents](#)

Command: m3admin environment server add_jmx_access**Description:**

Configures access to the JMX page

Usage:

```
m3admin environment server add_jmx_access [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--user, -u	string	X	-	* User name
--password, -pwd	string	X	-	* Password. Please note that password should not contain white spaces
--role	choice	X	READ_ONLY	* The role parameter for access the JMX user. Allowed value: ['FULL_ACCESS', 'READ_ONLY']. Available choices: FULL_ACCESS, READ_ONLY
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server add_profiles**Description:**

Adds profiles to specified Maestro server

Usage:

```
m3admin environment server add_profiles [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Server name
--profile, -pf	string	X	-	* Name or list of profile names which be added to server. Multiple values allowed (e.g. --profile value1 --profile value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server configure_access**Description:**

Configures access to Maestro server

Usage:

```
m3admin environment server configure_access [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--api_endpoint, -api	string	X	-	Api endpoint
--port	string	X	-	Application port
--protocol	choice	X	-	Transfer protocol. Available choices: http, https
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server configure_metrics**Description:**

Configures metrics service in Maestro server

Usage:

```
m3admin environment server configure_metrics [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--metric_expiration_timeout, -exp	string	X	-	Expiration time for metrics
--enable_metric, -E	flag	X	False	Flag to enable metrics service in m3server
--disable_metric, -D	flag	X	False	Flag to disable metrics service in m3server

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server delete_jmx_access

Description:

Removes access to jmx page

Usage:

```
m3admin environment server delete_jmx_access [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--user, -u	string	X	-	* User name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server delete_profiles

Description:

Removes profiles from specified Maestro server

Usage:

```
m3admin environment server delete_profiles [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Server name
--profile, -pf	string	X	-	* Name or list of profile names which be removed from the server. Multiple values allowed (e.g. --profile value1 – profile value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server deregister

Description:

Deregisters the server from the Maestro Environment

Usage:

```
m3admin environment server deregister [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server deregister_m3admin_configuration

Description:

Removes m3admin service access data from m3server configuration

Usage:

```
m3admin environment server deregister_m3admin_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server deregister_mail_configuration

Description:

Removes specified SMTP configuration from server config

Usage:

```
m3admin environment server deregister_mail_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--user, -u	string	X	-	* SMTP user
--server, -srv	string	X	-	* Name of sever were configuration will be saved
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin environment server deregister_mongo`

Description:

Deregisters MongoDB instance from Maestro Environment

Usage:

```
m3admin environment server deregister_mongo [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
<code>--server, -srv</code>	string	X	-	* M3-server name
<code>--db_type, -dtype</code>	choice	X	-	* Type of MongoDB. Available choices: operational, billing
<code>--json</code>	flag	X	False	Use this parameter to show command's response in a JSON view.
<code>--table</code>	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin environment server deregister_rabbit_configuration`

Description:

Deregisters RabbitMQ service configuraion

Usage:

```
m3admin environment server deregister_rabbit_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
<code>--server, -srv</code>	string	X	-	* M3-server name
<code>--json</code>	flag	X	False	Use this parameter to show command's response in a JSON view.
<code>--table</code>	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin environment server deregister_sdk_configuration`

Description:

Deregisters M3SDK service

Usage:

```
m3admin environment server deregister_sdk_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server describe**Description:**

Describes a server in the Maestro environment

Usage:

```
m3admin environment server describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server describe_jmx_access**Description:**

Describes access to jmx page

Usage:

```
m3admin environment server describe_jmx_access [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--user, -u	string	X	-	* User name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server describe_m3admin_configuration**Description:**

Describes m3admin service access data from m3server configuration

Usage:

```
m3admin environment server describe_m3admin_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server describe_mail_configuration

Description:

Describes server mail configuration

Usage:

```
m3admin environment server describe_mail_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Name of sever were configuration will be saved
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server describe_mongo

Description:

Describes MongoDB instance in Maestro Environment

Usage:

```
m3admin environment server describe_mongo [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin environment server describe_profiles****Description:**

Describes profiles attached to the server

Usage:

```
m3admin environment server describe_profiles [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin environment server describe_rabbit_configuration****Description:**

Describes RabbitMQ service configuration

Usage:

```
m3admin environment server describe_rabbit_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin environment server describe_sdk_configuration****Description:**

Describes M3SDK service

Usage:

```
m3admin environment server describe_sdk_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server disable

Description:

Disables server mode in Maestro environment

Usage:

```
m3admin environment server disable [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server enable

Description:

Enables server mode in Maestro environment

Usage:

```
m3admin environment server enable [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Server name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server evict_cache

Description:

Invalidates cache on Maestro Server

Usage:

```
m3admin environment server evict_cache [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cache	string	X	-	* Name of the cache that will be deleted. In case of (cache_name = all) - all cache will be deleted
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register**Description:**

Registers the server in the Maestro Environment

Usage:

```
m3admin environment server register [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--ip_address, -ip	string	X	-	M3-server instance address
--active, -A	flag	X	False	State of server. Default: False
--dns	string	X	-	M3-server dns name
--api_endpoint, -api	string	X	-	Api endpoint
--port	integer	X	-	Application port
--protocol	choice	X	-	Transfer protocol. Available choices: http, https
--override, -O	flag	X	False	Override existed server item. Default: False
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register_m3admin_configuration**Description:**

Registers m3admin service access data to m3server configuration

Usage:

```
m3admin environment server register_m3admin_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--protocol	string	X	http	Connection protocol. If not specified - 'http' is applied
--host	string	X	-	* M3admin service address. DNS is preferred
--port	integer	X	-	* M3admin service port
--username, -u	string	X	-	* Username of the user to access service
--password, -pwd	string	X	-	* Password of the user to access service
--endpoint, -endp	string	X	-	A specific URL path where the server can access the API
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register_mail_configuration

Description:

Registers required configuration for working with SMTP. For OAuth2 authentication provide --auth_mechanisms XOAUTH2, --oauth2_url and --protocol smtp

Usage:

```
m3admin environment server register_mail_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--host	string	X	-	* SMTP server host
--ssl_protocol	string	X	-	* SSL protocol
--port	integer	X	-	* SMTP server port
--user, -u	string	X	-	* SMTP user
--password, -pwd	string	X	-	* SMTP user password
--server, -srv	string	X	-	* Name of sever were configuration will be saved
--tls, -T	flag	X	False	Is tsl enabled
--auth, -A	flag	X	False	Is auth required
--connection_timeout, -ctimeout	integer	X	60000	SMTP server connection timeout. Default: 60000
--timeout	integer	X	60000	SMTP server timeout. Default: 60000
--write_timeout, -wtimeout	integer	X	60000	SMTP server write timeout. Default: 60000
--ssl_trust	string	X	(*,)	List of Hosts. Multiple values allowed (e.g. --ssl_trust value1 --ssl_trust value2)
--ssl_enable, -E	flag	X	False	If set to true SSL is used. False by default
--protocol	string	X	-	Mail protocol (e.g. smtp)

Option	Type	Req	Default	Description
--auth_mechanisms	string	X	-	Authentication mechanism (e.g. XOAUTH2)
--oauth2_url	string	X	-	OAuth2 endpoint URL (e.g. https://outlook.office365.com/)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register_mongo

Description:

Registers MongoDB instance in Maestro Environment

Usage:

```
m3admin environment server register_mongo [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--db_type, -dtype	choice	X	-	* Type of MongoDB. Available choices: operational, billing
--mongo_uri	string	X	-	* Mongo URI. Should be specified in the following form: mongodb://user:password@ip:port/databaseName?waitQueueMultiple=&maxPoolSize=
--ssl_enable, -E	flag	X	False	If set to true SSL is used. False by default
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register_rabbit_configuration

Description:

Registers RabbitMQ service configuration

Usage:

```
m3admin environment server register_rabbit_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--rabbit_uri, -uri	string	X	-	* Rabbit connection URI

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register_sdk_configuration

Description:

Registers M3SDK service

Usage:

```
m3admin environment server register_sdk_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--protocol	string	X	-	* Protocol type
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server register_terraform_versions

Description:

Registers installed Terraform versions on m3server

Usage:

```
m3admin environment server register_terraform_versions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server start_consuming

Description:

Starts consuming audit events on m3server

Usage:

```
m3admin environment server start_consuming [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server stop_consuming**Description:**

Stops consuming audit events on m3server

Usage:

```
m3admin environment server stop_consuming [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update**Description:**

Updates m3server in Maestro Environment

Usage:

```
m3admin environment server update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--ip_address, -ip	string	X	-	M3-server instance address
--active, -A	flag	X	False	Flag to activate the server
--deactivate, -D	flag	X	False	Flag to deactivate the server
--dns	string	X	-	M3-server dns name
--api_endpoint, -api	string	X	-	Api endpoint
--port	integer	X	-	Application port
--protocol	choice	X	-	Transfer protocol. Available choices: http, https

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_jmx_access

Description:

Updates access to the JMX page

Usage:

```
m3admin environment server update_jmx_access [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--user, -u	string	X	-	* User name
--password, -pwd	string	X	-	Password. Please note that password should not contain white spaces
--prompt_password, -P	flag	X	False	Prompt for password if not provided
--role	choice	X	-	The role parameter for access the JMX user. Allowed value: ['FULL_ACCESS', 'READ_ONLY']. Available choices: FULL_ACCESS, READ_ONLY
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_m3admin_configuration

Description:

Updates m3admin service access data

Usage:

```
m3admin environment server update_m3admin_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--protocol	string	X	-	Connection protocol. If not specified - 'http' is applied
--host	string	X	-	* M3admin service address. DNS is preferred
--port	integer	X	-	* M3admin service port
--username, -u	string	X	-	* Username of the user to access service

Option	Type	Req	Default	Description
--password, -pwd	string	X	-	* Password of the user to access service
--endpoint, -endp	string	X	-	A specific URL path where the server can access the API
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_mail_configuration

Description:

Updates server configuration for working with SMTP. For OAuth2 authentication provide --auth_mechanisms XOAUTH2, --oauth2_url and --protocol smtp

Usage:

```
m3admin environment server update_mail_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--host	string	X	-	SMTP server host
--ssl_protocol	string	X	-	SSL protocol
--port	integer	X	-	SMTP server port
--user, -u	string	X	-	SMTP user
--password, -pwd	string	X	-	SMTP user password
--server, -srv	string	X	-	* Name of sever were configuration will be saved
--tls, -T	flag	X	False	Is tsl enabled. Default: False
--auth, -A	flag	X	False	Is auth required. Default: False
--connection_timeout, -ctimeout	integer	X	-	SMTP server connection timeout
--timeout	integer	X	-	SMTP server timeout
--write_timeout, -wtimeout	integer	X	-	SMTP server write timeout
--ssl_trust	string	X	-	List of Hosts. Multiple values allowed (e.g. --ssl_trust value1 --ssl_trust value2)
--ssl_enable, -E	flag	X	False	If set to true SSL is used. Default: False
--protocol, -P	string	X	-	Mail protocol (e.g. smtp)
--auth_mechanisms	string	X	-	Authentication mechanism (e.g. XOAUTH2)
--oauth2_url	string	X	-	OAuth2 endpoint URL (e.g. https://outlook.office365.com/)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_mongo

Description:

Updates MongoDB instance in Maestro Environment

Usage:

```
m3admin environment server update_mongo [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--db_type, -dtype	choice	X	-	* Type of MongoDB. Available choices: operational, billing
--mongo_uri	string	X	-	* Mongo URI. Should be specified in the following form: mongodb://user:password@ip:port/databaseName?waitQueueMultiple=&maxPoolSize=
--ssl_enable, -E	flag	X	False	If set to true SSL is used. False by default
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_profiles

Description:

Overrides all existing profiles with the provided ones on the specified Maestro server

Usage:

```
m3admin environment server update_profiles [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* Server name
--profile, -pf	string	X	-	* Name of profile which will be updated on server. Multiple values allowed (e.g. --profile value1 --profile value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_rabbit_configuration

Description:

Updates RabbitMQ service configuration

Usage:

```
m3admin environment server update_rabbit_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--rabbit_uri, -uri	string	X	-	* Rabbit connection URI
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment server update_sdk_configuration

Description:

Updates M3SDK service

Usage:

```
m3admin environment server update_sdk_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	-	* M3-server name
--protocol	string	X	-	* Protocol type
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin environment setting

Description:

Manages environment settings

Usage:

```
m3admin environment setting
```

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add

Description:

Adds a key-value setting to home account

Usage:

```
m3admin environment setting add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	Setting value. Multiple values allowed (e.g. --value value1 --value value2)
--time_to_live, -ttl	string	X	-	Setting is valid in internal cache during this time
--setting_type, -stype	choice	X	-	Setting type. Allowed values: list, map, str, bool, int. Available choices: list, map, str, bool, int
--empty, -E	flag	X	False	Flag to set empty setting (should be used with --setting_type parameter)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_available_cloud_provider**Description:**

Adds available cloud provider to Maestro Environment

Usage:

```
m3admin environment setting add_available_cloud_provider [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--available_cp	string	X	-	* Cloud provider to add to the environment
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_aws_activation_settings**Description:**

Adds settings for terraform activation for AWS cloud

Usage:

```
m3admin environment setting add_aws_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--iam_user, -iamu	string	X	-	* Name of IAM user
--region, -r	string	X	-	* Region to activate
--temporary_access_enabled, -E, --temporary_access_disabled, -D	flag	X	False	Use or don't use assume role strategy
--policy	string	X	-	Policy name. Required in case of applying custom policies - used in cooperation with --policy_content parameter. Multiple values allowed (e.g. --policy value1 --policy value2)
--policy_content, -pcont	string	X	-	Policy content. Required in case of applying custom policies - used in cooperation with --policy parameter. Multiple values allowed (e.g. --policy_content value1 --policy_content value2)
--iam_group, -iamg	string	X	-	Name of the IAM group to include user. Required in case of attaching user to the group
--aws_managed_policy, -awsp	string	X	-	Name of AWS Managed policies to attach to the user. Required in case of attaching AWS Managed policy to the user or group. Multiple values allowed (e.g. --aws_managed_policy value1 --aws_managed_policy value2)
--iam_role, -iamr	string	X	-	Name of the IAM role to assume. Required if 'use_assume_role' set to True
--session_duration_seconds, -dur	integer (900 to 43200)	X	-	Session duration. Must be in range (900, 43200)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_azure_activation_settings

Description:

Adds settings for terraform activation for AZURE cloud

Usage:

```
m3admin environment setting add_azure_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -appid	string	X	-	* Application id
--app_registration_id, -appid	string	X	-	App registration object id
--arn_client_id, -acid	string	X	-	* ARN of client id
--arn_tenant_id, -atid	string	X	-	* ARN of teanant id

Option	Type	Req	Default	Description
--arn_client_key, -ack	string	X	-	* ARN of client key
--role_id, -rid	string	X	-	Role id
--temporary_access_enabled, -E, --temporary_access_disabled, -D	flag	X	False	Use or don't use temp credentials
--temp_credentials_expiration_hours, -tceh	integer	X	-	Temp credentials expiration hours
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_default_tenant

Description:

Adds a default tenant setting to Maestro Environment

Usage:

```
m3admin environment setting add_default_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_default_tenant_group

Description:

Adds a default tenant group setting to Maestro Environment

Usage:

```
m3admin environment setting add_default_tenant_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Specifies cloud provider to add in DEFAULT_TENANT_GROUPS. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant_group	string	X	-	* Specifies tenant groups to add to cloud provider. Multiple values allowed (e.g. --tenant_group value1 –tenant_group value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_google_activation_settings

Description:

Adds settings for terraform activation for GOOGLE cloud.

Temporary (expiring) access to Google Cloud resources use conditional role bindings to Identity and Access Management (IAM) policies. A conditional role binding can be used to grant time-bounded access to a resource, ensuring that a user can no longer access the resource after the specified expiry date and time. PLEASE NOTE! Any IAM entities will not be created in the Managed tenant(s). Instead some IAM entity will have temporary assignment to the project.

Service account managed access - creates IAM service account(s) in project(s) and use its service account keys. PLEASE NOTE! Service account(s) will be created for each project(s) with regular existence

Usage:

```
m3admin environment setting add_google_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service_account, -scn	string	X	-	Service account principal. Should be used for temporary access
--account, -acc	string	X	-	Account name. Should be used for service account managed
--account_description, -acd	string	X	-	Description
--project_roles, -pjr	string	X	-	Project role names. Multiple values allowed (e.g. –project_roles value1 –project_roles value2)
--predefined_roles, -pdr	string	X	-	Predefined role names. Multiple values allowed (e.g. –predefined_roles value1 –predefined_roles value2)
--access_duration_minutes, -adm	integer	X	-	Access duration minutes is required if '–temporary_access_enabled' is specified. Should be used for temporary access
--access_tenant, -atn	string	X	-	Access tenant name is required if '–temporary_access_enabled' is specified. Should be used for temporary access
--temporary_access_enabled, -E, --	flag	X	False	Temporary access enabled

Option	Type	Req	Default	Description
temporary_access_disabled, -D				
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_resolved_resource_name

Description:

Resolves resources name according to env. Resource name must be wrapped with curly brakes: {resource} Usage examples:
 1. m3admin add_resolved_resource_name --key test_key --resource {some_resource} Following setting will be inserted to be m3_Settings: { "s": "test_key", "v": "m3-some_resource-env_suffix" }
 2. m3admin add_resolved_resource_name --key test_key --resource arn:aws:sns:REGION_PLACEHOLDER:{stackAuditTopic} Following setting will be inserted to be m3_Settings: { "s": "test_key", "v": "arn:aws:sns:REGION_PLACEHOLDER:m3-stackAuditTopic-env-suffix" }

Usage:

```
m3admin environment setting add_resolved_resource_name [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--resource, -res	string	X	-	* Settings value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting add_resource_by_alias

Description:

Resolves resource alias according to m3admin_aliases.conf file Usage examples: m3admin_aliases.conf file contains pair 'resource_alias=resource' m3admin environment setting add_resource_by_alias --key test_key --alias resource_alias Following setting will be inserted into Settings table: { "s": "test_key", "v": "resources_prefix+resource+resources_suffix" }

Usage:

```
m3admin environment setting add_resource_by_alias [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--alias	string	X	-	* Alias to be resolved
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting configure_service

Description:

Makes service enabled or disabled

Usage:

```
m3admin environment setting configure_service [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	choice	X	-	* Name of the service with which the action will be performed. Available choices: terraform, ownership, mail_sender
--action, -a	choice	X	-	* Action with service. Available choices: enable, disable, check
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting delete

Description:

Deletes specified setting in home account

Usage:

```
m3admin environment setting delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting delete_aws_activation_settings

Description:

Deletes settings for terraform activation for AWS cloud

Usage:

```
m3admin environment setting delete_aws_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting delete_azure_activation_settings**Description:**

Deletes settings for terraform activation for AZURE cloud

Usage:

```
m3admin environment setting delete_azure_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting delete_google_activation_settings**Description:**

Deletes settings for terraform activation for GOOGLE cloud

Usage:

```
m3admin environment setting delete_google_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting describe**Description:**

Describes setting or settings

Usage:

```
m3admin environment setting describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting describe_aws_activation_settings**Description:**

Describes settings for terraform activation for AWS cloud

Usage:

```
m3admin environment setting describe_aws_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting describe_azure_activation_settings**Description:**

Describes settings terraform activation for AZURE cloud

Usage:

```
m3admin environment setting describe_azure_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting describe_google_activation_settings**Description:**

Describes settings for terraform activation for GOOGLE cloud

Usage:

```
m3admin environment setting describe_google_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting save_private_cloud_metrics

Description:

Adds data for private cloud metrics

Usage:

```
m3admin environment setting save_private_cloud_metrics [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--role_arn, -rarn	string	X	-	* Role ARN
--external_id, -eid	string	X	-	* External ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting update

Description:

Updates a key-value setting to home account

Usage:

```
m3admin environment setting update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key, -k	string	X	-	* Setting key
--value, -v	string	X	-	* Setting value. Multiple values allowed (e.g. --value value1 --value value2)
--setting_type, -stype	choice	✓	-	* Setting type. Allowed values: list, map, str, bool, int. Available choices: list, map, str, bool, int

Option	Type	Req	Default	Description
--time_to_live, -ttl	integer	X	-	Setting is valid in internal cache during this time
--empty, -E	flag	X	False	Flag to set empty setting (should be used with --setting_type parameter)
--insert, -l	flag	X	False	Flag. Applicable only to lists. Adds a value to the list only if it is unique and does not already exist in the list
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment setting update_aws_activation_settings

Description:

Updates settings for terraform activation for AWS cloud

Usage:

```
m3admin environment setting update_aws_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--iam_user, -iamu	string	X	-	Name of IAM user
--region, -r	string	X	-	Region to activate
--temporary_access_enabled, -E, --temporary_access_disabled, -D	flag	X	False	Use or don't use assume role strategy
--policy	string	X	-	Policy name. Multiple values allowed (e.g. --policy value1 --policy value2)
--policy_content, -pcont	string	X	-	Policy content
--iam_group, -iamg	string	X	-	Name of the IAM group to include user. Required in case of attaching user to the group
--aws_managed_policy, -awsp	string	X	-	Name of AWS Managed policies to attach to the user. Required in case of attaching AWS Managed policy to the user or group. Multiple values allowed (e.g. --aws_managed_policy value1 --aws_managed_policy value2)
--iam_role, -iamr	string	X	-	Name of the IAM role to assume. Required if 'use_assume_role' set to True
--session_duration_seconds, -dur	integer (900 to 43200)	X	-	Session duration. Must be in range (900, 43200)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin environment setting update_azure_activation_settings****Description:**

Updates settings for terraform activation for AZURE cloud

Usage:

```
m3admin environment setting update_azure_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -appid	string	X	-	Application id
--app_registration_id, -appid	string	X	-	App registration object id
--arn_client_id, -acid	string	X	-	ARN of client id
--arn_tenant_id, -atid	string	X	-	ARN of teanant id
--arn_client_key, -ack	string	X	-	ARN of client key
--role_id, -reid	string	X	-	Role id
--temporary_access_enabled, -E, --temporary_access_disabled, -D	flag	X	False	Use or don't use temp credentials
--temp_credentials_expiration_hours, -tceh	integer	X	-	Temp credentials expiration hours
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin environment setting update_google_activation_settings****Description:**

Updates settings for terraform activation for GOOGLE cloud.

Temporary (expiring) access to Google Cloud resources use conditional role bindings to Identity and Access Management (IAM) policies. A conditional role binding can be used to grant time-bounded access to a resource, ensuring that a user can no longer access the resource after the specified expiry date and time. PLEASE NOTE! Any IAM entities will not be created in the Managed tenant(s). Instead some IAM entity will have temporary assignment to the project.

Service account managed access - creates IAM service account(s) in project(s) and use its service account keys. PLEASE NOTE! Service account(s) will be created for each project(s) with regular existence

Usage:

```
m3admin environment setting update_google_activation_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service_account, -scn	string	X	-	Service account. Should be used for temporary access
--account, -acc	string	X	-	Account name. Should be used for service account managed
--account_description, -acd	string	X	-	Description
--project_roles, -pjr	string	X	-	Project role names. Multiple values allowed (e.g. --project_roles value1 --project_roles value2)
--predefined_roles, -pdr	string	X	-	Predefined role names
--access_duration_minutes, -adm	integer	X	-	Access duration minutes is required if '--temporary_access_enabled' is specified. Should be used for temporary access
--access_tenant, -atn	string	X	-	Access tenant name is required if '--temporary_access_enabled' is specified. Should be used for temporary access
--temporary_access_enabled, -E, --temporary_access_disabled, -D	flag	X	False	Temporary access enabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment add_application

Description:

Adds application entity

Usage:

```
m3admin environment add_application [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--type	string	X	-	* Application type
--meta	json	X	-	* Application meta escaped JSON string
--description, -d	string	X	-	* Application description
--secret_key, -skey	string	X	-	Application credentials
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment add_customer**Description:**

Registers new customer in Maestro

Usage:

```
m3admin environment add_customer [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Customer name
--domain, -dom	string	X	-	Customer domain used to authorize
--display_name, -dn	string	X	-	Customer display name, if not specified - value from --name parameter will be used
--authorization_url, -aurl	string	X	-	Auth url to redirect if type is SSO
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment add_domain_auth_mapping**Description:**

Adds domain auth mapping

Usage:

```
m3admin environment add_domain_auth_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--domain	string	X	-	* Domain name
--provider, -prov	string	X	-	* Provider name
--parent_id, -pid	string	X	-	* Id of the parent
--redirect_url, -rurl	string	X	-	* Environment redirect url
--authorization_url, -aurl	string	X	-	* Authorization url for oAuth
--token_url, -turl	string	X	-	* Token url for oAuth
--parameter, -param	string	X	-	* Additional parameters. Multiple values allowed (e.g. --parameter key1=value1 --parameter key2=value2)
--extraction_template, -etemp	string	X	-	Path to the file with extraction template. Allowed file extension - json
--customer_id, -cid	string	X	-	Customer ID
--default_owner, -do	string	X	-	Default owner
--primary_contact, -pct	string	X	-	Primary contact

Option	Type	Req	Default	Description
--secondary_contact, -sct	string	X	-	Secondary contact
--manager_contact, -mct	string	X	-	Manager contact
--active_directory_parent_id, -adpid	string	X	-	Parent ID for active directory
--active_directory_creation_enabled, -C	flag	X	False	Create active directory
--active_directory_mapping_enabled, -M	flag	X	False	Enable active directory mapping
--force, -F	flag	X	False	Overwrite region if the same one already exists
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment add_environment_testers*

Description:

Adds testers to the environment

Usage:

```
m3admin environment add_environment_testers [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Environment testers emails. Multiple values allowed (e.g. --email value1 --email value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment add_parent*

Description:

Adds parent entity

Usage:

```
m3admin environment add_parent [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--type	string	X	-	* Parent type
--application_id, -aid	string	X	-	* Id of the application
--customer_id, -cid	string	✓	-	* Customer ID
--description, -d	string	X	-	* Parent description
--meta	json	X	-	Parent meta JSON string
--scope, -s	string	X	-	Parent scope. Format TYPE#ACTION#TARGET
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment add_permission_group

Description:

Adds permission group

Usage:

```
m3admin environment add_permission_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	DEFAULT	Customer ID. If not specified 'DEFAULT' will be used
--group, -g	string	X	-	Permission group name
--group_type, -gtype	choice	X	ALLOW	Permission type. Available choices: ALLOW, DENY
--action, -a	string	X	[]	Permission action. Multiple values allowed (e.g. --action value1 --action value2)
--file_path, -fpath	string	X	-	Path to file with group configuration
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment add_region

Description:

Adds region to the list of supported regions on environment

Usage:

```
m3admin environment add_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--maestro_name, -mname	string	X	-	* Maestro name of the region
--native_name, -nname	string	X	-	* Native name of the region
--cloud, -c	choice	X	-	* Cloud of the region. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--availability_zone, -az	string	X	-	Availability zones of the region (Is required for AWS, Yandex and Google). Multiple values allowed (e.g. –availability_zone value1 –availability_zone value2)
--region_id, -rid	string	X	-	Id of the region
--deprecated, -D	flag	X	False	Mark region as deprecated
--billing_mix_mode, -B	flag	X	False	Mark as billing mix mode applicable to the region. Available only for public Cloud Providers: ['AZURE', 'GOOGLE', 'AWS', 'YANDEX']
--hardware, -H	flag	X	False	Mark region as a hardware one
--hidden, -h	flag	X	False	Mark region as hidden
--active, -A	flag	X	False	Mark region as an active one
--unreachable, -U	flag	X	False	Mark region as an unreachable
--force, -F	flag	X	False	Overwrite region is the same one already exists
--region_abbreviation	string	X	-	Short regions abbreviation
--exchange, -exc	string	X	-	Name of rabbit exchange used for m3-sdk integration with private cloud
--sync_request_queue	string	X	-	Name of rabbit queue used for m3-sdk sync requests
--async_request_queue	string	X	-	Name of rabbit queue used for m3-sdk async requests
--sdk_access_key, -skey	string	X	-	Name of sdk key used for m3-sdk integration with private-agent
--response_queue	string	X	-	Name of rabbit queue used for receiving responses from private-agent
--mobile, -M	flag	X	False	Use for Mobile Cloud
--vendor, -v	string	X	-	Vendor name, converted to uppercase
--vendor_display_name, -vdn	string	X	-	Display name for the vendor
--related_cloud, -rc	choice	X	-	Related cloud for the vendor, for example AWS for AWS_PAAS. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment add_tenant_to_tenant_group**Description:**

Adds tenants to one tenant group

Usage:

```
m3admin environment add_tenant_to_tenant_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenants that will be added
--tenant_group, -tg	string	X	-	* Name of the tenant group
--linked_date, -ldate	string	X	-	Linked date. Format “yyyy-mm-dd”
--force, -F	flag	X	False	Force link action
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment api_gateway_request_logging**Description:**

Manages debug mode on API Gateway

Usage:

```
m3admin environment api_gateway_request_logging [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -a	choice	X	-	Action that need to be done with API Gateway request logging. Available choices: enable, disable
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment audit**Description:**

Describes audit

Usage:

```
m3admin environment audit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	The name of the Tenant to filter audit. Multiple values allowed (e.g. --tenant value1 --tenant value2)
--region, -r	string	X	-	The name of the region to filter audit. Multiple values allowed (e.g. --region value1 --region value2)
--user, -u	string	X	-	User that performed command
--group, -g	string	X	-	Group that m3admin command belongs to
--command, -cmd	string	X	-	m3admin command name to filter audit
--from_date	string	X	-	From date. Format "yyyy-mm-dd"
--to_date	string	X	-	To date. Format "yyyy-mm-dd"
--limit	integer (1 to 100)	X	10	Amount of records that will be shown. The default value is 10, the minimum value is 1 and maximum value is 100
--email, -e	string	X	-	The email address to sent the query result to
--invalid, -l	flag	X	False	Show audit events with modified records
--reverse_order, -ro	flag	X	False	Reverse order of displayed audit events
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment block_users

Description:

Adds users to the environment black list

Usage:

```
m3admin environment block_users [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Blocked users emails. Multiple values allowed (e.g. --email value1 --email value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment change_customer_display_name

Description:

Renames existing customer

Usage:

```
m3admin environment change_customer_display_name [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--display_name, -dn	string	X	-	* Customer display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment configure_customer_admins*

Description:

Configures customer admin users

Usage:

```
m3admin environment configure_customer_admins [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Customer admins email. Multiple values allowed (e.g. --email value1 --email value2)
--customer_id, -cid	string	X	-	* Customer ID
--override, -O	flag	X	False	Override current customer admins
--force, -F	flag	X	False	Set this flag to ignore nonexistent users
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment delete_application*

Description:

Deletes application entity

Usage:

```
m3admin environment delete_application [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--application_id, -aid	string	X	-	Id of the application

Option	Type	Req	Default	Description
--force, -F	flag	X	False	Force flag for force delete application
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment delete_customer*

Description:

Deletes customer from Maestro

Usage:

```
m3admin environment delete_customer [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Customer name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment delete_customer_admins*

Description:

Removes customer admin users

Usage:

```
m3admin environment delete_customer_admins [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Customer admin email[s]. For several emails repeat the parameter. Multiple values allowed (e.g. --email value1 –email value2)
--customer_id, -cid	string	X	-	* Customer ID
--force, -F	flag	X	False	Use this flag to force customer admin deletion. Command will ignore if such user does not exist
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment delete_parent**Description:**

Deletes parent entity

Usage:

```
m3admin environment delete_parent [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--parent_id, -pid	string	X	-	* Id of the parent
--force, -F	flag	X	False	Force flag for force delete parent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment delete_permission_group**Description:**

Removes permission group

Usage:

```
m3admin environment delete_permission_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--group, -g	string	X	-	* Permission group name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment delete_region**Description:**

Marks region as deleted in Regions table

Usage:

```
m3admin environment delete_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment delete_sdk_key*

Description:

Removes sdk keys for system/user/customer

Usage:

```
m3admin environment delete_sdk_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--access_key, -akey	string	X	-	* Key name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment delete_secured_file_with_setting*

Description:

Removes secured file

Usage:

```
m3admin environment delete_secured_file_with_setting [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--setting_key, -skey	string	X	-	* Key to store SMM key in the database
--key	string	X	-	* Key to store sensitive data
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment delete_tenant_from_tenant_group*

Description:

Removes tenants from tenant group

Usage:

```
m3admin environment delete_tenant_from_tenant_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenants that will be unlinked from group
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment deploy_db_initial_data

Description:

Path that consists of folders with json file to be created in the database as items. Json files path format: table_name/item.json

Usage:

```
m3admin environment deploy_db_initial_data [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--path	string	X	-	* Path to JSON file
--db_type, -dbt	choice	X	DYNAMO	DB type. Default DYNAMO. Available choices: MONGO, DYNAMO
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment deploy_dictionaries

Description:

Path that consists of folders or files to be uploaded to S3 buckets

Usage:

```
m3admin environment deploy_dictionaries [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--path	string	X	-	* Str, bucket name in which files will be uploaded
--override	boolean	X	True	Boolean, specify if dictionary data will be overridden

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment deploy_s3_initial_data*

Description:

Path that consists of folders or files to be uploaded to S3 buckets

Usage:

```
m3admin environment deploy_s3_initial_data [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--path	string	X	-	* Str, bucket name in which files will be uploaded
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment deploy_ui*

Description:

Deploys UI

Usage:

```
m3admin environment deploy_ui [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--ui_path_to_git_repo	string	X	-	* Git repo path
--ui_folder_path, -uipath	string	X	-	* Folder path
--ui_artifact_path, -ui_path	string	X	-	* Artifact path
--environment, -env	string	X	prod	Environment where UI will be deployed
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment deregister_customer_access_key**Description:**

Deregisters customer access key

Usage:

```
m3admin environment deregister_customer_access_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment deregister_nessus_server**Description:**

Deregisters current default nessus server on m3server side

Usage:

```
m3admin environment deregister_nessus_server [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment describe_application**Description:**

Describes application entity

Usage:

```
m3admin environment describe_application [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--application_id, -aid	string	X	-	Id of the application
--application_type, -at	string	X	-	Type of the application

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment describe_customer_admins

Description:

Describes customer admins. The command will also perform a diagnostic to find possible mistakes in the configuration of admins by the following rules: * Check that the corresponding user exists. * Check that the customer's name is present in the user's "admin for customers" field * Check that the user has an admin secret key, and it exists in SSM

Usage:

```
m3admin environment describe_customer_admins [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment describe_parent

Description:

Describes parent entity

Usage:

```
m3admin environment describe_parent [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--parent_id, -pid	string	X	-	Id of the parent
--parent_type, -pt	string	X	-	Type of the parent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment describe_sdk_key**Description:**

Describes sdk keys or specified sdk key by name

Usage:

```
m3admin environment describe_sdk_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--access_key, -akey	string	X	-	Key name. If missing - all keys will be described
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment describe_vendor**Description:**

Describes vendor information

Usage:

```
m3admin environment describe_vendor [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment disable_autoscaling**Description:**

Disables auto-scaling for the given tables

Usage:

```
m3admin environment disable_autoscaling [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--table	string	X	-	* List of the Tables to disable auto-scaling. Multiple values allowed (e.g. --table value1 --table value2)
--dimension	choice	X	-	* The scalable dimension: [read, write]. Available choices: read, write

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin environment disable_instances_termination_protection`

Description:

Disabling termination protection for instances in specified stacks

Usage:

```
m3admin environment disable_instances_termination_protection [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--instance_stack, -inststk	string	X	['m3-admin-instan...	Logical IDs of stacks with instances for which termination protection would be disabled. Multiple values allowed (e.g. --instance_stack value1 --instance_stack value2)
--region, -r	string	X	-	Region were CloudFormation stacks exist
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin environment disable_maintenance_mode`

Description:

Disables maintenance mode

Usage:

```
m3admin environment disable_maintenance_mode [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--ui_bucket	string	X	-	* Name of the S3 bucket where UI is hosted
--index_doc	string	X	-	* Index page key in bucket
--error_doc	string	X	-	* Error page key in bucket
--distribution	string	X	-	* CloudFront distribution id to invalidate cache
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment disable_metric*

Description:

Disables specific metric by types aliases. Metric type to alias mapping:

CPU utilization - cpu

Disk read/write (bytes) - disk_rw_b

Disk read/write (operations) - disk_rw_o

Network traffic (I/O) - network

Status check - status_check

Chargeback - chargeback

Total instances - total_instances

Running instances - running_instances

Stopped instances - stopped_instances

CUSTOM_METRIC_TENANT_LEVEL - custom_tenant_level

CUSTOM_METRIC_VM_LEVEL - custom_vm_level

Usage:

```
m3admin environment disable_metric [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--metric_type, -mtype	choice	X	-	* List of metric types aliases that will be disabled. Multiple values allowed (e.g. --metric_type value1 --metric_type value2). Available choices: cpu, disk_rw_b, disk_rw_o, network, status_check, chargeback, total_instances, running_instances, stopped_instances, custom_tenant_level, custom_vm_level
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment download_deploy_output*

Description:

Downloads output file from s3

Usage:

```
m3admin environment download_deploy_output [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bundle, -bun	string	X	-	* Name of the bundle
--deploy	string	X	-	* Name of the deploy
--output_path, -opath	string	X	-	Path to save the file
--artifacts_bucket, -ab	string	X	-	Name of the artifacts bucket
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment enable_autoscaling*

Description:

Enables auto-scaling for the given tables

Usage:

```
m3admin environment enable_autoscaling [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--table	string	X	-	* List of the Tables to enable auto-scaling. Multiple values allowed (e.g. --table value1 --table value2)
--dimension	choice	X	-	* The scalable dimension: [read, write]. Available choices: read, write
--min_capacity	integer (1 to 9999)	X	-	Minimum provisioned capacity. Must be >= 1 and < 10000
--max_capacity	integer (1 to 9999)	X	-	Maximum provisioned capacity. Must be >= 1 and < 10000
--role	string	X	-	* Role name
--policy	string	X	-	Policy name
--target_utilization	float	X	-	Target utilization in percents
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment enable_maintenance_mode*

Description:

Enables maintenance mode on environment

Usage:

```
m3admin environment enable_maintenance_mode [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--mntc_sc_path, -mpath	string	X	-	* Maintenance static content path
--ro_path, -rpath	string	X	-	* Root object path to be set in bucket
--distribution	string	X	-	CloudFront distribution id to invalidate cache
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment enable_metric**Description:**

Enables specific metric by type. To enable metric its alias should be specified in `--metric_type` parameter. Metric type to alias mapping:

CPU utilization - `cpu`

Disk read/write (bytes) - `disk_rw_b`

Disk read/write (operations) - `disk_rw_o`

Network traffic (I/O) - `network`

Status check - `status_check`

Chargeback - `chargeback`

Total instances - `total_instances`

Running instances - `running_instances`

Stopped instances - `stopped_instances`

CUSTOM_METRIC_TENANT_LEVEL - `custom_tenant_level`

CUSTOM_METRIC_VM_LEVEL - `custom_vm_level`

Usage:

```
m3admin environment enable_metric [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--metric_type, -mtype	choice	X	-	* List of metric types that will be enabled. Multiple values allowed (e.g. <code>--metric_type value1 --metric_type value2</code>). Available choices: <code>cpu</code> , <code>disk_rw_b</code> , <code>disk_rw_o</code> , <code>network</code> , <code>status_check</code> , <code>chargeback</code> , <code>total_instances</code> , <code>running_instances</code> , <code>stopped_instances</code> , <code>custom_tenant_level</code> , <code>custom_vm_level</code>
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment find_deployment_object*

Description:

Finds and prints deployment description of resource by its name

Usage:

```
m3admin environment find_deployment_object [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--resource, -res	string	X	-	* Name of the resource
--deploy	string	X	-	* Deploy_name
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment generate_sdk_key*

Description:

Access and secret SDK keys have been automatically generated for the principal. Keys will be displayed only once

Usage:

```
m3admin environment generate_sdk_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--expiration, -exp	string	X	-	* Date of key expiration. Format "yyyy-mm-dd"
--principal, -prc	string	X	-	* Principal name (email)
--customer_id, -cid	string	X	-	Customer ID
--default	flag	X	False	Default key flag
--meta, -m	json	X	-	Meta JSON
--description, -des	string	X	-	* Text reason for creating the SDK key (e.g "User will use this key for ...")
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment link_parent_to_application*

Description:

Links parent entity to the application

Usage:

```
m3admin environment link_parent_to_application [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--parent_id, -pid	string	X	-	* Id of the parent
--application_id, -aid	string	X	-	* Id of the application
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment list_customers*

Description:

Show all available customers in Maestro

Usage:

```
m3admin environment list_customers [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment list_users*

Description:

Lists all white-list users

Usage:

```
m3admin environment list_users [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment manage_vendor*

Description:

Manages vendor information

Usage:

```
m3admin environment manage_vendor [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--vendor, -v	string	X	-	* Vendor name, converted to uppercase
--remove, -R	flag	X	False	Flag. Provide it if you need to remove a vendor
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment prolong_sdk_key*

Description:

Prolongs expiration of key

Usage:

```
m3admin environment prolong_sdk_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--access_key, -akey	string	X	-	* Name of the key to prolong
--expiration, -exp	string	X	-	* New date of key expiration. Format "yyyy-mm-dd"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment purge_s3_buckets**Description:**

Purges all buckets in cf stack

Usage:

```
m3admin environment purge_s3_buckets [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--root_stack, -rs	string	X	m3-backend	Name of the root cf stack, if not specified m3-backend will be used
--bucket_stack_logical_id, -bid	string	X	S3Bucket	Logical id of the bucket cf stack, if not specified S3Bucket will be used
--region, -r	choice	X	-	Region name where stacks exist, if not specified region will be resolved from config. Available choices: us-east-1, us-east-2, us-west-1, us-west-2, sa-east-1, ca-central-1, eu-west-1, eu-central-1, eu-west-2, eu-west-3, ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, ap-south-1, cn-north-1
--force, -F	flag	X	False	If flag would be set then custom_output.py during deleting objects from buckets would be ignored
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_api_id**Description:**

Registers M3 api gateway id

Usage:

```
m3admin environment register_api_id [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--api	string	X	maestro3	Name of the api gateway resource [optional]
--deploy	string	X	-	* Name of the maestro deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_api_stage**Description:**

Registers M3 api gateway stage

Usage:

```
m3admin environment register_api_stage [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--api	string	X	maestro3	Name of the api gateway resource [optional]
--deploy	string	X	-	* Name of the maestro deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_bundle**Description:**

Registers path to bundle in the database

Usage:

```
m3admin environment register_bundle [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bundle, -bun	string	X	<function check_r...	* Bundle name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_customer_access_key**Description:**

Generates and registers access key for customer

Usage:

```
m3admin environment register_customer_access_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--access_key, -akey	string	X	-	Access key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_identity_pool_id

Description:

Registers M3 cognito identity pool id

Usage:

```
m3admin environment register_identity_pool_id [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--identity_pool, -ipool	string	X	maestro3_e pam_ope...	Name of the identity pool
--deploy	string	X	-	* Name of the maestro deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_identity_pool_id_v2

Description:

Registers M3 cognito identity pool id

Usage:

```
m3admin environment register_identity_pool_id_v2 [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--identity_pool_logical_id, -iid	string	X	Maestro3Ep amOpenS...	Logical id of the identity pool
--root_stack, -rs	string	X	m3-backend	Name of the root cf stack
--cognito_stack_logical_id, -cid	string	X	CognitoFede ratedPool	Logical if of the cognito cf stack
--region, -r	choice	X	-	* Region name were stacks exist. Available choices: us-east-1, us-east-2, us-west-1, us-west-2, sa-east-1, ca-

Option	Type	Req	Default	Description
				central-1, eu-west-1, eu-central-1, eu-west-2, eu-west-3, ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, ap-south-1, cn-north-1
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment register_instance*

Description:

Registers M3 instances by deploy output

Usage:

```
m3admin environment register_instance [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--instance, -i	string	X	-	Name of the instance to register
--instance_address	choice	X	-	* Name of the instance's network interface to register. Available choices: public_dns, private_dns, public_ip, private_ip
--deploy	string	X	-	* Name of the deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment register_nessus_server*

Description:

Registers new nessus server on m3server side. Every new server will be marked as default server

Usage:

```
m3admin environment register_nessus_server [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username, -u	string	X	-	* Username for access to nessus server
--password, -pwd	string	X	-	* Password for access to nessus server
--url	string	X	-	* Nessus server url

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_notification_application

Description:

Registers notification application

Usage:

```
m3admin environment register_notification_application [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application, -app	string	X	maestro_mobile	* Name of the notification application
--deploy	string	X	-	* Name of the deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_notification_application_v2

Description:

Registers notification application

Usage:

```
m3admin environment register_notification_application_v2 [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_logical_id, -applgcid	string	X	SnsApplication	* Logical id of the notification application
--root_stack, -rs	string	X	m3-backend	Name of the root cf stack
--application_stack_logical_id, -aslid	string	X	SnsApplication	Logical id of the application cf stack
--region, -r	choice	X	-	* Region name where stacks exist. Available choices: us-east-1, us-east-2, us-west-1, us-west-2, sa-east-1, ca-central-1, eu-west-1, eu-central-1, eu-west-2, eu-west-3, ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, ap-south-1, cn-north-1

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment register_resources*

Description:

Registers all resources required by m3 installation

Usage:

```
m3admin environment register_resources [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--root_stack, -rs	string	X	m3-backend	Name of the root cf stack
--region, -r	choice	X	-	* Region name where stacks exist. Available choices: us-east-1, us-east-2, us-west-1, us-west-2, sa-east-1, ca-central-1, eu-west-1, eu-central-1, eu-west-2, eu-west-3, ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, ap-south-1, cn-north-1
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment register_s3_bucket*

Description:

Registers S3 bucket in the Maestro system

Usage:

```
m3admin environment register_s3_bucket [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--expiration, -exp	string	X	-	* Count of days
--expiration_rule	string	X	-	Rule name
--bucket, -b	string	X	-	* Bucket name for which the rule will be added
--bucket_key, -bkey	string	X	-	* Bucket key/type. For example: BUCKET_M3_CHARTS_BUCKET_SETTINGS_JSON, BUCKET_QUALYS_SCAN_RESULTS_SETTINGS_JSON, BUCKET_M3_EMAIL_NOTIFICATIONS_SETTINGS_JSON

Option	Type	Req	Default	Description
				ON, BUCKET_NESSUS_SCAN_RESULTS_SETTINGS_JSON
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment register_sdk_key*

Description:

Adds sdk keys for system/user

Usage:

```
m3admin environment register_sdk_key [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--access_key, -akey	string	X	-	* Key name
--secret_key, -skey	string	X	-	* Secret key value. Password length is 16/24/32 symbols, upper- and lowercase letters, numbers 0-9
--key_type, -ktype	choice	X	-	* Key type. Available choices: SYSTEM, USER
--default, -D	flag	X	False	Default key flag
--expiration, -exp	string	X	-	* Date of key expiration. Format "yyyy-mm-dd"
--principal	string	X	-	* Principal name
--customer_id, -cid	string	X	-	Customer ID
--meta, -m	json	X	-	Meta JSON
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment register_ui_bucket*

Description:

Registers UI bucket

Usage:

```
m3admin environment register_ui_bucket [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket, -b	string	X	-	Name of the bucket

Option	Type	Req	Default	Description
--bucket_alias, -balias	string	X	ui_bucket	Alias for bucket name
--deploy	string	X	-	* Name of the deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_ui_bucket_v2

Description:

Registers UI bucket

Usage:

```
m3admin environment register_ui_bucket_v2 [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket_logical_id, -bid	string	X	CloudOrche strator	Logical id of the bucket
--root_stack, -rs	string	X	m3-backend	Name of the root cf stack
--bucket_stack_logical_id, -bid	string	X	S3Bucket	Logical id of the schedule cf stack
--region, -r	choice	X	-	* Region name were stacks exist. Available choices: us-east-1, us-east-2, us-west-1, us-west-2, sa-east-1, ca-central-1, eu-west-1, eu-central-1, eu-west-2, eu-west-3, ap-northeast-1, ap-northeast-2, ap-southeast-1, ap-southeast-2, ap-south-1, cn-north-1
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment register_ui_components

Description:

Registers UI components

Usage:

```
m3admin environment register_ui_components [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--path	string	X	-	* Path to be processed

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment remove_ssm_parameter*

Description:

Removes parameter from SSM (Parameter Store)

Usage:

```
m3admin environment remove_ssm_parameter [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* The name of parameter from SSM
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment save_secured_file_with_setting*

Description:

Saves secured file and stored setting with ssm key in its value

Usage:

```
m3admin environment save_secured_file_with_setting [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--setting_key, -skey	string	X	-	* Key to store SMM key in the database
--key	string	X	-	* Key to store sensitive data
--file, -f	string	X	-	* Path to file which should be secured
--description, -d	string	X	-	Description for parameter
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment save_secured_parameter**Description:**

Saves secured key

Usage:

```
m3admin environment save_secured_parameter [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--setting_key, -skey	string	X	-	* Key to store SMM key in the database
--key	string	X	-	* Key to store sensitive data
--value	string	X	-	* Key value for EC2 Parameter Store
--description, -d	string	X	-	Description for parameter
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment set_available_features_to_customer**Description:**

Sets available features to customer

Usage:

```
m3admin environment set_available_features_to_customer [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--feature, -ftr	string	X	-	* Available feature name. Multiple values allowed (e.g. --feature value1 --feature value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment set_elastic_ip**Description:**

Sets elastic ip to EC2 instance

Usage:

```
m3admin environment set_elastic_ip [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--deploy	string	X	-	* Deploy name
--resource, -res	string	X	<function check_r...	* Resource name
--ip	string	X	<function check_r...	* IP
--file_path, -fpath	string	X	.	Path to output
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment set_hardware_credit_support**Description:**

Disables or enables hardware credit support for region

Usage:

```
m3admin environment set_hardware_credit_support [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region
--is_hardware_credit_supported, -l	flag	X	False	Disables or enables hardware credit support for region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment set_location_configuration**Description:**

Sets location configuration to AZURE region only

Usage:

```
m3admin environment set_location_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region

Option	Type	Req	Default	Description
--location	string	X	-	Azure region location (not required if -A is specified)
--location_alias, -lalias	string	X	-	* Azure region location aliases. Multiple values allowed (e.g. --location_alias value1 --location_alias value2)
--append_aliases, -A	flag	X	False	If True: specified Azure region location aliases will be added to existing. Otherwise existing aliases will be override
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment set_proxy_host

Description:

Disables or enables proxy host for region

Usage:

```
m3admin environment set_proxy_host [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region
--proxy_host, -phost	string	X	-	* Proxy host
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment set_sdk_key_autorotation

Description:

Sets flag that applies for specified sdk key autorotation process

Usage:

```
m3admin environment set_sdk_key_autorotation [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--access_key, -akey	string	X	-	* Key name
--action, -a	choice	X	-	* Action that need to be done regarding autorotation. Available choices: enable, disable
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment set_security_groups*

Description:

Sets security groups for the Customer

Usage:

```
m3admin environment set_security_groups [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID to which pre-configured security groups will be deployed
--sg_config, -sgc	string	X	-	Security groups configuration in escaped JSON format. String format: [{"n":String,"d":String,"ii": [{"d":String,"ip":String}]}], [{"n":String,"d":String,"ii": [{"d":String,"ip":String}]}]
--sg_config_file_path, -spath	string	X	-	Path to security group config json file. Config file format: [{"n":String,"d":String,"ii": [{"d":String,"ip":String}]}], [{"n":String,"d":String,"ii": [{"d":String,"ip":String}]}]
--remove, -R	flag	X	False	Marks the specified security group(s) for deletion
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin environment show_api_gateway_id*

Description:

Shows information about deployed Api Gateway. Info will be got from output file

Usage:

```
m3admin environment show_api_gateway_id [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--deploy	string	X	-	* Deploy name
--api_gateway, -ag	string	X	<function check_r...	* Resource name
--file_path, -fpath	string	X	.	Path to output
--raw_output, -R	flag	X	False	Get raw ID

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment status

Description:

Checks registration status of an M3 server. Uses default server from Settings if not specified

Usage:

```
m3admin environment status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -srv	string	X	CORE_SERVER_NAME	M3-server name. If not specified - will be taken from Settings
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment update_application

Description:

Adds application entity

Usage:

```
m3admin environment update_application [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	X	-	Application ID
--type	string	X	-	* Application type
--customer_id, -cid	string	X	-	* Customer ID
--meta	json	X	-	Application meta JSON string
--description, -d	string	X	-	Application description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment update_parent**Description:**

Updates parent entity

Usage:

```
m3admin environment update_parent [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--type	string	X	-	* Parent type
--parent_id, -pid	string	X	-	* Id of the parent
--customer_id, -cid	string	X	-	* Customer ID
--description, -d	string	X	-	Parent description
--meta	json	X	-	Parent meta JSON string
--scope, -s	string	X	-	Parent scope. Format TYPE#ACTION#TARGET
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin environment validate_db_initial_data**Description:**

Validates initial data according to provided schemas. Report contains only invalid items by default. :param path: path to initial data :param schema_path: path to json schemas to validate the data :param report: flag; if True - the result will be flushed to file :param full_report: flag; if True - all the valid items will be added to the report :return:

Usage:

```
m3admin environment validate_db_initial_data [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--path	string	X	-	* Path to data JSON file
--schema_path, -spath	string	X	-	* Path to schema JSON file
--report, -R	flag	X	False	Save command output to file with name validate_db_initial_data_\$date.json
--full_report, -F	flag	X	False	Includes valid items to the report
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin google**Description:**

Manages Google-related resources

Usage:

```
m3admin google
```

[↑ Back to Table of Contents](#)

Command: m3admin google activate**Description:**

Activates a Google tenant

Usage:

```
m3admin google activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Name of Tenant to activate
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--display_name, -dn	string	X	-	* Tenant name for UI
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--tenant_customer, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as personal
--project_type	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE". Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--google_project_id, -gpid	string	X	-	* Google project id number
--billing_project_id, -bpid	string	X	-	Billing(Admin) project native id, should be specified for Google cloud
--management_project_id, -mpid	string	X	-	Management project id
--network_link, -nl	string	X	-	Network link
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google activate_region**Description:**

Activates region in a tenant

Usage:

```
m3admin google activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--default_for_common_costs, -D	flag	X	False	Marks region as default for common costs
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google add_image**Description:**

Registers a Google image in Maestro. Note: this command should be used after Google Tenant is registered

Usage:

```
m3admin google add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Image name
--description, -d	string	X	-	* Image description
--os_type, -os	string	X	-	* Type of the operation system
--google_project_id, -gid	string	X	-	* Google image project ID. See https://cloud.google.com/compute/docs/images for more details
--google_image, -gimg	string	X	-	Google image name. Cannot be used with image family
--google_image_family	string	X	-	Google image family. Cannot be used with image name
--group, -g	choice	X	-	* Image group: [PUBLIC, ENTERPRISE]. Available choices: PUBLIC, ENTERPRISE
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag "--all_regions" is specified)
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google apply_sku_id_configuration**Description:**

Applies SKU ID configuration

Usage:

```
m3admin google apply_sku_id_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--sku_id	string	X	-	* SKU ID of the product (Stock Keeping Unit ID)
--tenant, -tn	string	X	-	* Tenant display name
--billing_account_id, -baid	string	X	-	* Billing account id (format 000000-AAAAAA-222222)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google create_firewall_rules**Description:**

Creates firewall rules in activated Google account

Usage:

```
m3admin google create_firewall_rules [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--sg_config_file_path, -spath	string	X	-	Custom path to security group config json file. Gets from the 'M3ADMIN_CONF/security_groups.json' file by default
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google create_network**Description:**

Creates network resources in activated Google account

Usage:


```
m3admin google create_network [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--sg_config_file_path, -spath	string	X	-	Path to security group config json file
--deploy_fr, -D	flag	X	False	If 'True' initiates the security groups deployment
--region, -r	string	X	-	Region name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google deactivate**Description:**

Deactivates a specified tenant in Maestro

Usage:

```
m3admin google deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenant which will be deactivated
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google delete_image**Description:**

Deletes Google Image

Usage:

```
m3admin google delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions

Option	Type	Req	Default	Description
--cloud, -c	string	X	Google	Cloud provider. Default is Google
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google delete_network*

Description:

Removes network resources in activated Google account

Usage:

```
m3admin google delete_network [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google describe_network*

Description:

Describes network resources in Google Account linked with Tenant

Usage:

```
m3admin google describe_network [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google describe_sku_id_configuration*

Description:

Describes a SKU ID configuration

Usage:

```
m3admin google describe_sku_id_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--billing_account_id, -baid	string	X	-	Billing account id (format 000000-AAAAAA-222222)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google describe_subnetnetwork**Description:**

Describes subnetnetwork resources in Google Account linked with Tenant

Usage:

```
m3admin google describe_subnetnetwork [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin google manage_alpha_locations**Description:**

Adds, describes or deletes alpha_location in Google region for billing purposes

Usage:

```
m3admin google manage_alpha_locations [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	Region name to be processed
--alpha_location	string	X	-	Alpha_location to be processed
--action, -a	choice	X	-	Action type the location is to be processed.. Available choices: add, describe, remove
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google manage_workspace*

Description:

Adds or removes host workspace projectId to tenant

Usage:

```
m3admin google manage_workspace [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name. Multiple values allowed (e.g. –tenant value1 –tenant value2)
--action, -a	choice	X	-	* Action to be processed. The “project_id” parameter is required in case of “add” operation is chosen. Available choices: add, remove
--project_id, -pid	string	X	-	Host workspace google projectId. Required in case of “add” operation is chosen
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google remove_sku_id_configuration*

Description:

Removes a SKU ID configuration

Usage:

```
m3admin google remove_sku_id_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--sku_id	string	X	-	* SKU ID of the product (Stock Keeping Unit ID)
--tenant, -tn	string	X	-	* Tenant display name
--billing_account_id, -baid	string	X	-	* Billing account id (format 000000-AAAAAA-222222)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google reset_vm_counters***Description:**

Resets counters values if they don't correspond to real instances quantity

Usage:

```
m3admin google reset_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin google validate_vm_counters***Description:**

Checks if counters values corresponds to real instances quantity

Usage:

```
m3admin google validate_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin hardware**Description:**

Manages hardware-related resources

Usage:

```
m3admin hardware
```

[↑ Back to Table of Contents](#)

Command: m3admin hardware activate**Description:**

Activates HARDWARE tenant

Usage:

```
m3admin hardware activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE. Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin hardware activate_region**Description:**

Activates HARDWARE region in tenant

Usage:

```
m3admin hardware activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin hardware deactivate*

Description:

Deactivates HARDWARE tenant

Usage:

```
m3admin hardware deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin hardware delete_image*

Description:

Removes image in Maestro

Usage:

```
m3admin hardware delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Image name
--tenant, -tn	string	X	-	Tenant display name
--region, -r	string	X	-	* Virtualization region. Specify "ALL" to delete image in all regions
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Group: m3admin maintenance**Description:**

[Installable Module] Manages Maestro environment state and maintenance operations

Usage:

```
m3admin maintenance
```

[↑ Back to Table of Contents](#)

Group: m3admin maintenance setting**Description:**

Manages Maintenance environment settings

Usage:

```
m3admin maintenance setting
```

[↑ Back to Table of Contents](#)

Command: m3admin maintenance setting add**Description:**

Sets Maintenance related settings

Usage:

```
m3admin maintenance setting add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin maintenance setting delete**Description:**

Deletes Maintenance related settings

Usage:

```
m3admin maintenance setting delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin maintenance setting describe

Description:

Describes Maintenance related settings

Usage:

```
m3admin maintenance setting describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	Setting key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin maintenance setting update

Description:

Updates Maintenance related settings

Usage:

```
m3admin maintenance setting update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin maintenance check_billing_lock

Description:

Displays billing status

Usage:

```
m3admin maintenance check_billing_lock [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--detailed, -D	flag	X	False	Boolean flag. Provide detailed information by each billing "Lock Type" for each Cloud provider
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin maintenance lock_billing**Description:**

Sets the lock which prevents Maestro Billing Engine to start processing the data

Usage:

```
m3admin maintenance lock_billing [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--hours, -h	integer	X	-	The duration in hours of the billing lock. The maximum billing lock duration can have a value from 1 hour to 72 hours
--expired	string	X	-	The date on which the current billing lock expire. Format: yyyy-mm-dd
--cloud, -c	choice	X	ALL	Cloud provider name on which billing is going to lock. The default value is "ALL". Available choices: AWS, AZURE, AZURE_PARTNER, GOOGLE, PRIVATE, YANDEX, MONGO_ATLAS, ALL
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin maintenance unlock_billing**Description:**

Unlocks m3server billing

Usage:

```
m3admin maintenance unlock_billing [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	ALL	Cloud provider name on which billing is going to unlock. The default value is "ALL". Available choices: AWS, AZURE, AZURE_PARTNER, GOOGLE, PRIVATE, YANDEX, MONGO_ATLAS, ALL
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin maintenance update_maestro_stage_throttling*

Description:

Updates stage throttling values

Usage:

```
m3admin maintenance update_maestro_stage_throttling [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--burst	string	X	-	* The rate at which tokens are added to the Token Bucket
--rate	string	X	-	* The capacity of the Token Bucket
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin notifications**Description:**

[Installable Module] Manages notification settings and configurations

Usage:

```
m3admin notifications
```

[↑ Back to Table of Contents](#)

Group: m3admin notifications setting**Description:**

Manages Notifications environment settings

Usage:

```
m3admin notifications setting
```

[↑ Back to Table of Contents](#)

Command: m3admin notifications setting add**Description:**

Sets Notifications related settings

Usage:

```
m3admin notifications setting add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications setting delete**Description:**

Deletes Notifications related settings

Usage:

```
m3admin notifications setting delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications setting describe

Description:

Describes Notifications related settings

Usage:

```
m3admin notifications setting describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	Setting key
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications setting update

Description:

Updates Notifications related settings

Usage:

```
m3admin notifications setting update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key
--value	string	X	-	* Setting value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications add_group_mapping

Description:

Adds notification group mapping

Usage:

```
m3admin notifications add_group_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--group, -g	string	X	-	* Name of the group mapping
--report, -rp	string	X	-	* Reports that will be added to the group. Multiple values allowed (e.g. --report value1 --report value2)
--overwrite, -O	flag	X	False	Flag, overwrites reports in the group instead of adding
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications add_mail_settings**Description:**

Adds mail settings to DynamoDB/MondoDB

Usage:

```
m3admin notifications add_mail_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--management_mail, -mmail	string	X	-	* Mail address of management team
--consulting_mail, -cmail	string	X	-	* Mail address of consulting team
--from_mail, -fmail	string	X	-	* Mail address that would be used as from email
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications add_receivers_stub**Description:**

Adds receivers stub. Created setting name - NOTIFICATIONS_EMAIL_RECEIVERS_STUB_MAPPING

Usage:

```
m3admin notifications add_receivers_stub [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	Person(s) that will receive the message

Option	Type	Req	Default	Description
--carbon_copy, -cc	string	X	-	E-mail will be copied to one or more recipients. Multiple values allowed (e.g. --carbon_copy value1 --carbon_copy value2)
--blind_carbon_copy, -bcc	string	X	-	E-mail will be copied to one or more recipients, but other recipients do not see these emails. Multiple values allowed (e.g. --blind_carbon_copy value1 --blind_carbon_copy value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications add_subscriber

Description:

Adds notification subscriber(s)

Usage:

```
m3admin notifications add_subscriber [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	* Receiver email
--subscriber, -subs	string	X	-	* Subscriber email. Multiple values allowed (e.g. --subscriber value1 --subscriber value2)
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant name
--notification_group, -ng	string	X	-	Maestro notification group(s) to subscribe to. Multiple values allowed (e.g. --notification_group value1 --notification_group value2)
--expiration, -exp	integer (1 to 365)	X	-	Subscription days expiration
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications configure_bcc

Description:

Defines additional BCC receivers for the given notification

Usage:

```
m3admin notifications configure_bcc [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--notification, -n	string	X	-	* Name of notification
--receiver, -to	string	X	-	Receiver mail(s). If is not specified remove notification from config. Multiple values allowed (e.g. --receiver value1 --receiver value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications configure_black_list**Description:**

Configures emails black list

Usage:

```
m3admin notifications configure_black_list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Person that will be added to black list
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications configure_customer_notifications**Description:**

Makes notifications enabled or disabled for specified customer

Usage:

```
m3admin notifications configure_customer_notifications [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--action, -a	choice	X	-	* Action with notification. Available choices: enable, disable
--notification, -n	string	X	-	Name of notification(s). Multiple values allowed (e.g. --

Option	Type	Req	Default	Description
				notification value1 –notification value2)
--all_notifications, -A	flag	X	False	Use this flag to apply an action to all available notifications
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications configure_notifications*

Description:

Manages 'NOTIFICATIONS_M3_ENABLED_LIST' and 'NOTIFICATIONS_M3_DISABLED_LIST' settings

Usage:

```
m3admin notifications configure_notifications [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--action, -act	choice	X	-	* Setting selection. Changes will be applied to NOTIFICATIONS_M3_ENABLED_LIST setting if value is 'enable', and to NOTIFICATIONS_M3_DISABLED_LIST setting if value is 'disable'. Available choices: enable, disable
--notification, -n	string	X	-	Required parameter if flag '--clear' not specified. Name of notification(s). Multiple values allowed (e.g. --notification value1 --notification value2)
--remove, -R	flag	X	False	Remove specified notification(s) from setting based on --action parameter
--overwrite, -O	flag	X	False	Replace all values in selected setting with new ones
--clear, -C	flag	X	False	Delete selected setting value based on '--action' parameter. If specified - you can skip '--notification' parameter
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications configure_sender*

Description:

Defines specific 'from' email for given notifications

Usage:

```
m3admin notifications configure_sender [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--sender, -from	string	X	-	* Sender mail. Specified notifications will be send from the given SMTP account
--notification, -n	string	X	-	Name of notification(s). If name is not specified remove sender from config. Multiple values allowed (e.g. –notification value1 –notification value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications delete_customer_notifications**Description:**

Deletes notification for specified customer

Usage:

```
m3admin notifications delete_customer_notifications [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--type	choice	X	-	* Type of notifications which will be deleted. Available choices: enabled, disabled
--notification, -n	string	X	-	Name of notification(s). Multiple values allowed (e.g. –notification value1 –notification value2)
--all_notifications, -A	flag	X	False	Use this flag to delete all notifications
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications delete_group_mapping**Description:**

Removes notification group mapping

Usage:

```
m3admin notifications delete_group_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--group, -g	string	X	-	* Name of the group mapping

Option	Type	Req	Default	Description
--report, -rp	string	X	-	* Reports that will be deleted from the group. Multiple values allowed (e.g. --report value1 --report value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications delete_mail_config

Description:

Removes mail configuration from customer

Usage:

```
m3admin notifications delete_mail_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID to remove mail properties
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications delete_mail_settings

Description:

Deletes mail configuration from DynamoDB/MondoDB

Usage:

```
m3admin notifications delete_mail_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--management_mail, -M	flag	X	False	Flag to delete management emails
--consulting_mail, -C	flag	X	False	Flag to delete consulting emails
--from_mail, -F	flag	X	False	Flag to delete mail address that used as -from- email
--all, -A	flag	X	False	Flag to delete all mail settings at once
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications delete_receivers_stub**Description:**

Deletes receivers stub. Affected setting name - NOTIFICATIONS_EMAIL_RECEIVERS_STUB_MAPPING

Usage:

```
m3admin notifications delete_receivers_stub [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	Deletes person(s) that will receive the message. Multiple values allowed (e.g. --receiver value1 --receiver value2)
--carbon_copy, -cc	string	X	-	Deletes e-mail(s) that will be copied to one or more recipients. Multiple values allowed (e.g. --carbon_copy value1 --carbon_copy value2)
--blind_carbon_copy, -bcc	string	X	-	Deletes e-mail(s) that will be copied to one or more recipients, but other recipients do not see these emails. Multiple values allowed (e.g. --blind_carbon_copy value1 --blind_carbon_copy value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications delete_subscriber**Description:**

Deletes notification subscriber(s)

Usage:

```
m3admin notifications delete_subscriber [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	* Receiver email
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant name
--notification_group, -ng	string	X	-	Maestro notification group(s) to subscribe to. Multiple values allowed (e.g. --notification_group value1 --notification_group value2)
--subscriber, -subs	string	X	-	Subscriber email. Multiple values allowed (e.g. --subscriber value1 --subscriber value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications describe_black_list*

Description:

Describes the email blacklist

Usage:

```
m3admin notifications describe_black_list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	Email of the user
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications describe_customer_notifications*

Description:

Describes notification for specified customer

Usage:

```
m3admin notifications describe_customer_notifications [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications describe_group_mapping*

Description:

Describes notification group mapping

Usage:

```
m3admin notifications describe_group_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--group, -g	string	X	-	Name of the group mapping. (multiple). Multiple values allowed (e.g. --group value1 --group value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications describe_mail_config**Description:**

Describes mail configuration of a customer

Usage:

```
m3admin notifications describe_mail_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID to describe mail properties
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications describe_mail_settings**Description:**

Describes mail settings in DynamoDB/MondoDB

Usage:

```
m3admin notifications describe_mail_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications describe_notification_group**Description:**

Describes notification group

Usage:

```
m3admin notifications describe_notification_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--notification_group, -ng	string	X	-	Maestro notification group
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications describe_receivers_stub*

Description:

Describes receivers stub from setting NOTIFICATIONS_EMAIL_RECEIVERS_STUB_MAPPING

Usage:

```
m3admin notifications describe_receivers_stub [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications describe_subscriptions*

Description:

Describes notifications subscriptions

Usage:

```
m3admin notifications describe_subscriptions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	* Receiver email
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant name
--notification_group, -ng	string	X	-	Maestro notification group(s) to subscribe to. Multiple values allowed (e.g. --notification_group value1 –

Option	Type	Req	Default	Description
				notification_group value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications get_customer_dls

Description:

Gets receiver DLs for the specified customer

Usage:

```
m3admin notifications get_customer_dls [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications set_customer_dls

Description:

Sets receiver DLs for the specified customer

Usage:

```
m3admin notifications set_customer_dls [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--consulting_address, -ca	string	X	-	* Consulting address
--support_l15, -sl15	string	X	-	* Support L1.5 address
--support_l2, -sl2	string	X	-	* Support L2 address
--support_l3, -sl3	string	X	-	* Support L3 address
--support_hybrid_l2, -shl2	string	X	-	* Support Hybrid L2 address
--security_address, -sa	string	X	-	* Security address
--security_infrastructure_addresses, -sia	string	X	-	* Security Infrastructure address

Option	Type	Req	Default	Description
--support_auto_esp, -sae	string	X	-	* Security auto ESP address
--wft_vulnerability_management, -wlm	string	X	-	* WFT vulnerability management address
--financial_department_address, -fda	string	X	-	* Cloud radar reporting address
--cloud_support_address, -csa	string	X	-	* Cloud support address
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications set_mail_config

Description:

Updates mail configuration for customer

Usage:

```
m3admin notifications set_mail_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID to update properties for
--subject_template, -st	string	X	-	Name of the email subject template
--header_template, -ht	string	X	-	Name of the email header template
--footer_template, -ft	string	X	-	Name of the email footer template
--icon_link	string	X	-	Name of the icon applied to the letters
--consulting_address	string	X	-	Email address of consulting team applicable for the customer
--orchestrator_url, -ourl	string	X	-	Environment redirect uri
--cli_section_mode, -climode	choice	X	-	Mode in which CLI tips are added to emails. Available choices: DEFAULT, DYNAMIC, SKIP
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications subscribe

Description:

Subscribes notification group

Usage:

```
m3admin notifications subscribe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	* Receiver email
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant name
--notification_group, -ng	string	X	-	Maestro notification group(s) to subscribe to. Multiple values allowed (e.g. --notification_group value1 --notification_group value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications unset_customer_dls

Description:

Removes receiver DLs from the specified customer

Usage:

```
m3admin notifications unset_customer_dls [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications unsubscribe

Description:

Unsubscribes notification group

Usage:

```
m3admin notifications unsubscribe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	* Receiver email
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant name
--notification_group, -ng	string	X	-	Maestro notification group(s) to subscribe to. Multiple values allowed (e.g. --notification_group value1 – notification_group value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications update_mail_settings*

Description:

Updates mail settings in DynamoDB/MondoDB

Usage:

```
m3admin notifications update_mail_settings [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--management_mail, -mmail	string	X	-	Mail address of management team
--consulting_mail, -cmail	string	X	-	Mail address of consulting team
--from_mail, -fmail	string	X	-	Mail address that would be used as from email
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin notifications update_receivers_stub*

Description:

Updates or overwrites receivers stub. Affected setting name - NOTIFICATIONS_EMAIL_RECEIVERS_STUB_MAPPING

Usage:

```
m3admin notifications update_receivers_stub [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	Person(s) that will receive the message

Option	Type	Req	Default	Description
--carbon_copy, -cc	string	X	-	E-mail will be copied to one or more recipients. Multiple values allowed (e.g. --carbon_copy value1 --carbon_copy value2)
--blind_carbon_copy, -bcc	string	X	-	E-mail will be copied to one or more recipients, but other recipients do not see these emails. Multiple values allowed (e.g. --blind_carbon_copy value1 --blind_carbon_copy value2)
--overwrite, -O	flag	X	False	Overwrites values in setting instead of updating
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin notifications update_subscriber

Description:

Updates notification subscriber(s)

Usage:

```
m3admin notifications update_subscriber [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--receiver, -to	string	X	-	* Receiver email
--cloud, -c	choice	X	-	Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--tenant, -tn	string	X	-	Tenant name
--notification_group, -ng	string	X	-	Maestro notification group(s) to subscribe to. Multiple values allowed (e.g. --notification_group value1 --notification_group value2)
--subscriber, -subs	string	X	-	Subscriber email. Multiple values allowed (e.g. --subscriber value1 --subscriber value2)
--expiration, -exp	integer (1 to 365)	X	-	Subscription days expiration
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin nutanix**Description:**

Manages nutanix-related resources

Usage:

```
m3admin nutanix
```

[↑ Back to Table of Contents](#)

Command: m3admin nutanix activate**Description:**

Activates Maestro Tenant

Usage:

```
m3admin nutanix activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd".
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute.. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE. Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin nutanix activate_region**Description:**

Activates Nutanix region in tenant

Usage:

```
m3admin nutanix activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin nutanix add_image*

Description:

Registers Nutanix Image in Maestro. Note: this command should be used after Nutanix Tenant registered

Usage:

```
m3admin nutanix add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--image_id, -iid	string	X	-	* Id of the image
--description, -d	string	X	-	* Description of the image
--image_os, -ios	string	X	-	* Operation system of image
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag "--all_regions" is specified)
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin nutanix deactivate*

Description:

Deactivates Nutanix tenant

Usage:

```
m3admin nutanix deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name

Option	Type	Req	Default	Description
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: “yyyy-mm-dd hh”.
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin nutanix delete_image*

Description:

Deletes a Nutanix Image

Usage:

```
m3admin nutanix delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions
--cloud, -c	string	X	NUTANIX	Cloud provider. Default is NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin nutanix describe_image*

Description:

Describes Nutanix Images in a tenant in the specified region

Usage:

```
m3admin nutanix describe_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--region, -r	string	X	-	* Image region
--alias	string	X	-	Alias for the image
--unlinked, -U	flag	X	False	Specify to list images that do not linked to tenants
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Group: m3admin openstack**Description:**

Manages OPENSTACK-related resources

Usage:

```
m3admin openstack
```

[↑ Back to Table of Contents](#)

Command: m3admin openstack activate**Description:**

Activates OPENSTACK tenant

Usage:

```
m3admin openstack activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE. Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin openstack activate_region**Description:**

Activates OPENSTACK region in tenant

Usage:

```
m3admin openstack activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin openstack add_image*

Description:

Registers OPENSTACK Image in Maestro. Note: this command should be used after OPENSTACK Tenant registered

Usage:

```
m3admin openstack add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--image_id, -iid	string	X	-	* Id of the image
--description, -d	string	X	-	* Description of the image
--image_os, -ios	string	X	-	* Operation system of image
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag "--all_regions" is specified)
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin openstack add_parameters_to_region*

Description:

Adds parameters to OPENSTACK region

Usage:

```
m3admin openstack add_parameters_to_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Name of region to be populated

Option	Type	Req	Default	Description
--exchange, -exc	string	X	-	* Name of rabbit exchange used for m3-sdk integration with private cloud
--sync_request_queue	string	X	-	* Name of rabbit queue used for m3-sdk sync requests
--async_request_queue	string	X	-	* Name of rabbit queue used for m3-sdk async requests
--sdk_access_key, -skey	string	X	-	* Name of sdk key used for m3-sdk integration with private-agent
--response_queue	string	X	-	* Name of rabbit queue used for receiving responses from private-agent
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin openstack add_public_image

Description:

Registers OPENSTACK public image in Maestro

Usage:

```
m3admin openstack add_public_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Image name
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag “--all_regions” is specified)
--description, -d	string	X	-	* Image description
--group, -g	choice	X	-	* Image group: [PUBLIC, ENTERPRISE]. Available choices: PUBLIC, ENTERPRISE
--default_ssh_user	string	X	-	* Default SSH user
--os_type, -os	choice	X	-	* Type of operating system: [WINDOWS, LINUX]. Required with description-template. Available choices: WINDOWS, LINUX
--openstack_image_id, -oid	string	X	-	OPENSTACK image ID
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--all_regions, -A	flag	X	False	All regions
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin openstack add_region_metrics**Description:**

Adds API metrics to the OPENSTACK region

Usage:

```
m3admin openstack add_region_metrics [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Activated region name where to save metrics
--tenant, -tn	string	X	-	Display tenant name
--username, -u	string	X	-	* Username
--project, -prj	string	X	-	* Name of the project
--password, -pwd	string	X	-	* Password
--auth_url, -aurl	string	X	-	* Authentication URL
--source_time_zone, -zone	string	X	-	* Time zone
--tenant_domain, -tnd	string	X	-	* Tenant domain name
--metrics_url, -murl	string	X	-	* Metrics URL
--project_id, -pid	string	X	-	* Id of the OPENSTACK project
--user_domain, -ud	string	X	-	* User domain name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin openstack deactivate**Description:**

Deactivates OPENSTACK tenant

Usage:

```
m3admin openstack deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin openstack delete_image*

Description:

Deletes a OPENSTACK Image

Usage:

```
m3admin openstack delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions
--cloud, -c	string	X	OPEN_STACK	Cloud provider. Default is OPEN_STACK
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin openstack delete_region_metrics*

Description:

Deletes API metrics from the OPENSTACK region

Usage:

```
m3admin openstack delete_region_metrics [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Activated region name from where to delete metrics
--tenant, -tn	string	X	-	Display tenant name

[↑ Back to Table of Contents](#)

Command: *m3admin openstack describe_image*

Description:

Describes OPENSTACK Images in a tenant in the specified region

Usage:

```
m3admin openstack describe_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--region, -r	string	X	-	* Image region
--alias	string	X	-	Alias for the image
--unlinked, -U	flag	X	False	Specify to list images that do not linked to tenants
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin openstack describe_region_metrics*

Description:

Describes API metrics from the OPENSTACK region

Usage:

```
m3admin openstack describe_region_metrics [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Activated region name where metrics are stored
--tenant, -tn	string	X	-	* Display tenant name

[↑ Back to Table of Contents](#)

Command: *m3admin openstack reset_vm_counters*

Description:

Resets counters values if they don't correspond to real instances quantity

Usage:

```
m3admin openstack reset_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin openstack update_region_metrics*

Description:

Updates API metrics for the OPENSTACK region

Usage:

```
m3admin openstack update_region_metrics [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Activated region name where to save metrics
--tenant, -tn	string	X	-	Display tenant name
--username, -u	string	X	-	Username
--project, -prj	string	X	-	Name of the project
--password, -pwd	string	X	-	Password
--auth_url, -aurl	string	X	-	Authentication URL
--source_time_zone, -zone	string	X	-	Time zone
--tenant_domain, -tnd	string	X	-	Tenant domain name
--metrics_url, -murl	string	X	-	Metrics URL
--project_id, -pid	string	X	-	Id of the OPENSTACK project
--user_domain, -ud	string	X	-	User domain name

[↑ Back to Table of Contents](#)

Command: *m3admin openstack validate_vm_counters*

Description:

Checks if counters values corresponds to real instances quantity

Usage:

```
m3admin openstack validate_vm_counters [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin paas**Description:**

Manages PaaS-related resources

Usage:

```
m3admin paas
```

[↑ Back to Table of Contents](#)

Group: m3admin paas configuration**Description:**

Manages the configuration for the auto-configuration script bucket

Usage:

```
m3admin paas configuration
```

[↑ Back to Table of Contents](#)

Command: m3admin paas configuration add**Description:**

Adds the configuration for the ACS bucket and creates bucket

Usage:

```
m3admin paas configuration add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket, -b	string	X	-	* Autoconfiguration bucket name
--chef_version	string	X	-	* Current chef version
--chef_env	string	X	-	* Chef environment
--chef_enabled, -C	flag	X	False	* Marks chef as enabled
--region, -r	string	X	-	* Region for creation init script storage url
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas configuration delete**Description:**

Deletes the existed ACS configuration

Usage:

```
m3admin paas configuration delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas configuration describe**Description:**

Describes the configuration for the ACS bucket

Usage:

```
m3admin paas configuration describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas configuration update**Description:**

Updates the ACS configuration and the ACS bucket

Usage:

```
m3admin paas configuration update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket, -b	string	X	-	* Autoconfiguration bucket name
--region, -r	string	X	-	* Region for creation init script storage url
--chef_version	string	X	-	Current chef version
--chef_env	string	X	-	Chef environment
--chef_enabled, -C	flag	X	False	Marks chef as enabled
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas add_service_support**Description:**

Registers service support

Usage:`m3admin paas add_service_support [OPTIONS]`**Options:**

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service
--support_title, -title	string	X	-	* Support title
--support_value, -value	string	X	-	* Support value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin paas add_service_usage****Description:**

Registers service usage

Usage:`m3admin paas add_service_usage [OPTIONS]`**Options:**

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service
--usage_title, -title	string	X	-	* Usage title
--usage_value, -value	string	X	-	* Usage value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: m3admin paas delete_init_script****Description:**

Removes auto-configuration init script

Usage:`m3admin paas delete_init_script [OPTIONS]`

Options:

Option	Type	Req	Default	Description
--os_type, -os	choice	X	-	* OS type name. Available choices: WINDOWS, LINUX
--cloud, -c	choice	X	-	Cloud name. Multiple values allowed (e.g. --cloud value1 --cloud value2). Available choices: ALL, AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas delete_service**Description:**

Removes service configuration

Usage:

```
m3admin paas delete_service [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service to remove
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas delete_service_parameter**Description:**

Removes service parameters

Usage:

```
m3admin paas delete_service_parameter [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service to remove
--parameter, -param	string	X	-	* Name of the parameter for the service
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin paas describe_init_script*

Description:

Describes auto-configuration init script

Usage:

```
m3admin paas describe_init_script [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--os_type, -os	choice	X	-	* OS type name. Available choices: WINDOWS, LINUX
--cloud, -c	choice	X	-	Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin paas describe_service*

Description:

Describes service configuration

Usage:

```
m3admin paas describe_service [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service to register
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin paas describe_service_parameter*

Description:

Describes service parameters

Usage:

```
m3admin paas describe_service_parameter [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	Name of the service to register
--parameter, -param	string	X	-	* Name of the parameter for the service
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin paas register_service**Description:**

Registers service configuration

Usage:

```
m3admin paas register_service [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service to register
--operating_system, -os	string	X	-	* Name of the operation system
--product_version, -v	string	X	-	* Version of the service
--title, -ti	string	X	-	* Official name of the service
--delivery_method, -dm	string	X	-	* The type of delivery
--category, -cat	string	X	-	Names of the categories. Can be used as multiple. Multiple values allowed (e.g. --category value1 --category value2)
--template_path, -tpath	string	X	-	* Path to the service template file
--icon_path, -ipath	string	X	-	* Path to the service icon file. The image extension should be .png. The size of the image should be: width=186px, height=129px
--discoverable_url, -durl	string	X	-	* URL to discover the service
--service_databag_item, -sdi	string	X	-	* Name of the service databag item
--provider_version, -t	string	X	-	Provider version
--description, -d	string	X	-	Description of the service to register
--summary_description, -sdes	string	X	-	Summary description
--price, -p	string	X	-	Price
--support_proxy, -S	flag	X	False	Flag. Should be specified if the service supports proxy

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin paas register_service_parameter*

Description:

Registers service parameters

Usage:

```
m3admin paas register_service_parameter [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service to register
--parameter, -param	string	X	-	* Name of the parameter for the service
--description, -d	string	X	-	Description of the parameter to register
--default_value, -def	string	X	-	The default value for the parameter
--required, -R	flag	X	False	Flag. Should be specified if the parameter is required
--secure, -S	flag	X	False	Flag. Should be specified if the parameter is secure
--read_only, -O	flag	X	False	Flag. Should be specified if the parameter is read_only
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin paas update_service*

Description:

Updates service configuration

Usage:

```
m3admin paas update_service [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--service, -s	string	X	-	* Name of the service to register
--description, -d	string	X	-	Description of the service to register
--file_path, -fpath	string	X	-	* Path to the service template file
--bucket, -b	string	X	-	Name of the bucket where template will be stored

Option	Type	Req	Default	Description
--terraform_version, -t	string	X	-	Terraform version
--discoverable_url, -durl	string	X	-	URL to discover the service
--service_databag_item, -sdi	string	X	-	Name of the service databag item
--support_proxy, -S	flag	X	False	Flag. Should be specified if the service supports proxy
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin paas upload_init_script*

Description:

Uploads auto-configuration init script

Usage:

```
m3admin paas upload_init_script [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--os_type, -os	choice	X	-	* OS type name. Available choices: WINDOWS, LINUX
--cloud, -c	choice	X	-	* Cloud name. Multiple values allowed (e.g. --cloud value1 --cloud value2). Available choices: ALL, AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--file_path, -fpath	string	X	-	* Path to the auto-configuration init script
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin patch**Description:**

Manages patch-related commands

Usage:

```
m3admin patch
```

[↑ Back to Table of Contents](#)

Command: m3admin patch patch_database**Description:**

Command that invokes script(s) for patching DynamoDB. If patch versions are not specified - it will automatically execute patches that are actual.

Usage:

```
m3admin patch patch_database [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--from_version, -minv	string	X	-	Number of the first script in range for patch
--to_version, -maxv	string	X	-	Number of the last script in range for patch. If not specified: all scripts after -f version will be executed.
--path	string	X	-	* Path to the folder that contains patch scripts. Default value: ~/.m3admin/patch_scripts
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin permissions**Description:**

[Installable Module] Manages user permissions and access control

Usage:

```
m3admin permissions
```

[↑ Back to Table of Contents](#)

Group: m3admin permissions setting**Description:**

Manages Permission environment settings

Usage:

```
m3admin permissions setting
```

[↑ Back to Table of Contents](#)

Command: m3admin permissions setting add**Description:**

Sets Permission related settings

Usage:

```
m3admin permissions setting add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key name
--value	string	X	-	* Setting value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions setting delete**Description:**

Deletes Permission related settings

Usage:

```
m3admin permissions setting delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key name

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions setting describe

Description:

Describes Permission related settings

Usage:

```
m3admin permissions setting describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	Setting key name. If not specified - all Permissions related settings will be described
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions setting update

Description:

Sets Permission related settings

Usage:

```
m3admin permissions setting update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key	string	X	-	* Setting key name
--value	string	X	-	* Setting value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions add_console_service_mapping

Description:

Adds service to permission mapping

Usage:

```
m3admin permissions add_console_service_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--mapping_id, -mid	string	X	-	* Permission mapping id
--service_id, -sid	string	X	-	* Console service id
--policy	string	X	[]	Native policies. Multiple values allowed (e.g. --policy value1 --policy value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions add_group**Description:**

Adds group for customer

Usage:

```
m3admin permissions add_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Permission group name
--description, -d	string	X	-	Permission group description
--group_type, -gtype	choice	X	ALLOW	Permission type. Available choices: ALLOW, DENY
--customer_id, -cid	string	X	-	* Customer ID
--operation, -op	string	X	-	* Operation name. For several operation repeat the parameter. Multiple values allowed (e.g. --operation value1 --operation value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions add_position_to_tenant**Description:**

Adds position of user to tenant Receives tenant name, list of positions and flag if positions should be overwritten

Usage:

```
m3admin permissions add_position_to_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	string	X	-	* Cloud name
--position, -p	string	X	-	* Position. Multiple values allowed (e.g. --position value1 --position value2)
--overwrite, -O	flag	X	False	Overwrite
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions add_user***Description:**

Adds user(s) to the Maestro whitelist for the specified customer

Usage:

```
m3admin permissions add_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Email of the user
--customer_id, -cid	string	X	-	* Customer ID
--api_rate_limit, -arl	integer (60 to 120000)	X	6000	API rate limit, min=60, max=120000, default=6000
--activation, -act	string	X	-	Date of activation. Format "yyyy-mm-dd"
--expiration, -exp	string	X	-	Date of expiration. Format "yyyy-mm-dd"
--api, -a	flag	X	False	Mark the user as an API user
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions assign_position***Description:**

Assigns user to the project

Usage:

```
m3admin permissions assign_position [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* User email address
--tenant, -tn	string	X	-	* General tenant name
--position, -p	string	X	-	* Position that would be added to the user. Multiple values allowed (e.g. --position value1 --position value2)
--reason, -rsn	string	X	-	* The reason of position is set to the user
--expiration_date, -edate	string	X	-	Permission expiration date. If not specified - unlimited expiration date will be set. Valid date format: [yyyy-MM-dd]
--force, -F	flag	X	False	The flag to confirm setting of expiration_date
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions block_user**Description:**

Blocks the user - set in attribute 'b' of Users collection "true"

Usage:

```
m3admin permissions block_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* User email address
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions delete_console_service_mapping**Description:**

Deletes service from permission mapping

Usage:

```
m3admin permissions delete_console_service_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--mapping_id, -mid	string	X	-	* Permission mapping id

Option	Type	Req	Default	Description
--service_id, -sid	string	X	-	* Console service id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions delete_group*

Description:

Removes the permission group

Usage:

```
m3admin permissions delete_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Permission group name. Multiple values allowed (e.g. –group value1 –group value2)
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions delete_mapping*

Description:

Deletes existing mapping(s) from PermissionGroupMappings collection. Parameters list depending on –permission_mapping_type value:

- 1) CUSTOMER: — ;
- 2) TENANT: –tenant [required];
- 3) CLOUD: –cloud [required];
- 4) USER: –tenant [required] –email [required];
- 5) POSITION: –position [required] –tenant [optional] –permission_group [optional] –expiration_date [optional];

Usage:

```
m3admin permissions delete_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--permission_mapping_type, -	choice	X	-	* Permission mapping type. Available choices:

Option	Type	Req	Default	Description
pmt				CUSTOMER, TENANT, CLOUD, USER, POSITION
--customer_id, -cid	string	X	-	* Customer ID
--permission_env, -pe	choice	X	-	* Environment for specified permissions mapping by customer. Multiple values allowed (e.g. --permission_env value1 --permission_env value2). Available choices: M3_SDK, M3_UI, AWS_CONSOLE, AZURE_CONSOLE, GOOGLE_CONSOLE
--tenant, -tn	string	X	-	General tenant name
--cloud, -c	choice	X	-	Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--email, -e	string	X	-	User email
--position, -p	string	X	-	User Position
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions delete_position_from_tenant*

Description:

Removes positions from tenant Receives tenant name, list of positions and flag if all the positions should be removed

Usage:

```
m3admin permissions delete_position_from_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	string	X	-	* Cloud name
--tenant, -tn	string	X	-	* Tenant display name
--position, -p	string	X	-	Position. Multiple values allowed (e.g. --position value1 --position value2). Should be specified if not "--remove_all/-R flag passed"
--remove_all, -R	flag	X	False	Remove all positions from tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions delete_title_position_mapping*

Description:

Removes the PMC mapping

Usage:

```
m3admin permissions delete_title_position_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	EPAM Systems	Customer ID. Default: EPAM Systems
--role_id, -rid	string	X	-	* Project roles. Can be used as multiple parameter (--role_id Role1, --role_id Role2)
--project	string	X	-	Project abbreviation in EPAM Cloud
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions delete_user

Description:

Deletes user from Maestro white list

Usage:

```
m3admin permissions delete_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Email of the user
--customer_id, -cid	string	X	-	* Customer ID
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions delete_user_auth_password

Description:

Disables user access to m3 via email and password

Usage:

```
m3admin permissions delete_user_auth_password [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--email, -e	string	X	-	* User email
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions describe_available_positions*

Description:

Describe available positions from tenant or from customer. Describing from tenant - If no positions set in tenant, then tenant customer positions will be listed. Describing from customer - listing positions assigned to customer from PermissionGroupMappings collection

Usage:

```
m3admin permissions describe_available_positions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant general name. Required if customer id not specified
--customer_id, -cid	string	X	-	Customer ID. Required if tenant not specified
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions describe_blocked_user_config*

Description:

Describes user from the environment black list, setting name: "PERMISSIONS_BLOCKED_USERS_LIST"

Usage:

```
m3admin permissions describe_blocked_user_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions describe_group**Description:**

Gets info about permission group

Usage:

```
m3admin permissions describe_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--name	string	X	-	Permission group name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions describe_mapping**Description:**

Describes existing mapping from PermissionGroupMappings collection by filters. Despite the fact that all parameters are marked as optional, the user should select at least 1 of them.

It is highly recommended to use the --mapping_id parameter or --customer_id parameter with/without filters to prevent unnecessary scans

Usage:

```
m3admin permissions describe_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--mapping_id, -mid	string	X	-	Mapping ID. If specified - any filter has no effect on query result
--customer_id, -cid	string	X	-	Filter report by customer ID
--tenant, -tn	string	X	-	Filter report by general tenant name
--cloud, -c	string	X	-	Filter report by cloud name
--tenant_group, -tg	string	X	-	Filter report by tenants group name
--position, -p	string	X	-	Filter report by position name
--user, -u	string	X	-	Filter report by user name
--console_mapping, -cm	choice	X	-	Available choices: AWS, AZURE, GOOGLE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions describe_title_position_mapping*

Description:

Describes the PMC mapping

Usage:

```
m3admin permissions describe_title_position_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	EPAM Systems	Customer ID. Default: EPAM Systems
--tenant, -tn	string	X	-	Tenant general name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions describe_user*

Description:

Describes Maestro users. One of the optional parameters email or customer_id should be specified

Usage:

```
m3admin permissions describe_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	Email of the user
--customer_id, -cid	string	X	-	Customer ID
--tenant, -tn	string	X	-	Tenant general name. Filter result by specified name. Parameter should be passed with email or with customer value
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions describe_user_permissions*

Description:

Describes all permission groups assigned to user in the specified tenant

Usage:

```
m3admin permissions describe_user_permissions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--email, -e	string	X	-	* User email address
--environment, -env	choice	X	-	* Maestro environment. Available choices: M3_UI, M3_SDK, AWS_CONSOLE, GOOGLE_CONSOLE, AZURE_CONSOLE
--tenant, -tn	string	X	-	* Tenant name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions get_blocked_user**Description:**

Describes all users with blocked state or describe specified user state

Usage:

```
m3admin permissions get_blocked_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	User email address
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions set_blocked_user_config**Description:**

Adds/Deletes users to/from the environment black list. Modifies setting "PERMISSIONS_BLOCKED_USERS_LIST"

Usage:

```
m3admin permissions set_blocked_user_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--email, -e	string	X	-	* Blocked users emails. Multiple values allowed (e.g. –email value1 –email value2)
--action, -act	choice	X	-	Action type. ADD - for adding user email to the black list, DELETE - for removing. Available choices: ADD, DELETE
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions set_console_mapping*

Description:

Adds cloud console permissions group mapping into PermissionGroupMappings collection. If the user specify –permission_group parameter than old values will be replaced with new ones.

Parameters list depending on –permission_mapping_type value:

- 1) CUSTOMER: –permission_group [optional] –expiration_date[optional];
- 2) TENANT: –tenant [required], –permission_group [optional] –expiration_date[optional];
- 3) CLOUD: –cloud [required] –permission_group [optional] –expiration_date[optional];
- 4) USER: –tenant [required] –email [required] –permission_group [optional] –expiration_date[optional];
- 5) POSITION: –position [required] –tenant [optional] –permission_group [optional] –expiration_date[optional];

Usage:

```
m3admin permissions set_console_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--permission_mapping_type, -pmt	choice	X	-	* Permission mapping type. Available choices: CUSTOMER, TENANT, CLOUD, USER, POSITION
--customer_id, -cid	string	X	-	* Customer ID
--permission_env, -pe	choice	X	-	* Type of permission environment. Available choices: AWS, AZURE, GOOGLE
--default_role, -dr	string	X	-	* Name of cloud console access default role
--tenant, -tn	string	X	-	General tenant name
--cloud, -c	choice	X	-	Cloud name. Available choices: AWS, AZURE, GOOGLE
--email, -e	string	X	-	User email
--position, -p	string	X	-	User Position
--permission_group, -pg	string	X	-	Permission group name. Old values will be replaced by new ones. Multiple values allowed (e.g. –permission_group value1 –permission_group value2)

Option	Type	Req	Default	Description
--expiration_date, -edate	string	X	-	Permission group mapping expiration date. Format “yyyy-mm-dd”
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions set_mapping

Description:

Adds permissions group mapping into PermissionGroupMappings collection. If the user specify --permission_group parameter than old values will be replaced with new ones.

Parameters list depending on --permission_mapping_type value:

- 1) CUSTOMER: --permission_group [optional] --scope[optional] --expiration_date[optional];
- 2) TENANT: --tenant [required], --permission_group [optional] --scope[optional] --expiration_date[optional];
- 3) CLOUD: --cloud [required], --permission_group [optional] --expiration_date[optional];
- 4) USER: --email [required] --tenant [optional] --permission_group [optional] --scope[optional] --expiration_date[optional];
- 5) POSITION: --position [required] --tenant [optional] --permission_group [optional] --expiration_date[optional];

If the user specify --scope USER, parameter ‘email’ becomes required

Usage:

```
m3admin permissions set_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--permission_mapping_type, -pmt	choice	X	-	* Permission mapping type. Available choices: CUSTOMER, TENANT, CLOUD, USER, POSITION
--customer_id, -cid	string	X	-	* Customer ID
--permission_env, -pe	choice	X	-	* Type of permission environment. Multiple values allowed: --permission_env SDK --permission_env UI. Available choices: SDK, UI
--tenant, -tn	string	X	-	General tenant name
--cloud, -c	choice	X	-	Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--scope, -s	choice	X	-	Permission mapping scope. Available choices: TENANT, USER, CUSTOMER
--email, -e	string	X	-	User email
--position, -p	string	X	-	User position
--permission_group, -pg	string	X	-	Permission group name. Old values will be replaced by

Option	Type	Req	Default	Description
				new ones. Multiple values allowed (e.g. –permission_group value1 –permission_group value2)
--expiration_date, -edate	string	X	-	Permission group mapping expiration date. Format “yyyy-mm-dd”
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions set_tenant_position_status

Description:

Sets status to positions of tenant Receives tenant name, list of positions, status and flag if status should be applied to all the positions

Usage:

```
m3admin permissions set_tenant_position_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	string	X	-	* Cloud name
--position, -p	string	X	-	Position. Multiple values allowed (e.g. –position value1 –position value2)
--position_status	choice	X	-	* Tenant position status. Available choices: enabled, disabled
--set_all, -S	flag	X	False	Overwrite
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions set_title_position_mapping

Description:

Sets title position mapping

Usage:

```
m3admin permissions set_title_position_mapping [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	EPAM	Customer ID. Default: EPAM Systems

Option	Type	Req	Default	Description
			Systems	
--role_id, -rid	string	X	-	* Project roles. Can be used as multiple parameter (--role Role1, --role Role2)
--group, -g	string	X	-	* Permission group name. For several groups repeat the parameter
--project	string	X	-	Project abbreviation in EPAM Cloud
--expiration_date, -edate	string	X	-	Permission expiration date. Valid date format: [yyyy-MM-dd]
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions set_user_auth_password*

Description:

Configures access to m3 via email and password

Usage:

```
m3admin permissions set_user_auth_password [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* User email
--password, -pwd	string	X	-	* Password
--username, -u	string	X	-	User name
--override, -O	flag	X	False	Override existing password for user
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin permissions unassign_position*

Description:

Unassigns user from the tenant

Usage:

```
m3admin permissions unassign_position [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--email, -e	string	X	-	* User email address
--tenant, -tn	string	X	-	* Tenant name
--position, -p	string	X	-	Position that will be removed from the user. Multiple values allowed (e.g. --position value1 --position value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions unblock_user

Description:

Unblocks the user - set in attribute 'b' of Users collection "false"

Usage:

```
m3admin permissions unblock_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--email, -e	string	X	-	* User email address
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin permissions update_group

Description:

Updates group for customer

Usage:

```
m3admin permissions update_group [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name	string	X	-	* Permission group name
--description, -d	string	X	-	Permission group description
--customer_id, -cid	string	X	-	* Customer ID
--operation, -op	string	X	[]	Operation name. For several operation repeat the parameter. Multiple values allowed (e.g. --operation value1 --operation value2). If not --operation parameter specified empty list will be set

Option	Type	Req	Default	Description
--override, -O	flag	X	False	Replace all operations with new ones. If operations were not specified, an empty list will be set
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private**Description:**

[Installable Module] Manages private agent configurations and operations

Usage:

```
m3admin private
```

[↑ Back to Table of Contents](#)

Group: m3admin private nutanix**Description:**

Manages Nutanix resources via private agent

Usage:

```
m3admin private nutanix
```

[↑ Back to Table of Contents](#)

Group: m3admin private nutanix image**Description:**

Manages images in Nutanix tenants

Usage:

```
m3admin private nutanix image
```

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix image create**Description:**

Creates a new image in a Nutanix tenant

Usage:

```
m3admin private nutanix image create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the tenant
--name, -n	string	X	-	* Name of the image
--alias, -a	string	X	-	* Alias for image name
--item_id, -id	string	X	-	* ID of the item associated with the image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix image delete*

Description:

Deletes a Nutanix image from a tenant

Usage:

```
m3admin private nutanix image delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--image_alias, -ialias	string	X	-	* Alias for the Nutanix image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix image get*

Description:

Retrieves details of a specific Nutanix image

Usage:

```
m3admin private nutanix image get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--image_alias, -ialias	string	X	-	* Alias for the Nutanix image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix image list*

Description:

Lists all images in a Nutanix tenant

Usage:

```
m3admin private nutanix image list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private nutanix region**Description:**

Manages Nutanix regions and their management status

Usage:

```
m3admin private nutanix region
```

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix region create**Description:**

Creates a new Nutanix region with cluster and storage configuration

Usage:

```
m3admin private nutanix region create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server	string	X	-	* Name of the server
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--username, -u	string	X	-	* Username
--password, -pwd	string	X	-	* Password
--element_server, -es	string	X	-	* Name of the Element server
--element_username, -eu	string	X	-	* Username for the Element server
--element_password, -epwd	string	X	-	* Password for the Element server
--cluster, -cl	string	X	-	* Name of the cluster
--cluster_uuid, -cuid	string	X	-	* UUID of the cluster
--management, -M	flag	X	False	Flag to indicate if the region is for management purposes
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix region delete*

Description:

Deletes a Nutanix region configuration

Usage:

```
m3admin private nutanix region delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--force, -F	flag	X	False	Force deletion even if there are dependencies
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix region get*

Description:

Retrieves details of a specific Nutanix region

Usage:

```
m3admin private nutanix region get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix region get_management_status*

Description:

Retrieves the management status of a Nutanix region

Usage:

```
m3admin private nutanix region get_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix region list**Description:**

Lists all configured Nutanix regions

Usage:

```
m3admin private nutanix region list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix region set_management_status**Description:**

Sets the management availability status for a Nutanix region

Usage:

```
m3admin private nutanix region set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--available, -A	flag	X	False	Flag to set the region management status to available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private nutanix shape**Description:**

Manages VM shapes in Nutanix regions

Usage:

```
m3admin private nutanix shape
```

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix shape clean**Description:**

Removes all custom VM shapes from a Nutanix region

Usage:

```
m3admin private nutanix shape clean [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix shape list**Description:**

Lists all available VM shapes in a Nutanix region

Usage:

```
m3admin private nutanix shape list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix shape set**Description:**

Creates or updates a VM shape in a Nutanix region

Usage:

```
m3admin private nutanix shape set [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--name	string	X	-	* Name of the shape
--cpu	string	X	-	* Set the number of CPUs for the shape
--memory	string	X	-	* Set the amount of memory in GB for the shape
--storage	string	X	-	* Set the storage size in GB for the shape
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private nutanix tenant**Description:**

Manages Nutanix tenants, their health checks, and management status

Usage:

```
m3admin private nutanix tenant
```

[↑ Back to Table of Contents](#)

Command: m3admin private nutanix tenant create**Description:**

Creates a new tenant in a Nutanix region

Usage:

```
m3admin private nutanix tenant create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant, -tn	string	X	-	* Name of the tenant
--management, -M	flag	X	False	Flag to indicate if the tenant is for management purposes
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix tenant delete***Description:**

Deletes a tenant from a Nutanix region

Usage:

```
m3admin private nutanix tenant delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--force, -F	flag	X	False	Force deletion even if there are dependencies
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix tenant get***Description:**

Retrieves details of a specific Nutanix tenant

Usage:

```
m3admin private nutanix tenant get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix tenant get_health_check_result***Description:**

Retrieves health check results for a Nutanix tenant

Usage:

```
m3admin private nutanix tenant get_health_check_result [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix tenant get_management_status*

Description:

Retrieves the management status of a Nutanix tenant

Usage:

```
m3admin private nutanix tenant get_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix tenant list*

Description:

Lists all tenants in a Nutanix region

Usage:

```
m3admin private nutanix tenant list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private nutanix tenant set_management_status***Description:**

Sets the management availability status for a Nutanix tenant

Usage:

```
m3admin private nutanix tenant set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the Nutanix region
--tenant_alias, -talias	string	X	-	* Alias for the Nutanix tenant
--available, -A	flag	X	False	Flag to set the tenant management status to available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private openstack***Description:**

Manages OPENSTACK resources via private agent

Usage:

```
m3admin private openstack
```

[↑ Back to Table of Contents](#)

Group: *m3admin private openstack image***Description:**

Manages images in OPENSTACK regions

Usage:

```
m3admin private openstack image
```

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack image create***Description:**

Creates a new image configuration in an OPENSTACK region

Usage:

```
m3admin private openstack image create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--name_alias, -nalias	string	X	-	* Alias for the OPENSTACK image name
--platform_type, -ptype	choice	X	-	* Platform type of the OPENSTACK image. Options are "WIN" for Windows, "LINUX" for Linux, or "OTHER" for other platforms. Available choices: LINUX, WIN, OTHER
--image_visibility	choice	X	-	* Visibility of the image. Options are "PUBLIC" or "PRIVATE". Available choices: PUBLIC, PRIVATE
--image_status	string	X	-	* Status of the image
--native_id, -nid	string	X	-	* Native ID of the image in OPENSTACK
--native_name, -nname	string	X	-	* Native name of the image in OPENSTACK
--required_memory, -rm	string	X	-	Required RAM memory for the image in GB
--required_storage, -rs	string	X	-	Required storage for the image in GB
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private openstack image list

Description:

Lists all images in an OPENSTACK region

Usage:

```
m3admin private openstack image list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private openstack projectmeta

Description:

Manages admin project metadata for OPENSTACK regions

Usage:

```
m3admin private openstack projectmeta
```

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack projectmeta add_image***Description:**

Adds an image to the admin project metadata

Usage:

```
m3admin private openstack projectmeta add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--image, -img	string	X	-	* Name of the OPENSTACK image
--platform_type, -ptype	choice	X	-	* Platform type of the OPENSTACK image. Options are "WIN" for Windows, "LINUX" for Linux, or "OTHER" for other platforms. Available choices: LINUX, WIN, OTHER
--memory, -ram	string	X	-	Size of RAM memory in GB
--storage	string	X	-	Size of storage in GB
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack projectmeta create***Description:**

Creates admin project metadata for an OPENSTACK region

Usage:

```
m3admin private openstack projectmeta create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--project_id, -pid	string	X	-	* ID of the OPENSTACK admin project meta
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack projectmeta delete_image***Description:**

Removes an image from the admin project metadata

Usage:

```
m3admin private openstack projectmeta delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack projectmeta get*

Description:

Retrieves admin project metadata for an OPENSTACK region

Usage:

```
m3admin private openstack projectmeta get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private openstack rabbit*

Description:

Manages RabbitMQ configuration for OPENSTACK regions

Usage:

```
m3admin private openstack rabbit
```

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack rabbit get_config*

Description:

Retrieves RabbitMQ configuration for an OPENSTACK region

Usage:

```
m3admin private openstack rabbit get_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack rabbit set_config*

Description:

Configures RabbitMQ connection settings for an OPENSTACK region

Usage:

```
m3admin private openstack rabbit set_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--host	string	X	-	* Hostname or IP address for the RabbitMQ server
--port	string	X	-	* Port number for the RabbitMQ server
--virtual_host, -vhost	string	X	-	* Name of the RabbitMQ virtual host
--username, -u	string	X	-	* Username for RabbitMQ connection
--password, -pwd	string	X	-	* Password for RabbitMQ connection
--reply_timeout, -rtimeout	string	X	-	* Timeout duration for RabbitMQ replies
--shutdown_timeout, -stimeout	string	X	-	* Timeout duration for RabbitMQ shutdown
--min_concurrent	string	X	-	* Minimum number of concurrent connections to RabbitMQ
--max_concurrent	string	X	-	* Maximum number of concurrent connections to RabbitMQ
--nova_exchange, -ne	string	X	-	* Name of the Nova exchange in RabbitMQ
--cinder_exchange, -ce	string	X	-	* Name of the Cinder exchange in RabbitMQ
--glance_exchange, -ge	string	X	-	* Name of the Glance exchange in RabbitMQ
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private openstack region*

Description:

Manages OPENSTACK regions and service tenant configuration

Usage:

```
m3admin private openstack region
```

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack region create***Description:**

Creates a new OPENSTACK region with Keystone configuration

Usage:

```
m3admin private openstack region create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name_alias, -nalias	string	X	-	* Alias for the OPENSTACK region
--region_number, -rnumber	string	X	-	* Unique number identifier for the OPENSTACK region
--server_prefix	string	X	-	* Prefix for the server
--keystone_auth_url, -kurl	string	X	-	* URL for Keystone authorization service
--region, -r	string	X	-	* OPENSTACK region name
--enable_describers, -E	flag	X	False	Flag to enable describers
--server_disk_config	choice	X	-	Disk configuration for the server. Options are "MANUAL" or "AUTO". Available choices: MANUAL, AUTO
--openstack_version	choice	X	-	Version of OPENSTACK. Options are "OCATA" or "OTHER". Available choices: OCATA, OTHER
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack region get***Description:**

Retrieves details of a specific OPENSTACK region

Usage:

```
m3admin private openstack region get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack region get_service_tenant*

Description:

Retrieves the service tenant configuration for an OPENSTACK region

Usage:

```
m3admin private openstack region get_service_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack region list*

Description:

Lists all configured OPENSTACK regions

Usage:

```
m3admin private openstack region list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack region set_management_status*

Description:

Sets the management availability status for an OPENSTACK region

Usage:

```
m3admin private openstack region set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--available, -A	flag	X	False	Flag to mark the region as available

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack region set_service_tenant*

Description:

Configures the service tenant for an OPENSTACK region

Usage:

```
m3admin private openstack region set_service_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--name	string	X	-	* Name of the tenant
--native_id, -nid	string	X	-	* Native ID of the tenant in OPENSTACK
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private openstack security*

Description:

Manages security mode configurations for OPENSTACK regions and tenants

Usage:

```
m3admin private openstack security
```

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack security configure*

Description:

Creates a security mode configuration for an OPENSTACK region

Usage:

```
m3admin private openstack security configure [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* OPENSTACK region alias

Option	Type	Req	Default	Description
--mode_name, -n	string	X	-	* Security mode name
--mode_description, -d	string	X	"	Security mode description
--security_group_id, -sid	string	X	"	The ID of a specific security group within the Admin project
--default, -D	flag	X	False	Should be set in case this configuration should be used by default
--override, -O	flag	X	False	Should be set in case the existing configuration should be overwritten
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack security delete*

Description:

Deletes a security mode configuration from an OPENSTACK region

Usage:

```
m3admin private openstack security delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* OPENSTACK region alias
--mode_name, -n	string	X	-	* Security mode name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack security describe*

Description:

Lists security mode configurations for OPENSTACK regions

Usage:

```
m3admin private openstack security describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	"	OPENSTACK region alias
--mode_name, -n	string	X	"	Security mode name

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack security set_tenant_mode*

Description:

Assigns a security mode to an OPENSTACK tenant

Usage:

```
m3admin private openstack security set_tenant_mode [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* OPENSTACK region alias
--mode_name, -n	string	X	-	* Security mode name
--tenant_alias, -talias	string	X	"	OPENSTACK tenant alias
--current_mode_name, -cmn	string	X	"	Current tenants' security mode name to switch from
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private openstack shape*

Description:

Manages VM shapes in OPENSTACK regions

Usage:

```
m3admin private openstack shape
```

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack shape create*

Description:

Creates a new VM shape in an OPENSTACK region

Usage:

```
m3admin private openstack shape create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--native_id, -nid	string	X	-	* Native ID of the shape in OPENSTACK
--name_alias, -nalias	string	X	-	* Alias for the OPENSTACK shape name
--native_name, -nname	string	X	-	* Native name of the shape in OPENSTACK
--cpu	string	X	-	* Number of CPUs for the shape
--memory	string	X	-	* Size of RAM memory for the shape in GB
--storage	string	X	-	* Size of storage for the shape in GB
--processor_type, -ptype	string	X	-	* Type of processor for the shape
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private openstack shape list

Description:

Lists all available VM shapes in an OPENSTACK region

Usage:

```
m3admin private openstack shape list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private openstack tenant

Description:

Manages OPENSTACK tenants, users, and network configuration

Usage:

```
m3admin private openstack tenant
```

[↑ Back to Table of Contents](#)

Command: m3admin private openstack tenant configure_network

Description:

Configures network settings for an OPENSTACK tenant

Usage:

```
m3admin private openstack tenant configure_network [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--tenant_alias, -talias	string	X	-	* Alias for the OPENSTACK tenant
--gateway_network_id, -gni	string	X	-	* Gateway Network ID for the tenant network
--network_name, -nn	string	X	-	* Name for the created tenant network
--cidr, -c	string	X	172.25.0.0/24	CIDR block to specify IP ranges for the tenant network. Default: 172.25.0.0/24
--gateway_subnet_id, -gsi	string	X	-	Gateway Subnet ID. Must be specified with --gateway_ip_address parameter
--gateway_ip_address, -gia	string	X	-	Gateway IP address. Must be specified with --gateway_subnet_id parameter
--highly_available, -ha	flag	X	False	Flag to set if the network router should be highly available (includes L3 Agent network on router)
--disable_snat, -ds	flag	X	False	Flag to disable Source NAT on the network
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private openstack tenant create**Description:**

Creates a new tenant in an OPENSTACK region

Usage:

```
m3admin private openstack tenant create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--native_id, -nid	string	X	-	* Native ID of the tenant from OPENSTACK
--network_id, -neid	string	X	-	* Network ID associated with the tenant in OPENSTACK
--native_name, -nname	string	X	-	* Native name of the tenant from OPENSTACK
--name_alias, -nalias	string	X	-	* Alias for the tenant
--security_group, -sg	string	X	"	Name of the security group associated with the tenant in OPENSTACK
--security_group_id, -sid	string	X	"	ID of the security group associated with the tenant in OPENSTACK

Option	Type	Req	Default	Description
--security_mode, -sm	string	X	"	Security mode for the tenant
--domain, -dom	string	X	-	Domain associated with the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack tenant create_user*

Description:

Creates a user for an OPENSTACK tenant

Usage:

```
m3admin private openstack tenant create_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--tenant_alias, -talias	string	X	-	* Alias for the OPENSTACK tenant
--name	string	X	-	* Name of the user
--password, -pwd	string	X	-	* Password for the user
--native_id, -nid	string	X	-	* Native ID of the user in OPENSTACK
--domain, -dom	string	X	-	Domain name associated with the user
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack tenant get*

Description:

Retrieves details of a specific OPENSTACK tenant

Usage:

```
m3admin private openstack tenant get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--tenant_alias, -talias	string	X	-	* Alias for the OPENSTACK tenant
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack tenant get_user*

Description:

Retrieves the user configuration for an OPENSTACK tenant

Usage:

```
m3admin private openstack tenant get_user [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--tenant_alias, -talias	string	X	-	* Alias for the OPENSTACK tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack tenant list*

Description:

Lists all tenants in an OPENSTACK region

Usage:

```
m3admin private openstack tenant list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private openstack tenant set_management_status*

Description:

Sets the management availability status for an OPENSTACK tenant

Usage:

```
m3admin private openstack tenant set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--tenant_alias, -talias	string	X	-	* Alias for the OPENSTACK tenant
--available, -A	flag	X	False	Flag to set the tenant as available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private openstack user**Description:**

Manages admin user configuration for OPENSTACK regions

Usage:

```
m3admin private openstack user
```

[↑ Back to Table of Contents](#)

Command: m3admin private openstack user get**Description:**

Retrieves the admin user configuration for an OPENSTACK region

Usage:

```
m3admin private openstack user get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private openstack user set**Description:**

Configures the admin user for an OPENSTACK region

Usage:

```
m3admin private openstack user set [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the OPENSTACK region
--name	string	X	-	* Name of the user
--password, -pwd	string	X	-	* Password for the user
--native_id, -nid	string	X	-	* Native ID of the user in OPENSTACK
--domain, -dom	string	X	-	Domain of the user
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private system**Description:**

Manages by private agent system related resources

Usage:

```
m3admin private system
```

[↑ Back to Table of Contents](#)

Command: m3admin private system register_agent**Description:**

Registers the private agent with the system

Usage:

```
m3admin private system register_agent [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--force, -F	flag	X	False	Force registration of the agent even if it is already registered
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private system set_tenant_describer_mode**Description:**

Sets the describer mode for a tenant (ALL or OUR resources)

Usage:

```
m3admin private system set_tenant_describer_mode [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the region
--tenant_alias, -talias	string	X	-	* Alias for the tenant
--mode	choice	X	-	Mode for tenant describer. Options are “ALL” or “OUR”. Available choices: ALL, OUR
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private system sync_private_images**Description:**

Synchronizes private images across the system

Usage:

```
m3admin private system sync_private_images [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--force, -F	flag	X	False	Force synchronization of private images even if there are conflicts
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware**Description:**

Manages VMware resources via private agent

Usage:

```
m3admin private vmware
```

[↑ Back to Table of Contents](#)

Group: m3admin private vmware organization**Description:**

Manages VMware organizations and tenant linkage

Usage:

```
m3admin private vmware organization
```

[↑ Back to Table of Contents](#)

Command: m3admin private vmware organization create

Description:

Creates a new VMware organization in the specified VMware region

Usage:

```
m3admin private vmware organization create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--alias, -a	string	X	-	* Alias for the organization
--username, -u	string	X	-	* Username for the organization
--password, -pwd	string	X	-	* Password for the organization
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware organization delete

Description:

Deletes a VMware organization by its UUID in the specified VMware region

Usage:

```
m3admin private vmware organization delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--id, -id	string	X	-	* UUID of the organization to delete
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware organization get

Description:

Retrieves VMware organizations filtered by region alias or organization alias

Usage:

```
m3admin private vmware organization get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	Alias for the VMware region (returns list by region)
--alias, -a	string	X	-	Alias of the organization (returns singleton list)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware organization link**Description:**

Links a VMware organization to a tenant in the specified VMware region

Usage:

```
m3admin private vmware organization link [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--organization_alias, -oa	string	X	-	* Alias of the organization to link
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware organization unlink**Description:**

Unlinks a VMware organization from a tenant in the specified VMware region

Usage:

```
m3admin private vmware organization unlink [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	Alias of the tenant (unlink by tenant)

Option	Type	Req	Default	Description
--organization_alias, -oa	string	X	-	Alias of the organization (unlink by organization)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware organization update

Description:

Updates an existing VMware organization in the specified VMware region

Usage:

```
m3admin private vmware organization update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--alias, -a	string	X	-	* Current alias of the organization to update
--new_alias, -na	string	X	-	New alias for the organization
--username, -u	string	X	-	New username for the organization
--password, -pwd	string	X	-	New password for the organization
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware quota

Description:

Manages resource quotas for VMware tenants

Usage:

```
m3admin private vmware quota
```

[↑ Back to Table of Contents](#)

Command: m3admin private vmware quota create

Description:

Creates a resource quota for a tenant in the specified VMware region

Usage:

```
m3admin private vmware quota create [OPTIONS]
```


Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--max_cpu_count, -cpu	string	X	-	Maximum CPU count for the tenant
--max_memory, -mem	string	X	-	Maximum memory for the tenant
--max_storage, -stor	string	X	-	Maximum storage for the tenant
--max_ip, -ip	string	X	-	Maximum IP count for the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware quota delete**Description:**

Deletes the resource quota for a tenant in the specified VMware region

Usage:

```
m3admin private vmware quota delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware quota get**Description:**

Retrieves the resource quota for a tenant in the specified VMware region

Usage:

```
m3admin private vmware quota get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region

Option	Type	Req	Default	Description
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware quota update

Description:

Updates an existing resource quota for a tenant in the specified VMware region

Usage:

```
m3admin private vmware quota update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--max_cpu_count, -cpu	string	X	-	Maximum CPU count for the tenant
--max_memory, -mem	string	X	-	Maximum memory for the tenant
--max_storage, -stor	string	X	-	Maximum storage for the tenant
--max_ip, -ip	string	X	-	Maximum IP count for the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware rabbit

Description:

Manages RabbitMQ configuration for VMware regions

Usage:

```
m3admin private vmware rabbit
```

[↑ Back to Table of Contents](#)

Command: m3admin private vmware rabbit get_config

Description:

Retrieves RabbitMQ configuration for the specified VMware region

Usage:

```
m3admin private vmware rabbit get_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware rabbit set_config**Description:**

Configures RabbitMQ connection settings for the specified VMware region

Usage:

```
m3admin private vmware rabbit set_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--host	string	X	-	* Hostname or IP address for the RabbitMQ server
--port	string	X	-	* Port number for the RabbitMQ server
--virtual_host, -vhost	string	X	-	* Name of the RabbitMQ virtual host
--username, -u	string	X	-	* Username for RabbitMQ connection
--password, -pwd	string	X	-	* Password for RabbitMQ connection
--reply_timeout, -rttimeout	string	X	-	* Timeout duration for RabbitMQ replies
--shutdown_timeout, -stimeout	string	X	-	* Timeout duration for RabbitMQ shutdown
--min_concurrent	string	X	-	* Minimum number of concurrent connections to RabbitMQ
--max_concurrent	string	X	-	* Maximum number of concurrent connections to RabbitMQ
--rabbit_queue	string	X	-	* Name of the queue in RabbitMQ
--exchange, -exc	string	X	-	* Name of the exchange in RabbitMQ. Multiple values are allowed
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware region**Description:**

Manages VMware region configurations

Usage:

```
m3admin private vmware region
```

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware region create*

Description:

Creates a new VMware region with vCloud configuration

Usage:

```
m3admin private vmware region create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server	string	X	-	* Name of the server
--api_version	string	X	-	* API version for the server
--region_alias, -r	string	X	-	* Alias for the VMware region
--username, -u	string	X	-	* Username
--password, -pwd	string	X	-	* Password
--management, -M	flag	X	False	Flag to indicate if the region is for management purposes
--init_script, -l	flag	X	False	Flag to initialize the script
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware region delete*

Description:

Deletes the specified VMware region configuration

Usage:

```
m3admin private vmware region delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--force, -F	flag	X	False	Force deletion even if there are dependencies
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin private vmware region get*****Description:**

Retrieves details of the specified VMware region

Usage:

```
m3admin private vmware region get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin private vmware region get_management_status*****Description:**

Retrieves the management status of the specified VMware region

Usage:

```
m3admin private vmware region get_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin private vmware region list*****Description:**

Lists all configured VMware regions

Usage:

```
m3admin private vmware region list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware region set_management_status*

Description:

Sets the management availability status for the specified VMware region

Usage:

```
m3admin private vmware region set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--available, -A	flag	X	False	Flag to set the region as available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private vmware shape*

Description:

Manages VM shapes for VMware tenants

Usage:

```
m3admin private vmware shape
```

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware shape clean*

Description:

Removes all custom VM shapes from a tenant in the specified VMware region

Usage:

```
m3admin private vmware shape clean [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--json	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware shape list*

Description:

Lists all available VM shapes for a tenant in the specified VMware region

Usage:

```
m3admin private vmware shape list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware shape set*

Description:

Sets a VM shape for a tenant in the specified VMware region

Usage:

```
m3admin private vmware shape set [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--name	string	X	-	* Name of the shape
--cpu	string	X	-	* Number of CPUs for the shape
--memory	string	X	-	* Amount of memory in GB for the shape
--storage	string	X	-	* Storage size in GB for the shape
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware template**Description:**

Manages VM templates in VMware regions

Usage:

```
m3admin private vmware template
```

[↑ Back to Table of Contents](#)

Command: m3admin private vmware template create**Description:**

Creates a new VM template in the specified VMware region

Usage:

```
m3admin private vmware template create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--template_id, -ti	string	X	-	* ID of the template to create
--template_href, -th	string	X	-	* HREF of the template to create
--vm_href, -vh	string	X	-	* HREF of the source VM for the template
--template_alias, -tma	string	X	-	* Alias for the VMware template
--template_name, -tn	string	X	-	* Template name
--tenant_alias, -tna	string	X	-	Alias of the VMware tenant
--network_name, -nn	string	X	-	Network for the template
--overwrite, -O	flag	X	False	Flag to overwrite the template if it already exists
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware template delete**Description:**

Deletes a VM template from the specified VMware region

Usage:

```
m3admin private vmware template delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--template_id, -tid	string	X	-	* ID of the template
--force, -F	flag	X	False	Flag to force the deletion of the template
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware template get*

Description:

Retrieves details of a specific VM template in the specified VMware region

Usage:

```
m3admin private vmware template get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--template_id, -tid	string	X	-	* ID of the template
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware template list*

Description:

Lists all VM templates in the specified VMware region

Usage:

```
m3admin private vmware template list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware template set_alias**Description:**

Sets the alias for a VM template in the specified VMware region

Usage:

```
m3admin private vmware template set_alias [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--template_id, -tid	string	X	-	* ID of the template
--alias	string	X	-	* Alias for the template
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware tenant**Description:**

Manages tenants in VMware regions

Usage:

```
m3admin private vmware tenant
```

[↑ Back to Table of Contents](#)

Command: m3admin private vmware tenant create**Description:**

Creates a new tenant in the specified VMware region

Usage:

```
m3admin private vmware tenant create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -tn	string	X	-	* Alias for the tenant
--organization, -org	string	X	-	* Organization name of the tenant
--default_vdc, -dv	string	X	-	* Default VDC for the VMware tenant
--default_network, -dnet	string	X	-	* Default network for the VMware tenant
--storage_profile, -sp	string	X	-	* Storage profile for the VMware tenant

Option	Type	Req	Default	Description
--management, -M	flag	X	False	Flag to indicate if the tenant is for management purposes
--describer, -d	choice	X	ALL	* Describer for the VMware tenant. Options are “ALL” or “OUR”. Available choices: ALL, OUR
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware tenant delete*

Description:

Deletes a tenant from the specified VMware region

Usage:

```
m3admin private vmware tenant delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--force, -F	flag	X	False	Force deletion even if there are dependencies
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware tenant get*

Description:

Retrieves details of a specific tenant in the specified VMware region

Usage:

```
m3admin private vmware tenant get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin private vmware tenant get_health_check*****Description:**

Retrieves health check results for a tenant in the specified VMware region

Usage:

```
m3admin private vmware tenant get_health_check [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin private vmware tenant get_management_status*****Description:**

Retrieves the management status of a tenant in the specified VMware region

Usage:

```
m3admin private vmware tenant get_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)**Command: *m3admin private vmware tenant get_usage*****Description:**

Retrieves the current resource usage for a tenant in the specified VMware region

Usage:

```
m3admin private vmware tenant get_usage [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware tenant list*

Description:

Lists all tenants in the specified VMware region

Usage:

```
m3admin private vmware tenant list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware tenant set_management_status*

Description:

Sets the management availability status for a tenant in the specified VMware region

Usage:

```
m3admin private vmware tenant set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--available, -A	flag	X	False	Flag to set the tenant management status to available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vmware vdc**Description:**

Manages Virtual Data Centers in VMware regions

Usage:

```
m3admin private vmware vdc
```

[↑ Back to Table of Contents](#)

Command: m3admin private vmware vdc add_readonly**Description:**

Adds a VDC as read-only for a tenant in the specified VMware region

Usage:

```
m3admin private vmware vdc add_readonly [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--vdc_name	string	X	-	* Name of the VDC to add as read-only
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vmware vdc get**Description:**

Retrieves details of a specific VDC in the specified VMware region

Usage:

```
m3admin private vmware vdc get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--vdc_name	string	X	-	* Name of the VDC to retrieve
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware vdc list_cloud*

Description:

Lists all cloud VDCs for a tenant in the specified VMware region

Usage:

```
m3admin private vmware vdc list_cloud [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware vdc list_configured*

Description:

Lists all configured VDCs for a tenant in the specified VMware region

Usage:

```
m3admin private vmware vdc list_configured [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias for the VMware tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vmware vdc remove_readonly*

Description:

Removes a VDC from read-only list for a tenant in the specified VMware region

Usage:

```
m3admin private vmware vdc remove_readonly [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the VMware region
--tenant_alias, -ta	string	X	-	* Alias of the tenant
--vdc_name	string	X	-	* Name of the VDC to remove from read-only
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vsphere

Description:

Manages vSphere resources via private agent

Usage:

```
m3admin private vsphere
```

[↑ Back to Table of Contents](#)

Group: m3admin private vsphere region

Description:

Manages vSphere regions, management status, and network configuration

Usage:

```
m3admin private vsphere region
```

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere region add_network

Description:

Adds a network to a vSphere region

Usage:

```
m3admin private vsphere region add_network [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--network_id, -nid	string	X	-	* ID of the network to add
--network_type, -nt	choice	X	-	* Type of the network. Options are "STANDARD_PORTGROUP" or "DISTRIBUTED_PORTGROUP". Available choices: STANDARD_PORTGROUP, DISTRIBUTED_PORTGROUP
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere region create*

Description:

Creates a new vSphere region

Usage:

```
m3admin private vsphere region create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--server, -s	string	X	-	* Name of the server
--region_alias, -r	string	X	-	* Alias for the vSphere region
--username, -u	string	X	-	* Username
--password, -pwd	string	X	-	* Password
--region_type, -rtype	choice	X	-	* Type of the vSphere region. Available choices: VCENTER, DATACENTER, CLUSTER
--management, -M	flag	X	False	Flag to indicate if the region is for management purposes
--cluster_id, -cid	string	X	-	ID of the cluster for the vSphere region
--datacenter_id, -did	string	X	-	ID of the datacenter for the vSphere region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere region delete*

Description:

Deletes a vSphere region configuration

Usage:

```
m3admin private vsphere region delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--force, -F	flag	X	False	Force deletion even if there are dependencies
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere region get*

Description:

Retrieves details of a specific vSphere region

Usage:

```
m3admin private vsphere region get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere region get_management_status*

Description:

Retrieves the management status of a vSphere region

Usage:

```
m3admin private vsphere region get_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere region list*

Description:

Lists all configured vSphere regions

Usage:

```
m3admin private vsphere region list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere region set_management_status*

Description:

Sets the management availability status for a vSphere region

Usage:

```
m3admin private vsphere region set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--available, -A	flag	X	False	Flag to set the region management status to available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: *m3admin private vsphere shape*

Description:

Manages VM shapes in vSphere regions

Usage:

```
m3admin private vsphere shape
```

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere shape clean*

Description:

Removes all custom VM shapes from a vSphere region

Usage:

```
m3admin private vsphere shape clean [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere shape list*

Description:

Lists all available VM shapes for a vSphere region

Usage:

```
m3admin private vsphere shape list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere shape set*

Description:

Creates a VM shape for a vSphere region

Usage:

```
m3admin private vsphere shape set [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--name	string	X	-	* Name of the shape
--cpu	string	X	-	* Set the number of CPUs for the shape
--memory	string	X	-	* Set the amount of RAM memory in GB for the shape
--storage	string	X	-	* Set the storage size in GB for the shape
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin private vsphere tenant**Description:**

Manages vSphere tenants, health checks, images, and management status

Usage:

```
m3admin private vsphere tenant
```

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere tenant create**Description:**

Creates a new tenant in a vSphere region

Usage:

```
m3admin private vsphere tenant create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -ta	string	X	-	* Alias for the vSphere tenant
--placement_type, -pt	choice	X	-	* Placement type for the vSphere tenant. Options are "CLUSTER", "RESOURCE_POOL" or "HOST". Available choices: CLUSTER, RESOURCE_POOL, HOST
--deploy_type, -dt	choice	X	-	* Deployment type for the vSphere tenant. Options are "ISO" or "CONTENT_TEMPLATE". Available choices: ISO, CONTENT_TEMPLATE
--describer, -d	choice	X	ALL	* Describer for the vSphere tenant. Available choices: ALL, OUR
--cluster_id, -cid	string	X	-	Cluster ID for the vSphere tenant
--vm_folder, -vf	string	X	-	VM folder for the vSphere tenant
--host, -h	string	X	-	Host for the vSphere tenant
--datacenter_id, -dci	string	X	-	Datacenter ID for the vSphere tenant
--datastore_id, -dsi	string	X	-	Datastore ID for the vSphere tenant
--datastore, -dsn	string	X	-	Datastore for the vSphere tenant
--iso_folder, -if	string	X	-	ISO folder for the vSphere tenant
--library_id, -li	string	X	-	Library ID for the vSphere tenant
--management, -M	flag	X	False	Flag to indicate if the tenant is for management purposes
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere tenant create_image**Description:**

Creates a new VM image in a vSphere tenant

Usage:

```
m3admin private vsphere tenant create_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -ta	string	X	-	* Alias for the vSphere tenant
--image_alias, -ia	string	X	-	* Alias for the vSphere image
--platform, -p	choice	X	-	* Platform of the vSphere image. Options are “WIN” for Windows, “LINUX” for Linux, or “OTHER” for other platforms. Available choices: WIN, LINUX, OTHER
--name, -n	string	X	-	Name of the vSphere image
--item_id, -iid	string	X	-	Item ID of the vSphere image
--guest_os, -os	string	X	-	Guest OS of the vSphere image
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere tenant delete**Description:**

Deletes a tenant from a vSphere region

Usage:

```
m3admin private vsphere tenant delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -talias	string	X	-	* Alias for the vSphere tenant
--force, -F	flag	X	False	Force deletion even if there are dependencies
--json	flag	X	False	Use this parameter to show command’s response in a JSON view.
--table	flag	X	False	Use this parameter to show command’s response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere tenant get**Description:**

Retrieves details of a specific vSphere tenant

Usage:

```
m3admin private vsphere tenant get [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -talias	string	X	-	* Alias for the vSphere tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere tenant get_health_check_result**Description:**

Retrieves health check results for a vSphere tenant

Usage:

```
m3admin private vsphere tenant get_health_check_result [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -talias	string	X	-	* Alias for the vSphere tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin private vsphere tenant get_management_status**Description:**

Retrieves the management status of a vSphere tenant

Usage:

```
m3admin private vsphere tenant get_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -talias	string	X	-	* Alias for the vSphere tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere tenant list*

Description:

Lists all tenants in a vSphere region

Usage:

```
m3admin private vsphere tenant list [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin private vsphere tenant set_management_status*

Description:

Sets the management availability status for a vSphere tenant

Usage:

```
m3admin private vsphere tenant set_management_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region_alias, -r	string	X	-	* Alias for the vSphere region
--tenant_alias, -talias	string	X	-	* Alias for the vSphere tenant
--available, -A	flag	X	False	Flag to set the tenant management status to available
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin region**Description:**

Manages regions-related resources

Usage:

```
m3admin region
```

[↑ Back to Table of Contents](#)

Command: m3admin region add_virt_profile**Description:**

Adds the virt profile to specified tenant or to tenants of the specified customer

Usage:

```
m3admin region add_virt_profile [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region to add virt profile to
--virt_profile, -vp	string	X	-	* Name of the virtual profile (Should not be specified with the following clouds: ['OPEN_STACK', 'VSPHERE', 'NUTANIX', 'VMWARE', 'GOOGLE'])
--shape_mapping, -smap	string	X	-	* Maestro shape to cloud shape mapping. Format: maestro_shape=cloud_shape. Multiple values allowed (e.g. --shape_mapping value1 --shape_mapping value2)
--tenant, -tn	string	X	-	Tenant display name to add virt profile to the tenant. See also 'all_tenants' option. This option excludes the all_tenants option
--customer_id, -cid	string	X	-	Required only in case the 'all_tenant' option is set. The ID of the customer to whose tenants specified virt profile will be set
--all_tenants, -A	flag	X	False	If True - the specified virt profile will be added in all tenants in the customer. This option excludes the tenant option
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin region delete_virt_profile**Description:**

Removes virt profile from tenant or from all tenants in the customer

Usage:

```
m3admin region delete_virt_profile [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region to remove virt profile from
--virt_profile, -vp	string	X	-	Name of the virtual profile (Should not be specified with the following clouds: ['OPEN_STACK', 'VSPHERE', 'NUTANIX', 'VMWARE', 'GOOGLE'])
--tenant, -tn	string	X	-	Tenant display name to remove virt profile from the tenant. See also 'all_tenants' option. This option excludes the all_tenants option
--customer_id, -cid	string	X	-	Required only in case the 'all_tenant' option is set. The ID of the customer to whose tenants specified virt profile will be set
--all_tenants, -A	flag	X	False	If True - the specified virt profile will be removed from all tenants in the customer. This option excludes the tenant option
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin region describe**Description:**

Lists regions by certain filters

Usage:

```
m3admin region describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	Apply filter by region name
--native_name, -nname	string	X	-	Apply filter by native name (Can be used only with cloud filter)
--cloud, -c	choice	X	-	Apply filter by cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--active, -A	flag	X	False	Apply filter by active
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin region describe_virt_profile**Description:**

Describes virt profile from tenant or from all tenants in the customer

Usage:

```
m3admin region describe_virt_profile [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region to describe virt profile from
--virt_profile, -vp	string	X	-	Name of the virtual profile. This should be specified for the following clouds: AWS, AZURE. If not provided, all profiles will be described. For example, for AWS: x64.hvm
--tenant, -tn	string	X	-	Tenant display name to describe virt profile from the tenant. See also 'all_tenants' option. This option excludes the all_tenants option
--customer_id, -cid	string	X	-	Required only in case the 'all_tenant' option is set. The ID of the customer to whose tenants specified virt profile will be set
--all_tenants, -A	flag	X	False	If True - the specified virt profile will be described from all tenants in the customer. This option excludes the tenant option
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin region update_virt_profile**Description:**

Updates the existing virt profile in specified tenant of virt profiles in all tenants in the customer

Usage:

```
m3admin region update_virt_profile [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region to update virt profile to
--virt_profile, -vp	string	X	-	Name of the virtual profile (Should not be specified with the following clouds: ['OPEN_STACK', 'VSPHERE', 'NUTANIX', 'VMWARE', 'GOOGLE'])
--shape_mapping, -smap	string	X	-	* Maestro shape to cloud shape mapping. Format: maestro_shape=cloud_shape. Multiple values allowed (e.g. --shape_mapping value1 --shape_mapping value2)
--tenant, -tn	string	X	-	Tenant display name to update virt profile to the tenant.

Option	Type	Req	Default	Description
				See also 'all_tenants' option. This option excludes the all_tenants option
--customer_id, -cid	string	X	-	Required only in case the 'all_tenant' option is set. The ID of the customer to whose tenants specified virt profile will be set
--all_tenants, -A	flag	X	False	If True - the specified virt profile will be updated to all tenants in the customer. This option excludes the tenant option
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin security**Description:**

Manages security platforms Maestro is integrated with

Usage:

```
m3admin security
```

[↑ Back to Table of Contents](#)

Command: m3admin security activate_custodian_for_tenant**Description:**

Creates Custodian Service credentials for tenant

Usage:

```
m3admin security activate_custodian_for_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Cloud name. Available choices: AWS, AZURE, GOOGLE
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin security add_qualys_cloud_view_policy**Description:**

Adds qualys Cloud View policy to selected platform

Usage:

```
m3admin security add_qualys_cloud_view_policy [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--platform_alias, -palias	string	X	-	* Platform alias
--policy_id, -pid	string	X	-	* Policy id
--cloud, -c	choice	X	-	* Policy cloud type. Available choices: AWS, AZURE, GOOGLE
--title	string	X	-	* Policy title
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin security add_qualys_configuration*

Description:

Adds qualys configuration

Usage:

```
m3admin security add_qualys_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--alias	string	X	-	* Platform id
--name	string	X	-	* Platform name
--api_host, -ahost	string	X	-	* Platform API host. Example: qualysapi.qualys.com
--platform_host, -phost	string	X	-	* Platform host. Example: qualysguard.qualys.com
--port	integer	X	-	* Platform port
--login, -l	string	X	-	* Platform login
--password, -pwd	string	X	-	* Platform password
--default_report_template, -drt	string	X	-	* Default report template
--default_report_format, -drf	string	X	-	* Default report format
--default, -D	flag	X	False	Mark qualys platform as default
--override, -O	flag	X	False	Use this flag to override existing platform configuration
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin security deactivate_custodian_for_tenant*

Description:

Removes Custodian Service credentials for tenant

Usage:

```
m3admin security deactivate_custodian_for_tenant [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Cloud name. Available choices: AWS, AZURE, GOOGLE

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin security delete_qualys_cloud_view_policy*

Description:

Removes qualys Cloud View policy from selected platform

Usage:

```
m3admin security delete_qualys_cloud_view_policy [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--platform_alias, -palias	string	X	-	* Platform alias
--policy_id, -pid	string	X	-	* Policy id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin security delete_qualys_configuration*

Description:

Removes qualys configuration

Usage:

```
m3admin security delete_qualys_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--alias	string	X	-	* Platform alias
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin security describe_qualys_configuration*

Description:

Describes qualys configurations

Usage:

```
m3admin security describe_qualys_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin security manage_qualys_excluded_controls

Description:

Adds or removes Quayls Cloud View Controls to list of excluded controls for selected platform

Usage:

```
m3admin security manage_qualys_excluded_controls [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--platform_alias, -palias	string	X	-	* Platform alias
--action, -a	choice	X	-	* Action. Available choices: add, describe, remove
--control_id, -cid	string	X	-	Control ID. Must be specified with "add" and "remove" action
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin security manage_qualys_recommended_controls

Description:

Adds or removes Quayls Cloud View Controls to list of recommended controls for selected platform

Usage:

```
m3admin security manage_qualys_recommended_controls [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--platform_alias, -palias	string	X	-	* Platform alias
--action, -a	choice	X	-	* Action. Available choices: add, describe, remove
--control_id, -cid	string	X	-	Control ID. Must be specified with "add" and "remove"

Option	Type	Req	Default	Description
				action
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin security set_qualys_platform

Description:

Configures qualys platform for region

Usage:

```
m3admin security set_qualys_platform [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Maestro name of the region
--qualys_platform_id, -qid	string	X	-	* Qualys platform id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin security update_qualys_configuration

Description:

Updates qualys configuration

Usage:

```
m3admin security update_qualys_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--alias	string	X	-	* Platform id
--name	string	X	-	Platform name
--api_host, -ahost	string	X	-	Platform API host. Example: qualysapi.qualys.com
--platform_host, -phost	string	X	-	Platform host. Example: qualysguard.qualys.com
--port	integer	X	-	Platform port
--login, -l	string	X	-	Platform login
--password, -pwd	string	X	-	Platform password
--default_report_template, -drt	string	X	-	Default report template

Option	Type	Req	Default	Description
--default_report_format, -drf	string	X	-	Default report format
--default, -D	flag	X	False	Mark qualys platform as default
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin tenant**Description:**

Manages tenants

Usage:

```
m3admin tenant
```

[↑ Back to Table of Contents](#)

Command: m3admin tenant add_contacts**Description:**

Sets contacts to the Tenant item

Usage:

```
m3admin tenant add_contacts [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--default_owner, -do	string	X	-	Default instance owner for tenant
--primary_contact, -pct	string	X	-	Primary contacts of tenant. Multiple values allowed (e.g. --primary_contact value1 --primary_contact value2)
--secondary_contact, -sct	string	X	-	Secondary contacts of tenant. Multiple values allowed (e.g. --secondary_contact value1 --secondary_contact value2)
--manager_contact, -mct	string	X	-	Contacts of managers of tenant. Multiple values allowed (e.g. --manager_contact value1 --manager_contact value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant add_vpc**Description:**

Adds VPC which is allowed to use while working with Tenant

Usage:

```
m3admin tenant add_vpc [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenant to associate vpc with it
--cloud, -c	choice	X	-	* Cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--region, -r	string	X	-	* Region where vpc is configured
--vpc_filter	string	X	-	* Vpc id, like: vpc-xxxxxxx. Multiple values allowed (e.g. -vpc_filter value1 -vpc_filter value2)
--override, -O	flag	X	False	Command property to manage override behavior
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant check_status

Description:

Checks the actual status of the tenant in a region

Usage:

```
m3admin tenant check_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant general name to check status
--region, -r	string	X	-	* Region name
--force_activate, -F	flag	X	False	Use this flag to force activation of the specified tenant
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant deactivate_region

Description:

Deactivates region in tenant

Usage:

```
m3admin tenant deactivate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to deactivate region

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--region, -r	string	X	-	Region to deactivate. Should be present if --all_regions flag is not specified
--all_regions, -A	flag	X	False	Flag to deactivate all regions. If specified --region parameter has no effect
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin tenant delete_chef_configuration*

Description:

Describes Chef configuration

Usage:

```
m3admin tenant delete_chef_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin tenant delete_contacts*

Description:

Removes specified contacts from the Tenant item

Usage:

```
m3admin tenant delete_contacts [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--default_owner, -D	flag	X	False	If flag set, the current default instance owner will be removed
--primary_contact, -pct	string	X	-	Primary contacts to remove from the tenant. Multiple values allowed (e.g. --primary_contact value1 – primary_contact value2)
--secondary_contact, -sct	string	X	-	Secondary contacts to remove from tenant. Multiple values allowed (e.g. --secondary_contact value1 – secondary_contact value2)
--manager_contact, -mct	string	X	-	Contacts of managers to remove from tenant. Multiple values allowed (e.g. --manager_contact value1 – manager_contact value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin tenant delete_instance_quota*

Description:

Deletes instance quota

Usage:

```
m3admin tenant delete_instance_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin tenant delete_volume_quota*

Description:

Deletes volume quota

Usage:

```
m3admin tenant delete_volume_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe

Description:

Lists tenants by certain filters

Usage:

```
m3admin tenant describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Apply filter by tenant display name
--customer_id, -cid	string	X	-	Apply filter by customer
--cloud, -c	choice	X	-	Apply filter by cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--active, -A	flag	X	False	Apply filter by active
--account, -acc	string	X	-	Apply filter by tenant's account. This parameter is case sensitive
--get_linked_tenants, -glt	flag	X	False	Flag. Set this flag if you wish to retrieve linked tenants
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_chef_configuration**Description:**

Describes Chef configuration

Usage:

```
m3admin tenant describe_chef_configuration [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_contacts**Description:**

Describes tenant contacts

Usage:

```
m3admin tenant describe_contacts [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_instance_quota**Description:**

Describes instance quota

Usage:

```
m3admin tenant describe_instance_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_regions**Description:**

Lists Customer's tenant(s) regions

Usage:

```
m3admin tenant describe_regions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer ID
--tenant, -tn	string	X	-	Tenant display name
--cloud, -c	choice	X	-	Filter result by cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--active, -A	flag	X	False	Flag, filter result by active tenants
--inactive, -I	flag	X	False	Flag, filter result by inactive tenants
--hidden, -H	flag	X	False	Flag, filter result by tenants with hidden regions
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_terraform**Description:**

Describes the Terraform configuration for a specific tenant

Usage:

```
m3admin tenant describe_terraform [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to describe terraform
--cloud, -c	choice	X	-	Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--include_inactive, -l	flag	X	False	Flag. If specified the inactive tenants will be displayed too
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_type

Description:

Describes the type of the tenant (billable/not billable). The result is sent via e-mail (or displayed in console if tenant is specified)

Usage:

```
m3admin tenant describe_type [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_type, -ttype	choice	X	ALL	Type of the Tenant (default ALL). Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED, ALL
--tenant, -tn	string	X	-	Display name of the Tenant
--email, -e	string	X	-	Email to send
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant describe_volume_quota

Description:

Describes volume quota

Usage:

```
m3admin tenant describe_volume_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant disable**Description:**

Disables tenant

Usage:

```
m3admin tenant disable [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Display name of the tenant to deactivate region
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant rename**Description:**

Renames selected tenant

Usage:

```
m3admin tenant rename [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name

Option	Type	Req	Default	Description
--cloud, -c	choice	X	-	* Apply filter by cloud. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--new_tenant, -ntn	string	X	-	* New tenant display name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin tenant set_deactivation_request_date`

Description:

Sets deactivation request date for specified tenant. Does not mark tenant as inactive

Usage:

```
m3admin tenant set_deactivation_request_date [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to deactivate region
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--deactivation_request_date, -exp	string	X	-	* Deactivation request date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: `m3admin tenant set_instance_quota`

Description:

Sets instance quota

Usage:

```
m3admin tenant set_instance_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name

Option	Type	Req	Default	Description
--region, -r	string	X	-	* Region name
--instance_count, -count	integer	X	-	Number of instances one can create during creation interval
--time, -t	integer	X	24	Period in hours during which the set count of instances can be created
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin tenant set_region_hidden_attribute*

Description:

Updates 'hidden' (hid) attribute of Tenant.regions

Usage:

```
m3admin tenant set_region_hidden_attribute [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant which has an activated region to mark as hidden
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--region, -r	string	X	-	* Maestro name of the region to mark as hidden
--hidden, -H	flag	X	False	Flag to manage 'hidden' attribute; True - hidden; False, default value - unhidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin tenant set_tenant_state_attribute*

Description:

Updates 'tenant_state' (ts) attribute of Tenant

Usage:

```
m3admin tenant set_tenant_state_attribute [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--state	choice	X	-	* Flag to manage 'tenant_state' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant set_type**Description:**

Sets tenant type

Usage:

```
m3admin tenant set_type [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the Tenant
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX, ALL
--tenant_type, -ttype	choice	X	-	* Tenant type, allowed values: BILLABLE / NOT_BILLABLE / NOT_DEFINED. Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant set_volume_quota**Description:**

Sets volume quota

Usage:

```
m3admin tenant set_volume_quota [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--region, -r	string	X	-	* Region name
--volume_count, -count	integer	X	-	Number of volumes one can create during creation interval
--volume_max_size, -size	integer	X	-	Volumes max size
--time, -t	integer	X	24	Period in hours during which the set count of volumes can be created
--cloud, -c	choice	X	-	* Cloud type. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin tenant update_contacts**Description:**

Updates the current Tenant contacts with provided items

Usage:

```
m3admin tenant update_contacts [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant display name
--cloud, -c	choice	X	-	* Cloud name. Available choices: AZURE, GOOGLE, AWS, OPEN_STACK, HARDWARE, YANDEX, WORKSPACE, ENTERPRISE, VSPHERE, VMWARE, NUTANIX
--default_owner, -do	string	X	-	Default instance owner for tenant
--primary_contact, -pct	string	X	-	Primary contacts of tenant. Multiple values allowed (e.g. --primary_contact value1 --primary_contact value2)
--secondary_contact, -sct	string	X	-	Secondary contacts of tenant. Multiple values allowed (e.g. --secondary_contact value1 --secondary_contact value2)
--manager_contact, -mct	string	X	-	Contacts of managers of tenant. Multiple values allowed (e.g. --manager_contact value1 --manager_contact value2)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin uisdk**Description:**

Manages Javascript UI SDK for API Gateway

Usage:

```
m3admin uisdk
```

[↑ Back to Table of Contents](#)

Command: m3admin uisdk add_customer_icon**Description:**

Adds customer logo on Maestro UI

Usage:

```
m3admin uisdk add_customer_icon [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer to which icon and theme will be applied
--theme, -thm	choice	X	default	Predefined values for theme: default, blue, orange. "DEFAULT" value set by default. Available choices: default, blue, orange
--icon_path, -ipath	path	X	-	* Path to the file
--mobile, -M	flag	X	False	Apply theme and icon in mobile browsing mode. Note that you can pass both flags at the same time
--desktop, -D	flag	X	False	Apply theme and icon in desktop browsing mode. Note that you can pass both flags at the same time
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin uisdk delete**Description:**

Deletes a specific UI SDK version from S3 bucket

Usage:

```
m3admin uisdk delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket, -b	string	X	-	* Bucket name to store SDK
--bucket_region, -br	string	X	-	* Bucket region to store SDK

Option	Type	Req	Default	Description
--env_prefix, -env	string	X	-	* Env prefix
--version_id, -vid	string	X	-	* UI SDK version id
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin uisdk delete_customer_icon*

Description:

Deletes customer logo on Maestro UI

Usage:

```
m3admin uisdk delete_customer_icon [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer to which icon and theme will be applied
--theme, -thm	choice	X	default	Predefined values for theme: default, blue, orange. "DEFAULT" value set by default. Available choices: default, blue, orange
--mobile, -M	flag	X	False	Apply theme and icon in mobile view. Note that you can pass both flags at the same time
--desktop, -D	flag	X	False	Apply theme and icon in desktop view. Note that you can pass both flags at the same time
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin uisdk describe_customer_icon*

Description:

Describes customer logo on Maestro UI

Usage:

```
m3admin uisdk describe_customer_icon [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer to which icon and theme will be applied
--mobile, -M	flag	X	False	Apply theme and icon in mobile browsing mode. Please select one of the two possible types: --mobile to load an

Option	Type	Req	Default	Description
				icon for mobile mode or –desktop for desktop mode of Maestro UI
--desktop, -D	flag	X	False	Apply theme and icon in desktop browsing mode. Please select one of the two possible types: –mobile to load an icon for mobile mode or –desktop for desktop mode of Maestro UI
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin uisdk generate

Description:

Generates UI SDK from API Gateway configuration

Usage:

```
m3admin uisdk generate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--api	string	X	maestro3	Name of the api gateway resource [optional]
--deploy	string	X	-	* Name of the maestro deploy
--file_path, -fpath	string	X	.	Path to the m3 deployment output file [optional]
--sdk_path, -spath	string	X	-	Path to the UI SDK
--stage	string	X	-	Name of the stage for API Gateway
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin uisdk list_versions

Description:

Lists all published UI SDK versions from S3 bucket

Usage:

```
m3admin uisdk list_versions [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket, -b	string	X	-	* Bucket name to store SDK

Option	Type	Req	Default	Description
--bucket_region, -br	string	X	-	* Bucket region to store SDK
--env_prefix, -env	string	X	-	* Env prefix
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin uisdk publish*

Description:

Publishes a new UI SDK version to S3 bucket

Usage:

```
m3admin uisdk publish [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--bucket, -b	string	X	-	* Bucket name to store SDK
--bucket_region, -br	string	X	-	* Bucket region to store SDK
--file_path, -fpath	string	X	-	SDK file path
--env_prefix, -env	string	X	-	* Env prefix
--metadata	string	X	-	* SDK metadata
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin uisdk save_current_native_version*

Description:

Registers the current native application version in a Maestro environment. (path: ACM1_BUCKET/ENV_PREFIX/)

Usage:

```
m3admin uisdk save_current_native_version [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--version, -v	string	X	-	* Current Native application version (both Android and iOS)
--android_url, -aurl	string	X	-	URL for downloading Android application
--ios_url, -iurl	string	X	-	URL for downloading iOS application

Option	Type	Req	Default	Description
--env_prefix, -env	string	X	-	* Env prefix that defines environment
--bucket_region, -br	string	X	-	* Bucket region to store version
--bucket, -b	string	X	-	* Name of bucket to store version
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin uisdk update_customer_icon*

Description:

Updates customer logo on Maestro UI

Usage:

```
m3admin uisdk update_customer_icon [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--customer_id, -cid	string	X	-	* Customer to which icon and theme will be applied
--theme, -thm	choice	X	default	Predefined values for theme: default, blue, orange. "DEFAULT" value set by default. Available choices: default, blue, orange
--icon_path, -ipath	path	X	-	* Path to the file
--mobile, -M	flag	X	False	Apply theme and icon in mobile browsing mode. Note that you can pass both flags at the same time
--desktop, -D	flag	X	False	Apply theme and icon in desktop browsing mode. Note that you can pass both flags at the same time
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin vclouddirector**Description:**

Manages vCloudDirector-related (Vmware) resources

Usage:

```
m3admin vclouddirector
```

[↑ Back to Table of Contents](#)

Command: m3admin vclouddirector activate**Description:**

Activates vCloudDirector tenant.

Usage:

```
m3admin vclouddirector activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE". Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin vclouddirector activate_region**Description:**

Activates vCloudDirector region in tenant

Usage:

```
m3admin vclouddirector activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin vclouddirector add_image*

Description:

Registers vCloudDirector(VMWARE) Image in Maestro. Note: this command should be used after vCloudDirector Tenant registered

Usage:

```
m3admin vclouddirector add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--image_id, -iid	string	X	-	* Id of the image
--description, -d	string	X	-	* Description of the image
--image_os, -ios	string	X	-	* Operation system of image
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag “--all_regions” is specified)
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin vclouddirector deactivate*

Description:

Deactivates vCloudDirector tenant

Usage:

```
m3admin vclouddirector deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--------	------	-----	---------	-------------

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: “yyyy-mm-dd hh”
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin vclouddirector delete_image

Description:

Deletes a vCloudDirector(VMWARE) Image

Usage:

```
m3admin vclouddirector delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions
--cloud, -c	string	X	VMWARE	Cloud provider. Default is vCloudDirector(VMWARE)
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin vclouddirector describe_image

Description:

Describes vCloudDirector Images in a tenant in the specified region

Usage:

```
m3admin vclouddirector describe_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--region, -r	string	X	-	* Image region
--alias	string	X	-	Alias for the image
--unlinked, -U	flag	X	False	Specify to list images that do not linked to tenants
--json	flag	X	False	Use this parameter to show command's response in a JSON view.

Option	Type	Req	Default	Description
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Group: m3admin vsphere**Description:**

Manages vsphere-related resources

Usage:

```
m3admin vsphere
```

[↑ Back to Table of Contents](#)

Command: m3admin vsphere activate**Description:**

Activates vSphere tenant

Usage:

```
m3admin vsphere activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE". Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin vsphere activate_region**Description:**

Activates vSphere region in tenant

Usage:

```
m3admin vsphere activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin vsphere add_image*

Description:

Registers vSphere Image in Maestro. Note: this command should be used after vSphere Tenant registered

Usage:

```
m3admin vsphere add_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--image_id, -iid	string	X	-	* Id of the image
--description, -d	string	X	-	* Description of the image
--image_os, -ios	string	X	-	* Operation system of image
--region, -r	string	X	-	Virtualization region. (Will have no effect in case the flag "--all_regions" is specified)
--all_regions, -A	flag	X	False	All regions. Should be specified if no regions values
--rewrite, -R	flag	X	False	Rewrite parameters of existing image
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin vsphere deactivate*

Description:

Deactivates vSphere tenant

Usage:

```
m3admin vsphere deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant

Option	Type	Req	Default	Description
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: “yyyy-mm-dd hh”
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin vsphere delete_image*

Description:

Deletes a vSphere Image

Usage:

```
m3admin vsphere delete_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	X	-	* Name of the image to delete (image_id)
--region, -r	string	X	ALL	Region where the image is located. Default is ALL regions
--cloud, -c	string	X	VSPHERE	Cloud provider. Default is vSphere
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin vsphere describe_image*

Description:

Describes vSphere Images in a tenant in the specified region

Usage:

```
m3admin vsphere describe_image [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	Tenant display name
--region, -r	string	X	-	Image region
--alias	string	X	-	Alias for the image
--unlinked, -U	flag	X	False	Specify to list images that do not linked to tenants
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a

Option	Type	Req	Default	Description
				Table view.

[↑ Back to Table of Contents](#)

Group: m3admin workspace

Description:

Manages workspaces-related resources

Usage:

```
m3admin workspace
```

[↑ Back to Table of Contents](#)

Command: m3admin workspace activate

Description:

Activates WORKSPACE tenant. Used for Billing+Reporting purposes only

Usage:

```
m3admin workspace activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Tenant name
--display_name, -dn	string	X	-	* Display name
--tenant_group, -tg	string	X	-	* Tenant group which tenant belongs to
--tenant_customer_id, -cid	string	X	-	* Customer which tenant belongs to
--read_only, -R	flag	X	False	Marks tenants as READ_ONLY
--personal, -P	flag	X	False	Marks tenant as a personal
--activation_date, -adate	string	X	-	Specify the date of activation. Format "yyyy-mm-dd"
--state	choice	X	ACTIVE	Flag to manage 'ts' attribute. Available choices: ACTIVE, CREATED, CLOSED, ON_HOLD, UNKNOWN
--project_type, -pt	choice	X	NOT_BILLABLE	Project type. Default value: "NOT_BILLABLE". Available choices: BILLABLE, NOT_BILLABLE, NOT_DEFINED
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin workspace activate_region

Description:

Activates WORKSPACE region in tenant. Used for Billing+Reporting purposes only

Usage:

```
m3admin workspace activate_region [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant to activate region
--region, -r	string	X	-	* Region to activate
--hidden, -H	flag	X	False	Marks region as hidden
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: *m3admin workspace deactivate*

Description:

Deactivates WORKSPACE tenant

Usage:

```
m3admin workspace deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant, -tn	string	X	-	* Display name of the tenant
--deactivation_date, -ddate	string	X	-	Deactivation date. Format: "yyyy-mm-dd hh"
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin disable_autocomplete**Usage:**

```
m3admin disable_autocomplete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin enable_autocomplete**Usage:**

```
m3admin enable_autocomplete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin get_operation_status

Description:

Returns request execution status by ID from long-running operations

Usage:

```
m3admin get_operation_status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--id, -id	string	X	-	Request id
--group, -g	string	X	-	Group name
--command, -cmd	string	X	-	Command name
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin mode**Usage:**

```
m3admin mode [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Command: m3admin policy

Usage:

```
m3admin policy [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	X	False	Use this parameter to show command's response in a JSON view.
--table	flag	X	False	Use this parameter to show command's response in a Table view.

[↑ Back to Table of Contents](#)

Version History

Version	Date	Summary

View Changelog: <https://git.epam.com/epmc-eoos/m3admin/-/blob/develop/CHANGELOG.md>

Documentation generated for: **M3Admin CLI 4.170.0**